

# Conditional Execution


## Chapter 3



Python for Everybody  
[www.py4e.com](http://www.py4e.com)



# Conditional Steps



Program:

```
x = 5
if x < 10:
    print('Smaller')
if x > 20:
    print('Bigger')
print('Finis')
```

Output:

**Smaller**  
**Finis**

# Comparison Operators

- **Boolean expressions** ask a question and produce a Yes or No result which we use to control program flow
- **Boolean expressions** using **comparison operators** evaluate to True / False or Yes / No
- Comparison operators look at variables but do not change the variables

Python	Meaning
<	Less than
<=	Less than or Equal to
==	Equal to
>=	Greater than or Equal to
>	Greater than
!=	Not equal

Remember: “=” is used for assignment.

[http://en.wikipedia.org/wiki/George\\_Boole](http://en.wikipedia.org/wiki/George_Boole)

# Comparison Operators

<pre>x = 5</pre>	
<pre>if x == 5 :</pre>	
<pre>    print('Equals 5')</pre>	Equals 5
<pre>if x &gt; 4 :</pre>	
<pre>    print('Greater than 4')</pre>	Greater than 4
<pre>if x &gt;= 5 :</pre>	
<pre>    print('Greater than or Equals 5')</pre>	Greater than or Equals 5
<pre>if x &lt; 6 : print('Less than 6')</pre>	Less than 6
<pre>if x &lt;= 5 :</pre>	
<pre>    print('Less than or Equals 5')</pre>	Less than or Equals 5
<pre>if x != 6 :</pre>	
<pre>    print('Not equal 6')</pre>	Not equal 6

# One-Way Decisions

```
x = 5
```

```
print('Before 5')
```

```
if x == 5 :
```

```
    print('Is 5')
```

```
    print('Is Still 5')
```

```
    print('Third 5')
```

```
print('Afterwards 5')
```

```
print('Before 6')
```

```
if x == 6 :
```

```
    print('Is 6')
```

```
    print('Is Still 6')
```

```
    print('Third 6')
```


```
print('Afterwards 6')
```

Before 5

Is 5  
Is Still 5  
Third 5

Afterwards 5  
Before 6

Afterwards 6




# Indentation


- **Increase indent** indent after an **if** statement or **for** statement (after : )
- **Maintain indent** to indicate the **scope** of the block (which lines are affected by the **if/for**)
- **Reduce indent** back to the level of the **if** statement or **for** statement to indicate the end of the block
- **Blank lines** are ignored - they do not affect **indentation**
- **Comments** on a line by themselves are ignored with regard to **indentation**

# Warning: Turn Off Tabs!!

- Atom automatically uses spaces for files with ".py" extension (nice!)
- Most text editors can turn **tabs** into **spaces** - make sure to enable this feature
  - Notepad++: Settings -> Preferences -> Language Menu/**Tab** Settings
  - TextWrangler: TextWrangler -> Preferences -> Editor Defaults
- Python cares a \*lot\* about how far a line is indented. If you mix **tabs** and **spaces**, you may get "**indentation errors**" even if everything looks fine




This will save you  
much unnecessary  
pain.





increase / maintain after if or for  
decrease to indicate end of block



```
x = 5
if x > 2 :
    print('Bigger than 2')
    print('Still bigger')
print('Done with 2')

for i in range(5) :
    print(i)
    if i > 2 :
        print('Bigger than 2')
    print('Done with i', i)
print('All Done')
```


# Think About begin/end Blocks

```
x = 5
if x > 2 :
    print('Bigger than 2')
    print('Still bigger')
print('Done with 2')
```

```
for i in range(5) :
    print(i)
    if i > 2 :
        print('Bigger than 2')
    print('Done with i', i)
print('All Done')
```


# Nested Decisions

```
x = 42
if x > 1 :
    print('More than one')
    if x < 100 :
        print('Less than 100')
print('All done')
```



# Two-way Decisions

- Sometimes we want to do one thing if a logical expression is true and something else if the expression is false
- It is like a fork in the road - we must choose **one or the other** path but not both




# Two-way Decisions with else:

```
x = 4
```

```
if x > 2 :  
    print('Bigger')  
else :  
    print('Smaller')
```

```
print('All done')
```




# Visualize Blocks

x = 4

```
if x > 2 :  
    print('Bigger')  
else :  
    print('Smaller')
```


```
print('All done')
```



More Conditional Structures...

# Multi-way


```
if x < 2 :  
    print('small')  
elif x < 10 :  
    print('Medium')  
else :  
    print('LARGE')  
print('All done')
```






# Multi-way

```
x = 0
if x < 2 :
    print('small')
elif x < 10 :
    print('Medium')
else :
    print('LARGE')
print('All done')
```




# Multi-way

```
x = 5
if x < 2 :
    print('small')
elif x < 10 :
    print('Medium')
else :
    print('LARGE')
print('All done')
```



# Multi-way

```
x = 20
if x < 2 :
    print('small')
elif x < 10 :
    print('Medium')
else :
    print('LARGE')
print('All done')
```



# Multi-way

```
# No Else
x = 5
if x < 2 :
    print('Small')
elif x < 10 :
    print('Medium')

print('All done')
```

```
if x < 2 :
    print('Small')
elif x < 10 :
    print('Medium')
elif x < 20 :
    print('Big')
elif x < 40 :
    print('Large')
elif x < 100:
    print('Huge')
else :
    print('Ginormous')
```



# Acknowledgements / Contributions



These slides are Copyright 2010- Charles R. Severance ([www.dr-chuck.com](http://www.dr-chuck.com)) of the University of Michigan School of Information and made available under a Creative Commons Attribution 4.0 License. Please maintain this last slide in all copies of the document to comply with the attribution requirements of the license. If you make a change, feel free to add your name and organization to the list of contributors on this page as you republish the materials.

Initial Development: Charles Severance, University of Michigan School of Information

... Insert new Contributors and Translators here