

Bias-Variance Tradeoff

CS229: Machine Learning Carlos Guestrin Stanford University


Slides include content developed by and co-developed with Emily Fox

©2021 Carlos Guestrin




2

Fit data with a line or ...?




3

What about a quadratic function?




/


Even higher order polynomial



Do you believe this fit?



Do you believe this fit?



"Remember that all models are wrong; the practical question is how wrong do they have to be to not be useful." George Box, 1987.

©2021 Carlos Guestrin CS229: Machine Learning




Assessing the loss


Part 1: Training error

CS229: Machine Learning


Define training data



Define training data




Example: Fit quadratic to minimize RSS




Example:

Use squared error loss $(y-f_{\hat{w}}(x))^2$




Training error vs. model complexity



Is training error a good measure of predictive performance?

Issue:

Training error is overly optimistic... www was fit to training data



16

CS229: Machine Learning




Part 2: Generalization (true) error

CS229: Machine Learning

Generalization error


Really want estimate of loss over all possible (1),\$) pairs




18


Generalization error definition


Really want estimate of loss over all possible (1,5) pairs




Generalization error vs. model complexity









True error vs. model complexity





Part 3: Test error

Training, true, test error vs. model complexity




3 sources of error + the bias-variance tradeoff

3 sources of error

In forming predictions, there are 3 sources of error:


- 1. Noise
- 2. Bias
- 3. Variance

Data inherently noisy




Bias contribution

Suppose we fit a constant function



Bias contribution

Over all possible size N training sets, what do I expect my fit to be?




Bias contribution

Bias(x) =
$$f_{w(true)}(x) - f_{\bar{w}}(x)$$


Is our approach flexible enough to capture $f_{w(true)}$?

If not, error in predictions.




Variance contribution

How much do specific fits vary from the expected fit?




Variance contribution

How much do specific fits vary from the expected fit?



Variance contribution


How much do specific fits vary from the expected fit?



32


Variance of high-complexity models

Assume we fit a high-order polynomial




Variance of high-complexity models


Suppose we fit a high-order polynomial



Variance of high-complexity models



Bias of high-complexity models




high complexity

6 ©2021 Carlos Guestrin CS229: Machine Learning

Sum of 3 sources of error


Average squared error at x_t

$$= \sigma^2 + \left[bias(f_{\hat{w}}(x_t)) \right]^2 + var(f_{\hat{w}}(x_t))$$





37

Bias-variance tradeoff



Error vs. amount of data





CS229: Machine Lea

What you can do now...

- Contrast relationship between model complexity and train, true and test loss
- Compute training and test error given a loss function for different model complexities
- List and interpret the 3 sources of avg. prediction error
 - Irreducible error, bias, and variance