DEJ SOFTWARE™

PHAROS DATA ARK

Content drive / split Ark

A library drive carries public content, configuration and the recovery kit. It can help rebuild a replacement host. A surviving host can prepare replacement library media. A content drive alone is not a bootable operating system.

> **Setup authorization:** use the trusted local installer or host terminal. No separate activation code is needed after owner credentials are set. If browser setup is deferred on a shared network, prepare a fresh private pairing code first.

What you need

- A supported running Linux host with administrative access and an attached library drive.
- Internet for missing operating-system packages and software dependencies. Existing public content is reused.

First start

1. Attach the library drive. Locate its DATA-ARK-CONFIG folder and included recovery kit; follow its README rather than executing an arbitrary script from unknown media.
2. Preview the bootstrap/recovery plan on the new host and select the intended library location.
3. Run the supported installation workflow with Linux administrative authorization. Set owner credentials locally when offered.
4. Verify library readers and content. When preparing a second Ark for someone else, use Make another Ark / Prepare for a new owner to establish a fresh identity and private setup code.

Browsing installed content needs no password. No online activation, registration or DEJ Software account is required.

Operating notes

- Never reuse the original owner credentials or printed setup code for a new recipient.
- When starting with configuration but no content, choose a capacity-appropriate restore preset; downloads need an upstream connection.

Further help

The complete handbook is included with the Ark. Online: dejsoftware.com/data-ark/docs/.

On an installed appliance, use System / System / Power before disconnecting power or removing storage. Containers use their host controls.