DEJ SOFTWARE™

PHAROS DATA ARK

Docker / container

The container serves a library on an existing local network using host-mounted media and persistent state. It does not manage the host's radios, disks, root account or power.

> **Setup authorization:** set the caretaker password in the Docker host terminal. The container does not use pairing codes and does not create Linux accounts.

What you need

- Docker Engine or Docker Desktop with Compose.
- An existing library folder, a writable public configuration folder and persistent private/state volumes.

First start

1. Follow the Container guide. Set ARK_MEDIA, ARK_CONFIGURATION and ARK_PORT in the supplied Compose environment file.
2. Build or select the reviewed image, then start it using the documented Compose command. Building needs internet; reading installed content does not.
3. Set the caretaker password using the documented caretaker-password command in the host terminal. No first-owner pairing code or Linux admin password is created by the container.
4. Open the host address and selected port in a browser. Keep the same media/configuration mounts and private/state volumes when recreating or updating it.

Browsing installed content needs no password. No online activation, registration or DEJ Software account is required.

Operating notes

- Networking, physical drives, host credentials, power and optional HTTPS are host responsibilities.
- Do not delete the private/state volumes when you intend to preserve passwords, posts, banner and operational state.

Further help

The complete handbook is included with the Ark. Online: dejsoftware.com/data-ark/docs/.

On an installed appliance, use System / System / Power before disconnecting power or removing storage. Containers use their host controls.