



INNOVATIVE IDEAS IN AIR CONDITIONING



Main Features

- **R454B** Environmentally Friendly Refrigerant
- Field Add-on **A2L** sensor option
- Universal High Wall for all outdoor models
- EnergyStar for all models
- 16FT Installation Kit included in packaging
- 115V Models available
- Low ambient operation to **-13°F**
- **IRA Tax Rebate** for select models
- 4-in-1 filter plus standard filters
- **WIFI included** with auto-diagnostic app
- Larger screen **LED Remote Control**
- Horizontal and Vertical Swing

UP TO 25 SEER²
EFFICIENCY

Q4



INVERTER

R454B



AIRI CERTIFIED
www.airincertified.org



Indoor Model			QHW09H1UZRA	QHW12H1UZRA	QHW09H2UZRA	QHW12H2UZRA	QHW18H2UZRA	QHW24H2UZRA
Outdoor Model			QOS09H1BM5A	QOS12H1BM5A	QOS09H2BM5A	QOS12H2BM5A	QOS18H2BM5A	QOS24H2BM5A
AHRI Certified Reference Number			215493758	215493759	215493760	215493761	215493762	215493763
Power Supply		Ph-V-Hz	1Ph, 115V~60Hz	1Ph, 115V~60Hz	1Ph, 208-230V~60Hz	1Ph, 208-230V~60Hz	1Ph, 208-230V~60Hz	1Ph, 208-230V~60Hz
Cooling	Capacity: Rated (Min/Max)	Btu/h	9000 (3600-10000)	12000 (4000-13000)	9000 (3600-10000)	12000 (4000-13000)	18000 (6500-19000)	24000 (8000-25000)
	Input	W	641	980	659	978	1390	1959
	Rated Current	A	6	8.8	2.5	4.3	6.1	8.7
	EER2	Btu/w	14.05	12.25	13.65	12.25	12.95	12.25
	SEER2	Btu/w	23	22	25	23	21	22.5
Heating at 47°F	Capacity: Rated (Min/Max)	Btu/h	9500 (3600-10000)	12000 (4000-13000)	9000 (3600-10000)	12000 (4000-13000)	18000 (6500-19000)	24000 (8000-25000)
	Input	W	696	960	659	902	1426	1954
	Rated Current	A	6.4	8.6	3.1	4.1	6.5	9.3
	COP	W/W	4	3.66	4	3.9	3.7	3.6
	HSPF2	Btu/w	10	9.5	11	10	10	9.5
Heating Capacity at 5°F as calculated by M1 (AHRI)		Btu/h	8700	9200	9000	11000	18000	19200
Heating Capacity at -4°F		Btu/h	6250	6900	6700	7700	13700	14100
Heating Capacity at -13°F		Btu/h	4600	5900	5400	6100	11500	12100
Heating Capacity Ratio @ 5°F		%	92%	77%	100%	92%	100%	80%
Heating COP at 5°F as calculated by M1 (AHRI)		W/W	1.9	1.9	2.1	2	1.9	1.9
Minimum Circuit Ampacity		A	16	16	9.5	10.5	20	22
Maximum Fuse		A	25	25	15	15	30	35
Compressor	Model		TSN108D34UEZ3	TSN108D34UEZ3	TSN108D34UEZ3	TSN108D34UEZ3	TTN240D57UMT	TTN240D57UMT
	Type		Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
	Brand		GMCC	GMCC	GMCC	GMCC	GMCC	GMCC
Indoor Air Flow (H/M/L)		CFM	383/294/247	394/312/253	383/294/247	394/312/253	647/483/383	706/559/442
Indoor Noise Level (H/M/L)		dB(A)	39/37/35	40/37/35	39/37/35	39/37/35	45/41/39	48/43/41
Indoor Unit	Dimension(W*H*D)	inch	34 x 11 ½ x 8 ¾	34 x 11 ½ x 8 ¾	34 x 11 ½ x 8 ¾	34 x 11 ½ x 8 ¾	45 ¼ x 13 ¼ x 10	45 ¼ x 13 ¼ x 10
	Net/Gross Weight	lbs.	22/26.5	22/26.5	18.7/23	18.7/23	31/37.5	31/37.5
Outdoor Noise Level		dB(A)	53	53	53	53	58	61
Outdoor Unit	Dimension(W*H*D)	inch	28 x 21 ¼ x 9 ½	28 x 21 ¼ x 9 ½	28 x 21 ¼ x 9 ½	28 x 21 ¼ x 9 ½	32 x 23 x 11	34 x 25 ½ x 12 ¼
	Net/Gross Weight	lbs.	75/86	77/86	70.5/81.5	70.5/81.5	97/105.8	112.4/121.3
Refrigerant	Type		R454B	R454B	R454B	R454B	R454B	R454B
	Pre-Charge Length	ft	25	25	25	25	25	25
	Additional Refrigerant charge	oz/ft	0.22	0.22	0.22	0.22	0.22	0.32
Refrigerant Piping	Liquid Side - Gas Side	inch	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	3/8 - 5/8
	Max. Refrigerant Pipe Length	ft	65	65	65	65	98	98
	Max. Difference In Level	ft	49	49	49	49	49	49
Thermostat Type			Remote Control and Wifi (Wired Control Optional)					
Operation Temperature	Indoor (Cooling/Heating)	°F	62~90 / 32~86					
	Outdoor (Cooling/Heating)	°F	5~115 / -13~75					

DISTRIBUTED BY:



SCAN FOR PRODUCT INFORMATION



INNOVAIR.COM