

Bike rental API specification

List of all endpoints

All endpoints to be prepended by /api/v1.



Cities

GET /cities

GET /cities/{id}

POST /cities

PUT /cities

DELETE /cities/{id}



Cities

GET /cities

Get a JSON-representation of all cities.

Sample request

```
GET /api/v1/cities
```

Response

```
[
  {
    "id": 1,
    "name": "Karlskrona",
    "lat": 56.193,
    "lon": 15.628,
    "dlat": 0.02,
    "dlon": 0.03
  },
  {
    "id": 2,
    "name": "Stockholm",
    "lat": 59.325,
    "lon": 18.071,
    "dlat": 0.08,
    "dlon": 0.2
  }
]
```

```
]
```

HTTP Status Code: 200 OK

Note: `dlat` and `dlon` denote city extension northwards and eastwards respectively.

GET /cities/{id}

Get a JSON-representation of a specific city.

Sample request

```
GET /api/v1/cities/1
```

Response

```
{
  "id": 1,
  "name": "Karlskrona",
  "lat": 56.193,
  "lon": 15.628,
  "dlat": 0.02,
  "dlon": 0.03
}
```

HTTP Status Code: 200 OK

Note: `dlat` and `dlon` denote city extension northwards and eastwards respectively.

POST /cities

Add a new city.

Sample request

```
POST /api/v1/cities
```

Required body keys

(currently `x-www-form-urlencoded`)

```
name
lat  = latitude
lon  = longitude
```

```
dlat = north-south extension of city (≈radius)
dlon = east-west extension of city (≈radius)
```

Response (success)

```
{
  "count": 1,
  "newId": 3,
  "message": "Ok"
}
```

HTTP Status Code: 201 Created

Note: count is inserted row count and newId is the id of added city.

Response (failure, name already exists)

```
{
  "count": 0,
  "newId": -1,
  "message": "UNIQUE constraint failed: cities.name"
}
```

HTTP Status Code: 400 Bad Request

PUT /cities

Update a city.

Sample request

```
PUT /api/v1/cities
```

Required body keys

(currently x-www-form-urlencoded)

```
id    = city id to update
name  = new name
lat   = latitude
lon   = longitude
dlat  = north-south extension of city (≈radius)
dlon  = east-west extension of city (≈radius)
```

Response (success)

```
{
  "count": 1,
```

```
"message": "Ok"
}
```

HTTP Status Code: 200 OK

Note: count is updated row count.

Response (failure, name already exists)

```
{
  "count": 0,
  "message": "UNIQUE constraint failed: cities.name"
}
```

HTTP Status Code: 400 Bad Request

Response (failure, id not found)

```
{
  "count": 0,
  "message": "id not found"
}
```

HTTP Status Code: 400 Bad Request

DELETE /cities/{id}

Delete a city.

Sample request

```
DELETE /api/v1/cities/1
```

Response (success)

```
{
  "count": 1,
  "message": "Ok"
}
```

HTTP Status Code: 200 OK

Note: count is deleted row count.

Response (failure, id not found)

```
{  
  "count": 0,  
  "message": "id not found"  
}
```

HTTP Status Code: 400 Bad Request

© Vteam 2023 Group 8