



Kin Core Plugin for Unity

Unity plugin responsible for providing access to the Kin native SDKs for managing Kin balance and transactions.

Android Setup

The Kin plugin uses the Gradle build system on Android. See the [Building with Gradle for Android](#) section of Unity's documentation and the [Providing a custom build.gradle template](#) to enable the use of a custom gradle file.

Open the `Plugins/Android/mainTemplate.gradle` file and add the following:

```
...

allprojects {
    repositories {
        ...
        jcenter()
        google()
        maven { url 'https://jitpack.io' }
    }
}

...

dependencies {

    ...

    implementation 'com.github.kinecosystem:kin-sdk-android:1.0.1'
    **DEPS**}

...

android {
    compileOptions {
        sourceCompatibility 1.8
        targetCompatibility 1.8
    }

    ...
}
```

iOS Setup

In the iOS Player Settings, the Target minimum iOS Version must be set to 8.1 or newer.

Get Started

Connecting to a service provider

Create a new `KinClient`, with an `Environment` enum that provides details of how to access the kin blockchain end point, `Environment` provides the predefined `Environment.TEST` and `Environment.PRODUCTION`.

`appId` is a 4 character string which represent the application id which will be added to each transaction. `appId` must contain only upper and/or lower case letters and/or digits and that the total string length is exactly 4.

An optional parameter is `storeKey` which can be used to create a multiple accounts data set, each different `storeKey` will have a separate data, an example use-case - store multiple users accounts separately.

The example below creates a `KinClient` that will be used to connect to the kin test network:

```
kinClient = new KinClient( Environment.TEST, "1acd" )
```

Creating and retrieving a KIN account

The first time you use KinClient you need to create a new account, the details of the created account will be securely stored on the device. Multiple accounts can be created using AddAccount.

```
KinAccount account;
try
{
    if( !kinClient.HasAccount() )
        account = kinClient.AddAccount();
}
catch( Exception e )
{
    Debug.LogError( e );
}
```

Calling GetAccount with the existing account index, will retrieve the account stored on the device.

```
if( kinClient.HasAccount() )
    account = kinClient.getAccount( 0 );
```

You can delete your account from the device using DeleteAccount, but beware! you will lose all your existing KIN if you do this.

```
kinClient.DeleteAccount( int index );
```

Onboarding

Before an account can be used on the configured network, it must be funded with the native network asset. This step must be performed by a service, see the [Kin SDK documentation](#) for details.

The second step is to activate this account on the client side, using Activate method. The account will not be able to receive or send Kin before activation.

```
account.Activate( ex =>
{
    if( ex != null )
        Debug.LogError( "Activate Failed. " + ex );
    else
        Debug.Log( "Account activated" );
});
```

Account Information

Public Address

Your account can be identified via its public address. To retrieve the account public address use:

```
account.GetPublicAddress();
```

Query Account Status

Current account status on the blockchain can be queried using GetStatus method, status will be one of the following 2 options:

- AccountStatus.NotCreated - Account is not created (funded with native asset) on the network. The account cannot send or receive KIN yet.
- AccountStatus.Created - Account was created, account can send and receive KIN.

```
account.GetStatus( ( ex, status ) =>
{
    if( ex == null )
        Debug.Log( "Account status: " + status );
    else
        Debug.LogError( "Get Account Status Failed. " + ex );
});
```

Retrieving Balance

To retrieve the balance of your account in KIN call the GetBalance method:

```
account.GetBalance( ( ex, balance ) =>
{
    if( ex == null )
        Debug.Log( "Balance: " + balance );
    else
        Debug.LogError( "Get Balance Failed. " + ex );
});
```

Transactions

Transferring Kin to another account

To transfer Kin to another account, you need the public address of the account you want to transfer the KIN to. Also if your app is not in the Kin whitelist then you need to also apply a fee. Amount of 1 fee equals to 1/100000 KIN. If you are in the whitelist then look after the next example to see how you can send a whitelist transaction.

The following code will transfer 20 Kin to the recipient account
"GDIRGGTBE3H4CUIHNIFZGUECGFQ5MBGIZTPWGUHPIEVOOHFHSCAGMEHO".

```
var toAddress = "GDIRGGTBE3H4CUIHNIFZGUECGFQ5MBGIZTPWGUHPIEVOOHFHSCAGMEHO";
var amountInKin = 20;
var fee = 100;

// we could use here some custom fee or we can call the blockchain in order to retrieve
// the current minimum fee by calling kinClient.getMinimumFee(). Then when you get the minimum
// fee returned and you can start the 'send transaction flow' with this fee.
account.BuildTransaction( toAddress, amountInKin, fee, ( ex, transaction ) =>
{
    if( ex == null )
    {
        // Here we already got a Transaction object before actually sending the transaction. This means
        // that we can, for example, send the transaction id to our servers or save it locally
        // in order to use it later. For example if we lose network just after sending
        // the transaction then we will not know what happened with this transaction.
        // So when the network is back we can check what is the status of this transaction.
        Debug.Log( "Build Transaction result: " + transaction );
        account.SendTransaction( transaction, ( ex, transactionId ) =>
        {
            if( ex == null )
                Debug.Log( "Send Transaction result: " + transactionId );
            else
                Debug.LogError( "Send Transaction Failed. " + ex );
        });
    }
    else
    {
        Debug.LogError( "Build Transaction Failed. " + ex );
    }
});
```

Transferring Kin to another account using whitelist service

The flow is very similar to the above code but here there is a middle stage in which you get the WhitelistedTransaction details from the 'Transaction' object just after you build the transaction and you send it to the whitelist service. Then you just use the method 'sendWhitelistTransaction(string whitelist)' and the parameter for that method is what you got from that service.

```
account.BuildTransaction( toAddress, amountInKin, fee, ( ex, transaction ) =>
{
    if( ex == null )
    {
        Debug.Log( "Build Transaction result: " + transaction );

        var whitelistTransaction = YourWhitelistService.WhitelistTransaction( transaction );
        account.SendWhitelistTransaction( transaction.Id, whitelistTransaction, ( ex, transactionId ) =>
        {
            if( ex == null )
                Debug.Log( "Send Transaction result: " + transactionId );
            else
                Debug.LogError( "Send Transaction Failed. " + ex );
        });
    }
});
```

```

    else
    {
        Debug.LogError( "Build Transaction Failed. " + ex );
    }
});

```

Memo

Arbitrary data can be added to a transfer operation using the memo parameter, the memo can contain a utf-8 string up to 21 bytes in length. A typical usage is to include an order number that a service can use to verify payment.

```

var memo = "arbitrary data";

account.BuildTransaction( toAddress, amountInKin, fee, memo, ( ex, transaction ) =>
{
    if( ex == null )
    {
        // Here we already got a Transaction object before actually sending the transaction. This means
        // that we can, for example, send the transaction id to our servers or save it locally
        // in order to use it later. For example if we lose network just after sending
        // the transaction then we will not know what happened with this transaction.
        // So when the network is back we can check what is the status of this transaction.
        Debug.Log( "Build Transaction result: " + transaction );
        account.SendTransaction( transaction, ( ex, transactionId ) =>
        {
            if( ex == null )
            {
                Debug.Log( "Send Transaction result: " + transactionId );
            }
            else
            {
                Debug.LogError( "Send Transaction Failed. " + ex );
            }
        });
    }
    else
    {
        Debug.LogError( "Build Transaction Failed. " + ex );
    }
});

```

```

account.SendTransaction( toAddress, amountInKin, memo, ( ex, transactionId ) => { if( ex == null ) Debug.Log( "Send Transaction: " +
transactionId ); else Debug.LogError( "Send Transaction Failed. " + ex ); });

```

Account Listeners

Listening to payments

Ongoing payments in Kin, from or to an account, can be observed, by adding payment listener:

```

```csharp
account.AddPaymentListener(this);

...

public void OnEvent(PaymentInfo payment)
{
 Debug.Log("On Payment: " + payment);
}

```

## Listening to balance changes

Account balance changes, can be observed by adding balance listener:

```

account.AddBalanceListener(this);

...

public void OnEvent(decimal balance)
{
 Debug.Log("On Balance: " + balance);
}

```

## Listening to account creation

Account creation on the blockchain network, can be observed, by adding create account listener:

```
account.AddAccountCreationListener(this);

...

public void OnEvent()
{
 Debug.Log("On Account Created");
}
```

To unregister any listener use `RemovePaymentListener`, `RemoveBalanceListener` or `RemoveAccountCreationListener` methods.

## Error Handling

The Kin Unity Plugin wraps Kin native exceptions in the C# `KinException` class. It provides a `NativeType` field that will contain the native error type, some of which are in the Common Error section that follows.

### Common Errors

`AccountNotFoundException` - Account is not created (funded with native asset) on the network.

`AccountNotActivatedException` - Account was created but not activated yet, the account cannot send or receive KIN yet.

`InsufficientKinException` - Account has not enough kin funds to perform the transaction.

## Demo Scene

The demo scene included with the Kin Unity Plugin covers the functionality of the plugin, and serves as a detailed example on how to use the it.

## Contributing

Please review our [CONTRIBUTING.md](#) guide before opening issues and pull requests.

## License

The kin-unity-plugin is licensed under [MIT license](#).