

LANDCO NEXA | BISSONNET 136, LLC

Development Standards

International Trade Park Houston

12000 Bissonnet Street, Houston, Texas 77099

136 Acres | 30 Lots | Mixed-Use Master-Planned Development

CONFIDENTIAL

Prepared by LANDCO NEXA

May 2026 | Version 1.0

1. Introduction & Project Vision

International Trade Park Houston (ITPH) is a 136-acre master-planned mixed-use development located at 12000 Bissonnet Street in Southwest Houston, Texas. The project encompasses 30 individually developable lots across four distinct use categories — multifamily residential, retail/commercial, flex/office-warehouse, and commercial/light industrial — supported by a unified infrastructure platform, MUD 584 bond reimbursement structure, and a comprehensive governance framework established through recorded CC&Rs.

These Development Standards establish the minimum quality expectations for all improvements within the community. They are intended to protect property values across the development, ensure a cohesive and professional built environment, provide predictability for lot buyers and their lenders, and position ITPH as a premier mixed-use district in the Houston market.

The standards set a quality floor — not a ceiling. Owners are encouraged to exceed these minimums. All development plans remain subject to review and approval by the Architectural Review Committee (ARC) established under the Declaration of Covenants, Conditions, Restrictions and Easements for ITP Houston (the “CC&Rs”), which are recorded against the property and govern all lots.

Project Identity

ITPH is not a conventional industrial park or a generic land subdivision. It is a planned economic ecosystem where industrial operations, workforce housing, neighborhood retail, and flexible commercial space coexist by design. The development is bounded by Cook Road to the west, S Kirkwood Road to the east, and Bissonnet Street to the south, with internal loop circulation connecting all districts. The site’s proximity to Beltway 8, the Energy Corridor, the Westchase District, and the Alief community’s diverse workforce provides a strong demand foundation for each use type.

Development within ITPH should reflect this intentional character — buildings that are well-designed, professionally constructed, and respectful of adjacent uses.

2. Applicability & Review Process

2.1 Applicability

These Development Standards apply to all new construction, exterior modifications, and site improvements on every lot within ITPH. No building permit application shall be submitted to the City of Houston until the owner has received written approval from the ARC confirming compliance with these standards and the CC&Rs.

2.2 Review Process

The development review process follows three steps:

- **Pre-Application Conference:** Lot owners or their design teams are encouraged to meet with the ARC prior to preparing formal plans to discuss the proposed use, building program, and design approach.

- **Plan Submission:** Complete architectural, site, landscape, and signage plans must be submitted to the ARC for review. Submissions must demonstrate compliance with these standards, the CC&Rs, and all applicable City, MUD, and TCEQ requirements.
- **ARC Approval:** The ARC will issue written approval, conditional approval with required modifications, or denial with stated reasons. Approval must be obtained before any building permit application, grading, or construction activity.

2.3 Relationship to CC&Rs

These Development Standards supplement the CC&Rs. In the event of a conflict, the CC&Rs govern. The ARC may adopt additional design guidelines by resolution without re-recording the CC&Rs, provided such guidelines are consistent with the recorded declaration.

3. Permitted Uses by District

ITPH is organized into four use districts. The following table summarizes the permitted uses, applicable lots, and approximate acreage for each district. All uses must comply with the CC&Rs (Section 2.1) and the Use Compatibility Standard (Section 2.4).

District	Lots	Acres	Permitted Uses
Multifamily	14, 15, 16	36.62 ac	Market-rate and affordable multifamily residential Workforce housing and senior living Accessory leasing offices, amenity buildings, recreation
Retail / Commercial	2–4, 8, 17, 19–30	23.48 ac	Neighborhood retail, restaurant, and service uses Professional and medical office Financial institutions, convenience retail, fuel stations (screened)
Flex	1, 5–7, 9, 13	21.55 ac	Flex/office-warehouse, light assembly, R&D Technology and data operations Showroom, distribution with office component
Commercial / Light Industrial	10–12, 18	6.00 ac	Light manufacturing, assembly, and fabrication Warehousing and logistics Automotive service (fully enclosed or screened)

Prohibited uses are defined in the CC&Rs (Section 2.2) and include heavy industrial operations, hazardous waste facilities, outdoor salvage or unscreened storage, adult-oriented businesses, and any use that violates MSD, TCEQ, or City requirements.

4. Site Planning & Setbacks

4.1 Minimum Setbacks

The following minimum setbacks apply. The ARC may require increased setbacks where adjacent uses warrant additional separation or where City or MUD requirements are more restrictive.

Condition	Multifamily	Retail	Flex	Industrial
Front (street-facing)	25 ft	15 ft	25 ft	30 ft
Side (interior)	15 ft	10 ft	15 ft	20 ft
Side (adjacent to MF)	15 ft	15 ft	25 ft	30 ft
Rear	20 ft	15 ft	20 ft	25 ft

4.2 Building Orientation

Primary building entrances shall face internal roads or shared circulation drives. Loading docks, service areas, and refuse collection points shall be oriented away from adjacent multifamily lots and street frontages to the maximum extent practicable.

4.3 Maximum Lot Coverage

Maximum impervious coverage shall not exceed 75% of the lot area for retail and commercial lots, and 80% for flex and industrial lots, unless otherwise approved by the ARC in coordination with MUD 584 stormwater requirements. Multifamily lots shall comply with City of Houston multifamily development standards for open space and impervious cover.

4.4 Grading and Drainage

All site grading must comply with the approved MUD 584 infrastructure design and the Kimley-Horn civil engineering plans for the community. No owner shall alter drainage patterns in a manner that adversely affects adjacent lots, common areas, or detention facilities. All stormwater detention and retention obligations must be satisfied per MUD and City requirements.

5. Architectural Standards

All buildings within ITPH shall present a professional, well-maintained appearance that reflects the quality of the overall development. The following material and design standards apply by district.

5.1 Exterior Materials — Multifamily District

- Primary facades (street-facing): Minimum 65% masonry (brick, stone, or stone veneer). Cementitious fiber board (HardiePlank or equivalent) permitted on secondary elevations.
- Accent materials: Architectural metal panel, glass curtain wall, stucco, and EIFS are permitted as accent elements (maximum 20% of any single facade).
- Roof: Composition shingle, standing seam metal, or membrane roofing systems. All roof-mounted equipment must be screened from view at ground level.

5.2 Exterior Materials — Retail / Commercial District

- Primary facades: Masonry, stone, architectural precast, or glass storefront systems on all street-facing and customer-facing elevations.
- EIFS is permitted only as an accent material (maximum 15% of any facade). EIFS may not be used below 8 feet on any elevation.
- Secondary facades not visible from streets or adjacent lots may use painted concrete masonry units (CMU) with a split-face or burnished finish.

5.3 Exterior Materials — Flex District

- Primary facades (street-facing): Architectural tilt-up concrete with reveals, texture, or color variation. Insulated metal panel systems are permitted on primary facades provided they include color banding or material variation.
- Office components and front entries shall incorporate glass, masonry, or composite panel systems to differentiate the office portion from the warehouse/flex area.
- Secondary facades: Insulated metal panel, painted tilt-up concrete, or engineered metal wall systems.

5.4 Exterior Materials — Commercial / Light Industrial District

- Primary facades (street-facing): Tilt-up concrete with architectural treatment (reveals, form liners, integral color, or applied texture). Minimum one design feature per 100 linear feet of facade to break visual monotony.
- Secondary facades: Tilt-up concrete, insulated metal panel, or engineered metal wall systems.
- Office entries and visitor-facing areas: Glass, masonry accent, or composite panel to distinguish public-facing elements.

5.5 Prohibited Materials (All Districts)

- Unfinished or plain concrete masonry units (CMU) on any facade visible from a street or adjacent lot
- Corrugated metal siding, T-111 or similar wood-grain sheet panels

- Vinyl siding, aluminum siding
- Untreated or unfinished plywood or particle board
- Exposed concrete block without architectural finish

5.6 Building Height

Building heights shall comply with City of Houston requirements. As general guidance: multifamily buildings are anticipated at 3–4 stories; retail and commercial buildings at 1–2 stories; flex and industrial buildings at 1–2 stories with clear heights appropriate to intended use. The ARC may approve taller structures where the design is compatible with adjacent development.

5.7 Roof Equipment Screening

All rooftop mechanical equipment, HVAC units, exhaust fans, and satellite dishes shall be screened from ground-level view from adjacent lots and public rights-of-way. Screening shall be architecturally integrated with the building design using materials compatible with the primary facade.

6. Signage Standards

All signage within ITPH is governed by the Signage Matrix recorded as Exhibit B of the CC&Rs. The matrix establishes maximum sign areas, heights, setbacks, and illumination standards by use type. The following is a summary of key provisions; the full Signage Matrix in the CC&Rs is the controlling document.

6.1 Key Provisions by Use Type

Use Type	Monument (max)	Height (max)	Setback (min)	Building Sign	Illumination
Retail	120 SF	10 ft	10 ft	1.0 SF/LF	Dusk–11 PM, shielded
Multifamily	100 SF	8 ft	10 ft	120 SF/bldg	Dusk–11 PM, shielded
Light Industrial	80 SF	8 ft	15 ft	0.75 SF/LF	Security lighting; no spillover
Flex / Office-WH	100 SF	8 ft	10 ft	0.9 SF/LF	Dusk–11 PM, shielded

6.2 General Signage Requirements

- All signage requires ARC approval prior to fabrication and installation.
- No pole signs are permitted in any district.
- No flashing, blinking, moving, or intermittent lighting is permitted.
- Electronic message centers require ARC approval and must comply with brightness and dwell time standards.
- Temporary construction signs are limited to 32 SF and must be removed within 10 days of certificate of occupancy or sale.

7. Screening & Service Areas

The CC&Rs (Section 2.4) require that loading, refuse, and service functions be located and screened to minimize visibility and impacts to adjoining lots. The following standards apply:

7.1 Loading and Service Areas

- Loading docks shall be oriented away from street frontages and adjacent multifamily lots where practicable.
- Where loading areas face a street or multifamily lot, a minimum 6-foot masonry or decorative screen wall is required, with landscaping at the base.
- Truck queuing and staging areas shall be on-site and shall not extend into public rights-of-way or internal circulation drives.

7.2 Refuse and Dumpster Enclosures

- All dumpsters and refuse containers shall be enclosed within a masonry screen wall with opaque gates, minimum 6 feet in height.
- Enclosures shall be located to the rear or side of buildings, away from primary entries and street frontages.
- Enclosure materials shall be compatible with the primary building facade.

7.3 Outdoor Storage

Outdoor storage is generally prohibited per the CC&Rs (Section 2.2). Where the ARC approves limited outdoor storage for flex or industrial uses, it must be fully screened from view from adjacent lots and streets by a minimum 8-foot opaque fence or wall with landscaping.

7.4 Mechanical Equipment

Ground-mounted mechanical equipment (HVAC condensers, generators, utility transformers) shall be screened from view from adjacent lots and streets by walls, fencing, or dense landscaping at least as tall as the equipment. Screening materials shall be compatible with the building facade. Rooftop equipment screening is addressed in Section 5.7.

8. Landscape & Hardscape

Landscaping within ITPH shall reinforce the professional character of the development, soften building edges, screen service areas, and buffer between incompatible uses. All landscape plans require ARC approval.

8.1 Minimum Landscape Coverage

- Multifamily lots: Minimum 20% of total lot area shall be landscaped open space.
- Retail and commercial lots: Minimum 15% of total lot area.
- Flex and industrial lots: Minimum 10% of total lot area.

8.2 Street Trees

Shade trees shall be planted at a minimum rate of one tree per 40 linear feet of street frontage along internal roads and perimeter boundaries. Trees shall be a minimum 3-inch caliper at installation and shall be selected from species adapted to the Houston climate and Harris County soil conditions.

8.3 Parking Lot Landscaping

Parking areas with more than 30 spaces shall include interior landscape islands at a minimum rate of one island per 15 spaces. Islands shall contain at least one shade tree and ground cover. Perimeter parking lot landscaping shall provide a minimum 5-foot landscape strip with shrubs and groundcover adjacent to streets and neighboring lots.

8.4 Buffers Between Districts

Where flex or industrial lots are adjacent to multifamily lots, a minimum 15-foot landscape buffer is required, incorporating a combination of evergreen trees, shrubs, and/or a 6-foot masonry or decorative wall. The buffer requirement may be satisfied within the setback area.

8.5 Irrigation

All required landscape areas shall be provided with a permanent, automatic irrigation system. Drip irrigation and water-efficient systems are encouraged.

9. Lighting & Security

Exterior lighting shall provide safe and functional illumination while minimizing glare, light trespass, and impacts on adjacent properties. The CC&Rs (Section 2.4) require that all exterior lighting be shielded and directed downward and inward.

9.1 General Requirements

- All exterior lighting fixtures shall be full cutoff or shielded to prevent direct light emission above the horizontal plane.
- Light levels at any property line shall not exceed 0.5 foot-candles, measured at grade.
- Parking lot pole lights shall not exceed 30 feet in height.

- Building-mounted security lighting shall be shielded and directed downward.

9.2 Prohibited Lighting

- Unshielded floodlights or spotlights directed toward adjacent properties or public rights-of-way.
- Flashing, blinking, or moving lights (except required safety lighting).
- Mercury vapor or high-pressure sodium fixtures in customer-facing areas (LED or metal halide preferred).

10. Parking & Circulation

Parking shall comply with City of Houston requirements. The following minimums apply as general guidance; the ARC may require additional parking based on specific use intensity.

Use Type	Minimum Ratio	Notes
Multifamily	1.5 spaces/unit	Per City of Houston MF code
Retail / Commercial	1 space/250 SF GLA	Per City of Houston
Office	1 space/300 SF	Per City of Houston
Flex / Warehouse	1 space/500 SF office + 1/1,000 SF warehouse	ARC may adjust for use intensity
Light Industrial	1 space/1,000 SF	Plus employee count requirements

Drive aisles shall be a minimum 24 feet wide for two-way traffic and 18 feet for one-way. Fire lanes shall comply with City requirements. Shared parking arrangements between adjacent lots are encouraged and may be facilitated through the reciprocal easement provisions of the CC&Rs (Article VII).

11. Sustainability & Stormwater

All development within ITPH must comply with the MUD 584 drainage infrastructure design prepared by Kimley-Horn. Stormwater detention and retention obligations are defined at the lot level and must be satisfied in coordination with the community-wide system.

11.1 Stormwater Management

- Lot owners shall connect to the MUD 584 storm drainage system at designated connection points as shown on the civil engineering plans.
- On-site detention may be required where lot development exceeds the pre-development runoff assumptions in the MUD engineering. The ARC and MUD engineer will confirm requirements during plan review.
- Community detention ponds and channels (24.27 acres) are maintained as common infrastructure. No owner shall discharge into or modify these facilities without approval.

11.2 Sustainable Design Encouraged

While not required, the following sustainable design practices are encouraged and may receive favorable ARC consideration: high-efficiency HVAC and lighting systems, cool roof materials, permeable paving in non-load-bearing areas, native and drought-tolerant landscape species, electric vehicle charging infrastructure, and water-efficient irrigation systems.

12. General Disclaimer & Modification Rights

12.1 Disclaimer

These Development Standards are provided as general design guidance for lot owners and their design professionals. They are not intended as a substitute for professional architectural, engineering, or legal advice. Each lot owner is responsible for engaging licensed professionals to prepare construction documents that comply with all applicable codes, regulations, and permit requirements.

Neither the Declarant, the Association, the ARC, nor their respective agents, representatives, or advisors make any warranty or representation regarding the completeness, accuracy, or sufficiency of these standards for any particular lot or use. Compliance with these standards does not guarantee approval by the City of Houston, MUD 584, TCEQ, or any other regulatory authority.

12.2 Right to Modify

The Declarant (during the Declarant Control Period) and the Association (thereafter) reserve the right to modify, supplement, or update these Development Standards at any time, consistent with the CC&Rs. Modifications may be adopted by ARC resolution without re-recording the CC&Rs, provided they do not conflict with the recorded declaration. Lot owners will be notified of material modifications.

12.3 Architectural Review Required

No provision of these Development Standards shall be construed to waive or reduce the requirement for ARC approval of all improvements. The ARC retains discretion to impose conditions, require modifications, or deny proposals that do not meet the overall quality and compatibility objectives of the community, even where the proposal technically complies with the minimum standards set forth herein.

12.4 Environmental Compliance

All development within ITPH is subject to the environmental covenants established in the CC&Rs (Article V), including compliance with the Municipal Setting Designation (MSD) and all TCEQ orders and requirements. Owners must obtain TCEQ authorization (TCEQ-20787) prior to any soil disturbance, excavation, or trenching activity. Environmental compliance is a prerequisite for ARC approval and building permit issuance.

Prepared for Bissonnet 136, LLC by LANDCO NEXA.

International Trade Park Houston | 12000 Bissonnet Street, Houston, TX 77099

May 2026 | Version 1.0