Lista REDIS – ubuntu server

1 a 16

```
davi@davi:~/nosql/redis$ docker run -d --name redis-lab -p 127.0.0.1:6380:6379 redis:7-alpine
Unable to find image 'redis:7-alpine' locally
7-alpine: Pulling from library/redis
4eb14bae0e1d: Pull complete
7eb50503c2b0: Pull complete
16333ee0c00f: Pull complete
83234986c742: Pull complete
4f4fb700ef54: Pull complete
1522f9c6f453: Pull complete
9928009b15c8: Pull complete
54779914f171: Download complete
3beebc06c4ca: Download complete
Digest: sha256:858f009f9709ce576febc734aa78b8f6d624b82571f9ddb6bda4377c833b3499
Status: Downloaded newer image for redis:7-alpine
cd2a96a1985d4a44d6fc0f8f5fbf3af8528690d5710d0c8947f5e04329662470
davi@davi:~/nosql/redis$ docker exec redis-lab redis-cli PING
PONG
davi@davi:~/nosql/redis$ docker exec -it redis-lab redis-cli
127.0.0.1:6379> SET sistema:nome "DataPlatform"
OK
127.0.0.1:6379> GET sistema:nome
"DataPlatform"
127.0.0.1:6379> MSET env:db "postgres" env:cache "redis" env:queue "rabbitmq"
OK
127.0.0.1:6379> MGET env:db env:cache
1) "postgres"
2) "redis"
127.0.0.1:6379> SETEX sessao:usuario:101 30 "xyz123"
OK
127.0.0.1:6379> TTL sessao:usuario:101
(integer) 27
127.0.0.1:6379> INCR pageviews:home
(integer) 1
127.0.0.1:6379> INCRBY pageviews:home 5
(integer) 6
127.0.0.1:6379> DECRBY pageviews:home 2
(integer) 4
127.0.0.1:6379>
```

```
127.0.0.1:6379> HSET usuario:201 nome "Carlos" email "carlos@email.com" nivel "admin"
(integer) 3
127.0.0.1:6379> HGET usuario:201 email
"carlos@email.com"
127.0.0.1:6379> HGETALL usuario:201
1) "nome"
2) "Carlos"
3) "email"
4) "carlos@email.com"
5) "nivel"
6) "admin"
127.0.0.1:6379> HINCRBY usuario:201 tentativas_login 1
(integer) 1
127.0.0.1:6379> HKEYS usuario:201
1) "nome"
2) "email"
3) "nivel"
4) "tentativas_login"
127.0.0.1:6379> RPUSH fila:email "email_1" "email_2" "email_3"
(integer) 3
127.0.0.1:6379> LPOP fila:email
"email_1"
127.0.0.1:6379> LRANGE fila:email 0 -1
1) "email_2"
2) "email_3"
127.0.0.1:6379>
```

```
127.0.0.1:6379> SADD tags:post:1 "dados" "redis" "nosql" "redis"
(integer) 3
127.0.0.1:6379> SCARD tags:post:1
(integer) 3
127.0.0.1:6379> SADD tags:post:2 "redis" "python" "backend"
(integer) 3
127.0.0.1:6379> SINTER tags:post:1 tags:post:2
1) "redis"
127.0.0.1:6379>
127.0.0.1:6379> SISMEMBER tags:post:1 "python"
(integer) 0
127.0.0.1:6379> ZADD placar:game 1500 "alice" 2200 "bob" 1800 "carol"
(integer) 3
127.0.0.1:6379> ZREVRANGE placar:game 0 -1 WITHSCORES
1) "bob"
2) "2200"
3) "carol"
4) "1800"
5) "alice"
6) "1500"
127.0.0.1:6379> ZINCRBY placar:game 800 "alice"
"2300"
127.0.0.1:6379> ZREVRANK placar:game "alice"
(integer) 0
127.0.0.1:6379>
```

NOTIFICAÇÕES (17)



Exercícios 18 a 20

```
davi@davi:~/nosql/redis$ docker exec -it redis-lab redis-cli
127.0.0.1:6379> SET conta:A 100
OK
127.0.0.1:6379> SET conta:B 50
OK
127.0.0.1:6379> MULTI
OK
127.0.0.1:6379(TX)> DECRBY conta:A 50
QUEUED
127.0.0.1:6379(TX)> INCRBY conta:B 50
QUEUED
127.0.0.1:6379(TX)> EXEC
1) (integer) 50
2) (integer) 100
127.0.0.1:6379> MGET conta:A conta:B
1) "50"
2) "100"
127.0.0.1:6379> EXISTS sistema:nome
(integer) 1
127.0.0.1:6379> RENAME sistema:nome sistema:app
OK
127.0.0.1:6379> DEL sistema:app
(integer) 1
127.0.0.1:6379> INFO memory
# Memory
used_memory:1812112
used_memory_human:1.73M
used_memory_rss:9203712
used_memory_rss_human:8.78M
used_memory_peak:1908936
used_memory_peak_human:1.82M
used_memory_peak_perc:94.93%
used_memory_overhead:951640
used_memory_startup:948360
used_memory_dataset:860472
used_memory_dataset_perc:99.62%
allocator_allocated:2814096
allocator_active:3010560
allocator_resident:5853184
allocator_muzzy:0
total_system_memory:3169456128
total_system_memory_human:2.95G
used_memory_lua:32768
used_memory_vm_eval:32768
```

```
127.0.0.1:6379> FLUSHDB
OK
127.0.0.1:6379> DBSIZE
(integer) 0
127.0.0.1:6379>
```