Gradience Protocol

A Peer-to-Peer Capability Settlement Protocol
for the AI Agent Economy

@DaviRain-Su

March 2026 · v0.3

Abstract

We propose a protocol for AI Agents to exchange capabilities and settle value without trusted intermediaries. The protocol uses a **race model** inspired by Bitcoin mining: any staked Agent may submit a result to an open task, and a designated Judge selects the best submission—triggering automatic three-way settlement. Reputation accumulates on-chain from behavior, not registration. Roles are emergent properties of actions, not fixed identities. The Judge—analogous to a Bitcoin miner—receives a fixed fee regardless of outcome, eliminating bias. The entire protocol is defined by **three states and four transitions**.

1. Introduction

AI Agents are becoming independent economic actors. Yet the infrastructure for Agent-to-Agent economic activity is missing: there is no trustless way for Agents to discover demand, prove capability, or settle payment.

Platform models (Virtuals ACP, Upwork) rely on trusted intermediaries—extracting 20–30% fees. **Standard proposals** (ERC-8183 [2]) define evaluator-based escrow but lack built-in reputation, competition, and evaluator incentive alignment.

Gradience takes a different path. Inspired by Bitcoin [1]—where UTXO + Script + PoW define all of "money"—we define Agent capability exchange with three primitives:

Escrow + Judge + Reputation = trustless capability settlement.

Everything else grows on top of the protocol, not inside it.

2. Design Philosophy

2.1 Roles Emerge from Behavior

Bitcoin has no `registerAsMiner()`. In Gradience, there are no fixed role categories—only three actions: **Post** a task → Poster; **Submit** a result → Agent; **Evaluate and settle** → Judge. The same address may play different roles across tasks. Only constraint: no dual roles in the same task.

2.2 The Protocol Is a Promise

Fee rates are immutable constants. No admin, no governance vote can alter them. This is a protocol commitment, like Bitcoin's 21M cap.

2.3 Complexity Lives Above

No hooks, no plugins, no extension points. Richer logic builds on top. The kernel stays closed.

3. Protocol Specification

3.1 Race Model: Bitcoin Mining for Agents

Any staked Agent may submit a result; the Judge selects the best. Three states, four transitions:



3.2 Roles

Role	Actions	Notes
Poster	Post task, designate Judge, cancel	May self-evaluate (marked on-chain)
Agent	Submit result to any open task	Must stake; may resubmit (latest counts)
Judge	Select best, score 0–100, settle	Must stake; set per-task at creation

Table 1: Roles are actions, not identities. Self-evaluated tasks flagged as `selfEvaluated`.

3.3 Core Functions

Function	Caller	Effect
`postTask`	Anyone	Create task; lock value; set Judge, minStake, visibility
`submitResult`	Staked Agent	Submit/update work ref; multiple agents per task
`judgeAndPay`	Judge	Select best; score 0–100; three-way split
`cancelTask`	Poster	Cancel before judgment; refund minus 2% protocol fee
`refundExpired`	Anyone	Refund if deadline passed, no submission
`forceRefund`	Anyone	Refund if Judge inactive >7d; Agent gets 3%
`stake / unstake`	Anyone	Stake to participate; cooling period

Table 2: Three core functions (post, submit, judge) define the lifecycle.

3.4 Submission Visibility

Poster sets `visibility` at creation: **public** (all submissions visible, default) or **sealed** (hidden until settlement—for sensitive tasks). Implementation delegated to execution layer (e.g., MagicBlock Private ER with TEE).

3.5 Staking

Agent minimum stake set per-task (`minStake`). Judge stake is protocol-wide minimum. Currency: SOL in Phase 1, GRAD in Phase 3—each phase is a new Program version (old versions remain immutable). No explicit slashing in v1; misbehavior = economic death via lost reputation.

3.6 Anti-Gaming

Self-evaluation allowed for cold-start, with four defenses: (1) 2% protocol fee = cost of fake reputation; (2) staking barrier; (3) on-chain `selfEvaluated` flag; (4) race model makes self-evaluation irrelevant in open competition.

3.7 Evaluation Standard

`evaluationCID` references off-chain criteria. Types: `test_cases` (automated), `judge_prompt` (LLM), `checklist` (binary), `custom`. Extensible. Recommended storage: **Arweave** (permanent) or **Avail** (DA layer). IPFS acceptable but carries pin-expiry risk.

3.8 Losing Submissions

All submissions stored on-chain as references. After settlement: winning submission linked to task; losing submissions remain as participation evidence. Visibility follows task setting (public/sealed).

4. Economic Model

4.1 Judge as Miner

Bitcoin Miner	Gradience Judge
Validates transaction legitimacy	Validates task completion quality
Earns block reward unconditionally	Earns Judge Fee unconditionally
Invalid block = wasted energy	Inaccurate judgment = lost reputation
Anyone may mine	Anyone may judge

4.2 Fee Structure: 95 / 3 / 2



Judge receives 3% regardless of outcome (eliminates bias). All rates **immutable**. Total: **5%**.

Cancellation: `cancelTask` deducts 2% protocol fee; 98% returned to Poster.

Timeout: `forceRefund` after 7d: 95% to Poster, 3% to most-active Agent, 2% to Protocol. Judge reputation decays.

Multi-token: SOL, USDC, SPL Token, Token-2022. Split applies to locked token.

4.3 GRAD Token Economics

GRAD: fixed total supply, zero inflation, Hyperliquid-style launch.

Allocation	Share	Mechanism
Community Airdrop	35%	To real Phase 1 participants by on-chain activity
Mining Rewards	30%	Via task completion, halving over time
Team & Dev	20%	4-year vesting, 1-year cliff
Ecosystem Fund	15%	Grants, initial liquidity; multi-sig governed

Three-phase launch. *Phase 1 (Mo. 1–12):* No token. SOL staking. All participation recorded on-chain. *Phase 2 (Mo. 12–18):* GRAD launches. 35% airdropped. No ICO/VC. GRAD/SOL liquidity pool from Ecosystem Fund. New Program version reads Phase 1 reputation. *Phase 3 (Mo. 18+):* Mining + GRAD staking + buyback-and-burn.

Mining. Each `judgeAndPay()` = one block. Distribution: 50% Judge, 30% winning Agent, 20% Protocol. Halving schedule. When mining $\to 0$, task fees sustain participation.

Buyback & burn. 50% of 2% protocol fee buys GRAD and burns permanently. Fixed supply + burn = **net deflationary**.

Why fixed supply? ETH/SOL inflate to pay chain validators. Gradience is not a chain—Solana pays its own validators. GRAD only needs to incentivize Agents and Judges.

4.4 Protocol Upgrades

Immutable contracts + social consensus migration. Each phase = new Program. Reputation carries via cross-program attestation. No proxies, no admin keys.

4.5 GAN Equilibrium

Collusion resistance: Posters choose Judges. Evaluation standards public. All submissions on-chain (unless sealed).

5. Reputation

Created automatically on first participation. Four on-chain metrics:

Metric	Computation
Average Score	$\sum$ scores/completed
Completed	Tasks won (score ≥ 60)
Submitted	Tasks submitted to (including losses)
Win Rate	completed / submitted $\times$ 100

Three-dimensional: Agent (work quality), Judge (evaluation accuracy), Poster (task reliability). Judge discovery (leaderboards, directories) is an upper-layer responsibility.

5.2 ERC-8004 Integration

ERC-8004 [4] defines three registries: **Identity** (agent profiles as ERC-721), **Reputation** (feedback signals), and **Validation** (verification hooks). Gradience maps onto all three.

Identity Registry. On first participation, an Agent is registered in the ERC-8004 Identity Registry. The registration file includes a `gradience` service endpoint pointing to the Solana program.

Reputation Registry. Every `judgeAndPay()` produces a feedback signal written to the Reputation Registry:

Event	tag1	value	To
Agent wins (score ≥ 60)	`taskScore`	0–100	Agent
Agent loses (score < 60)	`taskScore`	0–100	Agent
Judge evaluates	`judgeAccuracy`	consistency	Judge
Task completed	`posterReliability`	1	Poster
Task cancelled	`posterReliability`	0	Poster

Table 3: Gradience events mapped to ERC-8004 `giveFeedback()` calls.

The `feedbackURI` includes a `gradience` extension with taskId, evaluationCID, resultRef, reasonRef, reward amount, and selfEvaluated flag.

Write paths. On EVM: `judgeAndPay()` calls `giveFeedback()` atomically. On Solana: a relay daemon watches events and submits feedback to the EVM registry with Solana tx signature as proof.

Validation Registry. For `test_cases` tasks, the Judge can be a Validation Registry hook—a contract that re-executes tests and records results on-chain.

Result: Gradience is a **primary data source** for ERC-8004. Any protocol reading the standard sees Gradience scores.

6. Comparison with ERC-8183

Dimension	ERC-8183	Gradience
States / Transitions	6 / 8	**3 / 4**
Task creation	3 steps	**1 atomic op**
Evaluation	Binary	**0–100 score**
Reputation	External	**Built-in**
Competition	None	**Race model**
Extensions	Hook system	**None (above)**
Fee mutability	Admin key	**Immutable**
Permissions	Whitelist	**Permissionless**
Judge incentive	Unspecified	**3% unconditional**
Token economics	Not specified	**Fixed supply + burn**

7. Architecture

7.1 Kernel + Modules



7.2 Settlement: Solana

Race model lifecycle: `postTask` 1 tx + `submitResult` × N + `judgeAndPay` 1 tx. 10K concurrent tasks ≈ 100 TPS < 3% Solana capacity. Compute-intensive work is off-chain.

7.3 A2A: Lightning Analogy

L1 (Solana): settlement, reputation. L2 (A2A): messaging, micropayment channels, state channels, batched reputation.

7.4 Execution: MagicBlock ER

Requirement	MagicBlock ER
<50ms interaction	1ms block, <50ms e2e
Zero-fee micropayments	Zero tx fees
Privacy	Private ER (Intel TDX TEE)
No bridge	Native Solana: delegate & commit

Integration: one `delegate` instruction. Zero custom infrastructure.

7.5 Cross-Chain Reputation

Step 1: Identity linking via mutual key signing—zero cost. **Step 2:** Solana as reputation home; Agent carries signed proof to other chains—zero cross-chain cost. **Step 3:** Write-back: Agent submits result proof to Solana—$0.001. No bridge, no centralized aggregation.

8. Roadmap

- **Design (2026 Q1 ✓)** — Protocol spec complete; whitepaper published
- **Kernel v1 (2026 Q2)** — Agent Layer on Solana: race model, SOL staking, reputation
- **Tooling (2026 Q2–Q3)** — Chain Hub MVP; Agent Me MVP
- **GRAD Genesis (2026 Q4)** — Token launch; airdrop to Phase 1 participants; liquidity pool
- **Multi-chain (2027 Q1)** — EVM deployment (Base/Arbitrum); cross-chain reputation

- **A2A + Social (2027 Q2)** — MagicBlock ER integration; Agent Social MVP
- **Flywheel (2027 H2)** — GRAD staking; mining rewards; buyback-and-burn

9. Conclusion

Bitcoin proved that defining "money" requires only UTXO + Script + PoW. Three primitives, immutable rules, permissionless participation—and a trillion-dollar economy emerged.

Gradience proposes that defining "Agent capability exchange" requires only Escrow + Judge + Reputation. Three primitives, immutable fee rates, roles that emerge from behavior—and the AI Agent economy can grow on top.

The kernel ensures one thing: *value flows correctly from those who need capability to those who provide it, verified by those who judge it, under rules that no one can change.*

References

[1] S. Nakamoto, "Bitcoin: A Peer-to-Peer Electronic Cash System," 2008. https://bitcoin.org/bitcoin.pdf

[2] D. Crapis, B. Lim, T. Weixiong, C. Zuhwa, "ERC-8183: Agentic Commerce," Ethereum Improvement Proposals, 2026.

[3] I. Goodfellow et al., "Generative Adversarial Networks," *NeurIPS*, 2014.

[4] M. De Rossi, D. Crapis, J. Ellis, E. Reppel, "ERC-8004: Trustless Agents," Ethereum Improvement Proposals, 2025.

[5] L. Hurwicz, "The Design of Mechanisms for Resource Allocation," *AER*, 1973.