



ZAP by
Checkmarx

ZAP by Checkmarx Scanning Report

Latinoamerica Comparte

Sites: <https://cdnjs.cloudflare.com> <http://latinoamericacomparte.com>

Generated on Mon, 25 May 2026 23:46:37

ZAP Version: 2.17.0

ZAP by [Checkmarx](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	6
Low	3
Informational	2

Insights

Level	Reason	Site	Description	Statistic
Low	Warning		ZAP errors logged - see the zap. log file for details	5
Low	Warning		ZAP warnings logged - see the zap. log file for details	1
Info	Informational	http://latinoamericacomparte.com	Percentage of responses with status code 2xx	77 %
Info	Informational	http://latinoamericacomparte.com	Percentage of responses with status code 4xx	22 %
Info	Informational	http://latinoamericacomparte.com	Percentage of endpoints with content type image/jpeg	56 %

Info	Informational	http://latinoamericacomparte.com	Percentage of endpoints with content type image/png	30 %
Info	Informational	http://latinoamericacomparte.com	Percentage of endpoints with content type text/html	13 %
Info	Informational	http://latinoamericacomparte.com	Percentage of endpoints with method GET	100 %
Info	Informational	http://latinoamericacomparte.com	Count of total endpoints	76
Info	Informational	http://latinoamericacomparte.com	Percentage of slow responses	82 %
Info	Informational	https://cdnjs.cloudflare.com	Percentage of responses with status code 2xx	100 %
Info	Informational	https://cdnjs.cloudflare.com	Percentage of endpoints with content type application/javascript	100 %
Info	Informational	https://cdnjs.cloudflare.com	Percentage of endpoints with method GET	100 %
Info	Informational	https://cdnjs.cloudflare.com	Count of total endpoints	1
Info	Informational	https://cdnjs.cloudflare.com	Percentage of slow responses	100 %
Info	Informational	https://fonts.googleapis.com	Percentage of responses with status code 2xx	100 %
Info	Informational	https://fonts.googleapis.com	Percentage of slow responses	100 %
			Percentage of	

Info	Informational	https://fonts.gstatic.com	responses with status code 2xx	100 %
Info	Informational	https://latinoamericacomparte.com	Percentage of responses with status code 2xx	100 %
Info	Informational	https://latinoamericacomparte.com	Percentage of slow responses	100 %

Alerts

Name	Risk Level	Number of Instances
Absence of Anti-CSRF Tokens	Medium	2
Content Security Policy (CSP) Header Not Set	Medium	Systemic
Cross-Domain Misconfiguration	Medium	1
HTTP to HTTPS Insecure Transition in Form Post	Medium	2
Missing Anti-clickjacking Header	Medium	2
Sub Resource Integrity Attribute Missing	Medium	4
Cross-Domain JavaScript Source File Inclusion	Low	2
Timestamp Disclosure - Unix	Low	1
X-Content-Type-Options Header Missing	Low	Systemic
Modern Web Application	Informational	2
Retrieved from Cache	Informational	3

Alert Detail

Medium	Absence of Anti-CSRF Tokens
Description	No Anti-CSRF tokens were found in a HTML submission form. A cross-site request forgery is an attack that involves forcing a victim to send an HTTP request to a target destination without their knowledge or intent in order to perform an action as the victim. The underlying cause is application functionality using predictable URL /form actions in a repeatable way. The nature of the attack is that CSRF exploits the trust that a web site has for a user. By contrast, cross-site scripting (XSS) exploits the trust that a user has for a web site. Like XSS, CSRF attacks are not necessarily cross-site, but they can be. Cross-site request forgery is also known as CSRF, XSRF, one-click attack, session riding, confused deputy, and sea surf. CSRF attacks are effective in a number of situations, including: * The victim has an active session on the target site. * The victim is authenticated via HTTP auth on the target site. * The victim is on the same local network as the target site. CSRF has primarily been used to perform an action against a target site using the victim's privileges, but recent techniques have been discovered to disclose information by gaining access to the response. The risk of information disclosure is dramatically increased when the target site is vulnerable to XSS, because XSS can be used as a platform for CSRF, allowing the attack to operate within the bounds of the same-origin policy.

URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	<form class="contact-form-new" id="contactFormNew" action="https://api.web3forms.com/submit" method="POST" >
Other Info	No known Anti-CSRF token [anticsrf, CSRFTOKEN, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "access_key" "apellido" "cargo" "email" "from_name" "nombre" "nombreEmpresa" "subject" "telefono"].
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	<form class="contact-form-new" id="contactFormNew" action="https://api.web3forms.com/submit" method="POST" >
Other Info	No known Anti-CSRF token [anticsrf, CSRFTOKEN, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "access_key" "apellido" "cargo" "email" "from_name" "nombre" "nombreEmpresa" "subject" "telefono"].
Instances	2
Solution	Phase: Architecture and Design Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, use anti-CSRF packages such as the OWASP CSRFGuard. Phase: Implementation Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script. Phase: Architecture and Design Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330). Note that this can be bypassed using XSS. Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation. Note that this can be bypassed using XSS. Use the ESAPI Session Management control. This control includes a component for CSRF. Do not use the GET method for any request that triggers a state change. Phase: Implementation

	Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.
Reference	https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html https://cwe.mitre.org/data/definitions/352.html
CWE Id	352
WASC Id	9
Plugin Id	10202

Medium	Content Security Policy (CSP) Header Not Set
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	
Other Info	
URL	http://latinoamericacomparte.com/paises.html
Node Name	http://latinoamericacomparte.com/paises.html
Method	GET
Attack	
Evidence	
Other Info	
URL	http://latinoamericacomparte.com/quienes.html
Node Name	http://latinoamericacomparte.com/quienes.html
Method	GET
Attack	
Evidence	
Other Info	
URL	http://latinoamericacomparte.com/robots.txt
Node Name	http://latinoamericacomparte.com/robots.txt
Method	GET
Attack	
Evidence	
Other	

Info	
URL	http://latinoamericacomparte.com/sitemap.xml
Node Name	http://latinoamericacomparte.com/sitemap.xml
Method	GET
Attack	
Evidence	
Other Info	
Instances	Systemic
Solution	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Guides/CSP https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html https://www.w3.org/TR/CSP/ https://w3c.github.io/webappsec-csp/ https://web.dev/articles/csp https://caniuse.com/#feat=contentsecuritypolicy https://content-security-policy.com/
CWE Id	693
WASC Id	15
Plugin Id	10038

Medium	Cross-Domain Misconfiguration
Description	Web browser data loading may be possible, due to a Cross Origin Resource Sharing (CORS) misconfiguration on the web server.
URL	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Node Name	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Method	GET
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
Instances	1
Solution	Ensure that sensitive data is not available in an unauthenticated manner (using IP address white-listing, for instance). Configure the "Access-Control-Allow-Origin" HTTP header to a more restrictive set of domains, or remove all CORS headers entirely, to allow the web browser to enforce the Same Origin Policy (SOP) in a more restrictive manner.
Reference	https://vulncat.fortify.com/en/detail?category=HTML5&subcategory=Overly%20Permissive%20CORS%20Policy
CWE Id	264
WASC Id	14
Plugin Id	10098

Medium	HTTP to HTTPS Insecure Transition in Form Post
Description	This check looks for insecure HTTP pages that host HTTPS forms. The issue is that an insecure HTTP page can easily be hijacked through MITM and the secure HTTPS form can be replaced or spoofed.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	https://api.web3forms.com/submit
Other Info	The response to the following request over HTTP included an HTTPS form tag action attribute value: http://latinoamericacomparte.com/ The context was: <form class="contact-form-new" id="contactFormNew" action="https://api.web3forms.com/submit" method="POST" > <!-- Web3Forms Access Key --> <input type="hidden" name="access_key" value="7a1764d4-f138-4e7a-97e2-688c2b843930" /> <input type="hidden" name="subject" value="Nuevo mensaje desde Latinoamérica Comparte" /> <input type="hidden" name="from_name" value="Formulario Web" /> <div class="form-grid"> <div class="form-group"> <label for="nombre" class="form-label">Nombre *</label> <input type="text" id="nombre" name="nombre" class="form-input" placeholder="Tu nombre" required /> </div> <div class="form-group"> <label for="apellido" class="form-label">Apellido</label> <input type="text" id="apellido" name="apellido" class="form-input" placeholder="Tu apellido" /> </div> <div class="form-group"> <label for="telefono" class="form-label">Teléfono</label> <input type="tel" id="telefono" name="telefono" class="form-input" placeholder="+57 300 123 4567" /> </div> <div class="form-group"> <label for="pais" class="form-label">País</label> <select id="pais" name="pais" class="form-input form-select"> <option value="">Selecciona tu país</option> <option value="Colombia">Colombia</option> <option value="Ecuador">Ecuador</option> <option value="Chile">Chile</option> <option value="Argentina">Argentina</option> <option value="Otro">Otro</option> </select> </div> <!-- Campos de empresa (ocultos inicialmente) --> <div id="camposEmpresaNew" class="empresa-fields" style="display: none" > <div class="form-grid"> <div class="form-group"> <label for="nombreEmpresa" class="form-label">Nombre de la Empresa</label> <input type="text" id="nombreEmpresa" name="nombreEmpresa" class="form-input" placeholder="Empresa S. A." /> </div> <div class="form-group"> <label for="cargo" class="form-label">Cargo</label> <input type="text" id="cargo" name="cargo" class="form-input" placeholder="Tu cargo en la empresa" /> </div> </div> <div class="form-group form-group-full"> <label for="email" class="form-label">Correo electrónico *</label> <input type="email" id="email" name="email" class="form-input" placeholder="tucorreo@ejemplo.com" required /> </div> <div class="form-group form-group-full"> <label for="mensaje" class="form-label">¿En qué podemos ayudarte? *</label> <textarea id="mensaje" name="mensaje" class="form-textarea" rows="5" placeholder="Cuéntanos cómo podemos ayudarte..." required ></textarea> </div> <div class="form-actions"> <button type="submit" class="btn-submit-new"> Enviar mensaje <svg xmlns="http://www.w3.org/2000/svg" width="18" height="18" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-linejoin="round"> <line x1="22" y1="2" x2="11" y2="13"></line> <polygon points="22 2 15 22 11 13 9 22 2"></polygon> </svg> </button> </div> </form>
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	https://api.web3forms.com/submit
	The response to the following request over HTTP included an HTTPS form tag action attribute value: http://latinoamericacomparte.com/index.html The context was: <form class="contact-form-new" id="contactFormNew" action="https://api.web3forms.com/submit" method="POST" > <!-- Web3Forms Access Key --> <input type="hidden" name="access_key" value="7a1764d4-f138-4e7a-97e2-688c2b843930" /> <input type="hidden" name="subject" value="Nuevo mensaje desde Latinoamérica Comparte" /> <input type="hidden" name="from_name" value="Formulario Web" /> <div class="form-grid"> <div class="form-group"> <label for="nombre" class="form-label">Nombre *</label> <input type="text"

Other Info	<pre>id="nombre" name="nombre" class="form-input" placeholder="Tu nombre" required /> < /div> <div class="form-group"> <label for="apellido" class="form-label">Apellido</label> <input type="text" id="apellido" name="apellido" class="form-input" placeholder="Tu apellido" /> </div> <div class="form-group"> <label for="telefono" class="form-label" >Teléfono</label> <input type="tel" id="telefono" name="telefono" class="form-input" placeholder="+57 300 123 4567" /> </div> <div class="form-group"> <label for="pais" class="form-label">País</label> <select id="pais" name="pais" class="form-input form- select"> <option value="">Selecciona tu país</option> <option value="Colombia" >Colombia</option> <option value="Ecuador">Ecuador</option> <option value="Chile" >Chile</option> <option value="Argentina">Argentina</option> <option value="Otro">Otro< /option> </select> </div> </div> <!-- Campos de empresa (ocultos inicialmente) --> <div id=" camposEmpresaNew" class="empresa-fields" style="display: none" > <div class="form-grid" > <div class="form-group"> <label for="nombreEmpresa" class="form-label" >Nombre de la Empresa</label> <input type="text" id="nombreEmpresa" name="nombreEmpresa" class=" form-input" placeholder="Empresa S.A." /> </div> <div class="form-group"> <label for=" cargo" class="form-label">Cargo</label> <input type="text" id="cargo" name="cargo" class="form-input" placeholder="Tu cargo en la empresa" /> </div> </div> </div> <div class="form-group form-group-full"> <label for="email" class="form-label" >Correo electrónico *</label> <input type="email" id="email" name="email" class="form-input" placeholder="tucorreo@ejemplo.com" required /> </div> <div class="form-group form-group- full"> <label for="mensaje" class="form-label" >¿En qué podemos ayudarte? *</label> <textarea id="mensaje" name="mensaje" class="form-textarea" rows="5" placeholder=" Cuéntanos cómo podemos ayudarte..." required ></textarea> </div> <div class="form- actions"> <button type="submit" class="btn-submit-new"> Enviar mensaje <svg xmlns="http://www.w3.org/2000/svg" width="18" height="18" viewBox="0 0 24 24" fill=" none" stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-linejoin="round" > <line x1="22" y1="2" x2="11" y2="13"></line> <polygon points="22 2 15 22 11 13 2 9 22 2"></polygon> </svg> </button> </div> </form></pre>
Instances	2
Solution	Use HTTPS for landing pages that host secure forms.
Reference	
CWE Id	319
WASC Id	15
Plugin Id	10041

Medium	Missing Anti-clickjacking Header
Description	The response does not protect against 'ClickJacking' attacks. It should include either Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	
Other Info	
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	
Other Info	
Instances	2

Solution	Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app. If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors" directive.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options
CWE Id	1021
WASC Id	15
Plugin Id	10020

Medium	Sub Resource Integrity Attribute Missing
Description	The integrity attribute is missing on a script or link tag served by an external server. The integrity tag prevents an attacker who have gained access to this server from injecting a malicious content.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	<link href="https://fonts.googleapis.com/css2?family=Poppins:wght@300;400;600;700;800&display=swap" rel="stylesheet" />
Other Info	
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	<script src="https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js" defer ></script>
Other Info	
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	<link href="https://fonts.googleapis.com/css2?family=Poppins:wght@300;400;600;700;800&display=swap" rel="stylesheet" />
Other Info	
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	<script src="https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js" defer ></script>

Other Info	
Instances	4
Solution	Provide a valid integrity attribute to the tag.
Reference	https://developer.mozilla.org/en-US/docs/Web/Security/Subresource_Integrity
CWE Id	345
WASC Id	15
Plugin Id	90003

Low	Cross-Domain JavaScript Source File Inclusion
Description	The page includes one or more script files from a third-party domain.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	<script src="https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js" defer ></script>
Other Info	
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	<script src="https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js" defer ></script>
Other Info	
Instances	2
Solution	Ensure JavaScript source files are loaded from only trusted sources, and the sources can't be controlled by end users of the application.
Reference	
CWE Id	829
WASC Id	15
Plugin Id	10017

Low	Timestamp Disclosure - Unix
Description	A timestamp was disclosed by the application/web server. - Unix
URL	http://latinoamericacomparte.com/img/LOGOS/Logo_Homecenter_Sodimac.png
Node Name	http://latinoamericacomparte.com/img/LOGOS/Logo_Homecenter_Sodimac.png
Method	GET
Attack	
Evidence	1683426754
Other Info	1683426754, which evaluates to: 2023-05-06 22:32:34.

Instances	1
Solution	Manually confirm that the timestamp data is not sensitive, and that the data cannot be aggregated to disclose exploitable patterns.
Reference	https://cwe.mitre.org/data/definitions/200.html
CWE Id	497
WASC Id	13
Plugin Id	10096

Low	X-Content-Type-Options Header Missing
Description	The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://latinoamericacomparte.com/img/LOGOS/Alpina_S.A._logo.svg.png
Node Name	http://latinoamericacomparte.com/img/LOGOS/Alpina_S.A._logo.svg.png
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://latinoamericacomparte.com/img/LOGOS/Argentina%20Co%20N.png
Node Name	http://latinoamericacomparte.com/img/LOGOS/Argentina Co N.png
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://latinoamericacomparte.com/img/LOGOS/Colombia%20Co%20N.png
Node Name	http://latinoamericacomparte.com/img/LOGOS/Colombia Co N.png
Method	GET
Attack	

Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://latinoamericacomparte.com/img/LOGOS/Latinoam%C3%A9rica%20Co%20N.png
Node Name	http://latinoamericacomparte.com/img/LOGOS/Latinoamérica Co N.png
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
Instances	Systemic
Solution	Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages. If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application /web server to not perform MIME-sniffing.
Reference	https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85) https://owasp.org/www-community/Security_Headers
CWE Id	693
WASC Id	15
Plugin Id	10021

Informational	Modern Web Application
Description	The application appears to be a modern web application. If you need to explore it automatically then the Ajax Spider may well be more effective than the standard one.
URL	http://latinoamericacomparte.com/
Node Name	http://latinoamericacomparte.com/
Method	GET
Attack	
Evidence	<pre> Leer más <svg xmlns="http://www.w3.org/2000/svg" width="18" height="18" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-linejoin="round"> <line x1="5" y1="12" x2="19" y2="12"></line> <polyline points="12 5 19 12 12 19"></polyline> </svg> </pre>
Other Info	Links have been found that do not have traditional href attributes, which is an indication that this is a modern web application.
URL	http://latinoamericacomparte.com/index.html
Node Name	http://latinoamericacomparte.com/index.html
Method	GET
Attack	
Evidence	<pre> Leer más <svg xmlns="http://www.w3.org/2000/svg" width="18" height="18" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-linejoin="round"></pre>

	> <line x1="5" y1="12" x2="19" y2="12"></line> <polyline points="12 5 19 12 12 19"></polyline> </svg>
Other Info	Links have been found that do not have traditional href attributes, which is an indication that this is a modern web application.
Instances	2
Solution	This is an informational alert and so no changes are required.
Reference	
CWE Id	
WASC Id	
Plugin Id	10109

Informational	Retrieved from Cache
Description	The content was retrieved from a shared cache. If the response data is sensitive, personal or user-specific, this may result in sensitive information being leaked. In some cases, this may even result in a user gaining complete control of the session of another user, depending on the configuration of the caching components in use in their environment. This is primarily an issue where caching servers such as "proxy" caches are configured on the local network. This configuration is typically found in corporate or educational environments, for instance.
URL	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Node Name	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Method	GET
Attack	
Evidence	Age: 1473317
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
URL	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Node Name	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Method	GET
Attack	
Evidence	Age: 1473363
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
URL	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Node Name	https://cdnjs.cloudflare.com/ajax/libs/animejs/3.2.1/anime.min.js
Method	GET
Attack	
Evidence	Age: 1473411
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
Instances	3
	Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private

Solution	Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.
Reference	https://datatracker.ietf.org/doc/html/rfc7234 https://datatracker.ietf.org/doc/html/rfc7231 https://www.rfc-editor.org/rfc/rfc9110.html
CWE Id	525
WASC Id	
Plugin Id	10050