

- udpPacketManager: An International LOFAR Station
- ₂ Data (Pre-)Processor
- David J. McKenna 1,2¶, Evan F. Keane 2, and Peter T. Gallagher 1
- 1 Dublin Institute for Advanced Studies, Ireland 2 Trinity College Dublin, Ireland ¶ Corresponding author

DOI: 10.xxxxx/draft

Software

- Review 🗗
- Repository 🗗
- Archive ♂

Editor: Open Journals ♂

Reviewers:

@openjournals

Submitted: 01 January 1970 Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

18

Summary

International LOFAR stations are powerful radio telescopes, however they are delivered without the tooling nessisary to convert the raw data stream into common raw formats that can be used by normal processing pipelines, or science-ready data products.

udpPacketManager was developed with the intent of providing a faster-than-realtime software package for converting raw data into arbitrary data formats based on the needs of observers working with the Irish LOFAR station (I-LOFAR), and stations across Europe. It currently offers an open-source solution for both offline and online (pre-) processing of telescope data into a wide variety of formats.

Statement of need

International LOFAR stations (van Haarlem et al., 2013) produce a 3Gbps stream of UDP packets, split across 4 separate ports. Each packet c ontains a standard header with basic time and telescope hardware information, typically followed by 7808 bytes of time-major beamformed voltagdata, with 2 complex samples per antenna polarisation, for 16 time samples across a variable number of frequency samples (Virtanen, 2018). In order to convert this data into a usable format, the 4 ports must be combined, data integrity issues (such as packet loss) must be identified and mitigated, and the beamformed samples must be unpacked and reordered following a set specification in order to be processed efficiently.

Previous work in this regard includes the LOFAR und MPIfR Pulsare (LuMP) Software (Anderson, 2013), an open-source recorder that saves data to a PUMA2 derived data format that can be parsed using the DSPSR (W. van Straten & Bailes, 2011) ecosystem, and the ARTEMIS system (Serylak et al., 2012), a hardware-software package for online transient observations derived from the source-available PELICAN LOFAR backend (Developers, 2021). These were found not to meet the requirements of observers at I-LOFAR, such as supporting multi-mode observations (McKay-Bukowski, 2013), nor work within some constraints of the REALTA compute cluster. Consequently, udpPacketManager was built to better facilitate observations with the telescope.

The software has supported on-going observations of the Sun, Pulsars and Rotating Radio Transients (D. J. McKenna et al., 2023) in Ireland since early 2020, alongside multi-site work with Breakthrough Listen in the search for extraterrestrial life (SETI) in coordination with the Sweedish LOFAR station at Onsala since 2021 (Johnson et al., in prep.) and observations of Jupiter in coordination with the French LOFAR station and one of the German LOFAR station at Postdam in 2022 (Louis et al., 2022).



Inputs, Outputs, and Metadata

udpPacketManager contains a flexible interface for handling multiple different data sources and sinks in a semi-transparent manner, allowing for data to be read and writte out through normal files, FIFO named pipes, Zstandard (Collet & Kucherawy, 2021) compressed files (which allow for a greater than 2 times space-saving when handling raw voltages from LOFAR stations), PSRDADA ringbuffers for online processing (Willem van Straten et al., 2021), and write-only to HDF5 files that conform to LOFAR ICD003 (Alexov et al., 2012). These interfaces were also used to create the associated ILTDada project (D. McKenna, 2023), a UDP packet capture software that writes data to a PSRDADA ringbuffer for immediate processing with this software.

Given that the header attached to the data itself contains minimal metadata outside of the start time of the data block, metadata is parsed from an associated file that contains one or more commands to control the telescope (beamctl) and minimal other metadata, such as observer and project identifiers. This is then processed to generate a chosen output header, which can follow the GUPPI RAW (Lebofsky et al., 2019), SigProc (Lorimer, 2011), PSRDADA, or ICD003 specifications.

The library can reform the data to a number of output formats. For raw voltages outputs, standard time-major and beamlet-major orders, which can also be additionally split by antenna polarisation and complex sample components are available. Partial or full Stokes parameters are also generated in similar formats, with temporal downsampling up to a factor of 16 available in the library itself. A sample command-line-interface offers higher levels of downsampling and channelisation of Stokes parameters through the FFTW library (Frigo & Johnson, 2005) as an example of how to further utilise the outputs of the library. All of these outputs can be calibrated to correct for interferometric beam issues by applying, or generating for external use, Jones matrices generated by dreamBeam (Carozzi, 2023).

Acknowledgements

DMcK is receiving funding from the Irish Research Council's Government of Ireland Postgraduate
Scholarship Program (GOIPG/2019/2798). The Irish LOFAR Consortium is supported by
funding from Science Foundation Ireland and the Department of Further and Higher Education,
Research, Innovation and Science. The compute servers of REALTA used for development of
this software were funded by Science Foundation Ireland.

References

- Alexov, A. '., Anderson, K., Bahren, L., Grießmeier, J.-M., Hessels, J. W. T., Masters, J. S., & Stappers, B. W. (2012). LOFAR Data Format ICD Beam-Formed Data.
- Anderson, J. M. (2013). LOFAR und MPIfR Pulsare.
- 72 Carozzi, T. (2023). dreamBeam.
- Collet, Y., & Kucherawy, M. (2021). *Zstandard Compression and the 'application/zstd' Media Type* (No. RFC8878; p. RFC8878). RFC Editor. https://doi.org/10.17487/RFC8878
- Developers, P. (2021). *Pelican/pelican-lofar*.
- Frigo, M., & Johnson, S. G. (2005). The Design and Implementation of FFTW3. *Proceedings* of the IEEE, 93(2), 216–231. https://doi.org/10.1109/JPROC.2004.840301
- Johnson, O. A., Gajjar, V., Keane, E. F., Giese, C., McKenna, D., McKeon, B., Carozzi, T. D., Alcaria, C., Brennan, A., Gallagher, P. T., McCauley, J., MacMahon, D., Lebofsky, M.,



- Raeside, S. R., Croft, S., & Siemion, A. P. V. (in prep.). Simultaneous dual-site SETI with LOFAR international stations.
- Lebofsky, M., Croft, S., Siemion, A. P. V., Price, D. C., Enriquez, J. E., Isaacson, H.,
 MacMahon, D. H. E., Anderson, D., Brzycki, B., Cobb, J., Czech, D., DeBoer, D.,
 DeMarines, J., Drew, J., Foster, G., Gajjar, V., Gizani, N., Hellbourg, G., Korpela, E. J., ...
 Zhang, Y. G. (2019). The Breakthrough Listen Search for Intelligent Life: Public Data,
 Formats, Reduction, and Archiving. *Publications of the Astronomical Society of the Pacific*,
- Lorimer, D. R. (2011). SIGPROC: Pulsar Signal Processing Programs. *Astrophysics Source Code Library*, ascl:1107.016.

131(1006), 124505. https://doi.org/10.1088/1538-3873/ab3e82

- Louis, C. K., Jackman, C. M., Grießmeier, J.-M., Wucknitz, O., McKenna, D. J., Murphy, P. C., Gallagher, P. T., Carley, E. P., Ó Fionnagáin, D., Golden, A., McCauley, J., Callanan, P., Redman, M., & Vocks, C. (2022). Method to observe Jupiter's radio emissions at high resolution using multiple LOFAR stations: A first case study of the lo-decametric emission using the Irish IE613, French FR606, and German DE604 stations. *RAS Techniques and Instruments*, 1(1), 48–57. https://doi.org/10.1093/rasti/rzac005
- McKay-Bukowski, D. (2013). Making Observations with Mode-357. https://www.lofar-uk.org/wiki/uploads/Main/kaira_mode357_obs210413.pdf.
- McKenna, D. (2023). David-McKenna/ILTDada: V0.1.0-dev. Zenodo. https://doi.org/10.
 5281/ZENODO.7871665
- McKenna, D. J., Keane, E. F., Gallagher, P. T., & McCauley, J. (2023). A Census of Rotating
 Radio Transients at 150 MHz with the Irish LOFAR Station. https://doi.org/10.48550/
 ARXIV.2302.12661
- Serylak, M., Karastergiou, A., Williams, C., Armour, W., Giles, M., & Group, the L. P. W. (2012). Observations of transients and pulsars with LOFAR international stations and the ARTEMIS backend. *Proceedings of the International Astronomical Union*, 8(S291), 492–494. https://doi.org/10.1017/S1743921312024623
- van Haarlem, M. P., Wise, M. W., Gunst, A. W., Heald, G., McKean, J. P., Hessels, J. W. T.,
 de Bruyn, A. G., Nijboer, R., Swinbank, J., Fallows, R., Brentjens, M., Nelles, A., Beck,
 R., Falcke, H., Fender, R., Hörandel, J., Koopmans, L. V. E., Mann, G., Miley, G., ... van
 Zwieten, J. (2013). LOFAR: The LOw-Frequency ARray. Astronomy & Astrophysics, 556,
 A2. https://doi.org/10.1051/0004-6361/201220873
- van Straten, W., & Bailes, M. (2011). DSPSR: Digital Signal Processing Software for Pulsar Astronomy. *Publications of the Astronomical Society of Australia*, 28, 1–14. https://doi.org/10.1071/AS10021
- van Straten, Willem, Jameson, A., & OsÅ owski, S. (2021). PSRDADA: Distributed Acquisition and Data Analysis for Radio Astronomy. *Astrophysics Source Code Library*, ascl:2110.003.
- Virtanen, I. I. (2018). Station Data Cookbook. https://lofar.ie/wp-content/up-loads/2018/03/station_data_cookbook_v1.2.pdf.