

Spectral Graph Theory and High Performance Computing

Eigenvalue theory

David Wobrock `david.wobrock@inria.fr`

January 18, 2018

1 Theory

The filter W is built on top of the kernel matrix K measuring the similarity between each pixel. The most popular kernel functions are the *Bilateral filter* [1] and the *Non-local Mean filter* [2]. In general, the kernel functions create a symmetric positive semi-definite (PSD) matrix K with $k_{ij} \geq 0$. For these specific functions, we can even define $0 \leq k_{ij} \leq 1$.

We shall use the re-normalised [3] Laplacian, which will result in a normalisation-free filter [4]. We define the Laplacian operator as

$$\mathcal{L} = \alpha(D - K),$$

with $\alpha = \frac{1}{\bar{d}}$ and $\bar{d} = \text{mean}(d_j)$.

For this definition, we know that \mathcal{L} is symmetric and its eigenvalues $0 \leq \mu_i \leq 1$, meaning that \mathcal{L} is symmetric positive definite (SPD).

The filter is defined as $W = I - \mathcal{L}$. The identity I is obviously SPD, so the filter is also SPD. We know from [5] that the eigenvalues of W are defined as $0 \leq \lambda_i^W \leq 1$ and the largest eigenvalue $\lambda_1^W = 1$.

The image processing algorithm is computing the eigendecomposition of the submatrix W_A . From the properties of SPD matrices, since W_A is a principal submatrix of W , it is also SPD. Furthermore, we can say that the eigenvalues $0 \leq \lambda_i^{W_A} \leq 1$ and $\lambda_1^{W_A} \leq 1$.

Proof Let A be a symmetric matrix, λ_{max}^A be the largest eigenvalue of A and u the associated eigenvector.

$$\lambda_{max}^A = \max\left(\frac{A(u, u)}{(u, u)}\right).$$

Let R be the restriction operator, such as $Ru = \begin{pmatrix} \alpha_1 \\ \alpha_2 \\ \vdots \\ 0 \end{pmatrix}$ for example.

So $\lambda_{max}^{RAR^T} \leq \lambda_{max}^A$ and we can say that $\lambda_{max}^{RAR^T} = \max(\frac{A(R^T v, R^T v)}{(v, v)})$.
 So $(v, v) = (u, u)$. (??)

From the definition of the filter $W = I - \mathcal{L}$, we have the submatrix $W_A = I - \mathcal{L}_A$, with I being the identity of appropriate order. For the algorithm, we need to compute the largest eigenvalues of W_A .

Theorem Computing the largest eigenvalues of W_A is equivalent to computing the smallest eigenvalues of \mathcal{L}_A .

Proof

$$W_A x = \lambda x \Leftrightarrow (I - \mathcal{L}_A)x = \lambda x$$

References

- [1] C. Tomasi and R. Manduchi. “Bilateral filtering for gray and color images”. In: *Sixth International Conference on Computer Vision (IEEE Cat. No.98CH36271)*. Jan. 1998, pp. 839–846. DOI: 10 . 1109 / ICCV . 1998 . 710815.
- [2] C. Kervrann and J. Boulanger. “Optimal Spatial Adaptation for Patch-Based Image Denoising”. In: *IEEE Transactions on Image Processing* 15.10 (Oct. 2006), pp. 2866–2878. ISSN: 1057-7149. DOI: 10 . 1109 / TIP . 2006 . 877529.
- [3] Peyman Milanfar. *Non-conformist Image Processing with Graph Laplacian Operator*. 2016. URL: <https://www.pathlms.com/siam/courses/2426/sections/3234>.
- [4] Peyman Milanfar and Hossein Talebi. “A new class of image filters without normalization”. In: *Image Processing (ICIP), 2016 IEEE International Conference on*. IEEE, 2016, pp. 3294–3298.
- [5] Hossein Talebi and Peyman Milanfar. “Global Image Denoising”. In: *IEEE Transactions on Image Processing* 23.2 (Feb. 2014), pp. 755–768. ISSN: 1057-7149, 1941-0042. DOI: 10 . 1109 / TIP . 2013 . 2293425. URL: <http://ieeexplore.ieee.org/document/6678291/> (visited on 10/03/2017).