

# For Android Applications

## Contents


- [Introduction](#)
- [Pre-requisites](#)
- [Download and install the required resources](#)
- [Running the ITL REST Server](#)
- [Sending REST Requests using API Tester](#)
- [SSP Lower-Level Logging](#)

## Introduction

The following describes how to run the ITL REST server using the `Android_REST_API_Vx.x.x.apk` and make endpoint calls to it and receive response data. There are many different Android versions available. This documentation has been compiled using Android Version 12 and version 1.3.2 of the Android REST API.


## Pre-requisites







- Android Device, Android instance on a Virtual Machine or Emulator


 Minimum Android Version 10 (API 29)

- ITL cash handling device



## Download and install the required resources

Navigate to the following link to download the latest SDK.	<a href="#">ITL SDK Package</a>
Installing the <code>Android_REST_API_Vx.x.x.apk</code> Navigate to the APK <a href="#">download</a> and launch the file.	
Select to CONTINUE on any warning messages.	<div>Your tablet and personal data are more vulnerable to attack by unknown apps. By installing this app, you agree that you are responsible for any damage to your tablet or loss of data that may result from its use. <div>CANCELCONTINUE</div></div>
Select INSTALL to begin the process.	<div> <b>Android REST API</b> Do you want to install this app? <div>CANCELINSTALL</div></div>

Select DONE once the install completes.	
Download and install an API Tester like the following example:	<a href="#">API Tester</a>
Installing the API Tester.  Navigate to the APK download and launch the file.	
If sideloading the APK, select to CONTINUE on any warning messages.	
Select INSTALL to begin the process.	
Select OPEN to launch the application.	
Import the Collection to the API Tester.  Select the + icon.	
Select Collection.	

Select File.	<div>Import collection via link or file</div> <div> <div>Link</div> <div><b>File</b></div> <div>Cancel</div> </div>
Navigate to the saved collection file Android-API-Collection.json and select the file.	
Wait until the import completes.	<div> <div>Importing...</div> <div>It can take a few minutes</div> </div>
Once the import has completed you will find the collection list on the left of the API Tester app.	

## Running the ITL REST Server

Launch the Android REST API application	
<p>The server will launch and begin listening on <a href="http://127.0.0.1:5000/api/CashDevice">http://127.0.0.1:5000/api/CashDevice</a></p> 	


REST requests are case sensitive. Ensure upper case letters are used where advised.

The Android REST API application must remain active at all times. Closing the application will stop the API from communicating between your software and the cash device. A fix has been implemented from version 1.3.2 to ensure the server remains active until explicitly closed, however some Android versions can pause or stop apps running in the background e.g. switching between the server app and the API Testing app. Ensure your Android version can allow apps to remain active in the background.


## Sending REST Requests using API Tester [↗](#)

Set the baseUrl in the Variables table.

To access the Variables table, select the 3 dots contained in the circle to the right of the search bar.











Select Variables.






Ensure the correct baseUrl is set in the variables table.


1 http://127.0.0.1:5000/api



<p>Select Done to update the table and return to the request list.</p>	
<p>Request a Bearer Token for authorisation of upcoming REST requests using the <a href="#">Authenticate</a> request.</p> <p>Select the Authenticate request and select the play button from the top right to send the request.</p>	
<p>Copy the Bearer Token to the Variables table for future requests.</p> <p>Highlight the Bearer Token and select Copy.</p>	
<p>Paste the Bearer Token into the token value field of the variables table.</p>	
<p>Select Done to update the table and return to the request list.</p>	
<p>Send the <a href="#">GetConnectedUSBDevices</a> request to obtain the correct Port.</p>	
<p>Navigate to the Post Data for the <a href="#">OpenConnection</a> request.</p>	

<p>Update the Post Data to the correct Port returned for the <a href="#">GetConnectedUSBDevices</a> request.</p>	
<p>Send the <a href="#">OpenConnection</a> request once the Post Data has been updated. Please refer to the <a href="#">OpenConnection</a> details for further information on the full Post Data body.</p>	
<p>Update the deviceId in the variables table.</p> <p>The OpenConnection request will return the correct deviceId to use on subsequent requests.</p>	
<p>Save the deviceId to the variables table.</p>	
<p>Your validator will be enabled and ready to accept currency if the below parameters of the <a href="#">OpenConnection</a> request are set to true.</p> <pre> 1  "EnableAcceptor": true, 2  "EnablePayout": true </pre>	

## SSP Lower-Level Logging [↗](#)

 Available from version 1.3.2

Android will store the Lower level SSP logs from version 1.3.2.

By default, logs are stored at the following path:

```
/storage/emulated/0/Documents/ITL_SSP_logs/{default_log_name}.log
```

If you wish to use a custom log location, simply specify it in the JSON request using the following format:

```
"LogFilePath": "{directory}/{log_file_name}.log"
```

To access the default logs on your Android device, navigate to:

**Files -> Internal Storage -> Documents**