

LinkDelay Quick Reference

Version 4.0.9

Revision History

1/8/2010 Edited by AECOM Consult, Inc.

4/15/2010 Edited by RSG, Inc.

Syntax:

LinkDelay [-flag] [control_file]

Purpose:

1. Merge, average, and/or convert Link Delay files, and

2. Smooth the link delays between time increments.

Required Keys

NET_LINK_TABLE	[net_directory]filename
LINK_DELAY_FILE	[project_directory]filename
NEW_LINK_DELAY_FILE	[project_directory]filename

Optional Keys

TITLE	Text
REPORT_FILE	Filename
REPORT_FLAG	FALSE {true/false/yes/no/1/0}
MAX_WARNING_MESSAGES	100,000
MAX_WARNING_EXIT_FLAG	TRUE {true/false/yes/no/1/0}
PROJECT_DIRECTORY	Pathname
DEFAULT_FILE_FORMAT	VERSION3 {(1)}
NET_DIRECTORY	Pathname
NET_LANE_CONNECTIVITY_TABLE	[net_directory]filename
TIME_OF_DAY_FORMAT	24_HOUR_CLOCK {(2)}
PREVIOUS_LINK_DELAY_FILE	[project_directory]filename
PREVIOUS_WEIGHTING_FACTOR	1.0 (>= 1.0)
PROCESSING_METHOD	{(3)}
TIME_PERIOD_SORT	FALSE {true/false/yes/no/1/0} (4)
SMOOTH_GROUP_SIZE	3 {39}
PERCENT_MOVED_FORWARD	20 percent {0(100 – 50 / [smooth group size])
PERCENT_MOVED_BACKWARD	20 percent {0(100 – 50 / [smooth group size])
NUMBER_OF_ITERATIONS	3 {125}
CIRCULAR_GROUP_FLAG	TRUE {true/false/yes/no/1/0}
NET_DEFAULT_FORMAT	[default_file_format] {(1)}

NET_LINK_FORMAT	[net_default_format] {(1)}
NET_LANE_CONNECTIVITY_FORMAT	[net_default_format] {(1)}
DEMAND_FILE_FORMAT	[default_file_format] {(1)}
LINK_DELAY_FORMAT	[demand_file_format] {(1)}
NEW_LINK_DELAY_FORMAT	[demand_file_format] {(1)}
PREVIOUS_LINK_DELAY_FORMAT	[default_file_format] {(1)}

Notes

1	-	{VERSION3, BINARY, FIXED_COLUMN, COMMA_DELIMITED, SPACE_DELIMITED, TAB_DELIMITED, CSV_DELIMITED, DBASE, LANL, SQLITE3}
2	,	{HOURS, SECONDS, 24_HOUR_CLOCK, 12_HOUR_CLOCK}
3		{REPLACE_LINKS, SIMPLE_AVERAGE, WEIGHTED_AVERAGE}
4	1	The default sort is link number and then time period. The Microsimulator generates a file sorted by time period and then link number. If this key is TRUE, the output link delay file is sorted by time period and link number.

