

TransitNet - Quick Reference

Version 5.0.6



Usage

TransitNet [-flag] [control_file]

Optional Flags:

- Q[uiet] = execute without screen messages
- H[elp] = show program syntax and control keys
- C[ontrol] = create/update a default control file
- K[eyCheck] = list unrecognized control file keys
- P[ause] = pause before exiting
- N[oPause] = never pause before exiting
- D[etail] = execute with detailed status messages
- X[ML] = write an XML file with control keys

Purpose

1. Create or update transit network file from route header and nodes files.
2. Add transit-related activity locations, process links, and parking lots to the network files.

Configuration Keys

REQ? KEY	TYPE	DEFAULT	VALUE RANGES
TITLE	Text		
REPORT_FILE	File		filename[_partition][.prn]
REPORT_FLAG	Bool	FALSE	TRUE/FALSE, YES/NO, 1/0, T/F, Y/N
PROJECT_DIRECTORY	Path		
MODEL_START_TIME	Time	0:00	>= 0 [seconds], 0.0 [hours], 0:00
MODEL_END_TIME	Time	24:00	> [model_start_time]
UNITS_OF_MEASURE	Text	METRIC	METRIC, ENGLISH
RANDOM_NUMBER_SEED	Int.	0	0 = computer clock, > 0 = fixed
MAX_WARNING_MESSAGES	Int.	100000	>= 0
MAX_WARNING_EXIT_FLAG	Bool	TRUE	TRUE/FALSE, YES/NO, 1/0, T/F, Y/N
MAX_PROBLEM_COUNT	Int.	0	>= 0
NUMBER_OF_THREADS	Int.	1	1..24
TRANSITNET_REPORT_*	Text		program report name

System File Keys

REQ? KEY	TYPE	DEFAULT	VALUE RANGES
<input checked="" type="checkbox"/> NODE_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> LINK_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> CONNECTION_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> ROUTE_NODES_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> VEHICLE_TYPE_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> NEW_TRANSIT_STOP_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> NEW_TRANSIT_ROUTE_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> NEW_TRANSIT_SCHEDULE_FILE	File		[project_directory]filename
<input checked="" type="checkbox"/> NEW_TRANSIT_DRIVER_FILE	File		[project_directory]filename
ZONE_FILE	File		[project_directory]filename
SHAPE_FILE	File		[project_directory]filename
PARKING_FILE	File		[project_directory]filename
LOCATION_FILE	File		[project_directory]filename
ACCESS_FILE	File		[project_directory]filename
TRANSIT_STOP_FILE	File		[project_directory]filename
TRANSIT_ROUTE_FILE	File		[project_directory]filename
TRANSIT_SCHEDULE_FILE	File		[project_directory]filename
TRANSIT_DRIVER_FILE	File		[project_directory]filename
NEW_PARKING_FILE	File		[project_directory]filename
NEW_ACCESS_FILE	File		[project_directory]filename

File Service Keys

REQ? KEY	TYPE	DEFAULT	VALUE RANGES
NOTES_AND_NAME_FIELDS	Bool	FALSE	TRUE/FALSE, YES/NO, 1/0, T/F, Y/N
ZONE_EQUIVALENCE_FILE	File		[project_directory]filename

Control Keys

REQ? KEY	TYPE	DEFAULT	VALUE RANGES
PARK_AND_RIDE_FILE	File		[project_directory]filename
STOP_SPACING_BY_AREA_TYPE_*	List	200 meters	37.5..3200 meters
STOP_FACILITY_TYPE_RANGE	Text	PRINCIPAL..FRONTAGE	FREEWAY..EXTERNAL
TRANSIT_TIME_PERIODS	Text	NONE	e.g., NONE, 6:00, 10:00, 16:00
TRANSIT_TRAVEL_TIME_FACTORS_*	List	1.0	0.5..3.0
MINIMUM_DWELL_TIME	Time	5 seconds	0..300 seconds
INTERSECTION_STOP_TYPE	Text	NEAR SIDE	NEAR SIDE, FAR SIDE, MIDBLOCK
INTERSECTION_STOP_OFFSET	Dec.	10.0 meters	0..100 meters

Notes

Each '_FILE' key has a corresponding '_FORMAT' key. The following file formats can be used for input and output files.

TEXT, BINARY, FIXED_COLUMN, COMMA_DELIMITED, SPACE_DELIMITED, TAB_DELIMITED, CSV_DELIMITED, DBASE, SQLITE3, VERSION3