

Axes

David

2024-11-25


Table of contents

1. Box plot	1
2. Swap x and y axes	2
3. Arrange two plots side by side	3
4. Setting the Range of a Continuous Axis	4
5. Reversing a Continuous Axis	5
6. Practice: Multiple charts from Iris	7
7. Setting the Scaling Ratio of the X- and Y-Axes	8
8. Setting the Positions of Tick Marks	9
9. Removing Tick Marks and Labels	10
10. Changing the Text of Tick Labels	12
11. Lower ‘Tallish’ to include 6 people	13
12. Changing the Appearance of Tick Labels	14
13. Changing the Text of Axis Labels	16
14. Removing Axis Labels	16
15. Changing the Appearance of Axis Labels.	17

1. Box plot

- Draw a boxplot using `PlantGrowth` dataset.
- x axis represents group, y axis represents `weight`.
- Use `geom_boxplot()` function to draw boxplot.
- `labs()` function is to add title, axis labels, and caption.
- Use `theme()` function to center the title.


```
library(ggplot2)
ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))
```



2. Swap x and y axes

- Use `coord_flip()` function to swap x and y axes.

```
library(ggplot2)
ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  coord_flip() +
  labs(title = "Weight VS Group",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))
```



3. Arrange two plots side by side


- Install `gridExtra` library.
- Prepare two plots: `p1`, `p2`.
- Use `grid.arrange()` function to arrange plots and add title.

```
library(ggplot2)
library(gridExtra)

p1 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))

p2 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  coord_flip() +
  labs(title = "Weight VS Group",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))
```

```
grid.arrange(p1, p2, ncol = 2,
             top = 'Arrange two plots side by side')
```



4. Setting the Range of a Continuous Axis

- `ylim()`: Sets the limits of the y-axis.


```
library(ggplot2)
library(gridExtra)

p1 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))

p2 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20)) +
```

```
ylim(0, max(PlantGrowth$weight))

grid.arrange(p1, p2, ncol = 2,
             top = 'Setting the Range of a Continuous Axis')
```



5. Reversing a Continuous Axis

- `scale_y_reverse()` reverses the direction of the y-axis on a plot. So, what was previously the highest value on the y-axis becomes the lowest, and vice-versa.

```
library(ggplot2)
library(gridExtra)

p1 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = 'Group vs Weight',
       x = 'Group',
       y = 'Weight',
       caption = 'By David, DV, THU, 2024') +
  theme(plot.title = element_text(hjust = 0.5))
```

```

p2 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  scale_y_reverse() +
  labs(title = 'Group vs Weight',
        x = 'Group',
        y = 'Weight',
        caption = 'By David, DV, THU, 2024') +
  theme(plot.title = element_text(hjust = 0.5))

p3 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  scale_y_reverse() +
  ylim(6.5, 3.5) +
  labs(title = 'Group vs Weight',
        x = 'Group',
        y = 'Weight',
        caption = 'By David, DV, THU, 2024') +
  theme(plot.title = element_text(hjust = 0.5))

```

Scale for y is already present.

Adding another scale for y, which will replace the existing scale.


Scale for y is already present. Adding another scale for y, which will replace the existing scale.

```

grid.arrange(p1, p2, p3, ncol = 3,
              top = 'Reversing a Continuous Axis')

```

Reversing a Continuous Axis




6. Practice: Multiple charts from Iris

- `grid.arrange()` function from the `gridExtra` package in R to arrange four plots (named `plot1`, `plot2`, `plot3`, and `plot4`) into a single figure.

```
plot1<-ggplot(iris, aes(x = Species, y = Sepal.Length)) +
  geom_boxplot() +
  labs(title = "Species VS Sepal Length",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 10))
plot2<-ggplot(iris, aes(x = Species, y = Sepal.Width)) +
  geom_boxplot() +
  labs(title = "Species VS Sepal Length",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 10))
plot3<-ggplot(iris, aes(x = Species, y = Petal.Length)) +
  geom_boxplot() +
  labs(title = "Species VS Sepal Length",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 10))
plot4<-ggplot(iris, aes(x = Species, y = Petal.Width)) +
  geom_boxplot() +
```

```
labs(title = "Species VS Sepal Length",
      caption = "By David, DV, THU, 2024") +
theme(plot.title = element_text(hjust = 0.5, size = 10))

grid.arrange(plot1, plot2, plot3, plot4, ncol=4,
              top = 'David: Species and Features')
```



7. Setting the Scaling Ratio of the X- and Y-Axes

- `coord_fixed()` is a function that fixes the aspect ratio of the plot. This means that the units on the x-axis and y-axis will be of equal length.

```
library(gcookbook)


plot1 <- ggplot(marathon, aes(x=Half,y=Full)) +
  geom_point() +
  labs(title = "Half VS Full",
        caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))

plot2 <- ggplot(marathon, aes(x=Half,y=Full)) +
```



```
geom_point() +
coord_fixed() +
labs(title = "Half VS Full",
      caption = "By David, DV, THU, 2024") +
theme(plot.title = element_text(hjust = 0.5, size = 20))

grid.arrange(plot1, plot2, ncol=2,
              top = 'Setting the Scaling Ratio of the X- and Y-Axes')
```




8. Setting the Positions of Tick Marks

- `scale_y_continuous()` is a function used to control the y-axis of a plot when the y-axis variable is continuous (meaning it can take on any value within a range, like temperature, weight, or time).

```
p1 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = "Group VS Weight",
        caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))
```

```
p2 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  scale_y_continuous(breaks = c(4, 4.25, 4.5, 5, 6, 8)) +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))

# Add title
grid.arrange(p1, p2, ncol = 2,
             top = 'Setting the Positions of Tick Marks')
```



9. Removing Tick Marks and Labels

- To remove the tick marks, use `theme(axis.ticks=element_blank())`. This will remove the tick marks on both axes.
- To remove the tick marks, the labels, and the grid lines, set breaks to NULL

```
p1 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
```

```

  theme(plot.title = element_text(hjust = 0.5, size = 12))

p2 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  theme(axis.text.y = element_blank()) +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 12))

p3 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  theme(axis.ticks = element_blank(), axis.text.y = element_blank()) +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 12))


p4 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  scale_y_continuous(breaks = NULL) +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 12))

grid.arrange(p1, p2, p3, p4, ncol = 4,
             top = 'David: Removing Tick Marks and Labels')

```

David: Removing Tick Marks and Labels

Group VS Weig Group VS Weigh Group VS Weigh Group VS Weigh



y David, DV, THU, 2024By David, DV, THU, 2024By David, DV, THU, 2024By David, DV, THU, 2024

10. Changing the Text of Tick Labels

- **breaks:** Specifying the locations of the tick marks and labels on the y-axis (`breaks = seq(min, max, by = interval)`). This gives you more control over the spacing and readability of the axis labels.
- **labels:** Customizing the text of the axis labels (`labels = function(x) ...`). This allows for formatting, unit specification, or abbreviation of the labels.

```
library(gcookbook)

p1 <- ggplot(heightweight, aes(x = ageYear, y = heightIn)) +
  geom_point() +
  labs(title = "Age VS Height",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))


p2 <- ggplot(heightweight, aes(x = ageYear, y = heightIn)) +
  geom_point() +
  scale_y_continuous(
    breaks = c(50, 56, 60, 66, 72),
    labels = c("Tiny", "Really\nshort", "Short", "Medium", "Tallish")
  ) +
```

```

labs(title = "Age VS Height",
      caption = "By David, DV, THU, 2024") +
theme(plot.title = element_text(hjust = 0.5, size = 20))

# Add title
grid.arrange(p1, p2, ncol = 2,
              top = 'Changing the Text of Tick Labels')

```



11. Lower 'Tallish' to include 6 people

- Use `scale_y_continuous()` to change the text of the axis labels
- Use `breaks = c()` to break the axis labels
- Use `labels = c()` to add a name in axis labels

```

p1 <- ggplot(heightweight, aes(x = ageYear, y = heightIn)) +
  geom_point() +
  labs(title = "Age VS Height",
        caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 20))

p2 <- ggplot(heightweight, aes(x = ageYear, y = heightIn)) +


```

```

geom_point() +
scale_y_continuous(
  breaks = c(50, 56, 60, 66, 69),
  labels = c("Tiny", "Really\nshort", "Short", "Medium", "Tallish")
) +
labs(title = "Age VS Height",
      caption = "By David, DV, THU, 2024") +
theme(plot.title = element_text(hjust = 0.5, size = 20))

# Add title
grid.arrange(p1, p2, ncol = 2,
              top = 'Lower Tallish to include 6 people')

```



12. Changing the Appearance of Tick Labels


- `axis.text.x = element_text(...)`: This part specifically targets the text elements of the x-axis. `element_text` is a function that controls the formatting of text within the plot.
- `angle = 30`: This rotates the x-axis labels by 30 degrees. This is often useful when labels are long and overlapping.

```

library(ggplot2)
library(gridExtra)
pg_plot <- ggplot(PlantGrowth, aes(x = group, y = weight)) +
  geom_boxplot() +
  scale_x_discrete(
    breaks = c("ctrl", "trt1", "trt2"),
    labels = c("Control", "Treatment 1", "Treatment 2")
  ) +
  labs(title = "Group VS Weight",
       caption = "By David, DV, THU, 2024") +
  theme(plot.title = element_text(hjust = 0.5, size = 16))
p1 <- pg_plot
p2 <- pg_plot +
  theme(axis.text.x = element_text(angle = 90, hjust = 1, vjust = .5))
p3 <- pg_plot +
  theme(axis.text.x = element_text(angle = 30, hjust = 1, vjust = 1))

grid.arrange(p1, p2, p3, ncol = 3,
             top = 'Changing the Appearance of Tick Labels')


```



13. Changing the Text of Axis Labels

- Use `xlab()` or `ylab()` to change the text of the axis labels

```
hw_plot <- ggplot(heightweight, aes(x = ageYear, y = heightIn, colour = sex)) +  
  geom_point()  
  
p1 <- hw_plot  
p2 <- hw_plot +  
  xlab('Age in years') +  
  ylab('Height in inches')  
  
grid.arrange(p1, p2, ncol = 2,  
             top = 'Changing the Text of Axis Labels')
```




14. Removing Axis Labels

```
p1 <- ggplot(PlantGrowth, aes(x = group, y = weight)) +  
  geom_boxplot()  
  
p2 <- p1 +
```



```
xlab(NULL)

grid.arrange(p1, p2, ncol = 2,
             top = 'Removing Axis Labels')
```



15. Changing the Appearance of Axis Labels.

- `axis.title.x = element_text(...)`: This specifies that we're modifying the x-axis title. `element_text` is used to set text properties.

```
p1 <- ggplot(heightweight, aes(x = ageYear, y = heightIn)) +
  geom_point()
p2 <- p1 +
  theme(axis.title.x = element_text(face = "italic", colour = "darkred",
                                     size = 14))
grid.arrange(p1, p2, ncol = 2,
             top = 'Changing the Appearance of Axis Labels')
```

Changing the Appearance of Axis Labels

