

# ChatGarment: Garment Estimation, Generation and Editing via Large Language Models

Siyuan Bian<sup>1,2</sup> Chenghao Xu<sup>1,3</sup> Yuliang Xiu<sup>1,4</sup> Artur Grigorev<sup>1,5</sup> Zhen Liu<sup>1,6</sup>  
 Cewu Lu<sup>2</sup> Michael J. Black<sup>1</sup> Yao Feng<sup>1,5,7</sup>

<sup>1</sup>Max Planck Institute for Intelligent Systems <sup>2</sup>Shanghai Jiao Tong University <sup>3</sup>EPFL  
<sup>4</sup>Westlake University <sup>5</sup>ETH Zürich <sup>6</sup>Mila, University of Montreal <sup>7</sup> Meshcapade

[chatgarment.github.io](https://chatgarment.github.io)




Figure 1. As a multimodal 3D garment creator, ChatGarment understands both images and language. It can estimate complex 3D garments represented as sewing patterns from a single image, which can be easily animated and simulated. It also supports garment editing based on text instructions.

## Abstract

We introduce *ChatGarment*, a novel approach that leverages large vision-language models (VLMs) to automate the estimation, generation, and editing of 3D garments from images or text descriptions. Unlike previous methods that struggle in real-world scenarios or lack interactive editing capabilities, *ChatGarment* can estimate sewing patterns from in-the-wild images or sketches, generate them from text descriptions, and edit garments based on user instructions, all within an interactive dialogue. These sewing patterns can then be draped into 3D garments, which are easily animatable and simulatable. This is achieved by finetuning a VLM to directly generate a JSON file that includes both textual descriptions of garment types and styles, as well as continuous numerical attributes. This JSON file is then used to create sewing patterns through a programming parametric model. To support this, we refine the existing programming model, *GarmentCode*, by expanding its garment type coverage and simplifying its structure for efficient VLM fine-tuning. Additionally, we construct a large-scale dataset of image-to-sewing-pattern and text-to-sewing-pattern pairs through an automated data pipeline. Extensive evaluations demonstrate *ChatGarment*'s ability to accurately reconstruct, gen-

erate, and edit garments from multimodal inputs, highlighting its potential to revolutionize workflows in fashion and gaming applications. Code and data will be available at <https://chatgarment.github.io/>.

## 1. Introduction

Imagine seeing a photo of someone in a nice looking outfit that you would like for yourself or your 3D avatar. Our goal is to take that photo and convert it into a 2D sewing pattern and then enable the user to use language to edit the pattern, for example, making the sleeves longer or editing the neckline. We then drape the garment on a 3D body and animate it. This is illustrated in Fig. 1. With this approach, given just an image and/or text, we construct sewing patterns for 3D garments that can be immediately used in fashion or gaming applications. This lightweight process is in stark contrast to how sewing patterns and 3D garments are traditionally created by an artist or clothing designer. In contrast to the traditional labor-intensive process, our approach exploits large vision-language models (VLMs) for the first time to democratize the capture and design of clothing.

Recent work explores the generation or estimation of 3D clothing using text and/or images as input [6, 8, 21, 43].

These methods use various 3D representations including 3D meshes, point clouds, or implicit representations like Unsigned Distance Functions (UDFs) and Signed Distance Functions (SDFs). We observe, however, that most clothing is designed and manufactured using 2D patterns, and posit that this is a more natural representation. Representing 3D clothing with sewing patterns has the benefit that these can be readily imported into existing clothing design pipelines for animation or manufacturing. Accordingly, recent approaches [16, 32, 35] use sewing patterns for garment estimation and generation. However, mapping images or text to sewing patterns remains challenging due to limited datasets, leading to poor generalization across diverse clothing types. Additionally, these methods often lack interactive editing capabilities, a vital feature for 3D artists, making post-processing labor intensive. Fortunately, recent work, such as GarmentCode [25, 26], provides a programmatic framework for encoding garment information into a JSON file. This JSON file includes textual descriptions of garment types, styles and numerical attributes, offering a rich representation of sewing patterns. The JSON file is then processed by the GarmentCode framework to produce 2D sewing patterns, which can subsequently be draped into 3D garments. However, to date, there is no automated method to directly extract a GarmentCode representation (JSON file) from an image or text description.

Our observation is that JSON file resembles natural language, making it suitable for interpretation by large language models (LLMs). At the same time, Vision-LLMs (VLMs) excel at understanding images and garment concepts, such as types of garments and specific features like long sleeves. If we enable the VLM to translate its garment understanding into the structured format of GarmentCode, then it becomes capable of generating sewing patterns. This allows the VLM to take an image as input and output a garment, while also supporting garment generation and editing through text descriptions or interactive dialogue.

Specifically, we introduce **ChatGarment**, a method that finetunes a VLM to take text queries, optionally with images, as input and output a JSON garment file. This JSON file is then used to generate sewing patterns via GarmentCode. The JSON file includes textual descriptions of garment types (e.g., skirts, pants), styles (e.g., collar type), and continuous numerical attributes (e.g., pant length). Inspired by previous works [11, 14, 27], we encode these numerical values into a single token and train an MLP projection layer to decode them into precise numbers. Those numbers, combined with the VLM’s language output, are formatted into the final JSON file. In our approach, we keep the VLM’s vision encoder fixed, fine-tune the language model using LoRA [18], and jointly train the MLP projection layer. To adapt GarmentCode [25] for more efficient VLM training, we create an improved version that supports a wider range of clothing

types (e.g. open-jacket) and removes unnecessary settings to reduce token usage in training. We also develop an automated data construction pipeline that leverages existing tools for garment generation, draping, simulation, rendering, and automatic labeling with GPT-4o. This pipeline enables us to build a dataset of image-to-GarmentCode and text-to-GarmentCode pairs, with 20K new garments and 1M images with detailed descriptions, supporting both garment creation and editing.

We evaluate ChatGarment across a diverse set of tasks, including those specifically trained for, and novel applications that demonstrate the generalization capabilities of VLMs. For single-image garment reconstruction, ChatGarment outperforms prior sewing-pattern-specific and LLM-based models on the Dress4D [56] and CloSE [2] evaluation datasets. We demonstrate garment editing, generation, and multi-turn dialogue, highlighting our approach’s versatility. ChatGarment can flexibly use text and images to create and edit 3D garments that can be readily animated, introducing a new workflow for garment design.

We summarize our contributions as follows:

- A unified model capable of estimating, generating and editing sewing patterns from multimodal inputs.
- The first approach to leverage VLMs for directly generating JSON files for garment creation.
- A refined version of programming parametric sewing pattern model that supports more diverse garment types and is optimized for VLM training.
- An automatic data construction pipeline for generating image-to-sewing-pattern and text-to-sewing-pattern data, along with the release of a large-scale dataset.

## 2. Related Work

**Garment Creation.** Most 3D garments have predefined templates (e.g., sewing patterns) and categories (e.g., skirts, shirts, pants, dresses, etc.), but their non-rigid nature makes them highly deformable with dynamic motions. Efforts to create 3D garments can be grouped into “template-based” or “free-form” methods, based on their 3D representations.

For template-based creation, a line of work registers predefined garment templates to 2D visual inputs. These inputs can come from real captures, such as the monocular video [5, 21, 38, 43], and causal images [3, 6, 7, 64], generative data [50], or from the “proxy gradient” computed from 2D diffusion models [28, 48] via score distillation sampling (SDS). When the template classification is accurate, the predefined garment template, refined through coarse-to-fine step, ensures topological stability and correctness. However, if the classification fails, the reconstruction accuracy will drop significantly. Additionally, template-based methods struggle to accurately model garments that deviate from the predefined templates, particularly those with diverse styles,

such as long skirts, or garments that undergo topological changes, like opening a jacket.

To address these limitations, free-form representations like (un)signed distance functions [6, 8, 61], occupancy fields [46, 47, 58, 59], tetroherons [20, 37, 49], and point clouds [39, 40] are leveraged. However, this flexibility can compromise the inherent structure of garments, potentially leading to non-garment shapes and floating artifacts. Without shape regularization, incomplete observations lead to the reconstructed unseen parts being overly smooth. Even worse, rigging or simulating these free-form garments becomes extremely challenging.

The sewing pattern is a well-balanced solution – with pre-defined yet flexible templates. Several methods exploit sewing patterns to reconstruct 3D garments. MulayCap [52] estimates the parameters of a sewing pattern from a monocular video. ISP [32] parameterizes sewing patterns as implicit functions in a 2D space. Using ISP as garment representation, GarmentRecovery [31] trains a feedforward network to infer sewing patterns from in-the-wild photos. Neural-Tailor [24] uses RNN to produce more complex sewing patterns from point clouds, Wang *et al.* [55] learns a shared garment shape space which could be inferred from multimodal input like sketch, and SewFormer [35] uses transformer to infer multi-panel patterns from monocular images. Despite promising results, these approaches are limited to basic sewing patterns, featuring only front and back panels, or constrained by the limited sewing patterns seen in the training data. Additionally, none of the above works have explored using programming parametric sewing patterns, such as GarmentCode [25, 26] to create more complex garments, either in generation or reconstruction.

**VLMs for 3D tasks.** With their broad understanding of the world, LLMs and VLMs are widely used to reason about 3D. There has been significant work on generating, editing, and analyzing 3D objects and scenes [13, 17, 19, 33, 45, 53, 60, 63]. While these methods show the power of VLMs to reason about objects, they do not address our problem of representing 2D patterns that correspond to 3D shapes – this is a unique property of garments. Some attempts have been made to connect sewing patterns with language, such as DressCode [16]. This motivates us to present ChatGarment, which connects the large language model to GarmentCode, sharing a similar approach to recent strategies [11, 34] by finetuning LLMs [18, 36, 44]. Powered by VLMs, ChatGarment significantly improves generalization and robustness in reconstructing out-of-domain images and increases diversity in 3D clothing generation. It also supports sewing pattern editing and multi-turn dialogue, greatly simplifying the 3D garment workflow.




Figure 2. **Pipeline of ChatGarment.** ChatGarment takes texts or an image as input and generates a JSON file. The JSON file is decoded into a 2D sewing pattern using GarmentCode [25] and then draped onto the human body. The final 3D garments are compatible with simulation softwares (*e.g.*, MAYA, Blender, Style3D, *etc.*).

### 3. Method

The goal of ChatGarment is to simplify the workflow of garment creation by automatically estimating, generating, and editing garments from multimodal image and text input. Following previous work [11], we finetune LLaVA [34], an open-source VLM, that can take an image or text description as input and output text. The output of ChatGarment is a JSON file which can later be decoded into a sewing pattern using a programming parametric model GarmentCode [25]. The pipeline is introduced in Sec 3.1. To support the training of VLM on garment creation, we refine GarmentCode as illustrated in Sec. 3.1 and introduce an automatic data construction pipeline in Sec. 3.2 to create the training data. The training strategy is explained in Sec. 3.3 and we show how our trained unified model can be used for garment generation and editing in Sec. 3.4.

#### 3.1. Pipeline

The pipeline of ChatGarment is illustrated in Fig. 2. ChatGarment is a multimodal large language model  $f_\phi$ . It takes an input image  $X_v$  and text descriptions  $X_q$ , and produces a textual response  $Y_t$  as  $Y_t = f_\phi(X_q, X_v)$  or  $Y_t = f_\phi(X_q)$  in the absence of an image. From this output, a JSON file  $J_t$  is extracted as a subset of  $Y_t$ , which will be decoded into a sewing pattern using a decoder  $D_g$  adapted from GarmentCode [25] framework.

**LLM for Textual and Numeric Outputs.** The JSON file  $J_t$  contains both textual and numeric descriptions. Previous research [11, 14, 27] has shown that LLMs struggle in predicting continuous and precise numerical values. To overcome this, following ChatPose [11], we encode these continuous values into language token embeddings and train a projection layer to recover accurate numerical values, such as garment length. In this setup, the language embedding for  $Y_t$  is represented as  $H_t$ . From the textual output  $Y_t$ , upon encountering the start token  $\langle \text{STARTS} \rangle$ , we extract the textual content of the JSON file, which spans from  $\langle \text{STARTS} \rangle$  to  $\langle \text{ENDS} \rangle$ . The language embedding at the point of the end token  $\langle \text{ENDS} \rangle$ , where numeric information is encoded, is




Figure 3. **GarmentCodeRC**. Left: added options for open-front jackets and high-waist skirts, with adjusted parameter ranges to better model tight pant legs. The vanilla GarmentCode lacks support for open-front jackets, cannot adjust waist height and does not allow setting pants width smaller than 1.0. Right: simplified JSON configuration for more efficient LLM training.

represented as  $H_t^n$ . A projection layer uses this embedding to predict the numerical values as  $\mathbf{n} = g_{\Theta}(H_t^n)$ . Finally, we merge these numerical values with the textual descriptions extracted earlier and format them into our final sewing pattern JSON configuration file  $J_t$ .

**LLM-friendly Rich GarmentCode.** We use GarmentCode framework to convert the JSON file into a 3D garment mesh in the canonical pose. GarmentCode [25] is a programming parametric model that uses a domain-specific language (DSL) for creating 2D sewing patterns, with a hierarchical JSON structure to define garment components and stitching rules. These patterns can be draped onto body models via a warp-based pattern stitching algorithm [25, 41], and further be simulated easily. To better align GarmentCode with our model’s language-driven requirements, we develop an refined version, GarmentCodeRC (Richer & Cleaner) with two major improvements (see Fig. 3).

First, we modify stitching and panel positioning to better support diverse garment types, such as open-front jackets, high-waist skirts, and fitted pant legs. This allows us to model a broader range of real-world garments and aligns more closely with natural garment descriptions. Second, we simplify GarmentCode’s JSON configuration to better suit LLM training. The original configuration is redundant, applying the same settings across all garment types. We optimize this by automatically removing irrelevant settings during garment construction (e.g., omitting skirt-related parameters for upper-body garments). This adjustment reduces the average language token count from 900 to 350, decreasing ambiguity in LLM training and improving training efficiency. Furthermore, to stabilize model training, we normalize all floating-point values to a  $[0, 1]$  range. Throughout this paper, “GarmentCode” refers to our enriched and simplified version.




Figure 4. **Data Construction Pipeline.** We generate garments from JSON configurations, simulate them with ContourCraft [15] and render with Blender.

### 3.2. Automatic Data Construction

To train ChatGarment, we need image-to-JSON and text-to-JSON paired data. While some work like SewFormer [35] offers image-to-JSON pairs, they fall short in garment variety. For example, they lack tight-sleeve garments and support only one type of skirts. Additionally, text descriptions for garment editing are missing in current datasets. We addressed these gaps by developing an automated data construction pipeline that integrates various resources.

**Garment Generation, Simulation, and Rendering.** Following GarmentCodeData [26], we sample 20,000 garments by randomizing values in sewing pattern configurations. To improve real-world garment relevance, we adjust the sampling ratios and assign lower weights for asymmetric garments and those with intricate cuffs. To create outfits, we pair top and bottom garments together or use single-piece items like dresses or jumpsuits. The garment set is draped on a SMPL-X [42] neutral model.

We automate garment simulation using ContourCraft [15], chosen for its stability and scalability, with SMPL-X motion sequences sampled from the BEDLAM dataset [4]. To improve simulation accuracy, we finetune ContourCraft on sampled garments. Specific garment vertices are attached to corresponding body vertices using predefined rules to prevent garments from slipping off. For example, the upper edges of pants and skirts are connected to the nearest body vertices, and similar attachments are made for vertices of upper-body garments near the shoulders. To ensure smooth motion transitions, we interpolate between the rest-pose body and the initial motion frame using Slerp quaternion interpolation [51] across 60 frames.

Additionally, we filter out simulations with significant interpenetration or improper positioning, which involve two key components. First, GarmentCode performs a sewing-pattern validation check, ensuring the integrity of panel edges and stitching. Second, we verify simulation results by assessing inter-penetration between garment panels and between the garment and body, and identify garments at risk

of slipping off by inspecting the proximity of each garment vertex to the nearest body part. Each garment is then rendered in Blender from four random perspectives at elevation angles between 0 and 30 degrees, with garment and body textures sourced from the BEDLAM dataset. These steps are shown in Fig. 4.

**GPT-4o Labeling.** We generate descriptive text labels for garment geometry from both simulated images and SHHQ [12] images using GPT-4o. The previous method [16] prompts GPT-4o to generate the general geometric descriptions for garments, such as the garment types, lengths, widths and sleeve lengths. However, these general descriptions are insufficient for garment detail understanding: the finetuned VLM struggles to interpret detailed features of garment components, such as pant cuffs, or execute specific garment edits. To address this, we construct an additional dataset with low-level descriptions for individual garment parts. For image-based reconstruction, we refine the original prompts by instructing GPT-4o to generate descriptions for all visible garment parts in the image. For garment editing, we sample 5,000 unique garment parts (shirt main body, collar, sleeves, sleeve cuffs, waistband, pant legs, pant cuffs, and skirts), and use GPT-4o to generate descriptive text for each part. Assembling these components yields 20,000 new garments with detailed annotations. The GPT-4o prompts and example garment annotations are given in *Sup. Mat.*.

For garment editing, we randomly select two garments that differ in certain parts. The corresponding editing prompt is specified as: “Change the garment sewing pattern by modifying <PART-1> to <DESCRIPTIONS-1>, <PART-2> to <DESCRIPTIONS-2>, … while keeping other parts unchanged.”. Here, <PART-1>, <PART-2> … represent the names of the parts that differ between the two garments, and <DESCRIPTIONS-1>, <DESCRIPTIONS-2> are the descriptions of the target garment parts.

We finally build a synthetic dataset of over 40K garments and 1 million images with text annotations, supporting garment reconstruction and editing from multimodal inputs. Plus, we use GPT-4o to label part-level details of 38K SHHQ images to make the VLM better understand in-the-wild garment images. Compared to previous garment sewing pattern datasets [35], our dataset offers: 1) **Diversity**: GarmentCode generates a wider range of real-world garment types; 2) **Detailed descriptions**: Garments are labeled with detailed geometric features via GPT-4o; 3) **Precise Control**: Allows for precise, low-level garment manipulation.

### 3.3. Training

We use LLaVA [34] as our base VLM and finetune it with LoRA [18], with its parameters denoted as  $\phi_{lora}$ . Additionally, we optimize the LLM token embedding  $e_{token}$ ,

the LLM head  $lm\_head_{\Theta'}$ , and the sewing pattern projection layer  $g_{\Theta}$ . The final set of optimizable parameters is  $\{\phi_{lora}, e_{token}, \Theta', \Theta\}$ .

**Loss Function** As described in Sec. 3.1, the numeric embedding is extracted from the token [ENDS] as  $H_t^n$ . An MLP projection layer maps the embedding  $H_t^n$  to 76 float values  $n$  in the JSON configuration. Given the ground truth text output  $\hat{Y}_t$  and sewing pattern values  $\hat{n}$ , we optimize with:

$$\mathcal{L} = CE(\hat{Y}_t, Y_t) + \lambda_n |\hat{n} - n|. \quad (1)$$

where the first term is cross-entropy loss, and the second term is the L1 difference for numeric values, with  $\lambda_n = 0.1$  serving as the weight for the loss.

**Training Data Details.** The training data consists of four parts: garment reconstruction data (35%), garment description data (15%), garment editing data (15%), and visual instruction tuning data (35%). For more training details, please check out *Sup. Mat.*

- **Garment Reconstruction Data:** Includes 20,000 simulated garments with images rendered by Blender and text labels generated by GPT-4o. During training, text labels and images are omitted from the input with a 25% probability respectively.
- **Garment Description Data:** Contains 38,000 SHHQ images with text descriptions generated by GPT-4o.
- **Garment Editing Data:** Comprises 20,000 garments generated following the rules in section 3.2.
- **Visual Instruction Tuning Data:** Utilizes LLaVA-v1.5-mix665k dataset<sup>1</sup>.

### 3.4. Multi-turn Dialogue with Multimodal Inputs.

After training, our model can handle multimodal input reconstruction, garment generation, and editing, as reflected in the training data. Additionally, it exhibits *zero-shot* reasoning for garment sewing patterns within multi-turn dialogues, despite being trained only on single-turn dialogue datasets.

This enables users to create a garment from an image or text description and then refine it within the same interaction. A typical workflow might start with the VLM estimating a sewing pattern from an image. After reviewing the result, the user can request specific adjustments, providing a flexible, user-centered design process (see Fig 5 for an example).

## 4. Experiments

We employ LLaVA-1.5V-7B [34] as our base VLM, with CLIP for vision encoding and Vicuna-7B, finetuned from Llama 2 [54] on conversational data, for the LLM backbone. We keep the vision encoder and vision projection frozen and use LoRA [18] to finetune the LLM. The sewing pattern projection layer consists of a two-layer Multi-Layer Perceptron

<sup>1</sup>liuhuatian/LLaVA-Instruct-150K




Figure 5. ChatGarment three dialog modes. **Image** could be used either as observation (-based) or guidance (-guided). **Text instructions** indicates the tasks  $\{\text{estimate}, \text{generate}, \text{edit}\}$  and text output between STARTS and ENDS contains information about the JSON information, and finally will be converted as 3D garments (**JSON2Garment**) for visualization and simulation purposes.

(MLP) with a hidden size of 5120 and an output size of 76. The model is trained for 40 epochs, with 500 steps per epoch, using the AdamW optimizer [22] and a learning rate of 1e-4.

#### 4.1. Image-based Reconstruction

**Benchmarks.** We conduct image-based reconstruction experiments on CloSe [2] and Dress4D [56] datasets. The CloSe dataset is a large-scale scan collection including 3D clothing segmentations from 3,167 scans across 18 distinct clothing categories. Following CloSe evaluation, we use 145 scans from the CloSe dataset as our validation set. We further exclude samples with inaccurate SMPL-X fits. Each garment is rendered using Blender from randomly selected camera views. As the CloSe dataset offers limited instances of loose garments, such as skirts and dresses, we further add samples from Dress4D, which has 64 unique real-world outfits recorded using a high-end multi-view volumetric capture system. We include 4 loose-fitting outfits and 36 images rendered from these outfits.


**Implementation Details.** Our approach applies the Chain-of-Thought[57] method. It involves prompting the model with a text description of the given garment, later combined with the image to generate garment JSON files. More details are provided in *Sup. Mat.*

**Baselines.** We compare our method with three previous approaches, DressCode [16], SewFormer [35] and GarmentRecovery [31]. We use the publicly available code and checkpoints for these methods in our evaluation. For DressCode, we query GPT-4o for garment descriptions and then

generate garment sewing patterns based on the texts. Additionally, we introduce several new baseline models that are LLM related:

- **GPT-4o.** We design prompt templates and query GPT-4o using in-context learning (ICL) [10]. We use Garment Generator [23] as the sewing pattern configuration tool, as it has significantly fewer possible configurations than GarmentCode and allows for more efficient prompt template design and significantly fewer conversation rounds. Specifically, we first prompt GPT-4o to choose the most suitable template from a predefined list, then query the parameter value by displaying three garment renderings with uniformly sampled parameter values.
- **LLaVA\*.** In this setup, we use the LLaVA model to directly output the numerical values for the sewing pattern instead of using the sewing pattern projection layer. The remaining components are identical to our method.
- **LLaVA-T.** We first employ GPT-4o to generate detailed textual descriptions of the garment, and ChatGarment is prompted to reconstruct the sewing pattern based solely on the text description.
- **LLaVA-I.** We input the image into the model and prompt it to directly output the sewing pattern without referring to text descriptions.

For all methods except GarmentRecovery, the predicted 2D sewing patterns are draped onto a rest-pose human body (A-pose or T-pose) using the Warp-based stitching method [41] with default parameters. These methods reconstruct garments only in the rest pose, whereas GarmentRecovery reconstructs them in both A-pose and T-pose.



**Figure 6. Image-based Garment Reconstruction.** Unlike previous methods (SewFormer [35], DressCode [16], GarmentRecovery [31], and GPT-4o-based method) which often mess up or miss the garments. ChatGarment could faithfully capture the shape, style and the composition of the target garments.

Methods	Target-Pose		A-Pose		Failure Rate (↓)
	CD (↓)	F-Score (↑)	CD (↓)	F-Score (↑)	
Sewformer [35]	27.06	0.55	20.66	0.58	4.3%
DressCode [16]	20.16	0.60	12.12	0.61	11.4%
GPT-4o	11.04	0.62	10.44	0.65	0
GarmentRecovery [31]	9.69	0.55	5.75	0.64	-
LLaVA*	5.29	0.72	6.29	0.76	0
LLaVA-T	6.17	0.72	7.25	0.74	0
LLaVA-I	4.32	<b>0.75</b>	4.93	<b>0.78</b>	0
Ours	<b>3.12</b>	<b>0.75</b>	<b>3.06</b>	<b>0.78</b>	0

**Table 1. Quantitative comparisons of Image-based garment reconstruction on the Dress4D dataset.** ChatGarment achieves the best performance on all metrics.

tRecovery reconstructs garments in both the T-pose and the target pose. For a fair comparison, we apply Linear Blend Skinning [1] to align all garments to the ground-truth human body and pose.

**Results.** We employ the mean chamfer distance, the mean F-Score at  $\tau = 0.001$  and the stitching failure rate as quan-

Methods	CLOSE		
	CD (↓)	F-Score (↑)	Failure Rate (↓)
SewFormer [35]	9.70	0.708	8.33 %
DressCode [16]	15.77	0.616	7.0%
GPT-4o	3.52	0.755	0
GarmentRecovery [31]	<b>2.39</b>	0.785	-
LLaVA*	3.08	0.775	0
LLaVA-T	3.76	0.779	0
LLaVA-I	4.55	0.761	0
Ours	2.94	<b>0.790</b>	0

**Table 2. Quantitative comparisons of Image-based reconstruction results on the CloSe dataset.** The garments are all deformed to the target pose. ChatGarment performs comparably to GarmentRecovery [31] and surpasses other methods.


titative metrics. In some cases, previous methods may fail to reconstruct certain garments due to detection or stitching failure. We exclude such samples from the the calcu-

lation of chamfer distance and F-Score, considering only those with complete outfits. As Tab. 1 and Tab. 2 show, ChatGarment significantly outperforms existing methods on loose garments in the Dress4D dataset. In the CloSE dataset, which mostly features tight garments, our method performs comparably to GarmentRecovery [31] and surpasses other methods. GarmentRecovery achieves accurate results on tight garments by leveraging garment segmentation and normal maps as guidance in an optimization-based framework. However, these cues are insufficient for accurately reconstructing loose garments. Also, our algorithm demonstrates its robustness in garment reconstruction as it has no stitching failures. In contrast, DressCode and SewFormer often generate invalid garment panels leading to failed stitching. The primary difference lies in the output format of each method. DressCode and SewFormer directly predict the panel edges and stitches of the sewing pattern, while our method and the GPT-4o-based approach estimate the Json configuration. Although directly predicting panel edges and stitches theoretically allows for greater flexibility in sewing pattern configuration, our experiments reveal that this approach does not improve reconstruction accuracy. Instead, it increases the likelihood of generating invalid sewing patterns when handling out-of-distribution (OOD) data.

Our model demonstrates superior performance compared to LLaVA\*, highlighting the effectiveness of the proposed sewing pattern projection layer. Furthermore, our two-step garment reconstruction algorithm outperforms both image-based (LLaVA-I) and text-based (LLaVA-T) reconstruction baselines. Since ChatGarment is trained on a text-labeled real-world image dataset (SHHQ dataset [12]), it can accurately identify garment types and styles, which provides valuable information for garment reconstruction. Moreover, garment images offer intricate details that are often difficult to convey through natural language descriptions. As a result, combining both text and image inputs proves to be the most effective strategy for the image-based reconstruction task.

Figure 6 shows our model accurately estimates garment type, style, and details like skirt hems and collar styles. In contrast, other methods often misinterpret or overlook these details. Missing garments is a notable problem for previous methods such as SewFormer and GarmentRecovery when applied to real-world images. SewFormer occasionally fails to reconstruct certain garments due to detection or stitching failure. GarmentRecovery does not support whole-body dress templates, resulting in incomplete reconstructions for such garments. Additionally, inaccurate 2D garment segmentation [30] further leads to garment reconstruction failures for GarmentRecovery.

Garment designers often create image sketches before making sewing patterns. Surprisingly, despite not being trained on garment sketch images, ChatGarment demonstrates strong generalization, accurately predicting garment



**Figure 7. Reconstruction results from garment sketches.** The generated sewing patterns and 3D garments accurately capture the shape and style of the input sketch, despite our model being trained without sketches.

types and styles from sketches Fig. 7.

## 4.2. Garment Editing

**Benchmarks.** To evaluate garment editing performance, we constructed an extra evaluation dataset using methods outlined in Sec. 3.2. We manually selected garment pairs with clear textual descriptions and substantial visual differences. This dataset consists of 135 garment pairs, each accompanied by corresponding images and text descriptions. The evaluation of garment editing involves three components: the source garment, the target garment, and the editing prompts. The goal is to derive the sewing pattern for the target garment using the source garment and the editing prompts.


Methods	CD ( $\downarrow$ )	F-Score ( $\uparrow$ )
SewFormer [35]	28.77	0.548
DressCode [16]	10.97	0.750
Ours	<b>2.51</b>	<b>0.893</b>

**Table 3. Quantitative comparisons for garment editing.** ChatGarment outperforms other two methods by a large margin.

**Implementation Details.** For garment editing, we concatenate the source garment JSON file and the editing prompt together and pass it into ChatGarment.

**Baselines.** We modify DressCode [16] and SewFormer [35] for fair comparison with ChatGarment:

- **DressCode with edited text.** We get a text description of the edited garment and use DressCode to generate the corresponding sewing pattern. The description is generated by providing 1) the garment editing instructions and 2) the front and back views of the source garment to GPT-4o.
- **SewFormer with edited images.** We obtain the front view of the edited garment with TurboEdit [9] to which we pass 1) the front view of the source garment, 2) the text description of the source garment, and 3) the text instruction for garment editing, and then use SewFormer to turn the image of the edited garment into the corresponding



**Figure 8. Results on Garment Editing.** We present six examples where the models (SewFormer [35], DressCode [16], and ChatGarment) edit the source garment shown in the source image according to the given editing instructions in the prompt boxes.

Methods	CLIP score ( $\uparrow$ )
DressCode [16]	22.8
Ours	<b>23.7</b>

**Table 4. Quantitative comparisons for text-based garment generation.** ChatGarment achieves a higher CLIP score than DressCode, indicating better alignment with the text inputs.

sewing pattern. The text description of the source garment is generated by prompting GPT-4o with both the back and front views of the source garment.

**Results.** We compare our method with SewFormer and Dresscode on Chamfer Distance and F-score in Tab. Sec. 4.2, where our approach demonstrates superior performance. The qualitative results in Fig. 8 show that our method accurately modifies the targeted garment parts according to the input prompt. In contrast, SewFormer and DressCode often fail to precisely follow the prompt instructions and frequently alter other unintended areas of the garment.

### 4.3. Text-based Generation

Following DressCode [16], we use GPT-4o to generate 150 highly diverse text labels from 85 selected in-the-wild images featuring various tops, skirts, pants, and dresses. Next, we render the generated 3D garments with default textures and compute the CLIP score using the provided text labels. See quantitative results in Tab. 4. Our model achieves a higher CLIP score compared to DressCode [16], highlighting the superior prompt-following capabilities of our approach. The qualitative results are shown in *Sup. Mat.*.

### 4.4. Ablation

We evaluate the impact of different aspects of ChatGarment, including multi-modal LLM backbones, and various training datasets. Please refer to *Sup. Mat.*.

## 5. Conclusion

We introduce ChatGarment, a VLM-based model that estimates garments from images and generates or edits garments based on text descriptions. Leveraging the capabilities of LLMs, ChatGarment supports multi-turn dialogue interactions for 3D garment design. It surpasses existing sewing pattern-specific and LLM-based methods in accurately estimating sewing patterns from a single image. While ChatGarment excels in many areas, it may struggle with precise garment editing. For instance, altering the skirt length might unintentionally affect other parts of the garment. This issue could be addressed with more detailed text instructions or a differential CSG optimizer [62] for finer adjustments. Nonetheless, ChatGarment offers the first VLM-based framework for unified garment estimation, generation, and editing. Future directions could include expanding into garment manufacturing design or improving clothing simulation with more fine-grained material attributes.

**Acknowledgments** We thank *Maria Korosteleva* for help on GarmentCode, and *Giorgio Becherini* for advice on data processing. *Yuliang Xiu* has received funding from the European Union’s Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement No.860768 (*CLIPe* project), Max Planck Institute for Intelligent Systems, the Research Center for Industries of the Future (RCIF) at Westlake University, and the Westlake Education Foundation.

**Disclosure** MJB has received research gift funds from Adobe, Intel, Nvidia, Meta/Facebook, and Amazon. MJB has financial interests in Amazon and Meshcapade GmbH. While MJB is a co-founder and Chief Scientist at Meshcapade, his research in this project was performed solely at, and funded solely by, the Max Planck Society.

## References

- [1] Rinat Abdashitov, Kim Raichstat, Jared Monsen, and David Hill. Robust skin weights transfer via weight inpainting. In *SIGGRAPH Asia 2023 Technical Communications*, pages 1–4. 2023. 7
- [2] Dimitrije Antić, Garvita Tiwari, Batuhan Ozcomlekci, Riccardo Marin, and Gerard Pons-Moll. CloSe: A 3D clothing segmentation dataset and model. In *International Conference on 3D Vision (3DV)*, 2024. 2, 6, 15
- [3] Bharat Lal Bhatnagar, Garvita Tiwari, Christian Theobalt, and Gerard Pons-Moll. Multi-garment net: Learning to dress 3d people from images. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 5420–5430, 2019. 2
- [4] Michael J Black, Priyanka Patel, Joachim Tesch, and Jinlong Yang. Bedlam: A synthetic dataset of bodies exhibiting detailed lifelike animated motion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8726–8737, 2023. 4
- [5] Andrés Casado-Elvira, Marc Comino Trinidad, and Dan Casas. Pergamo: Personalized 3d garments from monocular video. In *Computer Graphics Forum*, pages 293–304. Wiley Online Library, 2022. 2
- [6] Enric Corona, Albert Pumarola, Guillem Alenya, Gerard Pons-Moll, and Francesc Moreno-Noguer. Smplicit: Topology-aware generative model for clothed people. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11875–11885, 2021. 1, 2, 3
- [7] R Daněřek, Endri Dibra, Cengiz Özti̇reli, Remo Ziegler, and Markus Gross. Deepgarment: 3d garment shape estimation from a single image. In *Computer Graphics Forum*, pages 269–280. Wiley Online Library, 2017. 2
- [8] Luca De Luigi, Ren Li, Benoit Guillard, Mathieu Salzmann, and Pascal Fua. Drapenet: Garment generation and self-supervised draping. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1451–1460, 2023. 1, 3
- [9] Gilad Deutch, Rinon Gal, Daniel Garabi, Or Patashnik, and Daniel Cohen-Or. Turboedit: Text-based image editing using few-step diffusion models. *arXiv preprint arXiv:2408.00735*, 2024. 8
- [10] Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Tianyu Liu, et al. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*, 2022. 6
- [11] Yao Feng, Jing Lin, Sai Kumar Dwivedi, Yu Sun, Priyanka Patel, and Michael J. Black. ChatPose: Chatting about 3d human pose. In *CVPR*, 2024. 2, 3
- [12] Jianglin Fu, Shikai Li, Yuming Jiang, Kwan-Yee Lin, Chen Qian, Chen-Change Loy, Wayne Wu, and Ziwei Liu. Stylegan-human: A data-centric odyssey of human generation. *arXiv preprint, arXiv:2204.11823*, 2022. 5, 8
- [13] Rao Fu, Xiao Zhan, Yiwen Chen, Daniel Ritchie, and Sri-nath Sridhar. Shapemcrafter: A recursive text-conditioned 3d shape generation model. *Advances in Neural Information Processing Systems*, 35:8882–8895, 2022. 3
- [14] Siavash Golkar, Mariel Pettee, Michael Eickenberg, Alberto Bietti, Miles Cranmer, Geraud Krawezik, Francois Lanusse, Michael McCabe, Ruben Ohana, Liam Parker, et al. xVal: A continuous number encoding for large language models. *arXiv preprint arXiv:2310.02989*, 2023. 2, 3
- [15] Artur Grigorev, Giorgio Becherini, Michael Black, Otmar Hilliges, and Bernhard Thomaszewski. Contourcraft: Learning to resolve intersections in neural multi-garment simulations. In *ACM SIGGRAPH 2024 Conference Papers*, pages 1–10, 2024. 4
- [16] Kai He, Kaixin Yao, Qixuan Zhang, Jingyi Yu, Lingjie Liu, and Lan Xu. Dresscode: Autoregressively sewing and generating garments from text guidance. *ACM Transactions on Graphics (TOG)*, 43(4):1–13, 2024. 2, 3, 5, 6, 7, 8, 9, 16, 17
- [17] Yining Hong, Haoyu Zhen, Peihao Chen, Shuhong Zheng, Yilun Du, Zhenfang Chen, and Chuang Gan. 3d-llm: Injecting the 3d world into large language models. *Advances in Neural Information Processing Systems*, 36:20482–20494, 2023. 3
- [18] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *ICLR*, 2022. 2, 3, 5, 13
- [19] Ziniu Hu, Ahmet Iscen, Aashi Jain, Thomas Kipf, Yisong Yue, David A Ross, Cordelia Schmid, and Alireza Fathi. Scenecraft: An llm agent for synthesizing 3d scenes as blender code. In *Forty-first International Conference on Machine Learning*, 2024. 3
- [20] Yangyi Huang, Hongwei Yi, Yuliang Xiu, Tingting Liao, Jiaxiang Tang, Deng Cai, and Justus Thies. TeCH: Text-guided Reconstruction of Lifelike Clothed Humans. In *International Conference on 3D Vision (3DV)*, 2024. 3
- [21] Boyi Jiang, Juyong Zhang, Yang Hong, Jinhao Luo, Ligang Liu, and Hujun Bao. Bcnet: Learning body and cloth shape from a single image. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XX 16*, pages 18–35. Springer, 2020. 1, 2
- [22] Diederik P Kingma. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014. 6, 14
- [23] Maria Korosteleva and Sung-Hee Lee. Generating datasets of 3d garments with sewing patterns. *arXiv preprint arXiv:2109.05633*, 2021. 6
- [24] Maria Korosteleva and Sung-Hee Lee. Neuraltailor: Reconstructing sewing pattern structures from 3d point clouds of garments. *ACM Transactions on Graphics (TOG)*, 41(4):1–16, 2022. 3
- [25] Maria Korosteleva and Olga Sorkine-Hornung. GarmentCode: Programming parametric sewing patterns. *ACM Transaction on Graphics*, 42(6), 2023. SIGGRAPH ASIA 2023 issue. 2, 3, 4, 13
- [26] Maria Korosteleva, Timur Levent Kesdogan, Fabian Kemper, Stephan Wenninger, Jasmin Koller, Yuhan Zhang, Mario Botsch, and Olga Sorkine-Hornung. GarmentCodeData: A dataset of 3D made-to-measure garments with sewing patterns. In *Computer Vision – ECCV 2024*, 2024. 2, 3, 4, 13
- [27] Peter Kulits, Haiwen Feng, Weiyang Liu, Victoria Abrevaya, and Michael J Black. Re-thinking inverse graphics with large

- language models. *Transactions on Machine Learning Research*, 2024. 2, 3
- [28] Boqian Li, Xuan Li, Ying Jiang, Tianyi Xie, Feng Gao, Huamin Wang, Yin Yang, and Chenfanfu Jiang. Garment-dreamer: 3dgs guided garment synthesis with diverse geometry and texture details. In *3DV*, 2025. 2
- [29] Minchen Li, Danny M. Kaufman, and Chenfanfu Jiang. Codimensional incremental potential contact. *ACM Trans. Graph. (SIGGRAPH)*, 40(4), 2021. 15
- [30] Peike Li, Yunqiu Xu, Yunchao Wei, and Yi Yang. Self-correction for human parsing. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(6):3260–3271, 2020. 8
- [31] Ren Li, Corentin Dumery, Benoît Guillard, and Pascal Fua. Garment recovery with shape and deformation priors. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1586–1595, 2024. 3, 6, 7, 8
- [32] Ren Li, Benoît Guillard, and Pascal Fua. Isp: Multi-layered garment draping with implicit sewing patterns. *Advances in Neural Information Processing Systems*, 36, 2024. 2, 3
- [33] Dingning Liu, Xiaoshui Huang, Yuenan Hou, Zhihui Wang, Zhenfei Yin, Yongshun Gong, Peng Gao, and Wanli Ouyang. Uni3d-llm: Unifying point cloud perception, generation and editing with large language models. *arXiv preprint arXiv:2402.03327*, 2024. 3
- [34] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning, 2023. 3, 5, 13
- [35] Lijuan Liu, Xiangyu Xu, Zhijie Lin, Jiabin Liang, and Shuicheng Yan. Towards garment sewing pattern reconstruction from a single image. *ACM Transactions on Graphics (TOG)*, 42(6):1–15, 2023. 2, 3, 4, 5, 6, 7, 8, 9
- [36] Weiyang Liu, Zeju Qiu, Yao Feng, Yuliang Xiu, Yuxuan Xue, Longhui Yu, Haiwen Feng, Zhen Liu, Juyeon Heo, Songyou Peng, Yandong Wen, Michael J. Black, Adrian Weller, and Bernhard Schölkopf. Parameter-efficient orthogonal finetuning via butterfly factorization. In *ICLR*, 2024. 3
- [37] Zhen Liu, Yao Feng, Yuliang Xiu, Weiyang Liu, Liam Paull, Michael J. Black, and Bernhard Schölkopf. Ghost on the shell: An expressive representation of general 3d shapes. In *The Twelfth International Conference on Learning Representations*, 2024. 3
- [38] Zhongjin Luo, Haolin Liu, Chenghong Li, Wanghao Du, Zirong Jin, Yinyu Nie, Weikai Chen, and Xiaoguang Han. Garverselod: High-fidelity 3d garment reconstruction from a single in-the-wild image using a dataset with levels of details. In *ACM Transactions on Graphics (TOG)*, 2024. 2
- [39] Qianli Ma, Jinlong Yang, Siyu Tang, and Michael J. Black. The power of points for modeling humans in clothing. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 10974–10984, 2021. 3
- [40] Qianli Ma, Jinlong Yang, Michael J. Black, and Siyu Tang. Neural point-based shape modeling of humans in challenging clothing. In *International Conference on 3D Vision (3DV)*, pages 679–689, 2022. 3
- [41] Miles Macklin. Warp: A high-performance python framework for gpu simulation and graphics. <https://github.com/nvidia/warp>, 2022. NVIDIA GPU Technology Conference (GTC). 4, 6
- [42] Georgios Pavlakos, Vasileios Choutas, Nima Ghorbani, Timo Bolkart, Ahmed A. A. Osman, Dimitrios Tzionas, and Michael J. Black. Expressive body capture: 3D hands, face, and body from a single image. In *CVPR*, 2019. 4
- [43] Lingteng Qiu, Guanying Chen, Jiapeng Zhou, Mutian Xu, Junle Wang, and Xiaoguang Han. Rec-mv: Reconstructing 3d dynamic cloth from monocular videos. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4637–4646, 2023. 1, 2
- [44] Zeju Qiu, Weiyang Liu, Haiwen Feng, Yuxuan Xue, Yao Feng, Zhen Liu, Dan Zhang, Adrian Weller, and Bernhard Schölkopf. Controlling text-to-image diffusion by orthogonal finetuning. In *NeurIPS*, 2023. 3
- [45] Zeju Qiu, Weiyang Liu, Haiwen Feng, Zhen Liu, Tim Z Xiao, Katherine M Collins, Joshua B Tenenbaum, Adrian Weller, Michael J Black, and Bernhard Schölkopf. Can large language models understand symbolic graphics programs? *arXiv preprint arXiv:2408.08313*, 2024. 3
- [46] Shunsuke Saito, Zeng Huang, Ryota Natsume, Shigeo Morishima, Hao Li, and Angjoo Kanazawa. PIFu: Pixel-aligned implicit function for high-resolution clothed human digitization. In *ICCV*, pages 2304–2314, 2019. 3
- [47] Shunsuke Saito, Tomas Simon, Jason Saragih, and Hanbyul Joo. PIFuHD: Multi-Level Pixel-Aligned Implicit Function for High-Resolution 3D Human Digitization. In *CVPR*, pages 81–90, 2020. 3
- [48] Nikolaos Sarafianos, Tuur Stuyck, Xiaoyu Xiang, Yilei Li, Jo-van Popovic, and Rakesh Ranjan. Garment3dgen: 3d garment stylization and texture generation. In *3DV*, 2025. 2
- [49] Tianchang Shen, Jun Gao, Kangxue Yin, Ming-Yu Liu, and Sanja Fidler. Deep marching tetrahedra: a hybrid representation for high-resolution 3d shape synthesis. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. 3
- [50] Yu Shen, Junbang Liang, and Ming C. Lin. Gan-based garment generation using sewing pattern images. In *ECCV*, 2020. 2
- [51] Ken Shoemake. Animating rotation with quaternion curves. In *Proceedings of the 12th annual conference on Computer graphics and interactive techniques*, pages 245–254, 1985. 4
- [52] Zhaoqi Su, Weilin Wan, Tao Yu, Lingjie Liu, Lu Fang, Wengping Wang, and Yebin Liu. Mulaycap: Multi-layer human performance capture using a monocular video camera. *IEEE Transactions on Visualization and Computer Graphics*, 28(4):1862–1879, 2020. 3
- [53] Chunyi Sun, Junlin Han, Weijian Deng, Xinlong Wang, Zishan Qin, and Stephen Gould. 3d-gpt: Procedural 3d modeling with large language models. *arXiv preprint arXiv:2310.12945*, 2023. 3
- [54] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023. 5, 13
- [55] Tuanfeng Y. Wang, Duygu Ceylan, Jovan Popović, and Niloy J. Mitra. Learning a shared shape space for multi-modal garment design. *ACM Trans. Graph.*, 37(6), 2018. 3

- [56] Wenbo Wang, Hsuan-I Ho, Chen Guo, Boxiang Rong, Artur Grigorev, Jie Song, Juan Jose Zarate, and Otmar Hilliges. 4D-DRESS: A 4D dataset of real-world human clothing with semantic annotations. In *IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2, 6, 15
- [57] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022. 6, 14, 15
- [58] Yuliang Xiu, Jinlong Yang, Dimitrios Tzionas, and Michael J. Black. ICON: Implicit Clothed humans Obtained from Normals. In *CVPR*, 2022. 3
- [59] Yuliang Xiu, Jinlong Yang, Xu Cao, Dimitrios Tzionas, and Michael J. Black. ECON: Explicit Clothed humans Optimized via Normal integration. In *CVPR*, 2023. 3
- [60] Runsen Xu, Xiaolong Wang, Tai Wang, Yilun Chen, Jiangmiao Pang, and Dahua Lin. Pointllm: Empowering large language models to understand point clouds. In *European Conference on Computer Vision*, pages 131–147. Springer, 2025. 3
- [61] Zhengming Yu, Zhiyang Dou, Xiaoxiao Long, Cheng Lin, Zekun Li, Yuan Liu, Norman Müller, Taku Komura, Marc Habermann, Christian Theobalt, et al. Surf-d: Generating high-quality surfaces of arbitrary topologies using diffusion models. In *ECCV*, pages 419–438. Springer, 2025. 3
- [62] Haocheng Yuan, Adrien Bousseau, Hao Pan, Chengquan Zhang, Niloy J Mitra, and Changjian Li. Diffcsg: Differentiable csg via rasterization. *arXiv preprint arXiv:2409.01421*, 2024. 9
- [63] Longwen Zhang, Ziyu Wang, Qixuan Zhang, Qiwei Qiu, Anqi Pang, Haoran Jiang, Wei Yang, Lan Xu, and Jingyi Yu. Clay: A controllable large-scale generative model for creating high-quality 3d assets. *ACM Transactions on Graphics (TOG)*, 43(4):1–20, 2024. 3
- [64] Heming Zhu, Lingteng Qiu, Yuda Qiu, and Xiaoguang Han. Registering explicit to implicit: Towards high-fidelity garment mesh reconstruction from single images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3845–3854, 2022. 2

# ChatGarment: Garment Estimation, Generation and Editing via Large Language Models

## Supplementary Material

In the supplementary material, we include additional details on training and evaluation, as well as ablation studies and qualitative visualizations.

### S1. More Implementation Details

#### S1.1. GarmentCodeRC

**Garment Sewing Pattern.** We use the JSON-format sewing pattern configurations provided by GarmentCode [25, 26]. We optimize this JSON file by adding new features, automatically removing irrelevant settings during garment construction (*e.g.*, omitting skirt-related parameters for upper-body garments) and normalizing floating-point values to [0, 1]. Here is a simplified GarmentCode JSON file for pants:

```
1 {  
2     "meta": {  
3         "upper": "None",  
4         "wb": "None",  
5         "bottom": "Pants"  
6     },  
7     "pants": {  
8         "length": 0.203,  
9         "width": 0.062,  
10        "flare": 0.516,  
11        "rise": 0.816,  
12        "cuff": {  
13            "type": "None"  
14        }  
15    }  
16 }
```

**Outfit Sewing Pattern.** From real images, we see that people often wear multiple garments, like a T-shirt and pants. In these cases, we combine them into a single outfit represented as a new JSON dictionary. If the subject wears one upper and one lower garment, the model will return in this format:

```
1 {  
2     "upperbody_garment": {  
3         (upper garment sewing pattern)  
4     },  
5     "lowerbody_garment": {  
6         (lower garment sewing pattern)  
7     }  
8 }
```

Otherwise, if the subject wears a single whole-body garment, the model will return in the following format:

```
1 {  
2     "wholebody_garment": {  
3         (wholebody garment sewing pattern)  
4     }  
5 }
```

### S1.2. ChatGarment Training Data

To create text descriptions for the garments in our training dataset, we render front and back images of the garments and then query GPT-4o to generate descriptions for the images. We use the prompts in Tab. S6 to generate descriptions for each garment part, and use the prompts in Tab. S7 to generate descriptions for all visible garment parts in the image. Additionally, we provide several examples from our dataset, including low-level and high-level garment descriptions, as well as garment editing descriptions; see in Fig. S1.


As described in Sec. 3, we construct question and answer pairs to finetune a multimodal LLM. Specifically, we build two datasets: an image-reconstruction dataset and a sewing pattern editing dataset. Text-based generation data is derived by removing the images from the image-reconstruction dataset. Detailed question lists of these datasets are illustrated in Tabs. S1 to S4 respectively. Example textual answers are shown in Tab. S5, where [Sewing pattern without floats] refers to a JSON configuration where all float values are replaced with “0”. Since the projection layer is used to calculate numeric values in the sewing pattern, it is unnecessary to output these numeric values directly in the textual answers. Replacing them with “0” simplifies the training process.

- “<image> Can you estimate the outfit sewing pattern code in the image?”
- “<image> Please estimate the outfit sewing pattern code.”
- “<image> Provide the sewing pattern codes for the garments according to the image.”
- “<image> What is the sewing pattern codes for the outfit shown in the image?”
- “<image> Could you tell the outfit sewing pattern codes for the garments?”


Table S1. **Example questions for image reconstruction.** <image> is the placeholder token of the input image.

### S1.3. Training Details


We use LLaVA-1.5V-7B [34] as our base VLM, integrating CLIP for vision encoding and Llama 2 [54], fine-tuned on conversational data, as the LLM backbone. We freeze the vision encoder and projection layers while finetune the LLM using LoRA [18]. The sewing pattern projection layer is a two-layer (5120 x 76) MLP. The model is trained for



(A). Low-level garment labeling



(B). High-level garment labeling



(C). Garment editing

Figure S1. Dataset samples include low-level, high-level, and garment editing descriptions.

- “<image> Can you estimate the outfit sewing pattern code based on the image and the Json-format garment geometry description? [Garment descriptions]”
- “<image> Please estimate the outfit sewing pattern code based on the image and the garment geometry descriptions in Json format. [Garment descriptions]”
- “<image> Provide the sewing pattern codes for the garments according to the image and the Json-format garment geometry description. [Garment descriptions]”
- “<image> What is the sewing pattern codes for the outfit according to the image and the Json-format garment geometry description? [Garment descriptions]”
- “<image> Could you tell the outfit sewing pattern codes for the garments based on the image and the garment geometry descriptions in Json format? [Garment descriptions]”

- “Can you estimate the outfit sewing pattern code based on the Json-format garment geometry description? [Garment descriptions]”
- “Please estimate the outfit sewing pattern code based on the garment geometry descriptions in Json format. [Garment descriptions]”
- “Provide the sewing pattern codes for the garments according to the image and the Json-format garment geometry description. [Garment descriptions]”
- “What is the sewing pattern codes for the outfit according to the Json-format garment geometry description? [Garment descriptions]”
- “Could you tell the outfit sewing pattern codes for the garments based on the garment geometry descriptions in Json format? [Garment descriptions]”

Table S2. Example questions for text-guided image reconstruction. [Garment descriptions] refers to garment descriptions.

40 epochs, 500 steps per epoch, using the AdamW optimizer [22] with a learning rate of 1e-4. Training is done with a batch size of 4 per device on 4 NVIDIA H100 GPUs.

#### S1.4. Inference Details

For image-based reconstruction, we apply the Chain-of-Thoughts (CoT) [57] for ChatGarment. This involves prompting the model to generate a text description of the given garment, which is then combined with the image to

Table S3. Example questions for text-based garment generation. [Garment descriptions] refers to garment descriptions.

produce the garment sewing pattern. Please see GPT-4o CoT prompts in Tab. S8.

#### S1.5. Rule-based Simulation Control

ChatGarment demonstrates garment estimation and editing capabilities. The next step for artists is often simulating realistic garment movement. While existing tools need precise physical parameters to achieve desired deformations, we develop a rule-based method to derive material-specific parameters from text or images. This leverages LLM reasoning

- “Adjust the old sewing pattern according to the text descriptions. The old garment sewing pattern is: [Old sewing pattern]. And the text descriptions are: [Text descriptions].”
- “Adjust the old sewing pattern [Old sewing pattern] according to the text descriptions [Text descriptions] without modifying other parts.”
- “Here is an old garment sewing pattern: [Old sewing pattern]. Modify the pattern to align with the text descriptions: [Text descriptions] without changing other parts.”
- “Update the old sewing pattern following the text descriptions: [Text descriptions]. The old garment sewing pattern is: [Old sewing pattern].”

Table S4. **Instructions for garment editing.** [Old sewing pattern] refers to the initial garment sewing pattern to be edited, and [Text descriptions] refers to the editing instructions.

- “[Sewing pattern without floats].”
- “It is [Sewing pattern without floats].”
- “Sure, it is [Sewing pattern without floats].”
- “The sewing pattern is [Sewing pattern without floats].”
- “The estimated sewing pattern is [Sewing pattern without floats].”

Table S5. **Example textual answers for reconstruction, generation, and editing.** [Sewing pattern without floats] refers to a simplified sewing pattern in which numeric values are replaced with “0”.

I will provide an image of a human model wearing the [garment name]. The top two subfigures show the front and back views of the model (from left to right), while the bottom two subfigures show the zoomed-in view of the front and back views of the [garment name]. Please ONLY focus on the [part name] on the [garment name].

Please describe the geometries and structures of the [part name] on the [garment name] according to the image. Strictly avoid mentioning other garment parts. Strictly avoid mentioning color, texture, seams, and material.

Return a Json LIST of several phrases, each describing a geometric feature of the [part name], in the Json list format: [geometry feature 1, geometry feature 2, geometry feature 3, ...].”

Table S6. **GPT-4o prompts for generating garment part labels in an image.** [garment name] refers to the name of the garment and [part name] refers to the name of the garment part.

to map garment characteristics to simulation inputs.

We use C-IPC [29] as the simulator, requiring parame-

ters like density, stretching stiffness, bending stiffness, and thickness, which are specific to the simulator and not directly derived from real-world measurements. To bridge this gap, we propose a hierarchical mapping approach. This involves initially matching inferred material properties to predefined material classes, followed by parameter refinement within each class. For initialization, we prompt ChatGarment to identify the closest material match from a set of predefined material classes (see Tab. S9). The physics parameters for the target material are initially set based on the matched material, after which we further refine specific parameters that significantly impact the simulation behavior.

Our analysis demonstrates that four primary parameters, *membE* (stretching stiffness), *bendE* (bending stiffness), *density*, and *thickness*, show strong correlations with the high-level descriptors: *rigid/soft*, *heavy/light*, *wrinkle/smooth*, and *perceived thickness*. Moreover, LLM can effectively compare high-level material performance rather than directly estimating precise parameter values. Based on these correlations, each physical parameter is decoupled and individually mapped to its respective descriptor. We then ask GPT-4o to assign scores ranging from 1 to 10 for these high-level descriptors. These scores are used to adjust the corresponding physical parameters based on the score differences between the target material and the initial matched material, as described by the following equations:

$$\log \text{memb} = \alpha_m \Delta_{\text{soft}} \cdot \log \text{memb}_{\text{base}} \quad (2)$$

$$\log \text{bendE} = \alpha_b \Delta_{\text{light}} \cdot \log \text{bendE}_{\text{base}} \quad (3)$$

$$\text{density} = \alpha_d \Delta_{\text{smooth}} \cdot \text{density}_{\text{base}} \quad (4)$$

$$\text{thickness} = \alpha_t \Delta_{\text{thickness}} \cdot \text{thickness}_{\text{base}} \quad (5)$$

where  $\Delta_*$  denotes the score differences derived from the inferred descriptors, allowing for refined adjustments of each parameter based on the closest matched material.

## S2. Ablation Study Details

**Multimodal LLM backbones.** As shown in Tab. S10, the LLaVA-7B and LLaVA-13B models achieve comparable results. For efficiency, we use the LLaVA-7B model for the other experiments in our paper.

**Training Data.** To assess the impact of part-level garment description datasets, we train a model (ChatGarment\*) exclusively on general garment descriptions. For image-based reconstruction, we continue to use the Chain-of-Thoughts [57] approach, prompting the model with a text description of the given garment as the first step. As shown in Tab. S11, the absence of part-level description datasets adversely affects image reconstruction results. In the Dress4D dataset [56], ChatGarment\* exhibits a worse Chamfer distance but a slightly higher F-Score. In the CLoSE dataset [2], ChatGarment\* performs worse on both metrics.

I will provide one image of a human model wearing several garments. Describe the outer layer garments the models are wearing. In each image, the model may wear one upper garment and one lower garment, or the model may wear a single wholebody garment. Avoid describing extra accessories such as the scarves, socks, watch, badges, and etc. We have known that the model wears [garment types].

For each garment, you should generate THREE strings.

In the first string, describe the garment type (If THE SUBJECT HAS NAME, INCLUDE ITS NAME FIRST!);

Example phrases for the first string: "hood", "T-shirt", "jacket", "tuxedo", etc.

In the second string, describe the structures of the garment (DO NOT INCLUDE ANY INFO ABOUT THE HUMAN MODEL AND THE COLOR OF THE GARMENT) in the format of a dict.

Select the keys from the following list: ['width', 'length', 'sleeves', 'pant legs', 'waist', 'skirt hems', 'skirt hems', 'collar', 'hood', 'waist', ... ]

In the value of the dict, please use several different short phrases in a list with the following tips:

Describe the width of the garment: wide, normal, narrow, etc.

Describe the length of the garment: long, normal, short, etc.

Describe the length and width of the sleeves: long, normal, short, tight, loose sleeveless, etc.

Describe the detailed structure of the sleeves. Example: "asymmetrical sleeves", "straight sleeves", "puff sleeves", "three-quarter sleeves", "accordion sleeves", etc.

Describe the length and width of the legs of trousers: long, normal, short, tight, loose legs, etc.

Describe the detailed structure of the pant legs. Example: "asymmetrical legs", "straight legs", "flared legs", "cropped legs", "cuffed legs", etc.

Describe the length and width of the dress: long, normal, short, tight, loose, etc.

Describe the detailed structure of the skirt hems. Example: "straight hem", "A-line hem", "pleated hem", "pencil hem", "slit hem", etc.

Describe the detailed structure of the neck or collar. Example: "crew neck", "V-neck", "turtle neck", "collarless", etc.

Describe the detailed structure of the hood. Example: "normal hood", "cape hood", "cowl hood", etc.

An example of the dict description for a T-shirt is:

'width': ['wide'], 'length': ['normal'], 'sleeves': ['elbow-length sleeves', 'tight sleeves', 'accordion sleeves'], 'collar': ['crew neck'], 'hood': ['no hood']

An example of the dict description for a skirt is:

'width': ['wide'], 'length': ['knee-length'], 'waist': ['high waist'], 'skirt hems': ['pencil hem', 'pleated hem']

In the third string, describe the extra detailed structures of the garment (DO NOT INCLUDE ANY INFO ABOUT THE HUMAN MODEL AND THE COLOR OR PATTERN OF THE GARMENT) that are missing in the second string using several different short phrases split by ','. Example phrases for the third string: "pleated skirt", "high-waist", "zipper closure", "frayed hem", "mid-rise waist", etc.

Please strictly avoid mentioning color, texture, and material.

In the image, if the model is wearing one upper garment and one lower garment, return the results in the following format: "upper garment": [upper garment type, upper garment geometric features, extra features], "lower garment": [lower garment type, lower garment geometric features, extra features]. Otherwise, the model is wearing a single wholebody garment , return the results in the following format: "wholebody garment": [wholebody garment type, wholebody garment geometric features, extra features]. Only return the JSON dictionary in the above format with a length of 1 or 2."

Table S7. **GPT-4o prompts for generating labels for all visible garment parts in an image.** [garment types] refers to the types of the garments the model is wearing.

## S3. More Results

### S3.1. Text-based Generation

We provide qualitative examples of text-based garment reconstruction results in Fig. S2, using the same prompt format as DressCode [16]. Compared to DressCode, our model accurately generates garments with correct lengths, widths, and detailed features. In contrast, DressCode occasionally produces incorrect garment types, inaccurate sizes, and missing details.

### S3.2. Rule-based Simulation Control

We present qualitative examples of rule-based simulation control in Fig. S3. The simulation parameters are aligned with the material characteristics in the input image as described in Sec. S1.5. Leveraging the high-level descriptors in our rule-based approach, we can also modify the simulation behavior to make the garment deform like other materials. For instance, decreasing the stiffness (Stiffness $\downarrow$ ) results in a softer garment with more pronounced wrinkles and larger




Figure S2. **Text-based generation results.** ChatGarment follows the instruction more accurately, generating more precise details (types, sleeves, length, etc.) compared to DressCode [16].




Figure S3. **Rule-based Simulation Control.** We apply our rule-based method to estimate the simulation parameters corresponding to the input images. This approach also allows control over different physical deformation behaviors, such as those of soft materials like silk (Stiffness $\downarrow$ ) and rigid materials like denim (Stiffness $\uparrow$ ).

deformations under the same motion. Conversely, increasing the stiffness (Stiffness $\uparrow$ ) produces a garment with rigid material properties, making it less prone to stretching.

## S4. Failure Cases and Future Work

As shown in Fig. S4, ChatGarment occasionally struggles to edit specific garment parts without affecting other areas. For example, when adjusting the length of a skirt as requested,

- “<image> Can you describe the garment outfit in in image in the Json format?”
- “<image> Can you estimate the outfit sewing pattern code based the image and the Json format garment geometry description? [Garment descriptions]”

Table S8. **GPT-4o CoT prompts for generating sewing patterns from images.** [Garment descriptions] refers to the textual descriptions of garments generated from the first question.

- “<image> Can you infer the garment material from the provided image input ?”
- “<existing material list> Based on your inference, can you identify the material from the provided list that most closely matches the inferred physical properties ?”

Table S9. **GPT-4o prompts for generating materials from images.** <existing material list> refers to the list of predefined materials. These prompts are used to initially infer the garment material from the existing material list and the provided image.

Methods	Dress4D		CLoSE	
	CD (↓)	F-Score (↑)	CD (↓)	F-Score (↑)
LLaVA-13B	3.73	<b>0.78</b>	<b>2.54</b>	0.784
LLaVA-7B	<b>3.06</b>	<b>0.78</b>	2.94	<b>0.790</b>

Table S10. **Ablation study: effect of multimodal LLM backbones.** Models utilizing LLaVA-7B and LLaVA-13B backbones demonstrate comparable performance on the two datasets.

Methods	Dress4D		CLoSE	
	CD (↓)	F-Score (↑)	CD (↓)	F-Score (↑)
ChatGarment *	4.04	<b>0.79</b>	4.06	0.76
ChatGarment	<b>3.06</b>	0.78	<b>2.94</b>	<b>0.79</b>

Table S11. **Ablation analysis of different training datasets.** ChatGarment \* is only trained on high-level garment description datasets and exhibits poorer image reconstruction performance.

slight unintended changes may occur in the upper-body T-shirt. Additionally, in image-based garment reconstruction, it may fail to capture intricate details. While it can accurately identify the garment type as a skirt and estimate its length, it may misinterpret finer details, such as mistaking the bottom style of the skirt for pleats.

Future improvements to our method could involve generating a more diverse training dataset that includes more detailed text labels and a broader range of garment types and styles. Additionally, the development of a more advanced programming parametric model for sewing patterns could enhance the diversity of generated garments and the precision of garment editing. Finally, employing a more stable and accurate garment simulation tool could lead to more




Figure S4. **Failure cases of sewing pattern editing and reconstruction.** ChatGarment might change the irrelevant garment parts (TOP: collars and sleeves). And ChatGarment occasionally misinterprets the garment details (BOTTOM: skirt style).

precise modeling of garment dynamics.