


Database Fundamentals

Lecture 5 (Remaining SQL)

Lecturer : Dr Irene Murtagh

Room :A15


Email: irene.murtagh@tudublin.ie



Learning Outcomes



Databases: Learning Outcomes





Objective for this lecture:

Data Definition:

- ‘Creating tables’, Changing the definition of an existing table, deleting tables

Also cover:

- Insert new data, update existing data, deleting rows.



SQL Section 1

CREATING DATABASE OBJECTS

Naming conventions



- Names must begin with a letter
- Names can be 1 - 30 characters long
- Must contain only A-Z, a-z, 0-9, _, \$ and #
- Every object owned by a user must have a different name
- Cannot use reserved words (as specified by the DBMS implementation)
- Names are **NOT** case sensitive, so **EMP** is the same as **eMP**.

Comments in Code



- There are two ways to specify a comment:

1. `--` (two dashes)

2. Multi-line comments

```
/* This is a comment */
```



CREATING OBJECTS

- There are a number of different database objects you can create, such as
 - tables
 - views
 - index

Table

RSI Num.	Emp Name	Emp Address	Car Reg	Salary	Grade	Job Title
112541	Banks	Dublin 12	98D1245	20000	4	Engineer
16221	Allen	Dublin 15	99D54421	30000	7	Manager
25541	Hope	Dublin 2	97D844	53000	9	Partner

View

Emp Name	Emp Address	Job Title
Banks	Dublin 12	Engineer
Allen	Dublin 15	Manager
Hope	Dublin 2	Partner

Index

Emp Name	Table Row
Allen	2
Banks	1
Hope	3

- Only the table holds data

Views & Indexes - <http://www.tomjewett.com/dbdesign/dbdesign.php?page=views.php>

Database Objects



Table – Basic **unit of storage** in relational databases

- Holds the **actual raw data** stored in a database

View - **portion** or **subset** of a table provided to a user to perform some task. It's a virtual table.

Index - Like an index in a book. You can build an index over any attribute in the table. The index will contain the list of distinct values for that attribute, and the address of rows in the table that contain that value.



Summary of DDL commands

- **CREATE TABLE**
 - basic table definition
 - add constraints
- **ALTER TABLE**
 - add new columns to the table
 - change existing column definitions
 - delete columns from the table
 - change constraints
- **DROP TABLE** – delete a table
- **TRUNCATE TABLE** – remove data from a table

Table Creation



- To create a table, use the **CREATE** command which has the following **syntax**

```
CREATE TABLE table_name  
    (column1 datatype (...),  
    (column2 datatype(..),  
    .....);
```

- ❖ **table** is the name of the table
- ❖ **column** is the name of the attribute
- ❖ **datatype** is the type and length of the attribute

Remember constraints (lect 2)?



1. Domain constraints
2. Entity integrity constraint
3. NULL constraint
4. Referential integrity constraint

These are defined in the **Create** statement

Example of CREATE



```
CREATE TABLE dept  
  (deptno    INT,  
   dname     VARCHAR(14),  
   loc       VARCHAR(13)  
  );
```

Table name

Attribute domain –
data type is character,
length is 14.

Attribute name



Example of CREATE

```
CREATE TABLE emp(  
  empno INT NOT NULL,  
  ename VARCHAR(10),  
  job VARCHAR(9),  
  mgr INT,  
  hiredate DATE,  
  sal DECIMAL(7,2),  
  comm DECIMAL(7,2),  
  deptno INT NOT NULL)
```

Table name

Null constraint



Datatypes

Valid Data types for MySQL include:

- `VARCHAR(length)`
- `BINARY[(length)]`
- `INTEGER[(length)]`
- `REAL[(length,decimals)]`
- `DECIMAL[(length[,decimals])]`
- `NUMERIC[(length[,decimals])]`
- `DATE`
- `TIME`

Full list: <http://dev.mysql.com/doc/refman/5.1/en/create-table.html>



Exercise

- What is the CREATE statement for the following table:
 - Course (courseID character length 5, course name character length 50, start date of type date)

```
Create table Course
(  
  CourseID varchar(5),  
  CourseName char(50),  
  date      Date,  
);
```

Syntax: CONSTRAINT constraint_name PRIMARY KEY
(column_name[,column name, . . .])



Defining the **primary key** (entity constraint)

```
CREATE TABLE DEPT (  
  DEPTNO          INT NOT NULL,  
  DNAME           VARCHAR(14),  
  LOC             VARCHAR(13),  
  CONSTRAINT DEPT_PK PRIMARY KEY  
    (DEPTNO));
```

Primary key column
must be NOT NULL

The attribute to be
used as the primary
key

Each constraint is
given a name

The type of
constraint, i.e.
defining a primary
key.

Defining a **foreign key** (referential integrity constraint)



```
CREATE TABLE EMP (  
  EMPNO          INT NOT NULL,  
  ENAME          VARCHAR(10),  
  JOB            VARCHAR(9),  
  MGR            INT,  
  HIREDATE        DATE,  
  SAL            DECIMAL(7,2),  
  COMM           DECIMAL(7,2),  
  DEPTNO         INT NOT NULL,  
  CONSTRAINT EMP_DEPTNO_FK FOREIGN KEY (DEPTNO) REFERENCES DEPT  
    (DEPTNO),  
  CONSTRAINT EMP_EMPNO_PK PRIMARY KEY (EMPNO));
```

Each constraint is given a name

The type of constraint, i.e. defining a foreign key.

The table and attribute the foreign key references



Syntax – foreign key

- The Syntax for defining a foreign key is:

```
CONSTRAINT constraint_name FOREIGN KEY  
  (column name ) REFERENCES table_name  
  (primarykey)
```

Question Time



Exercise



- Write SQL statements to create the following relations as MySQL tables:
- `course (course_id(PK), course_name)`
- `student(student_ID (PK), student_name, student_address, course_id(FK))`

Defining additional **domain constraints**

- **CHECK** is used to add additional restrictions to an attribute's domain, for example:

```
CREATE TABLE dept (  
    deptno INT CHECK (deptno BETWEEN 10 and 49),  
    dname VARCHAR(14),  
    loc VARCHAR(13) NOT NULL,  
    CONSTRAINT dept_pk PRIMARY KEY (deptno)  
);
```



CHECK constraint



- A check constraint can also be defined at the end of the create statements as follows:

```
CREATE TABLE dept (  
    deptno INT UNIQUE,  
    dname VARCHAR(14),  
    loc VARCHAR(13) NOT NULL,  
    CONSTRAINT dept_pk PRIMARY KEY (deptno),  
    CONSTRAINT check_deptno CHECK (deptno BETWEEN 10 and  
    49));
```

More examples of Constraints



```
CREATE TABLE jobs
```

```
( job_id int AUTO_INCREMENT,
```

```
job_desc varchar(50) NOT NULL DEFAULT 'New Position - title  
not formalized yet',
```

```
min_sal int NOT NULL CHECK (min_sal >= 10000),
```

```
max_sal int NOT NULL CHECK (max_sal <= 25000),
```

```
CONSTRAINT jobs_pk PRIMARY KEY (job_id)
```

```
);
```

AUTO_INCREMENT– a number that increments automatically everytime a row is added to the table. **USE SPARINGLY.**


Adding constraints to table columns



- The following are valid constraints in MySQL
 - **NOT NULL** - attribute must have a value
 - **NULL** - attribute allows NULL values
 - **UNIQUE** - column(s) must have a unique value for each row in the table
 - **PRIMARY KEY** - establishes a primary key (PK)
 - **FOREIGN KEY** - establishes a relationship between this column and a column in the referenced table
 - **CHECK** - specify a condition that must be true
 - **DEFAULT** –provide default values for columns
 - **AUTO_INCREMENT** – automatically increments the attribute value for new table rows.

Full Specification: <http://dev.mysql.com/doc/refman/8.0/en/create-table.html>

Altering the definition of an existing table





Altering the table definition

- Once created, you can add, modify or delete (drop) columns from a table using the ALTER statement

- Statement Syntax

ALTER TABLE table_name

ADD column_name datatype [DEFAULT expr] [,...]);

- Or

ALTER TABLE table_name

MODIFY column_name datatype [DEFAULT expr] [,...]);

- Or

ALTER TABLE table

DROP COLUMN column_name;



Adding a column to a table

- Example:

```
ALTER TABLE dept
```

```
ADD location VARCHAR(20);
```

- Note:

- The new column will become the last column in the table.
- If the table has data in it, the new column will default to NULL unless a default value is specified.



Modifying an existing column

- You can change a columns datatype, size and default value.

ALTER TABLE dept

MODIFY dname VARCHAR(20) NOT NULL;

- Note:
 - A change to the default value only affects new rows to be added
 - Changes the datatype, or reducing the size, should only be done if the column **only contains NULL values**

Dropping a column



- Example

```
ALTER TABLE dept  
DROP COLUMN job;
```

- Note:

- You can only drop one column at a time
- The column may contain data when dropped
- The table must have a least one column left after being altered
- Once a column is dropped, it can not be recovered



Changing constraints

- The ALTER command can also be used to add, modify, disable, enable or drop constraints.
- Examples:

ALTER TABLE dept

ADD CONSTRAINT dept_loc_fk FOREIGN KEY loc
REFERENCES location (loc);

ALTER TABLE emp

DISABLE CONSTRAINT emp_pk CASCADE;



Deleting a table

- The DROP command drops a table as follows:
 - syntax: DROP TABLE table_name
 - Example: DROP TABLE dept;
- Note:
 - This deletes the table and its indexes
 - Views are not dropped, but are now invalid
 - This statement is IRREVERSIBLE



Other commands

- To remove all data from a table:

TRUNCATE TABLE department;

The table still exists but all data has been deleted permanently



Exercises

- **Modify** the department (dept) table to add a check constraint to the **deptno** ensure it is always less than 100.

ALTER TABLE dept

Add CONSTRAINT check_deptno CHECK
(deptno < 100)

Exercises




- **Drop** all rows from the department table, but don't delete the table itself.
- **Delete** the department table.

Adding, updating and deleting data in tables

SQL Section 2

M.Brennan

35





Data Manipulation

- **INSERT** - Add new rows to a table
- **UPDATE** - Modify existing rows in a table
- **DELETE** - Remove existing rows from a table

SQL - Add new rows in a table



- To **add** data to the table, use the **INSERT** command.
- The **syntax** is:

```
INSERT INTO table_name [(column_1 [,column_2,...])]  
VALUES (value_1 [, value_2 . . . ]);
```

- You need a separate insert statement for every row added
- The order of the values inserted must be in the same order of the columns specified in the column list.
- If you want to insert data in all columns of a table, the column list can be omitted – but values must be ordered in the same way as they appear in the table definition.

INSERT EXAMPLE



```
INSERT INTO dept  
VALUES (05, 'development', 'Dublin');
```

Column names not needed,
but values must be in correct
order

```
INSERT INTO dept (deptno, loc)  
VALUES (05, 'Dublin');
```

Column names needed as not all
columns were getting a value. dname
will be set to NULL

```
INSERT INTO dept (deptno, loc, dname)  
VALUES (05, 'Dublin', 'development');
```

Column names needed as
values are not ordered
according to the table
definition.

More on Insert



- **AUTO_INCREMENT** column – when a row is inserted in a table with **AUTO_INCREMENT** column, you don't have to specify the **AUTO_INCREMENT** column in the INSERT statement – the value is automatically incremented.
- When a column is omitted in the column list of INSERT, the column is set to NULL **or** it is set to a default value, if one is defined on the column
- You can use system values such as **SYSDATE()** or **SYSTEM_USER** when inserting data

INSERT INTO order (order_ID, date, salesperson)

VALUES ('O_1001', GETDATE(), SYSTEM_USER);

Insert -dates



- MySQL recognizes date and time data enclosed in single quotation marks (') in the following format:
 - Date: YYYY-MM-DD or YY-MM-DD. Other delimiters are also accepted, e.g. YY/MM/DD
 - DateTime: YYYY-MM-DD HH:MM:SS or YY-MM-DD HH:MM:SS . As with date above, other delimiters are also accepted.

YY- two digit year – 09, 10

YYYY – four digit year – 2009, 2010

MM – numeric month: 01 to 12

DD – numeric day: 01 to 31

HH: hour in 24 hour clock 00 to 23

MM: minutes – 00 to 59

SS: seconds – 00 to 59



INSERT INTO

- You can populate a table by using a subset of another table with the same structure

```
INSERT INTO emp2  
SELECT *  
FROM emp  
WHERE job = 'clerk';
```

Changing data in a table



- The UPDATE command changes the value of an column:
- The syntax is:

```
UPDATE table_name  
SET column_1 = new_value,  
    column_2 = new_value, ....  
[WHERE condition];
```



Examples of UPDATE

UPDATE emp

SET deptno = 07;

- This statement will set the department number of all employees to 07.

before		after	
emp no	deptno	emp no	dept no
07	05	07	07
13	10	13	07
15	05	15	07
18	20	18	07

- To change a specific row, you use the WHERE clause



Examples if UPDATE

UPDATE emp

SET deptno = 20

WHERE empno = 15;

- This statement only changes the deptno for employee 15

before		after	
emp no	deptno	emp no	dept no
07	05	07	05
13	10	13	10
15	05	15	20
18	20	18	20

Deleting rows from a table



- The DELETE statement deletes rows permanently from a table.
- The syntax is

**DELETE [FROM] table_name
[WHERE condition];**

- If you don't use a WHERE clause, all rows will be deleted
- You can not delete a row where the primary key is a foreign key in another table,
- Example: You could not delete department 05 if there are employees in the emp table allocated to department 05 (**referential integrity constraint**).

Referential Integrity



Course

Course_id	Title
A123	Maths
B654	Economics
C299	Computing

Student

S_id	Name	Course_id
99111	Tom	A123
99112	Ken	B633
99113	Ray	C299

**Referential Integrity
Rule broken**

**B633 does not appear in the
Course Tables**



Examples of delete

DELETE department;

- All rows in the department table are deleted

DELETE emp

WHERE deptno = 05;

- Deletes all rows where department number is 05, i.e. all employees working in department 05.

before		after	
emp no	deptno	emp no	dept no
07	05	13	10
13	10	18	20
15	05		
18	20		

M. Brennan



Exercise

- Write SQL statements to do the following
 - **Add a row to the dept table for department 50, sales, based in New York**
 - **Delete the row from the dept table for deptno = 40**
 - **Change department 10 to be based in Washington**



Object Browser

Default: itb

- itb
 - Tables
 - Views
 - Routines
- marie
- test

Scratch x

```
1 • insert into dept values ( '50', 'sales', 'New York');
```

Add a row to the dept
department 50, sales
York

Overview

Output

Snippets



Show output from:

Actions

	Time	Action	Message
1	12:07:00	select * from deptLIMIT 0, 1000	7 row(s) returned
2	12:07:13	update dept set LOC = 'Cork' where deptno = 6	1 row(s) affectedRows matched: 1 C
3	12:07:45	select * from deptLIMIT 0, 1000	7 row(s) returned
4	12:09:28	alter dept set LOC = 'Los Angeles' where deptno = 6	Error Code: 1064You have an error in
5	12:10:08	update dept set LOC = 'Los Angeles' where deptno = 6	1 row(s) affectedRows matched: 1 C
6	12:10:24	select * from deptLIMIT 0, 1000	7 row(s) returned
7	12:13:30	insert into dept values ('50', 'sales', 'New York')	1 row(s) affected

Event 7 of type Info at 12:13:30

Action: insert into dept values ('50', 'sales', 'New York')

Message: 1 row(s) affected

MySQL Workbench

SQL Editor (Local instance M...)

File Edit View Query Database Plugins Scripting Community Help

Object Browser

ACTIONS

- Execute SQL File
- Add Schema
- Add Table
- Add View
- Add Routine

SCHEMAS

- itb
 - Tables
 - dept
 - emp
 - orders
 - product
 - salgrade
 - student
 - supplier
 - Views
 - Routines
- newdb
- test
- testproject

Object Information

Connection Information

Name: Local instance
MySQL
Host: localhost:3306
Server: MySQL

ReviseJoins.sql CreateTables.sql CreateTablesforMySQL.sql Query 3

```
1 • SELECT * FROM dept;  
2  
3 • DELETE FROM dept  
4   where deptno = 40;  
5  
6  
7  
8  
9  
10
```

Delete the row from the dept table for deptno = 40

Overview Output Snippets ReviseJoins.sql Result Query 3 Result

Fetches 3 records. Duration: 0.000 sec, fetched in: 0.000 sec

	DEPTNO	DNAME	LOC
▶	10	ACCOUNTING	NEW YORK
	20	RESEARCH	DALLAS
	30	SALES	CHICAGO



Object Browser

Default: itb

- itb
 - Tables
 - Views
 - Routines
- marie
- test

Scratch x

```
1  
2 • update dept set LOC = 'washington' where deptno = 10;
```

Change dept
to be based
Washington

Overview

Output

Snippets



Show output from:


Actions

	Time	Action	Message
✖	1 12:17:10	select * from deptLIMIT 0, 1000	Error Code: 1046No database selected
!	2 12:17:19	select * from deptLIMIT 0, 1000	7 row(s) returned
✖	3 12:19:20	alter dept set LOC = 'washington' where deptno = 10	Error Code: 1064You have an error in
!	4 12:19:39	update dept set LOC = 'washington' where deptno = 10	1 row(s) affectedRows matched: 1 C

Event 4 of type Info at 12:19:39


Action: update dept set LOC = 'washington' where deptno = 10

Message: 1 row(s) affected





Summary - SQL





Learning Outcomes

Databases: Learning Outcomes

