

CSC 1052 – Algorithms & Data Structures II: Stacks

Professor Henry Carter
Spring 2017

Recap

- Abstraction allows for information to be compartmentalized and simplifies modular use
- Interfaces are the Java construction for formal abstraction
- Generic collections allow for simplified implementation of data structures that may hold a variety of classes
- The stack is a LIFO data structure that allows efficient access to the top element

Stacks

- LIFO structure
- Collection of elements
- Good for:
 - Save state
 - Nested data
 - Backtracking



The Development Process

- The development process
 - Write code (lather)
 - Test code (rinse)
 - Repeat (repeat)




Setup

- Create three files:
 - / application (StackDriver class)
 - / interface (StackInterface interface)
 - / class (ArrayBoundedStack class)
- Does it compile?

Stack Operations

- Push
- Pop
- Top



Implementation

- Skeleton
- Class variables
- Basic functions

Test suite #1

- Declare and instantiate `ArrayBoundedStack<Integer>(3)`
- `Push(1)...Print Top()...Pop()`
- `Print Top()`

Exceptions

- Create StackUnderflowException Class
- New method declarations
 - Base constructors on super()
 - Declare Interface methods will throw exceptions
- New throw calls
 - Can this step be simplified?

New Observer

- Interface method header
- Implementation method body
- Test suite #2:
 - Declare and instantiate `ArrayBoundedStack<Integer>(3)`
 - `Push(1)...` Print `isEmpty()`... Print `Top()`...`Pop()`... Print `isEmpty()`...`Pop()`
- Repeat the addition of `StackUnderflowExceptions` to the `Pop()` method interface and implementation

Exceptions round 2

- Note that too many calls to Push(3) produces an exception
- Create StackOverflowException class
- New method declarations
 - Base constructors on super()
 - Declare Interface methods will throw exceptions
- New throw calls
 - Add isFull() observer

Bells and Whistles

- Second constructor
- Auto-sizing
- Layered abstraction



ArrayList Implementation

- ArrayList is an ADT that re-sizes automatically and is based on arrays
- Example declaration:
- To simplify our stack, we can implement our ADT on another ADT



Code Part I

```
//-----  
// ArrayListStack.java by Dale/Joyce/Weems Chapter 2  
//  
// Implements an unbounded stack using an ArrayList.  
//-----  
package ch02.stacks;  
  
import java.util.*;  
  
public class ArrayListStack<T> implements StackInterface<T>  
{  
    protected ArrayList<T> elements; // ArrayList that holds stack elements  
  
    public ArrayListStack()  
    {  
        elements = new ArrayList<T>();  
    }  
}
```

Code Part II

```
public boolean isEmpty()  
// Returns true if this stack is empty, otherwise returns false.  
{  
    return (elements.size() == 0);  
}  
  
public boolean isFull()  
// Returns false - an ArrayListStack is never full.  
{  
    return false;  
}
```

Code Part III

```
public void push(T element)
{
    elements.add(element);
}

public void pop()
{
    if (isEmpty())
        throw new StackUnderflowException("Pop attempted on empty stack.");
    else
        elements.remove(elements.size() - 1);
}

public T top()
{
    T topOfStack = null;
    if (isEmpty())
        throw new StackUnderflowException("Top attempted on empty stack.");
    else
        topOfStack = elements.get(elements.size() - 1);
    return topOfStack;
}
```


Recap

- Stack implementation using a bounded array
- Three phase development
 - Lather, rinse, repeat
- ADT can be layered to simplify each step
 - ADT inception

Next Time...

- Dale, Joyce, Weems Chapter 2.6, 2.9
 - Remember, you need to read it BEFORE you come to class!
- Check the course webpage for practice problems
- Peer Tutors
 - <http://www.csc.villanova.edu/help/>

