



# Contents

|          |                                                                                |          |
|----------|--------------------------------------------------------------------------------|----------|
| <b>1</b> | <b>Pointer Basics</b>                                                          | <b>3</b> |
| 1.1      | What is a pointer? . . . . .                                                   | 3        |
| 1.2      | Pointer variables . . . . .                                                    | 3        |
| 1.3      | Indirection . . . . .                                                          | 3        |
| 1.4      | What is the relationship between a pointer and an array (or string)? . . . . . | 4        |
| 1.4.1    | C strings . . . . .                                                            | 4        |
| 1.4.2    | Continuation . . . . .                                                         | 4        |
| 1.5      | Arrays, addresses, and pointers . . . . .                                      | 4        |
| 1.6      | Multiple indirection . . . . .                                                 | 6        |
| 1.7      | Multiple indirection with integers . . . . .                                   | 6        |
| 1.8      | Multiple indirection with strings . . . . .                                    | 8        |

# Chapter 1

## Pointer Basics

### 1.1 What is a pointer?

- Some languages don't let you use pointers.
- In C there is no getting away from pointers.
- C is a low level language and this is why it let's you use pointers.
- So what is a pointer? A pointer is a variable that points to an address in memory.
- What is an address? Think of the computer memory as a large series of locations where data is stored, all of these locations are labeled. A pointer is able to reference an address.

### 1.2 Pointer variables

- They are declared using the asterisk between the data type and the variable name.

```
#include <stdio.h>

int main(int argc, char **argv)
{
    int num2;
    int *numPtr;
    int num2;
    num = 100;
    numPtr = &num;
    num2 = *numPtr;
    printf("num=%d, numPtr=%d, address of num=%d, num2=%d\n", num, numPtr, &num, num2);
    return 0;
}
```

Figure 1.1: C program

### 1.3 Indirection

- If you have a pointer variable that hold the address in memory at which some other piece of data is stored, the address by itself is not really useful, but we can get the value in memory which is stored at the pointed location by using indirection or dereferencing.
- Given a pointer variable you can access the data being pointed to by adding an asterisk to the variable.

```
num2 = *numPtr;
```

Figure 1.2: Indirection operation

## Chapter 2

# Addresses and indirection

### 2.1 What is the relationship between a pointer and an array (or string)?

- Arrays in C are sequential data items stored in some direction in memory.
- The address of the array, is the same as the address of the first item in the array.
- The name of the array is also the address of the array.
- Let's see how strings are used in C.

#### 2.1.1 C strings

- In C strings are just arrays of characters.
- C treats the null character `'\0'` as the string's terminator.

```
1 #include <stdio.h>
2 int main() {
3     char str1[] = "Hello world";
4     printf("%s %c %d %d\n", str1, str1[0], &str1, &str1[0], str1);
5     return 0;
6 }
7 /* Output:
8 Hello world H 312473588 312473588
9 */
```

- Note that the string is stored in location 312473588 in RAM. When printing the address of the first element of the array and the address of the array we get exactly the same location.

#### 2.1.2 Continuation

- The address of an array is the same as the address of the first element in the array because it is where the array begins. The name of the array is mapped to the address of the array by the compiler, thus we can say that the name of the array is the location of the array and the location of the array is the location of the first member of the array.
- Array is a location in memory, thus an array is a pointer. However all thought an array is a pointer, it is not handled the same as a pointer in C. A pointer variable needs to be handled differently than an array, although behind the scenes an array is a pointer.

## 2.2 Arrays, addresses, and pointers

- Notice the following code and its output:

```
1 #include <stdio.h>
2 int main() {
3     char str1[] = "Hello"; // Array
4     char *str2 = "Goodbye"; // Pointer
5     printf("%u %u %s\n", &str1, str1, str1);
6     printf("%u %u %s\n", &str2, str2, str2);
7     return 0;
8 }
9 /*
10 Output:
11 3558866218 3558866218 Hello
12 3558866208 686526464 Goodbye
13 */
```

- Notice that when outputting the array str1's address and the array itself we get the same one, this is because the array is the pointer to the string "Hello". Notice that when outputting the array str2's address we get a different address than the str2 variable, that is because when we get the address of a pointer, a pointer has a location in memory, and the value of a pointer references the string, the pointer has a location in memory, different to the array pointer, the pointer is not the array in this case, the pointer is a separate variable that makes reference to the array as its value.
- Thus the second direction is different because we are printing the pointer address and the array address, which is not the same.
- An array variable such as str1 is an address, it is its own address, the array variable is the address of the array.
- But a pointer variable is not an array, it is a variable that stores the address of the array. The pointer variable itself is stored in one address, and the array is stored in another.
- Think of the example we gave earlier, the giant lot of warehouses that are labeled and we need to go to warehouse 13.



- The card is like a pointer variable, it is not the location, it contains the value of the location of the warehouse. The warehouse is like the array, it is not just a reference to the location, it is the location. The pointer is like the card containing the text "warehouse 13" the card is not the location, it contains the location that we need to go to, the card is not the warehouse 13.

|         |         |     |     |     |     |     |     |      |
|---------|---------|-----|-----|-----|-----|-----|-----|------|
| Data    | 'G'     | 'o' | 'o' | 'd' | 'b' | 'y' | 'e' | '\0' |
| Address | 4206628 |     |     |     |     |     |     |      |

  

|         |         |
|---------|---------|
| Name    | str2    |
| Data    | 4206628 |
| Address | 2696740 |

- Let's try out another example:

```

1 #include <stdio.h>
2 int main() {
3     char str1[] = "Hello"; // Array
4     char *str2 = str1; // Pointer
5     printf("%u %u %s\n", &str1, str1, str1);
6     printf("%u %u %s\n", &str2, str2, str2);
7     return 0;
8 }
9 /*
10 Output:
11 3911186266 3911186266 Hello
12 3911186256 3911186266 Hello
13 */

```

- Notice that get the different numbers in the second printing because now the pointer variable is pointing to the array. See how each of them are different? One is the reference to the location of the array and the other is the array.

## 2.3 Multiple indirection

- A pointer can also point to another pointer.
- For example: `int **ppi;`
- When we use a pointer to access data at an address we call it indirection or dereferencing.
- Using a pointer to access data from another pointer is called multiple indirection. Because it requires more than one step.
- Why would we ever need multiple indirection?
  - We might have a list of lists, that are accessed using pointer to pointer.

## 2.4 Multiple indirection with integers

```

1 #include <stdio.h>
2 #define LENGTH 3
3 int data[LENGTH]; // array of integers.
4 int main(int argc, char **argv) {
5     int *pi; // pointer to an int.
6     int **ppi; // pointer to pointer to int.
7     printf("multiple indirection example\n");
8     // initialize our integer array.
9     for (int i = 0; i < LENGTH; i++) {
10         data[i] = i;
11     }

```

```

12     for (int i = 0; i < LENGTH; i++) {
13         printf("%d\n", data[i]);
14     }
15     /*
16     A: simple pointer to a pointer to an integer.
17     */
18     pi = data; // the address of data is assigned to pi.
19     ppi = &pi; // the ppi points to the pointer pi.
20     for (int i = 0; i < LENGTH; i++) {
21         printf("\nLoop[%d] array address is %u\n", i, data);
22         printf("item pointed to by pi is %d\n", *pi);
23         printf("item pointed to by ppi is %u\n", *ppi);
24         printf("item pointed to by double indirection of ppi is %d\n\n", **ppi);
25         printf("The address of pi is %u\n\tand the value of pi (what it points to) is
↪ %u\n\n", &pi, ppi);
26         pi += 1;
27     }
28     return 0;
29 }
30 /*
31 multiple indirection example
32 0
33 1
34 2
35
36 Loop[0] array address is 341364800
37 item pointed to by pi is 0
38 item pointed to by ppi is 341364800
39 item pointed to by double indirection of ppi is 0
40
41 The address of pi is 727710864
42     and the value of pi (what it points to) is 727710864
43
44
45 Loop[1] array address is 341364800
46 item pointed to by pi is 1
47 item pointed to by ppi is 341364804
48 item pointed to by double indirection of ppi is 1
49
50 The address of pi is 727710864
51     and the value of pi (what it points to) is 727710864
52
53
54 Loop[2] array address is 341364800
55 item pointed to by pi is 2
56 item pointed to by ppi is 341364808
57 item pointed to by double indirection of ppi is 2
58
59 The address of pi is 727710864
60     and the value of pi (what it points to) is 727710864
61 */

```

- Notice the above code.

- The area we are really interested in understanding is the for loop with the multiple indirection. Lets have a closer look:

```
1 for (int i = 0; i < LENGTH; i++) {
```

- Iterating from i=0 to the length of the array.

```
1 printf("\nLoop[%d] array address is %u\n", i, data);
```

- This statement will print the index which we are using right now. And the address of the array data.

```
1 printf("item pointed to by pi is %d\n", *pi);
```

- This statement is used to print the value of the pointer pi.

```
1 printf("item pointed to by ppi is %u\n", *ppi);
```

- This statement is used to print the value of ppi, which is another pointer, thus the value being printed is the decimal form location of the other pointer in memory.

```
1 printf("item pointed to by double indirection of ppi is %d\n\n", **ppi);
```

- This statement is using double indirection to access the data pointed to by the double pointer.



- Notice the **\*\*ppi**, the double asterisk is to dereference twice. Get the value of the value of the pointer.

```
1 printf("The address of pi is %u\n\tand the value of pi (what it points to) is  
↪ %u\n\n", &pi, ppi);
```

- This statement is used to print the address of the pointer pi and also to print the pointer ppi, ppi is pointing to the address of pi, thus the address will always be the same in this program.

```
1 pi += 1;  
2 }
```

- pi is a pointer and it will be incremented by 1, since it is an int pointer it will be incremented by the sizeof one int. This is called pointer arithmetic.

## 2.5 Multiple indirection with strings

```
1 #include <stdio.h>  
2 #define LENGTH 3  
3 char *words[LENGTH]; // array of char.  
4 int main(int argc, char **argv) {  
5     char *pc; // pointer to an char.
```



```

6   char **ppc; // pointer to pointer to char.
7   printf("multiple indirection example\n");
8   // initialize our integer array.
9   words[0] = "zero";
10  words[1] = "one";
11  words[2] = "two";
12  for (int i = 0; i < LENGTH; i++) {
13      printf("%s\n", words[i]);
14  }
15  /*
16  B: simple pointer to an array of strings.
17     The same as a pointer to a pointer to a character.
18  */
19  printf("\nNow print the chars of each string...\n");
20  ppc = words; // ppc is pointing to the array location of words.
21  for (int i = 0; i < LENGTH; i++) {
22      ppc = words + i; // initialize the pointer to a pointer to a character
23      pc = *ppc; // loop over each string.
24      while (*pc != 0) {
25          printf("%c ", *pc); // process each character in a string.
26          pc += 1; // print out each character of the string individual.
27      }
28      printf("\n");
29  }
30  return 0;
31 }
32 /* Output:
33 multiple indirection example
34 zero
35 one
36 two
37
38 Now print the chars of each string...
39 z e r o
40 o n e
41 t w o
42 */

```

## 2.6 Indirection and commandline args

- As you know C programs accept command line arguments, we send these to the main function using the arguments argc and argv. The argv is a pointer to a pointer to a char.

```

1  int main(int argc, char **argv) {
2      ...
3  }

```

- The argc is the amount of arguments passed to the program, the argv variable is a pointer to a pointer of chars, which is an array of strings.
- Let's see an example:

```

1  #include <stdio.h>
2  int main(int argc, char **argv) {

```

```

3     for (int i = 0; i < argc; i++) {
4         printf("arg %d is %s\n", i, argv[i]);
5     }
6     printf("\n\n");
7     for (int i = 0; i < argc; i++) {
8         printf("arg %d is %s\n", i, *argv);
9         argv++;
10    }
11    return (0);
12 }
13 /* Output:
14 arg 0 is a
15 arg 1 is hello
16 arg 2 is this
17 arg 3 is an
18 arg 4 is argv
19 arg 5 is argument
20 arg 6 is setence
21
22
23 arg 0 is a
24 arg 1 is hello
25 arg 2 is this
26 arg 3 is an
27 arg 4 is argv
28 arg 5 is argument
29 arg 6 is setence
30 */

```

## 2.7 Generic pointers

- Sometimes we have a function that needs to perform an operation using several inputs. If the inputs are double, float, int or long does not matter, this case you would be inclined to write the same function for all the data types, but you would not be advised to not duplicate code. We can write just one funtion that takes in a generic pointer instead.
- A generic pointer is a pointer to void. To use it you must cast it into a data type.
- This is useful since it gives us more liberty and allows us to not repeat code.

### 2.7.1 Example

```

1 #include <stdio.h>
2
3 #define LENGTH 3
4 int data[LENGTH];
5 char *words[LENGTH];
6
7 int main(int argc, char **argv) {
8     void *gp;
9     printf("generic pointer example\n");
10
11     // initialize out integer array.

```

```

12     for (int i = 0; i < LENGTH; i++) {
13         data[i] = i;
14     }
15     for (int i = 0; i < LENGTH; i++) {
16         printf("%d\n", data[i]);
17     }
18     // initialize our string array.
19     words[0] = "zero";
20     words[1] = "one";
21     words[2] = "two";
22     for (int i = 0; i < LENGTH; i++) {
23         printf("%s\n", words[i]);
24     }
25     // example of a generic pointer.
26     gp = data;
27     printf("\ndata array address is %p\n", gp);
28     // cast to int *. then dereference.
29     printf("item pointed to by gp is %d\n", *(int*)gp);
30     gp = (int*)gp + 1; // casting to a pointer to int. add 1.
31     printf("item pointer to by gp is now %d\n", *(int*)gp);
32     // now using the pointer to point to a string.
33     gp = words;
34     printf("\nwords arra address is %p", gp);
35     // cast to a char ** and then dereference the pointer.
36     printf("item pointed to by gp is %s\n", *(char**)gp);
37     gp = (char**)gp + 1; // dereference and now add one
38     printf("item pointed to by gp is now %s", *(char**)gp);
39     return (0);
40 }
41 /* Output:
42 0
43 1
44 2
45 zero
46 one
47 two
48
49 data array address is 00007ff695f6d040
50 item pointed to by gp is 0
51 item pointer to by gp is now 1
52
53 words arra address is 00007ff695f6d050item pointed to by gp is zero
54 item pointed to by gp is now one
55 */

```

## 2.8 Allocating memory

- When we created arrays in the previous examples they were created we assigned a string. The memory is allocated for these bytes of data. But sometimes we don't know how much memory to allocate at compile time, we need the ability to allocate memory at run time.
- We can handle memory allocation using the malloc function.

- The malloc function returns a pointer to void, it allocates the memory we need at run time, thus we can request and free memory at run time as needed.
- The malloc function allocates memory in an area called the heap, normal arrays are allocated on the stack.

### 2.8.1 Example

```

1 #include <stdio.h>
2 #include <string.h>
3 #include <malloc.h>
4
5 #define MAXSTRLEN 100
6
7 char *string_function(char *astring) {
8     char *s;
9     s = (char*)malloc(MAXSTRLEN);
10    s[0] = 0; // initialize first char to null.
11    strcat(s, "Hello ");
12    strcat(s, astring);
13    strcat(s, "\n");
14    return s;
15 }
16
17 int main(int argc, char **argv){
18     printf(string_function("Fred"));
19     printf(string_function("Gussie Fink-Nottle"));
20     return 0;
21 }
22
23 /* Output:
24 Hello Fred
25 Hello Gussie Fink-Nottle
26 */

```

### 2.8.2 Conclutions

- The implementation above has some problem, namely that there could be a string passed in that is larger than 100 bytes, and therefore we can have a buffer overflow problem. Also all space allocated in the heap needs to be explicitly freed, this is a concept we will cover later.
- Thus the above implementation is flawed.

## 2.9 Malloc and sizeof

- Let's see how we can allocate just the right amount of memory:

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4
5 int main() {
6     char *s;
7     int stringsize;

```

```

8     stringsize = sizeof("hello"); // sizeof operator calculates the size of the
↪    data.
9     printf("size of 'hello' is %d\n", stringsize);
10
11     s = (char*)malloc(stringsize);
12     // if malloc returns null then there was an error and we must terminate the
↪    program.
13     if (s == NULL) {
14         printf("malloc failed.");
15         exit(0);
16     }
17     // now copy the string into the newly allocated string.
18     strncpy(s, "hello", stringsize);
19
20     // and change the first character (just to show we can)
21     printf("s is %s\n", s);
22     s[0] = 'c';
23     printf("s is now %s\n", s);
24     return (0);
25 }
26 /* Output:
27 size of 'hello' is 6
28 s is hello
29 s is now cello
30 */

```

## 2.10 Functions that cause errors or warnings

- Sometimes when using some functions, a warning will appear that will tell you that the function you are using is deprecated. There are sometimes reasons to still use them for example, to make the functions compatible with any C compiler.
- In many cases the best option will be to use the recommended function. Or you could define the constant `_CRT_SECURE_NO_WARNINGS` to turn off the deprecation warnings.
- By placing the constant:

```

1 #define _CRT_SECURE_NO_WARNINGS

```

- The compiler should stop pestering you about the deprecation status of the functions you use.

## 2.11 calloc

- There is a function called `calloc` that is similar to `malloc`. The `calloc` function performs everything the `malloc` function would but it also performs the additional step of clearing the memory with nulls.
- Uninitialized memory contains junk. You could allocate memory and the memory you allocate can contain anything, thus it is prone to errors and bugs.
- If you allocate memory with `calloc` the memory is allocated and cleared out with all 0s.
- If you are careful and always initialize all the memory after using `malloc`, then by all means use `malloc`. Otherwise use `calloc`.

### 2.11.1 Parameter differences between calloc and malloc

- malloc just takes in the amount of memory in bytes to be allocated.

```
1 s = (char*)malloc(6);
```

- calloc takes in two parameters, first the amount of elements to be allocated, then the size of each element.

```
1 s = (char*)calloc(6, sizeof(char)); // total space allocated 6*1.
```

- Basically the calloc function will multiply the amount of elements with the space required by each element.
- Notice the following example, we allocate memory and print the data contained within that space. Look that random numbers are thrown. Then using calloc, it is always 0s.

```
1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4
5 int main() {
6     char *s;
7     int *p;
8     s = (char*)malloc(6);
9     for (int i = 0; i < 6; i++) { printf("s[%d]=%d\n", i, s[i]); }
10    printf("\n");
11
12    s = (char*)calloc(6, sizeof(char));
13    for (int i = 0; i < 6; i++) { printf("s[%d]=%d\n", i, s[i]); }
14    free(s);
15    printf("\n");
16
17    p = (int*)calloc(6, sizeof(int));
18    for (int i = 0; i < 6; i++) { printf("p[%d]=%d\n", i, p[i]); }
19    free(p);
20    return (0);
21 }
22 /* Output:
23 s[0]=16
24 s[1]=104
25 s[2]=119
26 s[3]=12
27 s[4]=-108
28 s[5]=1
29
30 s[0]=0
31 s[1]=0
32 s[2]=0
33 s[3]=0
34 s[4]=0
35 s[5]=0
36
37 p[0]=0
38 p[1]=0
```

```
39 p[2]=0
40 p[3]=0
41 p[4]=0
42 p[5]=0
43 */
```

### 2.11.2 Null pointers

- Both `calloc` and `malloc` will return `NULL` pointer if the allocation fails. A null pointer is a pointer whose value is 0. By convention, a pointer with the value 0 is a pointer that does not contain a valid address.
- We can test for a null pointer by comparing it to the `NULL` constant.

## 2.12 free

- Once memory is allocated it is no longer available to the rest of your program.
- So you can run out of memory if you don't free it.
- This only applies to memory inside the heap, the stack memory is managed by the compiler.
- Keeping memory allocated is waste.
- Memory allocated but not used is called a memory leak. This can be a real problem for devices that don't have much memory, such as embedded devices or even device controllers.
- When the memory is no longer need you must free it.
- To free allocated memory you just need to call `free` with the pointer you used to allocate.
- In the previous example we used `free`:

```
1 free(s); // the only parameter is the pointer to the allocated data.
```

- If you call `free` on a variable that was never allocated or try to use allocated memory after you call `free` then your program can go horribly wrong.