



The email address you signed up with has not been verified. You won't be ranked on the leaderboard until you verify your account.

Re-send the verification email



All Domains > Security > Functions > Security - functions

Security - functions



Authored by [dheeraj](#) on May 03 2015

Problem

Submissions

Leaderboard

Discussions

Problem Statement

Before we jump into the concepts of Security, let us familiarize ourselves with the mathematical background required for it.

A set X is a collection of elements. $X = \{1, 2, 3\}$ is one such example. A collection of integers is also a set.

Given two sets X and Y , we define a function f which maps every element in X to precisely 1 element in Y .

if $X = \{1, 2, 3\}$ and $Y = \{\alpha, \beta, \gamma, \delta\}$ a function f can be

$f(1) = \alpha$, $f(2) = \gamma$ and $f(3) = \delta$.

Let us define a function $f_1(x) = x_r$, such that $x \in X$ and $x_r \in Y$ where x_r is defined as the remainder of x when divided by 11.

Your task is to complete the function which takes the input x and **returns** x_r .

Constraints

$1 \leq x \leq 1000$

Suggest Edits

Copyright © 2015 HackerRank.
All Rights Reserved

[598 hackers](#) have submitted code

Share



Download PDF

Current Buffer (saved locally, editable)

C++



```
1 /*
2  * Complete the function below.
3  */
4 int function(int x) {
```

```
5   return x % 11;  
6 }  
7  
8
```

Line: 1 Col: 1

[Upload Code as File](#)

Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Privacy Policy](#) | [Request a Feature](#)