

Closed-Form Richardson-Number Stability Functions from Monin–Obukhov Similarity Theory: Re-Derivation, Generalization, and Implementation Notes

A Technical Working Reference for Boundary-Layer Modeling

Department of Atmospheric & Earth Science

University of Alabama in Huntsville (UAH)

Building upon England & McNider (1995)

August 12, 2026

Abstract

This document provides a mathematically rigorous, fully self-consistent reference for transforming Monin–Obukhov Similarity Theory (MOST) flux-profile functions $\phi_m(\zeta)$ and $\phi_h(\zeta)$ into explicit, closed-form gradient Richardson number (Ri) stability functions $f_m(Ri)$ and $f_h(Ri)$. We correct historical transcription errors in the $\zeta \leftrightarrow Ri$ mapping relation, generalize the stable boundary layer (SBL) formulation to arbitrary heat profile exponents α_h , detail the unstable branch solutions, derive near-neutral series expansions via series reversion, and outline numerical implementation considerations (including surface roughness z_0 integration). This working reference is designed for boundary-layer researchers and numerical modelers at UAH.

1 Theoretical Foundations & Coupling Identities

In first-order eddy-diffusivity closures (K -theory), turbulent exchange coefficients for momentum (K_m) and heat (K_h) are parameterized using mixing-length theory driven by mean vertical shear $S = |\partial u / \partial z|$:

$$K_m = l_m^2 S f_m(Ri), \quad K_h = l_h^2 S f_h(Ri) \quad (1)$$

where $l_m = l_h = \kappa z$ near the surface. Conversely, Monin–Obukhov Similarity Theory (MOST) defines diffusivities as:

$$K_m = \frac{\kappa z u_*}{\phi_m(\zeta)}, \quad K_h = \frac{\kappa z u_*}{\phi_h(\zeta)} \quad (2)$$

Equating K -theory with MOST using the surface-layer profile relation $S = \frac{u_*}{\kappa z} \phi_m(\zeta)$ yields the fundamental coupling definitions:

$$f_m(Ri) = \frac{1}{\phi_m^2(\zeta)} \quad (1a)$$

$$f_h(Ri) = \frac{1}{\phi_m(\zeta)\phi_h(\zeta)} = \frac{f_m^{1/2}(Ri)}{\phi_h(\zeta)} \quad (1b)$$

1.1 The Corrected $\zeta \leftrightarrow Ri$ Transformation

The gradient Richardson number Ri is defined as:

$$Ri = \frac{g}{\theta_0} \frac{\frac{\partial \theta}{\partial z}}{\left(\frac{\partial u}{\partial z}\right)^2} = \zeta \frac{\phi_h(\zeta)}{\phi_m^2(\zeta)} \quad (3)$$

Substituting (??) and (??) into (??) yields the exact relation connecting Ri and ζ :

$$Ri = \zeta \frac{f_m^{1/2}/f_h}{f_m^{-1}} = \zeta \frac{f_m^{3/2}(Ri)}{f_h(Ri)} \implies \boxed{\zeta = Ri \frac{f_h(Ri)}{f_m^{3/2}(Ri)}} \quad (4)$$

Note on Correction: Equation (??) corrects the power on f_m from 1 to 3/2. This adjustment ensures internal self-consistency across all $Pr \neq 1$ formulations.

—

2 Stable Boundary Layer Formulation ($\zeta \geq 0$)

We generalize the stable non-dimensional profiles by retaining a linear momentum function ($\alpha_m = 1$) while allowing a general exponent α_h for heat:

$$\phi_m(\zeta) = 1 + \beta_m \zeta, \quad \phi_h(\zeta) = (1 + \beta_h \zeta)^{\alpha_h} \quad (\zeta \geq 0) \quad (5)$$

Defining $x \equiv f_m^{1/2}(Ri) = \phi_m^{-1}(\zeta)$, we invert $\phi_m(\zeta)$ to obtain:

$$\zeta = \frac{1-x}{\beta_m x} \quad (6)$$

2.1 Master Implicit Equation for $x \equiv f_m^{1/2}$

Substituting (??) into (??) gives the explicit expression for $f_h(Ri)$:

$$f_h(Ri) = \frac{x^2(1-x)}{\beta_m Ri} \quad (7)$$

Equating $\phi_h = x/f_h = \frac{\beta_m Ri}{x(1-x)}$ with $\phi_h(\zeta) = \left(1 + \beta_h \frac{1-x}{\beta_m x}\right)^{\alpha_h}$ produces the master implicit equation for arbitrary α_h :

$$\left[\frac{Ri \beta_m}{x(1-x)} \right]^{1/\alpha_h} = \frac{\beta_m x + \beta_h(1-x)}{\beta_m x} \quad (8)$$

2.2 Case 1: Standard Linear Heat Profile ($\alpha_h = 1$)

Setting $\alpha_h = 1$ reduces (??) directly to a quadratic polynomial in x :

$$Ri(\beta_h - \beta_m)x^2 - (1 + Ri\beta_h)x + 1 = 0 \quad (9)$$

Taking the physically meaningful root ($x \rightarrow 1$ as $Ri \rightarrow 0$) yields the exact closed-form momentum stability function:

$$f_m(Ri) = x^2 = \left[\frac{(1 + Ri\beta_h) - \sqrt{(1 + Ri\beta_h)^2 - 4Ri(\beta_h - \beta_m)}}{2Ri(\beta_h - \beta_m)} \right]^2 \quad (10)$$

The corresponding heat function $f_h(Ri)$ is evaluated directly via (??).

2.3 Case 2: Businger–Dyer Quadratic Heat Profile ($\alpha_h = 2$)

Setting $\alpha_h = 2$ and squaring both sides of (??) clears fractional exponents, yielding a cubic polynomial $a_3x^3 + a_2x^2 + a_1x + a_0 = 0$:

$$\begin{aligned} a_3 &= -(\beta_m - \beta_h)^2 \\ a_2 &= (\beta_m - \beta_h)^2 - 2\beta_h(\beta_m - \beta_h) \\ a_1 &= 2\beta_h(\beta_m - \beta_h) - \beta_h^2 - Ri\beta_m^3 \\ a_0 &= \beta_h^2 \end{aligned} \quad (11)$$

Special Equal-Parameter Limit ($\beta_m = \beta_h = \beta$):

When $\beta_m = \beta_h = \beta$, $a_3 = 0$ and $a_2 = 0$. The cubic collapses to $a_1x + a_0 = 0$:

$$x = \frac{1}{1 + \beta Ri} \implies \boxed{f_m(Ri) = (1 + \beta Ri)^{-2}, \quad f_h(Ri) = (1 + \beta Ri)^{-3}} \quad (12)$$

—

3 Unstable Boundary Layer Formulation ($\zeta < 0$)

For unstable stratification ($\zeta < 0$), standard Businger–Dyer profile functions take the generalized exponential form:

$$\phi_m(\zeta) = (1 - \beta_m \zeta)^{-\alpha_m}, \quad \phi_h(\zeta) = (1 - \beta_h \zeta)^{-\alpha_h} \quad (13)$$

For classical coefficients ($\alpha_m = 1/4$, $\alpha_h = 1/2$), the stability functions map in terms of ζ as:

$$f_m(\zeta) = (1 - \beta_m \zeta)^{1/2} \quad (14)$$

$$f_h(\zeta) = (1 - \beta_h \zeta)^{1/2} (1 - \beta_m \zeta)^{1/4} \quad (15)$$

3.1 Direct Coupling & Master Cubic in $x \equiv f_m^2$

Inverting (??) gives $1 - \beta_m \zeta = f_m^2$, allowing f_h to be expressed directly in terms of f_m :

$$f_h(f_m) = f_m^{1/2} \left[1 - \frac{\beta_h}{\beta_m} (1 - f_m^2) \right]^{1/2} \quad (16)$$

Substituting (??) into the corrected transformation $\zeta^2 = Ri^2 \frac{f_h^2}{f_m^3}$ and defining $x \equiv f_m^2(Ri)$ yields the exact master cubic equation for unstable stratification:

$$\boxed{x^3 - 2x^2 + \left(1 - Ri^2 \beta_m \beta_h\right)x - Ri^2 \beta_m (\beta_m - \beta_h) = 0} \quad (17)$$

3.2 Analytical Solution for Equal Coefficients ($\beta_m = \beta_h = 16$)

When $\beta_m = \beta_h = 16$, the constant term in (??) vanishes. Factoring out $x \neq 0$:

$$x^2 - 2x + (1 - 256Ri^2) = 0 \implies (1 - x)^2 = 256Ri^2 \implies x = 1 - 16Ri \quad (18)$$

Recalling $x \equiv f_m^2$, we recover the analytical expression:

$$\boxed{f_m(Ri) = (1 - 16Ri)^{1/2}} \quad (19)$$

—

4 Series Reversions & Pedagogical Models

4.1 Near-Neutral Series Expansions via Series Reversion

When exact inversion is mathematically intractable, Taylor expanding $\phi_m(\zeta) = 1 + \beta_m \zeta + \gamma_m \zeta^2$ and $\phi_h(\zeta) = 1 + \beta_h \zeta + \gamma_h \zeta^2$ around $\zeta = 0$ provides a forward series for $Ri(\zeta)$:

$$Ri_g(\zeta) = \zeta + (\beta_h - 2\beta_m)\zeta^2 + (3\beta_m^2 - 2\beta_m\beta_h - 2\gamma_m + \gamma_h)\zeta^3 + O(\zeta^4) \quad (20)$$

Reverting this series yields the inverted expression for $\zeta(Ri_g)$:

$$\boxed{\zeta(Ri_g) = Ri_g + (2\beta_m - \beta_h)Ri_g^2 + (5\beta_m^2 - 6\beta_m\beta_h + 2\beta_h^2)Ri_g^3 + O(Ri_g^4)} \quad (21)$$

Substituting $\zeta(Ri_g)$ into $f_m = \phi_m^{-2}$ and $f_h = (\phi_m \phi_h)^{-1}$ yields the low-order Ri -series forms:

$$f_m(Ri_g) = 1 - 2\beta_m Ri_g - \beta_m(\beta_m - 2\beta_h) Ri_g^2 + O(Ri_g^3) \quad (22)$$

$$f_h(Ri_g) = 1 - (\beta_m + \beta_h) Ri_g - (\beta_m^2 - 2\beta_h^2 + \gamma_m + \gamma_h) Ri_g^2 + O(Ri_g^3) \quad (23)$$

4.2 One-Parameter Toy Model with Finite Ri_c

Under the explicit assumption of equal profile parameters ($\beta_m = \beta_h = \beta \implies Pr_t = 1$), the transformation reduces to $Ri_g = \frac{\zeta}{1+\beta\zeta}$. Inverting directly gives:

$$\zeta(Ri_g) = \frac{Ri_g}{1 - \beta Ri_g} \implies \phi_m(Ri_g) = \frac{1}{1 - \beta Ri_g} \quad (24)$$

Defining the critical Richardson number $Ri_c \equiv 1/\beta$, the closure functions reduce to:

$$f_m(Ri_g) = f_h(Ri_g) = \left(1 - \frac{Ri_g}{Ri_c}\right)^2 = \left(\frac{Ri_c - Ri_g}{Ri_c}\right)^2 \quad (25)$$

—

5 Surface Layer Roughness (z_0) Integration

In numerical boundary layer models with finite vertical grid resolution, evaluating Ri across the lowest model layer (z_1) requires explicit integration of surface roughness z_0 . The bulk layer Richardson number is defined using effective integrated depth z_{eff} :

$$Ri_b = \frac{g}{\theta_0} \frac{\Delta\theta \Delta z}{(\Delta u)^2} \quad (26)$$

To ensure equivalence between discrete Ri_b closures and continuous MOST profiles, the effective height ratio ζ_{eff} is evaluated using logarithmic profile transformations:

$$z_{\text{eff}} = z_1 \left[\frac{\ln(z_1/z_0) - \Psi_m(z_1/L)}{\ln(z_1/z_0) - \Psi_h(z_1/L)} \right] \quad (27)$$

This formulation preserves consistency between boundary-layer stability functions and surface flux routines.

—

6 Summary Reference of Core Equations

Table 1: Key Mathematical Equations for MOST $\leftrightarrow$ Ri Conversions

Regime / Application	Equation	Mathematical Form
General Linkage	Corrected $\zeta(Ri)$	$\zeta = Ri \frac{f_h(Ri)}{f_m^{3/2}(Ri)}$
Stable Master (α_h general)	Implicit $x = f_m^{1/2}$	$\left[\frac{Ri \beta_m}{x(1-x)} \right]^{1/\alpha_h} = \frac{\beta_m x + \beta_h(1-x)}{\beta_m x}$
Stable Linear ($\alpha_h = 1$)	Closed $f_m(Ri)$	$f_m(Ri) = \left[\frac{(1 + Ri\beta_h) - \sqrt{(1 + Ri\beta_h)^2 - 4Ri(\beta_h - \beta_m)}}{2Ri(\beta_h - \beta_m)} \right]^2$
Unstable Master ($\alpha_m = \frac{1}{4}, \alpha_h = \frac{1}{2}$)	Master Cubic ($x \equiv f_m^2$)	$x^3 - 2x^2 + (1 - Ri^2\beta_m\beta_h)x - Ri^2\beta_m(\beta_m - \beta_h) = 0$
Unstable Equal ($\beta_m = \beta_h = 16$)	Closed $f_m(Ri)$	$f_m(Ri) = (1 - 16Ri)^{1/2}$
Equal-Profile Toy Model	$Pr_t = 1, Ri_c = 1/\beta$	$f_m(Ri_g) = f_h(Ri_g) = \left(1 - \frac{Ri_g}{Ri_c} \right)^2$