

AI WEB AUDITOR LAB REPORT

- Generated: 2026-08-30T18:22:52Z
- Report generator: ai-web-auditor 0.21.0
- Scan version: 0.21.0
- Scan status: completed

TARGET

Field Value

Original URL <http://127.0.0.1:56158/members/>

Normalized URL <http://127.0.0.1:56158/members/>

Host 127.0.0.1

Scheme http

Port 56158

ENGAGEMENT

Field Value

Client Practica Evolve

Auditor David

Engagement Demo v0.21.0

Scope summary <http://127.0.0.1:56158/members/>

Notes Laboratorio local controlado en localhost.

EXECUTIVE SUMMARY

The scan generated 22 finding(s): 0 critical, 3 high, 4 medium, 6 low and 9 informational.

SEVERITY SUMMARY

Severity Count

CRITICAL 0

HIGH 3

MEDIUM 4

LOW 6

INFO 9

RISK ASSESSMENT

- Risk level: HIGH
- Risk score: 89/100
- Priorities: 10
- Quick wins: 8

COVERAGE

Metric Value

Modules run 10

Module warnings 8

Module errors 0

URLs 35

Forms 2
Entry points 35
Entry point parameters 8
State-changing entry points 6
JavaScript endpoints 9
JavaScript scripts 3
Resolved subdomains 0
Open TCP ports 1
Passive rules matched 13
OWASP controls matched 34
Unmapped findings 0

PRIORITIES

Rank	Severity	Finding	Reason	Recommended action
------	----------	---------	--------	--------------------

- | | | | | |
|----|--------|--|--|---|
| 1 | HIGH | AUTH-BASIC-OVER-HTTP | HTTP Basic Authentication over HTTP credentials may be exposed before transport security is enforced | Force HTTPS before authentication and enable HSTS after validation. |
| 2 | HIGH | HTTP-NO-HTTPS-REDIRECT | HTTP is not redirected to HTTPS unencrypted HTTP remains reachable for the same service | Redirect all HTTP traffic to HTTPS and consider enabling HSTS after verification. |
| 3 | HIGH | METHOD-TRACE-ADVERTISED | HTTP method TRACE is advertised an unnecessary HTTP method is advertised by the server | Disable unnecessary HTTP methods or enforce strict authorization before use. |
| 4 | MEDIUM | METHOD-DELETE-ADVERTISED | HTTP method DELETE is advertised medium finding reported by the http_methods module | Disable unnecessary HTTP methods or enforce strict authorization before use. |
| 5 | MEDIUM | METHOD-PUT-ADVERTISED | HTTP method PUT is advertised medium finding reported by the http_methods module | Disable unnecessary HTTP methods or enforce strict authorization before use. |
| 6 | MEDIUM | COOKIE-SAMESITE-NONE-WITHOUT-SECURE | Cookie uses SameSite=None without Secure medium finding reported by the cookies module | Set Secure or avoid SameSite=None if cross-site usage is not required. |
| 7 | MEDIUM | HEADER-CONTENT_SECURITY_POLICY-MISSING | Content-Security-Policy header is missing medium finding reported by the security_headers module | Define an appropriate Content-Security-Policy header for this application. |
| 8 | LOW | COOKIE-HTTPONLY-MISSING | Cookie missing HttpOnly flag client-side scripts may access cookies without HttpOnly | Set HttpOnly for session or sensitive cookies. |
| 9 | LOW | COOKIE-HTTPONLY-MISSING | Cookie missing HttpOnly flag client-side scripts may access cookies without HttpOnly | Set HttpOnly for session or sensitive cookies. |
| 10 | LOW | COOKIE-SAMESITE-MISSING | Cookie missing SameSite attribute low finding reported by the cookies module | Set SameSite=Lax or SameSite=Strict unless cross-site usage is required. |

QUICK WINS

- HTTP is not redirected to HTTPS: Redirect all HTTP traffic to HTTPS and consider enabling HSTS after verification.
- Content-Security-Policy header is missing: Define an appropriate Content-Security-Policy header for this application.
- Clickjacking protection header is missing: Set frame-ancestors in Content-Security-Policy or use X-Frame-Options where appropriate.
- X-Content-Type-Options nosniff is missing: Set X-Content-Type-Options: nosniff.

- Referrer-Policy header is missing: Define an appropriate Referrer-Policy header for this application.
- Cookie missing HttpOnly flag: Set HttpOnly for session or sensitive cookies.
- Cookie missing SameSite attribute: Set SameSite=Lax or SameSite=Strict unless cross-site usage is required.
- Cookie missing HttpOnly flag: Set HttpOnly for session or sensitive cookies.

REMEDIATION PLAN

IMMEDIATE

Reduce the highest observable risk first.

- HTTP Basic Authentication over HTTP: Force HTTPS before authentication and enable HSTS after validation.
- HTTP is not redirected to HTTPS: Redirect all HTTP traffic to HTTPS and consider enabling HSTS after verification.
- HTTP method TRACE is advertised: Disable unnecessary HTTP methods or enforce strict authorization before use.
- Cookie missing HttpOnly flag: Set HttpOnly for session or sensitive cookies.
- Review every open TCP port and confirm it is required for the approved scope.

SHORT TERM

Apply low-effort hardening and validation.

- HTTP method DELETE is advertised: Disable unnecessary HTTP methods or enforce strict authorization before use.
- HTTP method PUT is advertised: Disable unnecessary HTTP methods or enforce strict authorization before use.
- Cookie uses SameSite=None without Secure: Set Secure or avoid SameSite=None if cross-site usage is not required.
- Content-Security-Policy header is missing: Define an appropriate Content-Security-Policy header for this application.
- HTTP is not redirected to HTTPS: Redirect all HTTP traffic to HTTPS and consider enabling HSTS after verification.
- Clickjacking protection header is missing: Set frame-ancestors in Content-Security-Policy or use X-Frame-Options where appropriate.
- X-Content-Type-Options nosniff is missing: Set X-Content-Type-Options: nosniff.
- Referrer-Policy header is missing: Define an appropriate Referrer-Policy header for this application.

PLANNED

Improve evidence quality and follow-up coverage.

- Cookie missing SameSite attribute: Set SameSite=Lax or SameSite=Strict unless cross-site usage is required.
- Review JavaScript-discovered endpoints before selecting later validation tests.
- Review OWASP WSTG/ASVS rule mappings before finalizing audit scope and report traceability.

COVERAGE NOTES

- http: warning - HTTP/HTTPS reachability and redirects checked.
- security_headers: warning - Security headers checked.
- cookies: warning - Checked 2 cookie(s).
- basic_auth: warning - HTTP authentication challenge checked.
- http_methods: warning - HTTP methods advertised by OPTIONS checked.
- ports: warning - Checked 3 TCP port(s), found 1 open port(s).
- fingerprinting: warning - Identified 4 technology signal(s) and checked 4 public metadata path(s).
- crawler: warning - Crawled 5 page(s), discovered 9 in-scope URL(s), 9 from metadata.
- HTML forms were identified passively; no form submission was performed.
- Entry points were derived from passive evidence: URLs, query strings, forms and advertised HTTP methods.
- State-changing entry points were inferred from methods or form actions; no request bodies were sent.
- Some entry point parameters have sensitive-looking names and should be reviewed without exposing their values.
- JavaScript endpoint references were extracted passively; discovered endpoints were not requested by this module.
- Passive rules mapped scan evidence to OWASP WSTG/ASVS references for audit traceability.
- Open TCP ports were detected using TCP connect checks only; no payloads or banners were requested.

SAFETY NOTES

- This assessment is generated from existing non-intrusive scan evidence only.
- No exploitation, brute force, fuzzing or destructive validation was performed.
- Risk should be reviewed against the authorized scope and business context.

PASSIVE RULE MAPPING

Metric Value

Rules matched 13

Rules total 15

Findings mapped 21

Findings unmapped 0

OWASP controls matched 34

MATCHED RULES

Severity Rule Evidence Frameworks Next review

HIGH RULE-TRANSPORT-ENFORCE-TLS: Transport encryption and HTTPS enforcement findings: AUTH-BASIC-OVER-HTTP, HTTP-NO-HTTPS-REDIRECT OWASP WSTG WSTG-CRYP-03, OWASP WSTG WSTG-ATHN-01, OWASP ASVS 5.0 V12.2.1, OWASP ASVS 5.0 V14.2.1 Confirm HTTPS is enforced for every entry point and that HTTP redirects safely before authentication or session exchange.

MEDIUM RULE-SESSION-COOKIE-ATTRIBUTES: Cookie security attributes findings: COOKIE-HTTPONLY-MISSING, COOKIE-SAMESITE-MISSING, COOKIE-SAMESITE-NONE-WITHOUT-SECURE OWASP WSTG WSTG-SESS-02, OWASP ASVS 5.0 V3.3.1, OWASP ASVS 5.0 V3.3.2, OWASP ASVS 5.0 V3.3.4 Confirm session cookies use Secure, HttpOnly and a deliberate SameSite value based on the application flow.

MEDIUM RULE-FRONTEND-BROWSER-SECURITY-HEADERS: Browser security mechanism headers

findings: HEADER-CLICKJACKING-MISSING, HEADER-CONTENT_SECURITY_POLICY-MISSING, HEADER-NOSNIFF-MISSING, HEADER-PERMISSIONS_POLICY-MISSING, HEADER-REFERRER_POLICY-MISSING OWASP WSTG WSTG-CONF-12, OWASP WSTG WSTG-CLNT-09, OWASP WSTG WSTG-CONF-14, OWASP ASVS 5.0 V3.4 Review CSP, frame-ancestors/X-Frame-Options, X-Content-Type-Options, Referrer-Policy and Permissions-Policy per route.

HIGH RULE-CONFIG-HTTP-METHODS: Advertised HTTP methods findings: METHOD-DELETE-ADVERTISED, METHOD-PUT-ADVERTISED, METHOD-TRACE-ADVERTISED OWASP WSTG WSTG-CONF-06, OWASP ASVS 5.0 V4.1.4, OWASP ASVS 5.0 V13.4.4 Verify that each advertised method is intentionally supported and protected by route-level authorization.

INFO RULE-INFO-TECH-FINGERPRINTING: Technology and version disclosure findings: FINGERPRINT-GENERATOR-DISCLOSED, FINGERPRINT-POWERED-BY-DISCLOSED, FINGERPRINT-SERVER-VERSION-DISCLOSED; signals: technologies_identified OWASP WSTG WSTG-INFO-02, OWASP WSTG WSTG-INFO-08, OWASP WSTG WSTG-INFO-10, OWASP ASVS 5.0 V13.4 Keep useful technology evidence, then remove precise version disclosure where it is not operationally required.

INFO RULE-INFO-WEBSERVER-METAFILES: Public metadata files and declared paths signals: public_metadata OWASP WSTG WSTG-INFO-03, OWASP WSTG WSTG-INFO-07, OWASP ASVS 5.0 V13.4 Review discovered metadata paths manually and decide what belongs in scope before following sensitive paths.

INFO RULE-INFO-ENTRY-POINTS: Application entry point inventory signals: entry_points_present, sensitive_parameters, state_changing_entry_points OWASP WSTG WSTG-INFO-06, OWASP WSTG WSTG-INFO-07, OWASP ASVS 5.0 V4.1.2 Prioritize state-changing endpoints, sensitive parameters and authenticated flows for later authorized testing.

INFO RULE-INFO-JAVASCRIPT-SURFACE: Client-side JavaScript exposed routes findings: JS-ENDPOINTS-DISCOVERED, JS-OUT-OF-SCOPE-ENDPOINTS, JS-SENSITIVE-PARAMETER-NAMES; signals: javascript_endpoints OWASP WSTG WSTG-INFO-05, OWASP WSTG WSTG-INFO-06, OWASP ASVS 5.0 V13.4 Review JavaScript-discovered endpoints before selecting any later validation or attack simulation.

INFO RULE-AUTH-AUTHENTICATION-SURFACE: Authentication and account-management surface signals: auth_routes OWASP WSTG WSTG-ATHN-01, OWASP WSTG WSTG-ATHN-09, OWASP ASVS 5.0 V6.1.3, OWASP ASVS 5.0 V6.4.3 Document every authentication path, recovery path and callback before testing controls in a later authorized phase.

INFO RULE-AUTHZ-ADMIN-SURFACE: Administrative and privileged route inventory signals: admin_routes OWASP WSTG WSTG-CONF-05, OWASP ASVS 5.0 V8.4.2 Confirm ownership, required roles and whether the route should remain in scope before any access-control testing.

INFO RULE-FILE-UPLOAD-SURFACE: File upload route inventory signals: upload_routes OWASP ASVS 5.0 V5.2.1, OWASP ASVS 5.0 V5.2.2 Confirm accepted file types, size limits, storage location and authorization before any upload testing.

INFO RULE-INFRA-DISCOVERY-SURFACE: Infrastructure surface from DNS and TCP checks findings: PORTS-OPEN-TCP-PORTS; signals: ports_open OWASP WSTG WSTG-INFO-04, OWASP WSTG WSTG-INFO-10, OWASP ASVS 5.0 V13.1.1 Confirm every resolved host and open port with the application owner before expanding testing beyond the main URL.

INFO RULE-SCOPE-EXTERNAL-REFERENCES: External and out-of-scope references findings: CRAWLER-OUT-OF-SCOPE-LINKS, JS-OUT-OF-SCOPE-ENDPOINTS; signals: external_references OWASP WSTG WSTG-INFO-10, OWASP ASVS 5.0 V13.2.4 Classify each external host as third-party, dependency, redirect target or candidate scope extension.

OWASP TRACEABILITY

Framework Control Severity Rules Evidence

OWASP ASVS 5.0 V12.2.1: TLS is used for client connectivity HIGH RULE-TRANSPORT-ENFORCE-TLS AUTH-BASIC-OVER-HTTP, HTTP-NO-HTTPS-REDIRECT

OWASP ASVS 5.0 V13.1.1: Application communication needs are documented INFO RULE-INFRA-

DISCOVERY-SURFACE PORTS-OPEN-TCP-PORTS

OWASP ASVS 5.0 V13.2.4: External resource allowlists are defined INFO RULE-SCOPE-

EXTERNAL-REFERENCES CRAWLER-OUT-OF-SCOPE-LINKS, JS-OUT-OF-SCOPE-ENDPOINTS

OWASP ASVS 5.0 V13.4: Unintended information leakage INFO RULE-INFO-JAVASCRIPT-SURFACE, RULE-INFO-TECH-FINGERPRINTING, RULE-INFO-WEBSERVER-METAFILES FINGERPRINT-GENERATOR-DISCLOSED, FINGERPRINT-POWERED-BY-DISCLOSED, FINGERPRINT-SERVER-VERSION-DISCLOSED, JS-ENDPOINTS-DISCOVERED, JS-OUT-OF-SCOPE-ENDPOINTS, JS-SENSITIVE-PARAMETER-NAMES

OWASP ASVS 5.0 V13.4.4: HTTP TRACE method is not supported in production HIGH RULE-CONFIG-HTTP-METHODS METHOD-DELETE-ADVERTISED, METHOD-PUT-ADVERTISED, METHOD-TRACE-ADVERTISED

OWASP ASVS 5.0 V14.2.1: Sensitive data is sent through protected channels HIGH RULE-TRANSPORT-ENFORCE-TLS AUTH-BASIC-OVER-HTTP, HTTP-NO-HTTPS-REDIRECT

OWASP ASVS 5.0 V3.3.1: Cookies have Secure attributes MEDIUM RULE-SESSION-COOKIE-ATTRIBUTES COOKIE-HTTPONLY-MISSING, COOKIE-SAMESITE-MISSING, COOKIE-SAMESITE-NONE-WITHOUT-SECURE

OWASP ASVS 5.0 V3.3.2: Cookies define a SameSite policy MEDIUM RULE-SESSION-COOKIE-ATTRIBUTES COOKIE-HTTPONLY-MISSING, COOKIE-SAMESITE-MISSING, COOKIE-SAMESITE-NONE-WITHOUT-SECURE

OWASP ASVS 5.0 V3.3.4: Sensitive cookies use HttpOnly MEDIUM RULE-SESSION-COOKIE-ATTRIBUTES COOKIE-HTTPONLY-MISSING, COOKIE-SAMESITE-MISSING, COOKIE-SAMESITE-NONE-WITHOUT-SECURE

OWASP ASVS 5.0 V3.4: Browser security mechanism headers MEDIUM RULE-FRONTEND-BROWSER-SECURITY-HEADERS HEADER-CLICKJACKING-MISSING, HEADER-CONTENT_SECURITY_POLICY-MISSING, HEADER-NOSNIFF-MISSING, HEADER-PERMISSIONS_POLICY-MISSING, HEADER-REFERRER_POLICY-MISSING

OWASP ASVS 5.0 V4.1.2: Only intended user-facing endpoints are exposed INFO RULE-INFO-ENTRY-POINTS signals: entry_points_present, sensitive_parameters, state_changing_entry_points

OWASP ASVS 5.0 V4.1.4: Only explicitly supported HTTP methods are accepted HIGH RULE-CONFIG-HTTP-METHODS METHOD-DELETE-ADVERTISED, METHOD-PUT-ADVERTISED, METHOD-TRACE-ADVERTISED

OWASP ASVS 5.0 V5.2.1: Accepted files have safe size limits INFO RULE-FILE-UPLOAD-SURFACE signals: upload_routes

OWASP ASVS 5.0 V5.2.2: Uploaded file extension and content are validated INFO RULE-FILE-UPLOAD-SURFACE signals: upload_routes

OWASP ASVS 5.0 V6.1.3: Multiple authentication pathways are documented INFO RULE-AUTH-AUTHENTICATION-SURFACE signals: auth_routes

OWASP ASVS 5.0 V6.4.3: Secure forgotten password reset process INFO RULE-AUTH-AUTHENTICATION-SURFACE signals: auth_routes

OWASP ASVS 5.0 V8.4.2: Administrative interfaces include stronger access controls INFO RULE-AUTHZ-ADMIN-SURFACE signals: admin_routes

OWASP WSTG WSTG-ATHN-01: Credentials transported over an encrypted channel HIGH RULE-AUTH-AUTHENTICATION-SURFACE, RULE-TRANSPORT-ENFORCE-TLS AUTH-BASIC-OVER-HTTP, HTTP-NO-HTTPS-REDIRECT

OWASP WSTG WSTG-ATHN-09: Weak password change or reset functionality INFO RULE-AUTH-AUTHENTICATION-SURFACE signals: auth_routes

OWASP WSTG WSTG-CLNT-09: Clickjacking MEDIUM RULE-FRONTEND-BROWSER-SECURITY-HEADERS HEADER-CLICKJACKING-MISSING, HEADER-CONTENT_SECURITY_POLICY-MISSING, HEADER-NOSNIFF-MISSING, HEADER-PERMISSIONS_POLICY-MISSING, HEADER-REFERRER_POLICY-MISSING

OWASP WSTG WSTG-CONF-05: Enumerate infrastructure and application admin interfaces INFO RULE-AUTHZ-ADMIN-SURFACE signals: admin_routes

OWASP WSTG WSTG-CONF-06: HTTP methods HIGH RULE-CONFIG-HTTP-METHODS METHOD-DELETE-ADVERTISED, METHOD-PUT-ADVERTISED, METHOD-TRACE-ADVERTISED

OWASP WSTG WSTG-CONF-12: Content Security Policy MEDIUM RULE-FRONTEND-BROWSER-SECURITY-HEADERS HEADER-CLICKJACKING-MISSING, HEADER-CONTENT_SECURITY_POLICY-MISSING, HEADER-NOSNIFF-MISSING, HEADER-PERMISSIONS_POLICY-MISSING, HEADER-REFERRER_POLICY-MISSING

OWASP WSTG WSTG-CONF-14: Other HTTP security header misconfigurations MEDIUM RULE-FRONTEND-BROWSER-SECURITY-HEADERS HEADER-CLICKJACKING-MISSING, HEADER-CONTENT_SECURITY_POLICY-MISSING, HEADER-NOSNIFF-MISSING, HEADER-PERMISSIONS_POLICY-MISSING, HEADER-REFERRER_POLICY-MISSING

OWASP WSTG WSTG-CRYP-03: Sensitive information sent via unencrypted channels HIGH RULE-TRANSPORT-ENFORCE-TLS AUTH-BASIC-OVER-HTTP, HTTP-NO-HTTPS-REDIRECT

OWASP WSTG WSTG-INFO-02: Fingerprint web server INFO RULE-INFO-TECH-FINGERPRINTING FINGERPRINT-GENERATOR-DISCLOSED, FINGERPRINT-POWERED-BY-DISCLOSED, FINGERPRINT-SERVER-VERSION-DISCLOSED

OWASP WSTG WSTG-INFO-03: Review webserver metafiles for information leakage INFO RULE-INFO-WEBSERVER-METAFILES signals: public_metadata

OWASP WSTG WSTG-INFO-04: Enumerate applications on webserver INFO RULE-INFRA-DISCOVERY-SURFACE PORTS-OPEN-TCP-PORTS

OWASP WSTG WSTG-INFO-05: Review web page content for information leakage INFO RULE-INFO-JAVASCRIPT-SURFACE JS-ENDPOINTS-DISCOVERED, JS-OUT-OF-SCOPE-ENDPOINTS, JS-SENSITIVE-PARAMETER-NAMES

OWASP WSTG WSTG-INFO-06: Identify application entry points INFO RULE-INFO-ENTRY-POINTS, RULE-INFO-JAVASCRIPT-SURFACE JS-ENDPOINTS-DISCOVERED, JS-OUT-OF-SCOPE-ENDPOINTS, JS-SENSITIVE-PARAMETER-NAMES

OWASP WSTG WSTG-INFO-07: Map execution paths through application INFO RULE-INFO-ENTRY-POINTS, RULE-INFO-WEBSERVER-METAFILES signals: entry_points_present, public_metadata, sensitive_parameters, state_changing_entry_points

OWASP WSTG WSTG-INFO-08: Fingerprint web application framework INFO RULE-INFO-TECH-FINGERPRINTING FINGERPRINT-GENERATOR-DISCLOSED, FINGERPRINT-POWERED-BY-DISCLOSED, FINGERPRINT-SERVER-VERSION-DISCLOSED

OWASP WSTG WSTG-INFO-10: Map application architecture INFO RULE-INFO-TECH-FINGERPRINTING, RULE-INFRA-DISCOVERY-SURFACE, RULE-SCOPE-EXTERNAL-REFERENCES CRAWLER-OUT-OF-SCOPE-LINKS, FINGERPRINT-GENERATOR-DISCLOSED, FINGERPRINT-POWERED-BY-DISCLOSED, FINGERPRINT-SERVER-VERSION-DISCLOSED, JS-OUT-OF-SCOPE-ENDPOINTS, PORTS-OPEN-TCP-PORTS

OWASP WSTG WSTG-SESS-02: Cookie attributes MEDIUM RULE-SESSION-COOKIE-ATTRIBUTES COOKIE-HTTPONLY-MISSING, COOKIE-SAMESITE-MISSING, COOKIE-SAMESITE-NONE-WITHOUT-SECURE

RULE SAFETY NOTES

- Rules are evaluated from existing passive scan evidence only.
- A matched rule is review guidance, not proof of exploitability.
- Out-of-scope references are recorded but must not be scanned without explicit authorization.

MODULE SUMMARY

Module Status Summary

scope passed Target URL validated and inside configured scope.

http warning HTTP/HTTPS reachability and redirects checked.

security_headers warning Security headers checked.

cookies warning Checked 2 cookie(s).

basic_auth warning HTTP authentication challenge checked.

http_methods warning HTTP methods advertised by OPTIONS checked.

ports warning Checked 3 TCP port(s), found 1 open port(s).

fingerprinting warning Identified 4 technology signal(s) and checked 4 public metadata path(s).

crawler warning Crawled 5 page(s), discovered 9 in-scope URL(s), 9 from metadata.

javascript passed Analyzed 5 page(s) and 3 script block(s), discovered 9 in-scope endpoint reference(s).

FINDINGS

HIGH - HTTP BASIC AUTHENTICATION OVER HTTP

- ID: AUTH-BASIC-OVER-HTTP
- Category: authentication
- Module: basic_auth
- Target: http://127.0.0.1:56158/members/

Description

The server requests Basic Authentication over unencrypted HTTP.

Recommendation

Force HTTPS before authentication and enable HSTS after validation.

Evidence

- status_code: 401
- www-authenticate: Basic realm="AI Web Auditor Lab"

HIGH - HTTP IS NOT REDIRECTED TO HTTPS

- ID: HTTP-NO-HTTPS-REDIRECT
- Category: transport-security
- Module: http
- Target: http://127.0.0.1:56158/members/

Description

The requested HTTP URL remains available without being upgraded to HTTPS.

Recommendation

Redirect all HTTP traffic to HTTPS and consider enabling HSTS after verification.

Evidence

- initial_url: http://127.0.0.1:56158/members/
- final_url: http://127.0.0.1:56158/members/
- status_code: 401

HIGH - HTTP METHOD TRACE IS ADVERTISED

- ID: METHOD-TRACE-ADVERTISED

- Category: http-methods
- Module: http_methods
- Target: http://127.0.0.1:56158/members/

Description

TRACE can expose request data and is rarely needed.

Recommendation

Disable unnecessary HTTP methods or enforce strict authorization before use.

Evidence

- allow: GET, POST, OPTIONS, PUT, DELETE, TRACE
- access-control-allow-methods: GET, POST, OPTIONS, PUT, DELETE, TRACE

MEDIUM - COOKIE USES SAMESITE=NONE WITHOUT SECURE

- ID: COOKIE-SAMESITE-NONE-WITHOUT-SECURE
- Category: cookies
- Module: cookies
- Target: http://127.0.0.1:56158/members/

Description

SameSite=None cookies should also use Secure.

Recommendation

Set Secure or avoid SameSite=None if cross-site usage is not required.

Evidence

- cookie: tracking_id

MEDIUM - CONTENT-SECURITY-POLICY HEADER IS MISSING

- ID: HEADER-CONTENT_SECURITY_POLICY-MISSING
- Category: security-headers
- Module: security_headers
- Target: http://127.0.0.1:56158/members/

Description

The response does not include the Content-Security-Policy header.

Recommendation

Define an appropriate Content-Security-Policy header for this application.

MEDIUM - HTTP METHOD DELETE IS ADVERTISED

- ID: METHOD-DELETE-ADVERTISED
- Category: http-methods
- Module: http_methods
- Target: http://127.0.0.1:56158/members/

Description

DELETE may allow destructive actions if authorization is weak.

Recommendation

Disable unnecessary HTTP methods or enforce strict authorization before use.

Evidence

- allow: GET, POST, OPTIONS, PUT, DELETE, TRACE
- access-control-allow-methods: GET, POST, OPTIONS, PUT, DELETE, TRACE

MEDIUM - HTTP METHOD PUT IS ADVERTISED

- ID: METHOD-PUT-ADVERTISED
- Category: http-methods
- Module: http_methods
- Target: http://127.0.0.1:56158/members/

Description

PUT may allow content upload if authorization is weak.

Recommendation

Disable unnecessary HTTP methods or enforce strict authorization before use.

Evidence

- allow: GET, POST, OPTIONS, PUT, DELETE, TRACE
- access-control-allow-methods: GET, POST, OPTIONS, PUT, DELETE, TRACE

LOW - COOKIE MISSING HTTPONLY FLAG

- ID: COOKIE-HTTPONLY-MISSING
- Category: cookies
- Module: cookies
- Target: http://127.0.0.1:56158/members/

Description

A cookie is accessible to client-side scripts when HttpOnly is absent.

Recommendation

Set HttpOnly for session or sensitive cookies.

Evidence

- cookie: sessionid

LOW - COOKIE MISSING HTTPONLY FLAG

- ID: COOKIE-HTTPONLY-MISSING
- Category: cookies
- Module: cookies
- Target: http://127.0.0.1:56158/members/

Description

A cookie is accessible to client-side scripts when HttpOnly is absent.

Recommendation

Set HttpOnly for session or sensitive cookies.

Evidence

- cookie: tracking_id

LOW - COOKIE MISSING SAMESITE ATTRIBUTE

- ID: COOKIE-SAMESITE-MISSING
- Category: cookies
- Module: cookies
- Target: http://127.0.0.1:56158/members/

Description

A cookie does not declare a SameSite policy.

Recommendation

Set SameSite=Lax or SameSite=Strict unless cross-site usage is required.

Evidence

- cookie: sessionid

LOW - CLICKJACKING PROTECTION HEADER IS MISSING

- ID: HEADER-CLICKJACKING-MISSING
- Category: security-headers
- Module: security_headers
- Target: http://127.0.0.1:56158/members/

Description

The response does not include X-Frame-Options or a CSP frame-ancestors directive.

Recommendation

Set frame-ancestors in Content-Security-Policy or use X-Frame-Options where appropriate.

LOW - X-CONTENT-TYPE-OPTIONS NOSNIFF IS MISSING

- ID: HEADER-NOSNIFF-MISSING
- Category: security-headers
- Module: security_headers
- Target: http://127.0.0.1:56158/members/

Description

The browser may try to infer content types when nosniff is absent.

Recommendation

Set X-Content-Type-Options: nosniff.

Evidence

- x-content-type-options: missing

LOW - REFERRER-POLICY HEADER IS MISSING

- ID: HEADER-REFERRER_POLICY-MISSING
- Category: security-headers
- Module: security_headers
- Target: http://127.0.0.1:56158/members/

Description

The response does not include the Referrer-Policy header.

Recommendation

Define an appropriate Referrer-Policy header for this application.

INFO - CRAWLER FOUND LINKS OUTSIDE SCOPE

- ID: CRAWLER-OUT-OF-SCOPE-LINKS
- Category: crawler
- Module: crawler
- Target: http://127.0.0.1:56158/members/

Description

The crawler discovered links outside the configured scope. They were recorded but not requested.

Recommendation

Review whether any external host should be added to the authorized scope before scanning it.

Evidence

- sample_url: <https://example.org/external>

INFO - HTML GENERATOR METADATA IS EXPOSED

- ID: FINGERPRINT-GENERATOR-DISCLOSED
- Category: fingerprinting
- Module: fingerprinting
- Target: <http://127.0.0.1:56158/members/>

Description

The HTML generator metadata can disclose CMS or framework details.

Recommendation

Remove generator metadata if it is not required.

Evidence

- generator: WordPress 4.7.0

INFO - X-POWERED-BY HEADER DISCLOSES TECHNOLOGY INFORMATION

- ID: FINGERPRINT-POWERED-BY-DISCLOSED
- Category: fingerprinting
- Module: fingerprinting
- Target: <http://127.0.0.1:56158/members/>

Description

The X-Powered-By header can reveal backend technology details to attackers.

Recommendation

Remove or reduce technology-identifying response headers where practical.

Evidence

- x-powered-by: PHP/5.6.40

INFO - SERVER HEADER DISCLOSES VERSION INFORMATION

- ID: FINGERPRINT-SERVER-VERSION-DISCLOSED
- Category: fingerprinting
- Module: fingerprinting

- Target: <http://127.0.0.1:56158/members/>

Description

The Server header appears to include product version information.

Recommendation

Avoid exposing precise server versions unless there is an operational reason.

Evidence

- server: AIWebAuditorLab/0.21

INFO - PERMISSIONS-POLICY HEADER IS MISSING

- ID: HEADER-PERMISSIONS_POLICY-MISSING
- Category: security-headers
- Module: security_headers
- Target: <http://127.0.0.1:56158/members/>

Description

The response does not include the Permissions-Policy header.

Recommendation

Define an appropriate Permissions-Policy header for this application.

INFO - JAVASCRIPT ENDPOINT REFERENCES DISCOVERED

- ID: JS-ENDPOINTS-DISCOVERED
- Category: javascript-enumeration
- Module: javascript
- Target: <http://127.0.0.1:56158/members/>

Description

Client-side JavaScript contains URL references that expand the passive review surface.

Recommendation

Review these endpoints against the authorized scope before deciding whether later validation is needed.

Evidence

- endpoint: <http://127.0.0.1:56158/api>
- endpoint: POST [http://127.0.0.1:56158/api/member-profile?csrf_token=\[redacted\]](http://127.0.0.1:56158/api/member-profile?csrf_token=[redacted])
- endpoint: POST [http://127.0.0.1:56158/api/profile?session_id=\[redacted\]](http://127.0.0.1:56158/api/profile?session_id=[redacted])
- endpoint: POST <http://127.0.0.1:56158/api/upload>
- endpoint: GET <http://127.0.0.1:56158/api/users?role=member>

INFO - JAVASCRIPT REFERENCES ENDPOINTS OUTSIDE SCOPE

- ID: JS-OUT-OF-SCOPE-ENDPOINTS
- Category: javascript-enumeration
- Module: javascript
- Target: <http://127.0.0.1:56158/members/>

Description

Client-side JavaScript references hosts outside the configured scope. They were recorded but not requested.

Recommendation

Confirm whether those hosts belong to the engagement before scanning them.

Evidence

- endpoint: <https://example.org/collect>

INFO - JAVASCRIPT REFERENCES SENSITIVE-LOOKING PARAMETER NAMES

- ID: JS-SENSITIVE-PARAMETER-NAMES
- Category: javascript-enumeration
- Module: javascript
- Target: <http://127.0.0.1:56158/members/>

Description

Some JavaScript-discovered URLs contain parameter names commonly associated with authentication, sessions or secrets. Values are redacted.

Recommendation

Review how these parameters are generated, logged and exposed. Do not include raw secrets in reports.

Evidence

- parameter_name ([http://127.0.0.1:56158/api/member-profile?csrf_token=\[redacted\]](http://127.0.0.1:56158/api/member-profile?csrf_token=[redacted])): csrf_token
- parameter_name ([http://127.0.0.1:56158/api/profile?session_id=\[redacted\]](http://127.0.0.1:56158/api/profile?session_id=[redacted])): session_id
- parameter_name ([http://127.0.0.1:56158/reset-password?token=\[redacted\]](http://127.0.0.1:56158/reset-password?token=[redacted])): token

INFO - OPEN TCP PORTS DETECTED

- ID: PORTS-OPEN-TCP-PORTS
- Category: network-exposure
- Module: ports
- Target: 127.0.0.1

Description

The limited TCP connectivity check found open ports on the target host. This is inventory evidence, not exploitation.

Recommendation

Review whether each exposed service is expected, patched and covered by the authorized audit scope.

Evidence

- open_port: 56158

TECHNOLOGY FINGERPRINTING

Technology	Category	Confidence	Signals
AIWebAuditorLab/0.21	server	low	header:server
Django	framework	medium	cookie:sessionid
PHP 5.6.40	language	high	header:x-powered-by
WordPress 4.7.0	cms	high	html:meta-generator

PUBLIC METADATA FILES

Path	Status	Present
/robots.txt	200	True
/.well-known/security.txt	200	True
/security.txt	404	False
/sitemap.xml	200	True

CRAWLER

- Seed URL: http://127.0.0.1:56158/members/
- Max depth: 1
- Max pages: 20
- Fetched URLs: 5
- Discovered in-scope URLs: 9
- Metadata-discovered URLs: 9
- Classified interesting routes: 6
- robots.txt: present (200)
- Sitemaps checked: 1 (1 present)
- .well-known endpoints checked: 8 (2 present)
- Out-of-scope URLs recorded but not visited: 1
- Excluded URLs recorded but not visited: 3

INTERESTING ROUTES

URL	Types	Sources
http://127.0.0.1:56158/api/users	api	crawler_fetched, sitemap
http://127.0.0.1:56158/login	form, login	crawler_fetched, sitemap
http://127.0.0.1:56158/members/	account, form, login	crawler_fetched, html_link, robots_allow, seed, sitemap

http://127.0.0.1:56158/oauth/authorize callback, login well_known_endpoint
http://127.0.0.1:56158/oauth/token callback well_known_endpoint
http://127.0.0.1:56158/reset-password password_reset crawler_fetched, sitemap

PRESENT .WELL-KNOWN ENDPOINTS

Path Status Highlights

/.well-known/security.txt 200 contact: mailto:security@example.test; policy:

http://127.0.0.1/security-policy

/.well-known/openid-configuration 200 endpoints: 2

DISCOVERED URLS

- http://127.0.0.1:56158/
- http://127.0.0.1:56158/.well-known/openid-configuration
- http://127.0.0.1:56158/.well-known/security.txt
- http://127.0.0.1:56158/api/users
- http://127.0.0.1:56158/login
- http://127.0.0.1:56158/members/
- http://127.0.0.1:56158/oauth/authorize
- http://127.0.0.1:56158/oauth/token
- http://127.0.0.1:56158/reset-password

OUT-OF-SCOPE URLS

- https://example.org/external

EXCLUDED URLS

- http://127.0.0.1:56158/admin/
- http://127.0.0.1:56158/private/
- http://127.0.0.1:56158/private/report

JAVASCRIPT ANALYSIS

- Pages checked: 5
- Script blocks analyzed: 3
- In-scope endpoint references: 9
- Sensitive-looking parameter names: 3
- Out-of-scope endpoint references recorded but not requested: 1
- Excluded endpoint references recorded but not requested: 1

Only HTML and JavaScript resources inside the configured scope were requested. Discovered endpoints were not executed.

JAVASCRIPT ENDPOINT REFERENCES

URL Method Parameters Route types Sources

http://127.0.0.1:56158/api unknown unknown api external_script

http://127.0.0.1:56158/api/member-profile?csrf_token=%5Bredacted%5D POST csrf_token
account, api, state_changing_candidate inline_script

http://127.0.0.1:56158/api/profile?session_id=%5Bredacted%5D POST session_id account,

api, state_changing_candidate external_script, inline_script
http://127.0.0.1:56158/api/upload POST unknown api, state_changing_candidate, upload
external_script
http://127.0.0.1:56158/api/users?role=member GET role api external_script
http://127.0.0.1:56158/callback/oauth unknown unknown callback external_script
http://127.0.0.1:56158/health unknown unknown health inline_script
http://127.0.0.1:56158/oauth/authorize?client_id=demo unknown client_id callback, login
external_script
http://127.0.0.1:56158/reset-password?token=%5Bredacted%5D unknown token password_reset
inline_script

SCRIPTS ANALYZED

Kind	URL/Page	Status	Type	Endpoints
external	http://127.0.0.1:56158/static/app.js	200	application/javascript; charset=utf-8	6
inline	http://127.0.0.1:56158/members/	unknown	unknown	2
inline	http://127.0.0.1:56158/	unknown	unknown	1

OUT-OF-SCOPE JAVASCRIPT REFERENCES

- https://example.org/collect

EXCLUDED JAVASCRIPT REFERENCES

- http://127.0.0.1:56158/admin/export?token=%5Bredacted%5D

WEB INVENTORY

- Total URLs: 35
- Fetched URLs: 16
- Interesting URLs: 23
- Forms detected: 2
- Out-of-scope URLs recorded but not visited: 2
- Excluded URLs recorded but not visited: 4

URL INVENTORY

URL	Status	Type	Forms	Interest
http://127.0.0.1:56158/.well-known/change-password	404	unknown	0	password_reset, password_reset_path
http://127.0.0.1:56158/.well-known/oauth-authorization-server	404	unknown	0	callback, callback_path
http://127.0.0.1:56158/admin/	unknown	unknown	0	admin, admin_path
http://127.0.0.1:56158/admin/export?token=%5Bredacted%5D	unknown	unknown	0	admin, admin_path
http://127.0.0.1:56158/api	unknown	unknown	0	api, api_path
http://127.0.0.1:56158/api/member-profile?csrf_token=%5Bredacted%5D	unknown	unknown	0	account, api, state_changing_candidate, account_area, api_path, post_method
http://127.0.0.1:56158/api/profile?session_id=%5Bredacted%5D	unknown	unknown	0	account, api, state_changing_candidate, account_area, api_path, post_method
http://127.0.0.1:56158/api/upload	unknown	unknown	0	api, state_changing_candidate,

upload, api_path, upload_path, post_method
 http://127.0.0.1:56158/api/users 200 application/json; charset=utf-8 0 api, api_path
 http://127.0.0.1:56158/api/users?role=member unknown unknown 0 api, api_path
 http://127.0.0.1:56158/callback/oauth unknown unknown 0 callback, callback_path
 http://127.0.0.1:56158/health unknown unknown 0 health, health_status_path
 http://127.0.0.1:56158/login 200 text/html; charset=utf-8 1 form, login, login_path, form_detected
 http://127.0.0.1:56158/login/ unknown unknown 0 login, state_changing_candidate, login_path, post_method
 http://127.0.0.1:56158/members/ 401 text/html; charset=utf-8 1 account, form, login, login_path, account_area, form_detected
 http://127.0.0.1:56158/oauth/authorize unknown unknown 0 callback, login, login_path, callback_path
 http://127.0.0.1:56158/oauth/authorize?client_id=demo unknown unknown 0 callback, login, login_path, callback_path
 http://127.0.0.1:56158/oauth/token unknown unknown 0 callback, callback_path
 http://127.0.0.1:56158/private/ unknown unknown 0 account, account_area
 http://127.0.0.1:56158/private/report unknown unknown 0 account, account_area
 http://127.0.0.1:56158/reset-password 200 text/html; charset=utf-8 0 password_reset, password_reset_path
 http://127.0.0.1:56158/reset-password?token=%5Bredacted%5D unknown unknown 0 password_reset, password_reset_path
 http://127.0.0.1:56158/session unknown unknown 0 login, state_changing_candidate, login_path, post_method
 http://127.0.0.1:56158/ 200 text/html; charset=utf-8 0 unknown
 http://127.0.0.1:56158/.well-known/openid-configuration 200 unknown 0 unknown
 http://127.0.0.1:56158/.well-known/security.txt 200 unknown 0 unknown
 https://example.org/collect unknown unknown 0 unknown
 https://example.org/external unknown unknown 0 unknown
 http://127.0.0.1:56158/.well-known/apple-app-site-association 404 unknown 0 unknown
 http://127.0.0.1:56158/.well-known/assetlinks.json 404 unknown 0 unknown
 http://127.0.0.1:56158/.well-known/webfinger 404 unknown 0 unknown
 http://127.0.0.1:56158/robots.txt 200 unknown 0 unknown
 http://127.0.0.1:56158/security.txt 404 unknown 0 unknown
 http://127.0.0.1:56158/sitemap.xml 200 unknown 0 unknown
 http://127.0.0.1:56158/static/app.js 200 application/javascript; charset=utf-8 0 static_asset

FORMS

Page Action Method Inputs Password Fields

http://127.0.0.1:56158/login http://127.0.0.1:56158/session POST 2 1
 http://127.0.0.1:56158/members/ http://127.0.0.1:56158/login/ POST 3 1

ENTRY POINTS

- Endpoints: 35
- Review candidates: 28
- Forms: 2
- Parameters: 8
- State-changing endpoints: 6

Only passive evidence was used: URLs, query strings, forms and advertised HTTP methods. No form submission was performed.

HTTP METHODS OBSERVED

Method Endpoints State-changing

DELETE 1 True

GET 17 False

OPTIONS 1 False

POST 6 True

PUT 1 True

TRACE 1 False

ENDPOINT REVIEW LIST

URL State Methods Parameters Forms Route types Notes

http://127.0.0.1:56158/login/ form_action POST csrf_token, password, username 1 login, state_changing_candidate form_action, login_route, parameters_observed, sensitive_parameter_name, state_changing_method

http://127.0.0.1:56158/session form_action POST password, user 1 login, state_changing_candidate form_action, login_route, parameters_observed, sensitive_parameter_name, state_changing_method

http://127.0.0.1:56158/api/member-profile?csrf_token=%5Bredacted%5D discovered POST csrf_token 0 account, api, state_changing_candidate api_route, parameters_observed, sensitive_parameter_name, state_changing_method

http://127.0.0.1:56158/api/profile?session_id=%5Bredacted%5D discovered POST session_id 0 account, api, state_changing_candidate api_route, parameters_observed, sensitive_parameter_name, state_changing_method

http://127.0.0.1:56158/api/upload discovered POST unknown 0 api, state_changing_candidate, upload api_route, state_changing_method, upload_route

http://127.0.0.1:56158/members/ fetched DELETE, GET, OPTIONS, POST, PUT, TRACE unknown 0 account, form, login login_route, state_changing_method

http://127.0.0.1:56158/api/users?role=member discovered GET role 0 api api_route, parameters_observed

http://127.0.0.1:56158/oauth/authorize?client_id=demo discovered unknown client_id 0 callback, login callback_route, login_route, parameters_observed

http://127.0.0.1:56158/reset-password?token=%5Bredacted%5D discovered unknown token 0 password_reset parameters_observed, password_reset_route, sensitive_parameter_name

http://127.0.0.1:56158/ fetched GET unknown 0 unknown unknown

http://127.0.0.1:56158/.well-known/apple-app-site-association fetched GET unknown 0 unknown unknown

http://127.0.0.1:56158/.well-known/assetlinks.json fetched GET unknown 0 unknown unknown

http://127.0.0.1:56158/.well-known/change-password fetched GET unknown 0 password_reset password_reset_route

http://127.0.0.1:56158/.well-known/oauth-authorization-server fetched GET unknown 0 callback callback_route

http://127.0.0.1:56158/.well-known/openid-configuration fetched GET unknown 0 unknown unknown

http://127.0.0.1:56158/.well-known/security.txt fetched GET unknown 0 unknown unknown

http://127.0.0.1:56158/.well-known/webfinger fetched GET unknown 0 unknown unknown

http://127.0.0.1:56158/api discovered unknown unknown 0 api api_route

http://127.0.0.1:56158/api/users fetched GET unknown 0 api api_route
 http://127.0.0.1:56158/callback/oauth discovered unknown unknown 0 callback
 callback_route
 http://127.0.0.1:56158/health discovered unknown unknown 0 health unknown
 http://127.0.0.1:56158/login fetched GET unknown 0 form, login login_route
 http://127.0.0.1:56158/oauth/authorize metadata unknown unknown 0 callback, login
 callback_route, login_route
 http://127.0.0.1:56158/oauth/token metadata unknown unknown 0 callback callback_route
 http://127.0.0.1:56158/reset-password fetched GET unknown 0 password_reset
 password_reset_route
 http://127.0.0.1:56158/robots.txt fetched GET unknown 0 unknown unknown
 http://127.0.0.1:56158/security.txt fetched GET unknown 0 unknown unknown
 http://127.0.0.1:56158/sitemap.xml fetched GET unknown 0 unknown unknown
 http://127.0.0.1:56158/admin/export?token=%5Bredacted%5D excluded unknown token 0 admin
 admin_route, parameters_observed, sensitive_parameter_name
 http://127.0.0.1:56158/admin/ excluded unknown unknown 0 admin admin_route
 http://127.0.0.1:56158/private/ excluded unknown unknown 0 account unknown
 http://127.0.0.1:56158/private/report excluded unknown unknown 0 account unknown
 http://127.0.0.1:56158/static/app.js fetched GET unknown 0 static_asset unknown
 https://example.org/collect out_of_scope unknown unknown 0 unknown unknown
 https://example.org/external out_of_scope unknown unknown 0 unknown unknown

FORM ENTRY POINTS

Page Action Method Inputs Password fields CSRF candidates

http://127.0.0.1:56158/login http://127.0.0.1:56158/session POST 2 1 unknown
 http://127.0.0.1:56158/members/ http://127.0.0.1:56158/login/ POST 3 1 csrf_token

SENSITIVE-LOOKING PARAMETERS

Parameter Locations Occurrences Methods

csrf_token form, query 2 POST
 password form 2 POST
 session_id query 1 unknown
 token query 2 unknown

TCP PORT CHECK

- Host: 127.0.0.1
- Ports checked: 3
- Open ports: 1
- Closed ports: 0
- Filtered ports: 2
- Only TCP connect checks were performed; no payloads or banners were requested.

Port Service Status Elapsed

56158 unknown open 0 ms
 80 http filtered 500 ms
 443 https filtered 500 ms

LIMITATIONS

- This report is based on non-intrusive checks only.
- No exploitation, brute force, aggressive fuzzing or destructive testing was performed.
- Findings should be validated against the authorized scope and business context.