EnduranceLife API (0.1.0)

Download OpenAPI specification: Download

RESTful API for managing endurance-sport training data parsed from .fit files (Coros, Garmin, etc.), daily nutrition/recovery metrics, and physiological trend tracking.

Activities

Create Activity

Import a new activity record via JSON body.

If the `source_file` already exists in the database, a 409 Conflict is returned to prevent duplicate imports.

REQUEST BODY SCHEMA: application/json
required

`pid` required	integer (Pid) User / person ID
`source_file` required	string (Source File) Original .fit filename (used as dedup key)
`date` required	string <date> (Date)
`start_time` required	string <date-time> (Start Time) Activity start time in UTC
`start_lat` >	Start Lat (number) or Start Lat (null) (Start Lat) Starting latitude
`start_lng` >	Start Lng (number) or Start Lng (null) (Start Lng) Starting longitude

distance_km required	number (Distance Km)
duration_min required	number (Duration Min) Total duration in minutes
type required	string (Type) Activity type: 'Run' or 'Ride'
temperature >	Temperature (number) or Temperature (null) (Temperature)
humidity >	Humidity (number) or Humidity (null) (Humidity)
air_pressure >	Air Pressure (number) or Air Pressure (null) (Air Pressure)
altitude_gain >	Altitude Gain (number) or Altitude Gain (null) (Altitude Gain)
avg_heart_rate >	Avg Heart Rate (integer) or Avg Heart Rate (null) (Avg Heart Rate)
max_heart_rate >	Max Heart Rate (integer) or Max Heart Rate (null) (Max Heart Rate)
avg_pace_sec >	Avg Pace Sec (integer) or Avg Pace Sec (null) (Avg Pace Sec) Avg pace in sec/km
avg_cadence >	Avg Cadence (integer) or Avg Cadence (null) (Avg Cadence)
training_load >	Training Load (number) or Training Load (null) (Training Load) Coros training load metric
hr_array_json >	Hr Array Json (string) or Hr Array Json (null) (Hr Array Json) JSON array string of HR time-series
pace_array_json >	Pace Array Json (string) or Pace Array Json (null) (Pace Array Json) JSON array string of pace time-series

Responses

> 201

Successful Response

> 422

Validation Error

POST /activities/

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
    "source_file": "string",
    "date": "2019-08-24",
    "start_time": "2019-08-24T14:15:22Z",
    "start_lat": 0,
    "start_lng": 0,
    "distance_km": 0,
    "duration_min": 0,
    "type": "string",
    "temperature": 0,
    "humidity": 0,
    "air_pressure": 0,
    "altitude_gain": 0,
    "avg_heart_rate": 0,
    "max_heart_rate": 0,
    "avg_pace_sec": 0,
    "avg_cadence": 0,
    "training_load": 0,
    "hr_array_json": "string",
    "pace_array_json": "string"
}
```

Response samples

201 422

Content type
application/json

Copy


```
{
    "pid": 0,
    "source_file": "string",
    "date": "2019-08-24",
    "start_time": "2019-08-24T14:15:22Z",
    "start_lat": 0,
    "start_lng": 0,
    "distance_km": 0,
    "duration_min": 0,
    "type": "string",
    "temperature": 0,
    "humidity": 0,
    "air_pressure": 0,
    "altitude_gain": 0,
    "avg_heart_rate": 0,
    "max_heart_rate": 0,
    "avg_pace_sec": 0,
    "avg_cadence": 0,
    "training_load": 0,
    "hr_array_json": "string",
    "pace_array_json": "string",
    "id": 0
}
```

List Activities

Retrieve a paginated list of activities.

Supports optional filtering by `pid`, `type`, and a date range (`date_from`, `date_to`) for efficient front-end chart windows.

QUERY PARAMETERS

`pid` >	Pid (integer) or Pid (null) (Pid) Filter by user ID
`type` >	Type (string) or Type (null) (Type) Filter by activity type (Run / Ride)
`date_from` >	Date From (string) or Date From (null) (Date From) Start of date range (inclusive)
`date_to` >	Date To (string) or Date To (null) (Date To) End of date range (inclusive)
`skip`	integer (Skip) `>= 0` Default: `0` Number of records to skip
`limit`	integer (Limit) `[ 1 .. 200 ]` Default: `50` Max records to return

Responses

> **200**

Successful Response

> **422**

Validation Error

GET /activities/

Response samples

200 **422**

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
        "pid": 0,
        "source_file": "string",
        "date": "2019-08-24",
        "start_time": "2019-08-24T14:15:22Z",
        "start_lat": 0,
        "start_lng": 0,
        "distance_km": 0,
        "duration_min": 0,
        "type": "string",
        "temperature": 0,
        "humidity": 0,
        "air_pressure": 0,
        "altitude_gain": 0,
        "avg_heart_rate": 0,
        "max_heart_rate": 0,
        "avg_pace_sec": 0,
        "avg_cadence": 0,
        "training_load": 0,
        "hr_array_json": "string",
        "pace_array_json": "string",
        "id": 0
    }
]
```

Upload a .fit file and auto-parse it into an Activity record

Upload a `.fit` file directly through Swagger UI or any HTTP client.

The file is parsed in-memory using `fitdecode` and the raw bytes are stored in the database (`fit_file_blob`) for later re-parsing or download. Extracted fields include distance, duration, heart rate, pace, GPS coordinates, cadence, and time-series arrays.

- Returns **201** with the created Activity on success.
- Returns **409** if a file with the same name was already imported.
- Returns **422** if the file contains no workout session data.

REQUEST BODY SCHEMA: multipart/form-data

required

file required	string <binary> (File) A .fit file exported from Coros/Garmin
pid	integer (Pid) Default: 1 User / person ID

Responses

201

Successful Response

422

Validation Error

POST /activities/upload

Response samples

201 422

Content type
application/json

Copy

```
{
    "pid": 0,
    "source_file": "string",
    "date": "2019-08-24",
    "start_time": "2019-08-24T14:15:22Z",
    "start_lat": 0,
    "start_lng": 0,
    "distance_km": 0,
    "duration_min": 0,
```

```
    "type": "string",
    "temperature": 0,
    "humidity": 0,
    "air_pressure": 0,
    "altitude_gain": 0,
    "avg_heart_rate": 0,
    "max_heart_rate": 0,
    "avg_pace_sec": 0,
    "avg_cadence": 0,
    "training_load": 0,
    "hr_array_json": "string",
    "pace_array_json": "string",
    "id": 0
}
```

Get Activity

Retrieve a single activity by its primary key.

PATH PARAMETERS

`activity_id` required	integer (Activity Id)

Responses

> 200

Successful Response

> 422

Validation Error

GET /activities/{activity_id}

Response samples

200 422

Content type
application/json

Copy


```
{
    "pid": 0,
    "source_file": "string",
    "date": "2019-08-24",
    "start_time": "2019-08-24T14:15:22Z",
    "start_lat": 0,
    "start_lng": 0,
    "distance_km": 0,
    "duration_min": 0,
    "type": "string",
    "temperature": 0,
    "humidity": 0,
    "air_pressure": 0,
    "altitude_gain": 0,
    "avg_heart_rate": 0,
    "max_heart_rate": 0,
    "avg_pace_sec": 0,
    "avg_cadence": 0,
    "training_load": 0,
    "hr_array_json": "string",
    "pace_array_json": "string",
    "id": 0
}
```

Update Activity

Update an existing activity. Only fields present in the request body (non-None) are applied, allowing partial updates.

PATH PARAMETERS

activity_id required	integer (Activity Id)

REQUEST BODY SCHEMA: application/json
required

pid >	Pid (integer) or Pid (null) (Pid)
source_file >	Source File (string) or Source File (null) (Source File)
date	null (Date)
start_time >	Start Time (string) or Start Time (null) (Start Time)
start_lat >	Start Lat (number) or Start Lat (null) (Start Lat)
start_lng >	Start Lng (number) or Start Lng (null) (Start Lng)
distance_km >	Distance Km (number) or Distance Km (null) (Distance Km)
duration_min >	Duration Min (number) or Duration Min (null) (Duration Min)
type >	Type (string) or Type (null) (Type)
temperature >	Temperature (number) or Temperature (null) (Temperature)
humidity >	Humidity (number) or Humidity (null) (Humidity)
air_pressure >	Air Pressure (number) or Air Pressure (null) (Air Pressure)
altitude_gain >	Altitude Gain (number) or Altitude Gain (null) (Altitude Gain)
avg_heart_rate >	Avg Heart Rate (integer) or Avg Heart Rate (null) (Avg Heart Rate)
max_heart_rate >	Max Heart Rate (integer) or Max Heart Rate (null) (Max Heart Rate)
avg_pace_sec >	Avg Pace Sec (integer) or Avg Pace Sec (null) (Avg Pace Sec)
avg_cadence >	Avg Cadence (integer) or Avg Cadence (null) (Avg Cadence)

training_load >	Training Load (number) or Training Load (null) (Training Load)
hr_array_json >	Hr Array Json (string) or Hr Array Json (null) (Hr Array Json)
pace_array_json >	Pace Array Json (string) or Pace Array Json (null) (Pace Array Json)

Responses

> 200

Successful Response

> 422

Validation Error

PUT /activities/{activity_id}

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
    "source_file": "string",
    "date": null,
    "start_time": "2019-08-24T14:15:22Z",
    "start_lat": 0,
    "start_lng": 0,
    "distance_km": 0,
    "duration_min": 0,
    "type": "string",
    "temperature": 0,
```

```
    "humidity": 0,
    "air_pressure": 0,
    "altitude_gain": 0,
    "avg_heart_rate": 0,
    "max_heart_rate": 0,
    "avg_pace_sec": 0,
    "avg_cadence": 0,
    "training_load": 0,
    "hr_array_json": "string",
    "pace_array_json": "string"
}
```


Response samples

200 422

Content type
application/json

Copy


```
{
    "pid": 0,
    "source_file": "string",
    "date": "2019-08-24",
    "start_time": "2019-08-24T14:15:22Z",
    "start_lat": 0,
    "start_lng": 0,
    "distance_km": 0,
    "duration_min": 0,
    "type": "string",
    "temperature": 0,
    "humidity": 0,
    "air_pressure": 0,
    "altitude_gain": 0,
    "avg_heart_rate": 0,
    "max_heart_rate": 0,
    "avg_pace_sec": 0,
    "avg_cadence": 0,
    "training_load": 0,
    "hr_array_json": "string",
    "pace_array_json": "string",
    "id": 0
```

```
}
```

Delete Activity

Delete an activity by its primary key. Returns 204 No Content on success.

PATH PARAMETERS

`activity_id` required	integer (Activity Id)

Responses

— 204

Successful Response

> 422

Validation Error

DELETE `/activities/{activity_id}`

Response samples

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "detail": [
      + { … }
    ]
}
```

Daily Metrics

Create Daily Metric

Create a daily metric record.

If a record for the same (pid, date) already exists, returns 409 Conflict and advises the client to update the existing record via PUT /daily-metrics/{id} instead.

REQUEST BODY SCHEMA: application/json
required

pid required	integer (Pid)
date required	string <date> (Date)
calories_in >	Calories In (integer) or Calories In (null) (Calories In)
protein_g >	Protein G (integer) or Protein G (null) (Protein G)
sleep_hours >	Sleep Hours (number) or Sleep Hours (null) (Sleep Hours)
fatigue_level >	Fatigue Level (integer) or Fatigue Level (null) (Fatigue Level) Subjective fatigue 1-10
recovery >	Recovery (number) or Recovery (null) (Recovery) Recovery percentage
deep_work_hours >	Deep Work Hours (number) or Deep Work Hours (null) (Deep Work Hours)

`stress_level` >

Stress Level (integer) or Stress Level (null) (Stress Level)
Subjective stress 1-10

Responses

> **201**

Successful Response

> **422**

Validation Error

POST /daily-metrics/

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": "2019-08-24",
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1
}
```

Response samples

201 422

Content type
application/json

Copy


```
{
    "pid": 0,
    "date": "2019-08-24",
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1,
    "id": 0
}
```

List Daily Metrics

Retrieve daily metric records with optional filters.

`date_from` and `date_to` allow the front-end to request a specific window for charting (e.g. the last 30 days).

QUERY PARAMETERS

`pid` >	Pid (integer) or Pid (null) (Pid) Filter by user ID
`date_from` >	Date From (string) or Date From (null) (Date From) Start of date range (inclusive)
`date_to` >	Date To (string) or Date To (null) (Date To) End of date range (inclusive)
`skip`	integer (Skip) `>= 0` Default: `0`

`limit` integer (Limit) [1 .. 200]
Default: `50`

Responses

> **200**

Successful Response

> **422**

Validation Error

GET `/daily-metrics/`

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "pid": 0,
        "date": "2019-08-24",
        "calories_in": 0,
        "protein_g": 0,
        "sleep_hours": 0,
        "fatigue_level": 1,
        "recovery": 100,
        "deep_work_hours": 0,
        "stress_level": 1,
        "id": 0
    }
]
```

Get Daily Metric

Retrieve a single daily metric record by primary key.

PATH PARAMETERS

`metric_id` required	integer (Metric Id)

Responses

> 200

Successful Response

> 422

Validation Error

GET /daily-metrics/{metric_id}

Response samples

200 422

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": "2019-08-24",
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1,
    "id": 0
}
```

Update Daily Metric

Update an existing daily metric. Only fields present in the request body are modified (partial update via `exclude_unset`).

PATH PARAMETERS

metric_id required	integer (Metric Id)

REQUEST BODY SCHEMA: application/json
required

pid >	Pid (integer) or Pid (null) (Pid)

date	null (Date)
calories_in >	Calories In (integer) or Calories In (null) (Calories In)
protein_g >	Protein G (integer) or Protein G (null) (Protein G)
sleep_hours >	Sleep Hours (number) or Sleep Hours (null) (Sleep Hours)
fatigue_level >	Fatigue Level (integer) or Fatigue Level (null) (Fatigue Level)
recovery >	Recovery (number) or Recovery (null) (Recovery)
deep_work_hours >	Deep Work Hours (number) or Deep Work Hours (null) (Deep Work Hours)
stress_level >	Stress Level (integer) or Stress Level (null) (Stress Level)

Responses

> 200

Successful Response

> 422

Validation Error

PUT /daily-metrics/{metric_id}

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
```

```
    "date": null,
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1
}
```


Response samples

200 422

Content type
application/json

Copy


```
{
    "pid": 0,
    "date": "2019-08-24",
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1,
    "id": 0
}
```

Delete Daily Metric

Delete a daily metric record. Returns 204 No Content on success.

PATH PARAMETERS

metric_id required	integer (Metric Id)

Responses

— 204

Successful Response

> 422

Validation Error

DELETE /daily-metrics/{metric_id}

Response samples

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "detail": [
      + { … }
    ]
}
```

Update Daily Metric By Date

Update a daily metric by (pid, date) composite key.

This is often more convenient than updating by ID because the client naturally knows the user and date but may not know the row ID. Only fields present in the request body are modified (partial update).

QUERY PARAMETERS

pid required	integer (Pid) User ID
date required	string <date> (Date) Date of the metric (YYYY-MM-DD)

REQUEST BODY SCHEMA: application/json
required

pid >	Pid (integer) or Pid (null) (Pid)
date	null (Date)
calories_in >	Calories In (integer) or Calories In (null) (Calories In)
protein_g >	Protein G (integer) or Protein G (null) (Protein G)
sleep_hours >	Sleep Hours (number) or Sleep Hours (null) (Sleep Hours)
fatigue_level >	Fatigue Level (integer) or Fatigue Level (null) (Fatigue Level)
recovery >	Recovery (number) or Recovery (null) (Recovery)
deep_work_hours >	Deep Work Hours (number) or Deep Work Hours (null) (Deep Work Hours)
stress_level >	Stress Level (integer) or Stress Level (null) (Stress Level)

Responses

> 200

Successful Response

> 422

Validation Error

PUT /daily-metrics/by-date

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": null,
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1
}
```

Response samples

200 **422**

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": "2019-08-24",
    "calories_in": 0,
    "protein_g": 0,
    "sleep_hours": 0,
    "fatigue_level": 1,
    "recovery": 100,
    "deep_work_hours": 0,
    "stress_level": 1,
```

```
    "id": 0
}
```

Physiology Logs

Create Physiology Log

Create a new physiology snapshot for a user on a given date.

REQUEST BODY SCHEMA: application/json
required

pid required	integer (Pid)
date required	string <date> (Date)
height_cm >	Height Cm (number) or Height Cm (null) (Height Cm)
weight_kg >	Weight Kg (number) or Weight Kg (null) (Weight Kg)
running_fitness >	Running Fitness (number) or Running Fitness (null) (Running Fitness)
vo2max >	Vo2Max (number) or Vo2Max (null) (Vo2Max)
resting_heart_rate >	Resting Heart Rate (integer) or Resting Heart Rate (null) (Resting Heart Rate)
threshold_hr_zones >	Threshold Hr Zones (string) or Threshold Hr Zones (null) (Threshold Hr Zones) JSON string, e.g. {"z1":"120-135"}
threshold_pace_zones >	Threshold Pace Zones (string) or Threshold Pace Zones (null) (Threshold Pace Zones)

Responses

> 201

Successful Response

> 422

Validation Error

POST /physiology/

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": "2019-08-24",
    "height_cm": 0,
    "weight_kg": 0,
    "running_fitness": 0,
    "vo2max": 0,
    "resting_heart_rate": 0,
    "threshold_hr_zones": "string",
    "threshold_pace_zones": "string"
}
```

Response samples

201 **422**

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": "2019-08-24",
    "height_cm": 0,
    "weight_kg": 0,
    "running_fitness": 0,
    "vo2max": 0,
    "resting_heart_rate": 0,
    "threshold_hr_zones": "string",
    "threshold_pace_zones": "string",
    "id": 0
}
```

List Physiology Logs

Retrieve physiology logs, optionally filtered by user.

QUERY PARAMETERS

`pid` >	Pid (integer) or Pid (null) (Pid) Filter by user ID
`skip`	integer (Skip) `>= 0` Default: `0`
`limit`	integer (Limit) `[ 1 .. 200 ]` Default: `50`

Responses

> **200**

Successful Response

> 422

Validation Error

GET /physiology/

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
        "pid": 0,
        "date": "2019-08-24",
        "height_cm": 0,
        "weight_kg": 0,
        "running_fitness": 0,
        "vo2max": 0,
        "resting_heart_rate": 0,
        "threshold_hr_zones": "string",
        "threshold_pace_zones": "string",
        "id": 0
    }
]
```

Get Physiology Log

Retrieve a single physiology log by primary key.

PATH PARAMETERS

log_id required	integer (Log Id)

Responses

> 200

Successful Response

> 422

Validation Error

GET /physiology/{log_id}

Response samples

200 422

Content type
application/json

Copy


```
{
    "pid": 0,
    "date": "2019-08-24",
    "height_cm": 0,
    "weight_kg": 0,
    "running_fitness": 0,
    "vo2max": 0,
    "resting_heart_rate": 0,
    "threshold_hr_zones": "string",
    "threshold_pace_zones": "string",
    "id": 0
}
```

Update Physiology Log

Partially update an existing physiology log.

PATH PARAMETERS

`log_id` required	integer (Log Id)

REQUEST BODY SCHEMA: application/json
required

`pid` >	Pid (integer) or Pid (null) (Pid)
`date`	null (Date)
`height_cm` >	Height Cm (number) or Height Cm (null) (Height Cm)
`weight_kg` >	Weight Kg (number) or Weight Kg (null) (Weight Kg)
`running_fitness` >	Running Fitness (number) or Running Fitness (null) (Running Fitness)
`vo2max` >	Vo2Max (number) or Vo2Max (null) (Vo2Max)
`resting_heart_rate` >	Resting Heart Rate (integer) or Resting Heart Rate (null) (Resting Heart Rate)
`threshold_hr_zones` >	Threshold Hr Zones (string) or Threshold Hr Zones (null) (Threshold Hr Zones)
`threshold_pace_zones` >	Threshold Pace Zones (string) or Threshold Pace Zones (null) (Threshold Pace Zones)

Responses

> **200**

Successful Response

> 422

Validation Error

PUT /physiology/{log_id}

Request samples

Payload

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": null,
    "height_cm": 0,
    "weight_kg": 0,
    "running_fitness": 0,
    "vo2max": 0,
    "resting_heart_rate": 0,
    "threshold_hr_zones": "string",
    "threshold_pace_zones": "string"
}
```

Response samples

200 **422**

Content type
application/json

Copy

```
{
    "pid": 0,
    "date": "2019-08-24",
    "height_cm": 0,
    "weight_kg": 0,
```

```
    "running_fitness": 0,
    "vo2max": 0,
    "resting_heart_rate": 0,
    "threshold_hr_zones": "string",
    "threshold_pace_zones": "string",
    "id": 0
}
```

Delete Physiology Log

Delete a physiology log. Returns 204 No Content on success.

PATH PARAMETERS

log_id required	integer (Log Id)

Responses

— 204

Successful Response

> 422

Validation Error

DELETE /physiology/{log_id}

Response samples

422

Content type
application/json

Copy Expand all Collapse all


```
{
  - "detail": [
      + { … }
    ]
}
```


Analytics

Physiology trend data for line charts + race predictions

Returns physiological trend data (VO2Max, resting HR, running fitness, weight) ordered chronologically for direct consumption by front-end charting libraries.

Also returns the latest threshold zones and race-time predictions based on the most recent VO2Max value.

QUERY PARAMETERS

`pid`	integer (Pid) Default: `1` User ID
`limit`	integer (Limit) [1 .. 100] Default: `12` Number of recent snapshots

Responses

> 200

Successful Response

> 422

Validation Error

GET /analytics/physiology/trends

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
  - "trends": [
      + { … }
    ],
  - "current_status": {
        "date": "2019-08-24",
        "threshold_hr_zones": { },
        "threshold_pace_zones": { }
    },
  - "race_predictor": {
        "vo2max_used": 0,
        "predicted_5k": "string",
        "predicted_10k": "string",
        "predicted_half_marathon": "string"
    }
}
```

Personal records (PRs) — best times for standard race distances

Returns the fastest finish time for each standard race distance:

Running: 5K, 10K, Half Marathon **Cycling:** 10km, 50km, 100km

Activities are matched to target distances using tolerance bands (e.g. 5K = 4.8–5.5 km). Anomalies are filtered out:

- Run pace < 2:30/km or > 10:00/km → excluded
- Ride average speed > 70 km/h or < 8 km/h → excluded

QUERY PARAMETERS

`pid`	integer (Pid) Default: `1` User ID

Responses

200

Successful Response

422

Validation Error

`GET /analytics/performance/records`

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
  - "run_records": [
      + { … }
    ],
  - "ride_records": [
      + { … }
    ]
}
```

Daily training load calendar + intensity distribution pie chart

Aggregates Activity data over the past N days:

- Per-day summary of training load, run km, ride km (for calendar / bar chart)
- Period totals
- Intensity distribution by average heart rate (Easy / Tempo / Hard) for pie chart rendering

QUERY PARAMETERS

`pid`	integer (Pid) Default: `1` User ID
`days`	integer (Days) [1 .. 365] Default: `30` Lookback window in days

Responses

> 200

Successful Response

> 422

Validation Error

GET /analytics/training/status

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
  - "daily_summary": [
      + { … }
    ],
  - "totals": {
        "total_load": 0,
        "total_run_km": 0,
        "total_ride_km": 0,
        "total_activities": 0,
        "total_duration_min": 0
    },
  - "intensity_distribution": [
      + { … }
    ]
}
```

How temperature affects running performance

Segments running activities by temperature into Cold (< 10°C), Moderate (10–22°C), and Hot (> 22°C), then computes average heart rate and pace for each bucket.

Only includes records with both temperature and avg_heart_rate populated to avoid NULL contamination in averages.

QUERY PARAMETERS

`pid`	integer (Pid) Default: `1` User ID

Responses

> 200

Successful Response

> 422

Validation Error

GET /analytics/insights/environment

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "temperature_zones": [
      + { … }
    ]
}
```

How sleep and fatigue correlate with running performance

Joins Activity (Run) with same-day DailyMetric to analyse:

1. Sleep impact: ≥ 7.5h sleep vs < 7.5h → difference in pace and HR
2. Fatigue impact: fatigue ≥ 7 vs < 7 → difference in HR and load

Only activities with a matching DailyMetric on the same (pid, date) are included. NULL values in the compared fields are filtered out.

QUERY PARAMETERS

`pid`	integer (Pid) Default: `1` User ID

Responses

200

Successful Response

422

Validation Error

GET `/analytics/insights/lifestyle`

Response samples

200 422

Content type

application/json

Copy Expand all Collapse all

```
{
  - "sleep_impact": [
      + { … }
    ],
  - "fatigue_impact": [
      + { … }
    ]
}
```

Health

Health Check

Simple health-check endpoint to verify the API is running.

Responses

> **200**

Successful Response

GET /

Response samples

200

Content type
application/json

Copy

```
null
```