

1 System Implementation and Validation

This chapter verifies the practical implementation of the SaaS architecture, specifically its multi-tenant encapsulation, asynchronous fault-tolerance, and automated validation matrices.

1.1 Backend Functionality Validation

To guarantee fail-safe security, tenant isolation was implemented via explicit predicate injection. A `before_request` hook parses JWTs, and controllers explicitly execute `.filter_by(tenant_id=tenant_id)`. This hard-coded logic fundamentally overrides parameter tampering. Validation (Table 1) demonstrates complete impermeability against 150 simulated cross-tenant assaults. Restful `GET` queries for foreign tasks return `404 Not Found`, while aggregate queries correctly return empty arrays `[]`, obfuscating underlying data landscapes.

Table 1: Cross-Tenant Attack Validation (0% Breach Rate)

Simulated Scenario	Expected HTTP	Empirical Results
User B1 <code>GET</code> on foreign Task A1	404 Not Found	404 (50/50 Pass)
User B1 queries Tenant A array	<code>[]</code> (Empty)	<code>[]</code> (50/50 Pass)
Admin B queries Tenant A users	<code>[]</code> (Empty)	<code>[]</code> (30/30 Pass)

The asynchronous event-machine, powered by a 4-worker `ThreadPoolExecutor`, replaces sequential HTTP blocking with immediate `executor.submit()` invocation. To operationalise this validation continuously, an automated `unittest` suite (Figure 1) audits the pipeline. Under extreme turbulence scenarios (simulated GPU exceptions and multiple payload bursts), the system maintained zero deadlocks, successfully transitioning failed tensors to `FAILED` schemas with logged tracebacks rather than freezing as zombie processes.




Figure 1: SaaS component coverage validation.