

# Genomic-Benchmarks Test

## Table of contents

0.1	Libraries used . . . . .	1
0.2	Downloading data . . . . .	2
0.3	Formatting data . . . . .	2
0.4	Characterizing sequences . . . . .	2
0.5	Concatenating CSV's . . . . .	3
0.6	Primary analysis . . . . .	3

## 0.1 Libraries used

```
# For genome-functions.R
library(stringr)
library(stringi)
library(primes)
# For parallel computing
library(doParallel)
library(foreach)
# For biological functions:
#   - Local/Global alignments
#   - DNA Shape computing
library(Biostrings)
library(DNASHapeR)
# For my own functions
source("/home/davidfm/Projects/UBMI-IFC/EnhaProm/scripts/genome-functions.R")
# For plotting
library(ggplot2)
library(dplyr)
library(plyr)
```

## 0.2 Downloading data

```
# Listing available datasets
from genomic_benchmarks.data_check import list_datasets
list_datasets()
# Inspecting each dataset to select two
from genomic_benchmarks.data_check import info as info_gb
info_gb("human_nontata_promoters") # <- This one will be used
info_gb("human_ensembl_regulatory")
info_gb("human_enhancers_cohn")    # <- This one will also be used
info_gb("human_enhancers_ensembl")
# Downloading datasets
from genomic_benchmarks.loc2seq import download_dataset
import os
os.chdir("/home/davidfm/Projects/UBMI-IFC/EnhaProm/datasets/GenomicBenchmarks")
download_dataset("human_nontata_promoters", version=0)
download_dataset("human_enhancers_cohn", version=0)
```

## 0.3 Formatting data

```
cd /home/davidfm/Projects/UBMI-IFC/EnhaProm/datasets/GenomicBenchmarks/
awk 'BEGIN{counter=0}{print ">promoter_"counter"|train|positive";
    print $0; counter+=1}' human_nontata_promoters/train/positive/*.txt \
    > promoters_train_positive.fasta
awk 'BEGIN{counter=0}{print ">enhancer_"counter"|train|positive";
    print $0; counter+=1}' human_enhancers_cohn/train/positive/*.txt \
    > enhancers_train_positive.fasta
```

## 0.4 Characterizing sequences

```
# Scanning sequences
prom_fasta <- "datasets/GenomicBenchmarks/promoters_train_positive.fasta"
enha_fasta <- "datasets/GenomicBenchmarks/enhancers_train_positive.fasta"
prom_seqs <- scan(prom_fasta, character(), quote = "")[seq(2, 29484, 2)]
enha_seqs <- scan(enha_fasta, character(), quote = "")[seq(2, 20842, 2)]
# Preparing clusters for parallel computing
corescluster <- makeCluster(6)
registerDoParallel(corescluster)
```

```

# Characterizing sequences and exporting to CSV
list_seqs <- list(promoters = prom_seqs, enhancers = enha_seqs)
reg_elems <- c("promoters", "enhancers")
for (reg_elem in reg_elems) {
  foreach(i = 1:6) %dopar% {
    library(stringr)
    library(stringi)
    library(primes)
    i_start <- ((i - 1) * 273) + 1
    i_final <- i * 273
    if (i > 1) {
      write.table(sequences_characterizer(list_seqs[[reg_elem]][i_start:i_final],
                                          k_max = 6, optim = TRUE),
                  paste("datasets/GB-Testing/test", reg_elem, "-minitraining_",
                        i, ".csv", sep = ""), sep = ",",
                  row.names = FALSE, col.names = FALSE)
    } else {
      write.csv(sequences_characterizer(list_seqs[[reg_elem]][i_start:i_final],
                                       k_max = 6, optim = TRUE),
               paste("datasets/GB-Testing/", reg_elem, "-minitraining_",
                     i, ".csv", sep = ""), row.names = FALSE)
    }
  }
}

```

## 0.5 Concatenating CSV's

```

cat datasets/GB-Testing/testpromoters-minitraining_*.csv \
  > datasets/GB-Testing/test-1638-promoters-6mers.csv
cat datasets/GB-Testing/testenhancers-minitraining_*.csv \
  > datasets/GB-Testing/test-1638-enhancers-6mers.csv

```

## 0.6 Primary analysis

```

setwd("/home/davidfm/Projects/UBMI-IFC/EnhaProm")
testpromoters <- read.csv("datasets/GB-Testing/test-1638-promoters-6mers.csv",
                          check.names = F)
testenhancers <- read.csv("datasets/GB-Testing/test-1638-enhancers-6mers.csv",
                          check.names = F)

```

First we get an overview of the dimensions of our data:

```
dim(testpromoters)
```

```
[1] 1638 21830
```

```
dim(testenhancers)
```

```
[1] 1638 21830
```

It's noticeable the fact that we have way more columns than rows in this test table. Let's get a glimpse of the records corresponding to the first three promoters.

```
# knitr::kable(testpromoters[1:3,1:30])
```

	A	T	C	G	temp	shan
0.1673307	0.2231076	0.3306773	0.2788845	87.21315	1.956136	
0.2629482	0.2788845	0.2549801	0.2031873	81.00598	1.990374	
0.3625498	0.2031873	0.2470120	0.1872510	80.02590	1.948719	

k2.1_prod	k2.1_barcode	k2.1_pals	k2.1_rev	k2.2_prod	k2.2_barcode
9	1.959765	2.177403e+09	1.374020e+12	17.11198	1.531862
17	2.633165	1.138401e+17	2.971115e+17	26.44579	2.624612
38	5.347025	3.981015e+36	8.100763e+29	24.89016	1.855662

k2.2_pals	k2.2_rev	k2.3_prod	k2.3_barcode	k2.3_pals	k2.3_rev
3.845422e+15	3.525451e+11	26.44579	2.445328	4.788062e+13	1.305836e+26
2.607331e+20	6.308689e+14	24.89016	2.513656	1.320117e+14	6.435389e+19
1.156904e+25	3.573059e+12	34.22397	3.431445	6.011592e+17	7.178542e+17

k2.3_rev	k2.4_prod	k2.4_barcode	k2.4_pals	k2.4_rev	k2.5_prod	k2.5_barcode
1.305836e+26	5.5	0.8121254	2.425939e+04	4.209683e+05	24.89016	2.163271
6.435389e+19	17.6	2.0647821	6.207541e+13	2.740751e+16	32.66833	2.801290
7.178542e+17	16.5	1.9121725	2.419251e+12	2.941608e+15	40.44651	3.119615

k2.5_pals	k2.5_revc	k2.6_prod	k2.6_bar	k2.6_pals	k2.6_revc
5.956114e+12	1.907086e+14	48	3.032966	1.321014e+23	8.039297e+19
9.988736e+16	2.535748e+18	34	2.389166	2.028406e+16	2.066402e+13
3.054415e+20	3.054391e+20	24	1.636697	5.764911e+11	8.636812e+10

```
print(testenhancers[1:3,1:30])
```

	A	T	C	G	temp	shan	k2.1_prod	k2.1_bar	k2.1_pals			
1	0.240	0.236	0.234	0.290	85.0392	1.993988	36	10.432345	1.885437e+37			
2	0.204	0.286	0.210	0.300	84.4652	1.978249	20	6.153015	5.673403e+20			
3	0.250	0.280	0.258	0.212	82.8252	1.992923	31	9.936447	1.640775e+32			
	k2.1_revc	k2.2_prod	k2.2_bar	k2.2_pals	k2.2_revc	k2.3_prod						
1	8.632413e+30	24.89016	6.027803	1.579134e+29	1.707234e+31	76.22611						
2	1.061673e+53	23.33452	4.984255	4.485619e+32	1.810188e+35	73.11484						
3	5.563175e+39	46.66905	9.301359	9.951038e+37	3.612544e+25	60.66976						
	k2.3_bar	k2.3_pals	k2.3_revc	k2.4_prod	k2.4_bar	k2.4_pals						
1	13.43518	3.557032e+41	5.830130e+44	20.9	5.182017	2.534298e+18						
2	13.29662	3.273426e+39	3.755909e+39	22.0	6.098819	2.555384e+17						
3	12.53356	4.255600e+33	3.010280e+57	27.5	6.353834	3.581633e+31						
	k2.4_revc	k2.5_prod	k2.5_bar	k2.5_pals	k2.5_revc	k2.6_prod						
1	2.395938e+20	43.55778	9.672032	1.852950e+24	3.825771e+48	80						
2	2.343823e+21	48.22468	10.185028	1.559529e+27	2.552638e+46	58						
3	2.035799e+26	57.55849	10.894642	3.730036e+31	2.060459e+35	60						
	k2.6_bar	k2.6_pals	k2.6_revc									
1	14.452432	1.791119e+41	4.233849e+41									
2	7.732096	2.784552e+29	9.930851e+52									
3	9.025510	1.288568e+31	2.183286e+27									

```
meanpromoters <- colMeans(testpromoters)
meanenhancers <- colMeans(testenhancers)
sdpromoters <- apply(testpromoters, 2, sd)
sdenhancers <- apply(testenhancers, 2, sd)
# names_test <- rep(names(testpromoters),2)
cre_summary <- data.frame(Type = factor(rep(c("Promoter","Enhancer"),
                                         each = length(testpromoters))),
                          Field = rep(names(testpromoters),2),
                          Means = c(meanpromoters, meanenhancers),
                          StDevs = c(sdpromoters, sdenhancers))
# head(cre_summary)
knitr::kable(cre_summary[c(1:10,21831:21840),])
```

	Type	Field	Means	StDevs
1	Promoter	A	1.911256e-01	7.145510e-02
2	Promoter	T	1.995826e-01	7.599340e-02
3	Promoter	C	2.962655e-01	8.067840e-02
4	Promoter	G	3.130263e-01	8.524230e-02
5	Promoter	temp	8.720208e+01	5.379461e+00
6	Promoter	shan	1.891724e+00	9.437000e-02
7	Promoter	k2.1_prod	1.196276e+01	8.995306e+00
8	Promoter	k2.1_barcode	1.500971e+00	1.229003e+00
9	Promoter	k2.1_pals	2.634405e+51	1.065029e+53
10	Promoter	k2.1_revc	9.789346e+62	3.960331e+64
21831	Enhancer	A	2.653712e-01	5.853000e-02
21832	Enhancer	T	2.678205e-01	5.815610e-02
21833	Enhancer	C	2.351111e-01	5.648440e-02
21834	Enhancer	G	2.316972e-01	5.435370e-02
21835	Enhancer	temp	8.269434e+01	3.785299e+00
21836	Enhancer	shan	1.959202e+00	3.892580e-02
21837	Enhancer	k2.1_prod	4.093346e+01	1.835697e+01
21838	Enhancer	k2.1_barcode	1.208127e+01	5.751107e+00
21839	Enhancer	k2.1_pals	2.567318e+112	1.038419e+114
21840	Enhancer	k2.1_revc	3.321646e+121	1.344343e+123

```
# Get only 'prod' columns of each kmer
k2 <- n_ki(2); k3 <- n_ki(3); k4 <- n_ki(4); k5 <- n_ki(5); k6 <- n_ki(6)
kmer_sections_indexes <- c(1,
                           k2,
                           k2 + 1,
                           k2 + k3,
                           k2 + k3 + 1,
                           k2 + k3 + k4,
                           k2 + k3 + k4 + 1,
                           k2 + k3 + k4 + k5,
                           k2 + k3 + k4 + k5 + 1,
                           k2 + k3 + k4 + k5 + k6)
prod_indexes <- seq(7,21827,4)
barcode_indexes <- seq(8,21828,4)
pals_indexes <- seq(9,21829,4)
revc_indexes <- seq(10,21830,4)
all_prod_indexes <- c(prod_indexes, 21830 + prod_indexes)
all_barcode_indexes <- c(barcode_indexes, 21830 + barcode_indexes)
all_pals_indexes <- c(pals_indexes, 21830 + pals_indexes)
```

```
all_revc_indexes <- c(revc_indexes, 21830 + revc_indexes)
knitr::kable(head(testenhancers[, barc_indexes])[,c(1:8,length(barc_indexes))])
```

k2.1_bar	k2.2_bar	k2.3_bar	k2.4_bar	k2.5_bar	k2.6_bar	k2.7_bar	k2.8_bar	k6.4096_bar
10.432345	6.027803	13.435177	5.182017	9.672032	14.452432	2.0213095	13.731694	0.0000000
6.153015	4.984254	13.296620	6.098819	10.185028	7.732096	1.3635487	10.150355	0.3058662
9.936447	9.301359	12.533556	6.353834	10.894642	9.025510	1.3565393	16.335286	0.0000000
23.252879	8.744180	13.868229	9.853451	12.204317	3.958776	0.0930320	8.444184	0.0000000
3.814939	7.617881	9.290377	5.365261	10.457174	13.017956	1.4893074	14.727846	2.7938687
14.929810	6.939986	12.525913	11.864119	10.686542	2.227940	0.9421584	7.264738	0.0000000

```
knitr::kable(head(testenhancers[, barc_indexes], 5)[kmer_sections_indexes], table.attr = "qu
  kableExtra::kable_styling(full_width = FALSE) |>
  kableExtra::column_spec(column = 2:4, width = "0.4in")
```

k2.1_bar	k2.16_bar	k3.1_bar	k3.64_bar	k4.1_bar	k4.256_bar	k5.1_bar	k5.1024_bar	k6.1_bar	k6.1024_bar
10.432345	7.3372223	4.298935	3.133496	0.8724755	0.2043103	0.000000	0.0000000	0	0
6.153015	19.441056	6.9076157	4.449599	0.2736402	1.8634239	0.000000	0.6130383	0	0
9.936447	12.059759	6.6860719	1.791785	1.4367855	2.0880247	0.000000	0.8123330	0	0
23.252879	12.044970	1.4527954	0.433695	5.8892630	2.0034714	2.332278	0.4316400	0	0
3.814939	11.720066	6.8633094	4.455931	0.0810805	3.7301540	0.000000	3.2607779	0	0

```
knitr::kable(cre_summary[c(prod_indexes[1:5],(21830+prod_indexes)[1:5]),])
```

	Type	Field	Means	StDevs
7	Promoter	k2.1_prod	11.962760	8.995306
11	Promoter	k2.2_prod	15.840314	6.536126
15	Promoter	k2.3_prod	27.649084	9.205828
19	Promoter	k2.4_prod	8.638156	6.974283
23	Promoter	k2.5_prod	22.012519	7.995609
21837	Enhancer	k2.1_prod	40.933455	18.356973
21841	Enhancer	k2.2_prod	39.367630	9.765868
21845	Enhancer	k2.3_prod	58.095082	13.575118
21849	Enhancer	k2.4_prod	31.738828	12.985948
21853	Enhancer	k2.5_prod	57.394191	11.806409

```
subset_cre_prod <- cre_summary[c(prod_indexes[17:64],(21830+prod_indexes)[17:64]),]
subset_cre_barcode <- cre_summary[c(barcode_indexes[17:64],(21830+barcode_indexes)[17:64]),]
subset_cre_pals <- cre_summary[c(pals_indexes[17:64],(21830+pals_indexes)[17:64]),]
subset_cre_revcomp <- cre_summary[c(revc_indexes[17:64],(21830+revc_indexes)[17:64]),]
knitr::kable(cbind(subset_cre_prod[subset_cre_prod$Type=="Promoter",],
  subset_cre_prod[subset_cre_prod$Type=="Enhancer",])[,c(2,1,3,4,5,7,8)][1:10,])
```

	Field	Type	Means	StDevs	Type.1	Means.1	StDevs.1
71	k3.1_prod	Promoter	3.733822	4.441567	Enhancer	15.169109	10.176757
75	k3.2_prod	Promoter	3.208713	2.679694	Enhancer	9.520357	4.701251
79	k3.3_prod	Promoter	5.069128	3.448887	Enhancer	13.390625	5.694958
83	k3.4_prod	Promoter	2.363513	2.747660	Enhancer	9.863853	5.715001
87	k3.5_prod	Promoter	3.646951	3.485361	Enhancer	12.881026	5.906393
91	k3.6_prod	Promoter	5.124804	3.324229	Enhancer	11.042922	5.162449
95	k3.7_prod	Promoter	3.650813	3.084850	Enhancer	3.254059	3.143177
99	k3.8_prod	Promoter	3.756481	2.794403	Enhancer	11.358009	4.689413
103	k3.9_prod	Promoter	5.426771	4.453803	Enhancer	14.490419	6.240096
107	k3.10_prod	Promoter	9.318083	4.745578	Enhancer	15.674036	6.345508

```
field_order <- subset_cre_prod$Field[1:48]
subset_cre_prod$Means
```

```
[1] 3.733822 3.208713 5.069128 2.363513 3.646951 5.124804 3.650813
[8] 3.756481 5.426771 9.318083 10.158642 4.176949 1.544579 2.586327
[15] 3.239394 2.656703 3.611691 6.037643 10.872411 3.075680 7.635905
[22] 16.233211 13.569377 9.680538 3.858207 15.529754 14.896730 3.878496
[29] 2.538018 10.020076 10.994143 5.127896 5.050658 5.404646 10.835603
[36] 2.981746 7.776152 17.063672 16.874431 9.484900 9.996806 18.264419
[43] 18.109890 5.977352 2.278580 5.645854 7.411662 3.606654 15.169109
[50] 9.520357 13.390625 9.863853 12.881026 11.042922 3.254059 11.358009
[57] 14.490419 15.674036 18.408043 11.153142 7.060554 8.359265 11.077995
[64] 9.899835 11.545321 14.397051 23.188692 11.087836 18.015617 19.891331
[71] 5.727871 19.145295 2.791931 4.866958 5.859807 3.292382 7.877964
[78] 17.602037 23.114300 13.710489 13.085873 10.235576 16.551690 8.261753
[85] 14.303432 18.128486 5.008222 15.694325 15.411434 18.289740 19.267399
[92] 10.688575 6.708704 9.933502 14.408686 9.522875
```


```
subset_cre_prod$StDevs
```



[1]	4.441567	2.679694	3.448887	2.747660	3.485361	3.324229	3.084850
[8]	2.794403	4.453803	4.745578	5.654427	2.825089	2.320564	2.326571
[15]	2.940212	2.932436	2.961735	4.319168	5.122931	2.710304	4.148137
[22]	13.073051	11.370095	5.614338	3.258066	13.292805	12.485377	3.391027
[29]	2.205837	6.267927	4.903813	3.502554	3.538477	3.306454	7.179443
[36]	2.542758	4.163639	10.888245	14.776918	4.521492	5.794870	12.101920
[43]	13.708462	3.609159	2.133656	3.406684	5.143815	2.739559	10.176757
[50]	4.701251	5.694958	5.715001	5.906393	5.162449	3.143177	4.689413
[57]	6.240096	6.345507	8.713120	4.492683	5.473509	3.767892	4.972782
[64]	5.789404	5.183821	7.055220	8.610000	4.881815	7.569853	15.722251
[71]	8.408784	8.852986	3.128115	8.279593	8.690941	3.054289	4.096377
[78]	9.084188	8.638399	5.479771	5.904495	4.697275	8.449506	3.947652
[85]	5.899648	11.718258	8.439162	6.478037	7.443246	11.906084	14.723036
[92]	5.092138	4.127505	4.906655	9.083055	4.695775		

```
ggplot(subset_cre_prod) +
  geom_bar(aes(x = factor(Field, levels = field_order),
               y = ifelse(Type == "Enhancer", -Means, Means),
               fill = paste(Type, "Means")),
           stat = "identity", position = "identity",
           alpha = 0.6, width = 0.7) +
  geom_bar(aes(x = factor(Field, levels = field_order),
               y = ifelse(Type == "Enhancer", -StDevs, StDevs),
               fill = paste(Type, "SDs")),
           stat = "identity", position = "identity",
           alpha = 0.6) +
  coord_flip() +
  scale_y_continuous(breaks=seq(-30, 30, 10), labels=abs(seq(-30, 30, 10))) +
  scale_fill_manual(values = c("Enhancer Means" = "skyblue",
                              "Promoter Means" = "salmon",
                              "Enhancer SDs" = "turquoise",
                              "Promoter SDs" = "coral")) +
  labs(y = "Means/SDs", x = "Kmers",
       title = "KSG-Product Means and Standard-Deviations per Kmer",
       fill = "Type Means/SDs") +
  theme_minimal()
```

## KSG-Product Means and Standard-Deviations per Kmer



```
ggplot(subset_cre_prod) +
  geom_bar(aes(x = factor(Field, levels = field_order),
    y = ifelse(Type == "Enhancer", -Means, Means),
    fill = paste(Type, "Means")),
    stat = "identity", position = "identity",
    alpha = 0.6, width = 0.7) +
  geom_errorbar(aes(x = factor(Field, levels = field_order),
    ymin = ifelse(Type == "Enhancer",
      -Means + StDevs, Means - StDevs),
    ymax = ifelse(Type == "Enhancer",
      -Means - StDevs, Means + StDevs)),
    width = 0.5, colour = "black", alpha = 0.6) +
  coord_flip() +
  scale_y_continuous(breaks=seq(-30, 30, 10), labels=abs(seq(-30, 30, 10))) +
  scale_fill_manual(values = c("turquoise", "coral")) +
  labs(y = "Means", x = "Kmers",
    title = "KSG-Product Means per Kmer",
    fill = "CRE Type") +
  theme_minimal()
```

Kmers

CRE Type

Enhancer Means

Promoter Means