

TUSCAN 2K MONITOR
ADDR CODE

SMT SOURCE STATEMENT

TCL Z80 ASSEMBLER PAGE 0026

```

FE93 EDB1      1452      CPIR
FE95 2041      1453      JR      NZ,FPARER      ;NOT FOUND
FE97 216900    1454      LD      HL,AFSAV      ;PTR TO REGISTERS
FE9A 09        1455      ADD     HL,BC      ;ADD OFFSET
FE9B 09        1456      ADD     HL,BC      ; (WORDS)
FE9C E5        1457      PUSH    HL
FE9D 7E        1458      LD      A,(HL)      ;GET OLD DATA
FE9E 23        1459      INC     HL
FE9F 66        1460      LD      H,(HL)
FEA0 6F        1461      LD      L,A      ;INTO HL
FEA1 CD8CFC    1462      CALL    PRTHLSP      ;DISPLAY IT
FEA4 CDF1FB    1463      CALL    READPAR      ;GET NEW VALUE
FEA7 EB        1464      EX      DE,HL      ;INTO DE
FEA8 E1        1465      POP     HL      ;HL=TABLE PTR
FEA9 D8        1466      RET      C      ;NO PAR, SO NO CHANGE
FEAA 73        1467      LD      (HL),E      ;SAVE NEW VALUE
FEAB 23        1468      INC     HL
FEAC 72        1469      LD      (HL),D
FEAD C9        1470      RET
FEAE 116A00    1471      ;
FEAE 1803      1472      ACCMFY: LD      DE,AFSAV+1      ;GET OLD ACC
FEAE 1803      1473      JR      MFY8
FEAE 1803      1474      ;
FEB3 116800    1475      INTMFY: LD      DE,ISAV+1      ;GET OLD I
FEB6 1A        1476      MFY8:  LD      A,(DE)
FEB7 D5        1477      PUSH    DE      ;SAVE PTR
FEB8 CDEEFB    1478      CALL    MODPAR      ;PRINT OLD VALUE & GET NEW
FEBB D1        1479      POP     DE
FEBD D8        1480      RET      C      ;NO CHANGE
FEBD 7D        1481      LD      A,L      ;8 BIT VALUE
FEBE 12        1482      LD      (DE),A      ;INTO PSEUDO REGISTER
FEBF C9        1483      RET
FEBF C9        1484      ;
FEC0 CD64FE    1485      FLGMFY: CALL    FLAGDIS      ;DISPLAY CURRENT FLAGS
FEC3 CDDCF9    1486      CALL    GETIBUF      ;GET NEW ONES
FEC6 0E00      1487      LD      C,0      ;START WITH NONE SET
FEC8 CDA6FB    1488      FLG1:  CALL    GETUCT      ;GET FLAG TO SET
FECB D8        1489      RET      C      ;TERMINATOR FOUND
FECC 2192FF    1490      LD      HL,FLGTAB+1      ;SEARCH FOR LETTER
FECE 0606      1491      LD      B,6      ;SIX POSSIBILITIES
FED1 BE        1492      FLG2:  CP      (HL)      ;MATCH?
FED2 2807      1493      JR      Z,FSET      ;YES,SET THIS FLAG
FED4 23        1494      INC     HL
FED5 23        1495      INC     HL
FED6 10F9      1496      DJNZ    FLG2      ;CONTINUE SEARCH
FED8 C3DEFB    1497      FPARER: JP      PARER      ;ERROR IF NOT FOUND
FED8 C3DEFB    1498      ;
FEDB 79        1499      FSET:  LD      A,C      ;GET FLAGS SO FAR
FEDC 2B        1500      DEC     HL      ;PTR TO MASK
FEDD B6        1501      OR      (HL)      ;ADD IT IN
FEDE 23        1502      INC     HL
FEDE 326900    1503      LD      (AFSAV),A      ;SAVE FLAGS
FEE2 4F        1504      LD      C,A
FEE3 18E3      1505      JR      FLG1      ;GET ANY MORE FLAGS
FEE3 18E3      1506      ;
FEE3 18E3      1507      ;SET      FUNCTION TO SET BYTES OF MEMORY
FEE3 18E3      1508      ;      THE COMMAND FORMAT IS :
FEE3 18E3      1509      ;      SNNN WHERE NNN IS THE ADDRESS TO SET

```