

Interrupt Service Routines. Configuring a timer interrupt.

1 Introduction

This lab is concerned with development of interrupt service routines for the LPC_2378_STK development board. It's concerned particularly with how to configure one of the on-chip timers to generate an interrupt and how to write a handler to service that interrupt. Interrupt handling is the foundation of developing software for both time-triggered and event-triggered systems.

2 In the lab

1. Clone the repository https://github.com/DavidKendall/cm0605_lab01.git.
2. Change directory into `cm0605_lab01`, start up EWARM and load the workspace `workspace.eww`.
3. Connect a LPC-2378-STK board to a USB port on your computer.
4. Download and debug the project `lab01`. Run it and observe its behaviour. Try pressing button 1 a few times.
5. The code is organised in two groups: `app` and `bsp`, each of which contain `include` and `src` groups. The `include` group contains the header files for its containing group. The `src` group contains the C source files for the its containing group.
6. Find the definition of `IRQ_Handler` (what's the easy way to do this in the IDE?). Notice that this definition replaces the default definition in `$TOOLKIT_DIR$arm\src\lib\arm\vectortrap.s` which is linked with `$TOOLKIT_DIR$arm\src\lib\arm\cstartup.s` and defines the initial behaviour of the board after reset. Read p.46 in [The Insider's Guide](#) to help your understanding of what's going on here.
7. Find the definition of `vicInit` and study how the Vectored Interrupt Controller (VIC) is initialised. Read p.82 in [The Insider's Guide](#) for more information about the VIC.

8. Read section 4.3 in [The Insider's Guide](#) for information about the timers. We are going to use `TIMER0` in match mode, i.e. whenever the value of the timer counter is equal to the value in the match register, an interrupt will be raised and the value of the timer counter will be reset.
9. Find the definition of `initTimer0` and study the code carefully. Make sure that you can explain how the code works, based on your reading in the previous task.
10. Based on your reading of the code so far, explain how it is that `timer0ISR` is called whenever `TIMER0` raises an interrupt.
11. In `main.c` comment out the statement `__enable_interrupt()`. Rebuild, download and debug the project. Explain the behaviour that you observe.
12. In `main.c` uncomment the statement `__enable_interrupt()` and comment out the statement `clearInterruptTimer0()`. Rebuild, download and debug the project. Explain the behaviour that you observe.
13. In order to test your understanding of what you've looked at so far. Develop new functions `initTimer1()` and `timer1ISR`, and use them to flash the USB CONNECT LED at the same time as the program is carrying on with its current behaviour. You should configure the timer so that the CONNECT LED flashes at a rate of 1Hz.