

# Computer Networks, Security, and Operating Systems

David Kendall

Northumbria University

# Introduction – Getting started with Linux

- How the operating system starts running
- Terminal, console, shell
- The command line - why bother?
- The file system - managing files
- I/O redirection
- Advanced use of the terminal - tmux


# How the operating system starts running

- Turning on the computer (or pressing the reset button) forces the CPU to begin executing instructions from a fixed location in the computer memory
- The contents of memory starting at this location need to be *non-volatile*, i.e. to survive a power down/power on – usually use *ROM* (Read Only Memory).
- The ROM that stores the program used to start the operating system is called the *boot* ROM. On most PCs, the boot program is called the *BIOS* (Basic Input/Output System)
- Don't store the complete OS in the boot ROM
  - ▶ ROM is slow and expensive compared to RAM
  - ▶ ROM is hard to update
  - ▶ OS needs frequent updates


# How the operating system starts running

- So load the operating system in stages:
  - ▶ The boot ROM contains a small program that is able to read a fixed-size block of bytes from a fixed position on the disk (*the bootloader*)
    - ★ Note the boot program doesn't need to know about the file system – it just has to be able to read a block of raw bytes from a known location
    - ★ The bootloader may have a *digital signature* to ensure that it hasn't been tampered with
  - ▶ Once the BIOS has loaded the bootloader into memory, it jumps to its first instruction and starts executing code from there
  - ▶ The job of the bootloader is to load the OS kernel into memory
    - ★ The OS kernel is usually stored in the file system on disk, so the bootloader needs to know how to find a file in the file system and read it.
  - ▶ Once the kernel has been loaded, it can initialise its data structures and then start the first process (called *init* in Linux), which can start a login process so that the user can login and start work.

# How the operating system starts running



# Terminal, Console, Shell



- DEC VT220 terminal, popular in the 1980s
- A physical terminal used to communicate with a mini or mainframe computer over a serial communication link
- A console was the keyboard/monitor directly connected to the console port of the computer
- Gnome terminal – a *virtual terminal* that *emulates* the behaviour of a physical terminal – also KDE and xterm
- The *shell* is a program that receives command input from the terminal and makes calls to the computer operating system to execute the commands. Shells include bash, zsh, csh.

# Command line – why bother?


## Command line advantages

- Available everywhere – many servers and small embedded systems don't have a GUI
- Uses less resources
- More efficient once you've learnt the commands – faster than clicking and scrolling, then clicking and scrolling, then clicking and scrolling some more just to do something simple
- Can easily compose commands to do complex tasks
- Can automate commands, go away and leave them running

## GUI's are also good

- Browse the web using GUI
- Read email using GUI (although there are good terminal mail readers)
- Read pdf documents
- View and edit photos
- Use graphical design tools, stream video, ...

# File system tree




[http://etutorials.org/shared/images/tutorials/tutorial\\_95/rh4\\_0401.gif](http://etutorials.org/shared/images/tutorials/tutorial_95/rh4_0401.gif)

- When we first login, we are positioned in the file system directory tree at our *home directory*, e.g. `/home/bill`
- Wherever we are in the tree is called the *current working directory*
- Every directory has a *parent directory* (except the top-level directory, `/`, called the *root directory*). The parent of a directory is the one directly above it in the tree, e.g. `/home` is the parent of `/home/bill`
- The parent of the current working directory can be referred to using the symbol, `..` (the current working directory is referred to using `.`)



# File system tree



[http://etutorials.org/shared/images/tutorials/tutorial\\_95/rh4\\_0401.gif](http://etutorials.org/shared/images/tutorials/tutorial_95/rh4_0401.gif)

**pwd** where am I? (**p**rint **w**orking **d**irectory)

**cd** go somewhere else (**c**hange **d**irectory)

**ls** what's in here? (**l**ist contents of directory)

- A *path name* is a description of the location of a directory in the file system tree
- We can use *relative* path names, which start at the current working directory, e.g. `ls books`
- or *absolute* path names, which start at the root of the file system, e.g. `ls /home/bill/books`

# Useful commands for working with files

**ls** lists contents of directory  
**less** display contents of text file  
**file** indicate file type  
**cp** copy files and directories  
**mv** move/rename files and directories  
**rm** remove files and directories

- Command format: `command -option arguments`

- e.g. `ls -l /home/bill`

**man** look up the manual entry for a command

- e.g. `man ls`

# Wildcards

Using *wildcard* characters can make the use of the file commands even more powerful

Wildcard	Matches
*	Any characters
?	Any single character
[ <i>characters</i> ]	Any character that is in the set <i>characters</i>
[ ! <i>characters</i> ]	Any character that is <i>not</i> in the set <i>characters</i>

Pattern	Matches
*	All files
s*	All files beginning with s
f*.txt	All files beginning with f followed by any characters and ending in .txt
Log??	All files beginning with Log followed by exactly two characters
[xyz]*	All files beginning with x, y, or z

# I/O Redirection – Output

- Most the commands that we've used generate some *output*
- Sometimes the output is the data that we were after, sometimes it's an error message or status information
- All output is sent to a file: good data is usually sent to the *standard output* file, error messages etc. are sent to the *standard error* file
- Usually the standard output file and the standard error file are both mapped to our display, so we see the output appearing on the screen

- We can choose to *redirect* the standard output to a different file, e.g.

```
ls -l /home/bill/books > ls_output.txt
```

- We can also redirect standard error, e.g.

```
ls -l /bill/home/books 2> ls_errors.txt
```

- We can redirect standard output and standard error to the *same* file, e.g.

```
ls -l /home/bill/books > ls_output.txt 2>&1
```

# I/O Redirection – Input

- Just as the standard output and standard error files are usually mapped to the display, the *standard input* file is usually mapped to the keyboard
- `cat` is a program that normally reads data from the standard input (keyboard) and sends the data to the standard output (display), e.g.

```
$ cat
```

```
Much have I travelled in the realms of gold  
Much have I travelled in the realms of gold
```

- We can redirect the output as usual, e.g.

```
$ cat > gold.txt
```

```
Much have I travelled in the realms of gold
```


- We can also redirect the *input*, e.g.

```
$ cat < gold.txt > keats.txt
```

# Next steps ...

- We've just scratched the surface of the capabilities of the command line
- You can find out more by reading chapters 1 to 6 and 9 in the [The Linux Command Line](#)
- We'll also be covering additional commands in the lab session this week and in later sessions of the module as appropriate
- The key steps to making progress are to read more and to play around with a Linux system as much as possible

# Advanced use of the terminal: tmux [Optional]



The screenshot shows a terminal window with a dark background. The left pane displays a script for managing a tmux session named 'my\_session'. The script includes commands for creating the session, attaching to it, and detaching. The right pane shows system information, including the kernel version (4.15.0-101-generic) and the tmux version (2.9.1).

```
#!/bin/bash
# tmux session management script
# Create a new tmux session named 'my_session'
tmux new-session -s my_session -c /bin/bash

# Attach to the session
tmux attach-session -t my_session

# Detach from the session
tmux detach-session -t my_session

# List all tmux sessions
tmux ls

# Kill the session
tmux kill-session -t my_session
```

- **tmux** – terminal **m**ultiplexer
- create sessions, attach and detach from a session, leaving it running exactly as it was
- create multiple windows
- create multiple panes within a window
- Makes it more convenient to use a terminal to manage a remote server
- There's a [nice tmux blog post](#) and a [tmux home page](#).