EN.601.414/614 Computer Networks

Lab

Xin Jin

Spring 2019 (MW 3:00-4:15pm in Shaffer 301)



 The Internet is a network of networks. The Internet ties together different networks with the TCP protocol.

 The Internet is a network of networks. The Internet ties together different networks with the TCP protocol.

False. With the IP protocol.

• End-systems and networks are connected by switches, instead of directly connecting them.

- End-systems and networks are connected by switches, instead of directly connecting them.
 - True. This is for scalability. Directly connecting N nodes to each other would require N² links.

• End-systems, switches and routers implement all five layers.

- End-systems, switches and routers implement all five layers.
 - False. Switches only implement physical and datalink layers, and routers only implement physical, datalink and network layers.

• HTTP is a stateless protocol. As a result, there is no way to keep state.

- HTTP is a stateless protocol. As a result, there is no way to keep state.
 - False. We can use cookies.

 CDNs are useful for web pages that contain only static content.

- CDNs are only useful for web pages that contain static content.
 - False. They can still serve the static parts of a web page that also includes dynamic content. Moreover, some CDNs can perform some dynamic processing on behalf of the content provider.

- Two end-points (A and B) communicate by a path of 5 routers. The packet size is 1500 bytes. The distance between A and B is 6000 km. The bit propagation speed is $2x10^8$ m/s. Assume 1 Mb/s = 10^6 bit/s and 1 Gb/s = 10^9 bit/s.
- (1) What are the four components to evaluate network delay?
- (2) Assume there is no queueing delay and processing delay. Assume all links run at 10Mb/s. What is the end-to-end delay (one way, not round trip) for sending a packet?
- (3) Assume there is no queueing delay and processing delay. Assume all links run at 10Gb/s. What is the end-to-end delay (one way, not round trip) for sending a packet?
- (4) Assume there is no processing delay. Assume all links run at 10Mb/s. Assume the buffer size in each router is 10 packets. What is the maximum end-to-end delay (one way, not round trip) for sending a packet?

- Two end-points (A and B) communicate by a path of 5 routers. The packet size is 1500 bytes. The distance between A and B is 6000 km. The bit propagation speed is $2x10^8$ m/s. Assume 1 Mb/s = 10^6 bit/s and 1 Gb/s = 10^9 bit/s.
- (1) What are the four components to evaluate network delay?
- Transmission delay, propagation delay, queuing delay, and processing delay.

- Two end-points (A and B) communicate by a path of 5 routers. The packet size is 1500 bytes. The distance between A and B is 6000 km. The bit propagation speed is $2x10^8$ m/s. Assume 1 Mb/s = 10^6 bit/s and 1 Gb/s = 10^9 bit/s.
- (2) Assume there is no queueing delay and processing delay. Assume all links run at 10Mb/s. What is the end-to-end delay (one way, not round trip) for sending a packet?
- Transmission delay = $1500x8 / (10x10^6) = 1.2 \text{ ms}$
- Propagation delay = $6000000/(2x10^8) = 30 \text{ ms}$
- Delay = propagation delay + transmission delay x 6 hops = 37.2 ms

- Two end-points (A and B) communicate by a path of 5 routers. The packet size is 1500 bytes. The distance between A and B is 6000 km.
 The bit propagation speed is 2x10⁸ m/s. Assume 1 Mb/s = 10⁶ bit/s and 1 Gb/s = 10⁹ bit/s.
- (3) Assume there is no queueing delay and processing delay. Assume all links run at 10Gb/s. What is the end-to-end delay (one way, not round trip) for sending a packet?
- Transmission delay = $1500x8 / (10x10^9) = 0.0012 \text{ ms}$
- Propagation delay = $6000000/(2x10^8) = 30 \text{ ms}$
- Delay = propagation delay + transmission delay x 6 hops = 30.0072 ms

- Two end-points (A and B) communicate by a path of 5 routers. The packet size is 1500 bytes. The distance between A and B is 6000 km. The bit propagation speed is $2x10^8$ m/s. Assume 1 Mb/s = 10^6 bit/s and 1 Gb/s = 10^9 bit/s.
- (4) Assume there is no processing delay. Assume all links run at 10Mb/s. Assume the buffer size in each router is 10 packets. What is the maximum end-to-end delay (one way, not round trip) for sending a packet?
- Transmission delay = $1500x8 / (10x10^6) = 1.2 \text{ ms}$
- Propagation delay = $6000000/(2x10^8) = 30 \text{ ms}$
- Queueing delay = 9 * 1.2 = 10.8ms
- Delay = propagation delay + transmission delay x 6 hops + queueing delay x 5 routers = 91.2ms

A user would like to download 100 objects from the server using HTTP.
There are a few different methods: one-at-a-time, concurrent (assume using 10 concurrent connections), persistent, and pipelined. Assume the RTT is 100 ms, and assume the objects are small objects. What are the latencies to download the objects with each method?

A user would like to download 100 objects from the server using HTTP.
There are a few different methods: one-at-a-time, concurrent (assume
using 10 concurrent connections), persistent, and pipelined. Assume
the RTT is 100 ms, and assume the objects are small objects. What are
the latencies to download the objects with each method?

One-at-a-time: 20 s

Concurrent: 2 s

Persistent: 10.1 s

Pipelined: 200ms

 Now assume the objects are large. All objects have the same size of 100 MB (i.e., 10⁸ bytes). Assume the bandwidth for each TCP connection is 10 Mb/s (i.e., 10⁷ bit/s). What are the latencies to download the objects with each method?

 Now assume the objects are large. All objects have the same size of 100 MB (i.e., 10⁸ bytes). Assume the bandwidth for each TCP connection is 10 Mb/s (i.e., 10⁷ bit/s). What are the latencies to download the objects with each method?

• Transmission time: $\frac{100MB}{10Mb/s} = 80s$

One-at-a-time: 8000 s

Concurrent: 800 s

Persistent: 8000 s

Pipelined: 8000 s

Assignment Tips

- Do I get a full score?
 - ➤ Pass all test cases in test_client_server.sh
- What to submit?
 - ≥4 files.
 - > server-c.c, client-c.c
 - > server-python.py, client-python.py

Assignment Tips

- Search error messages on Google
- Restart the VM
- Don't forget to compile C program

Assignment Tips

How to read stdin?

- n = fread(buffer, sizeof(char), SEND_BUFFER_SIZE, stdin)
- buffer = sys.stdin.read(SEND_BUFFER_SIZE)

Why does my program fail on BINARY message?

There might be characters like EOL(\n) or NULL(\0)

Thanks! Q&A