

- Mark your completed exercises in the OLAT course of the PS.
- You can start from `template_05.hs` provided on the proseminar page.
- Upload your modified `.hs` file in OLAT.
- Your `.hs` file must be compilable with `ghci`.
- Try to define auxiliary functions within a `where` or `let ... in` construct.

**Exercise 1** *Recursion on Lists***6 p.**

1. Define a type synonym `Age` for a tuple containing the name and `Integer` age of a person. What is the difference between the keywords `type` and `data` in Haskell? (0.5 points)

**Examples:**

```
exampleAges :: [Age]
exampleAges = [("Alice",17), ("Bob",35), ("Clara",17)]
```

2. A ticket costs €5 for a child aged 0–12, €7.50 for a teenager aged 13–17, and €15 for an adult aged  $\geq 18$ . In this task, you will implement two equivalent functions `ticketCostA`, `ticketCostB :: Age -> String` which return a string "[name] pays [cost] euros for a ticket" using different Haskell constructs. To avoid copy-pasting strings, define a *local* auxiliary function `formatCost :: String -> String` which takes a cost and returns the output string for each variant. (1.5 points)
  - (i) Implement `ticketCostA` using if-then-else expressions to differentiate between ages. Define the auxiliary function `formatCost` using a `let`-expression. You may not use guarded equations.
  - (ii) Implement `ticketCostB` using guarded equations. Define the auxiliary function `formatCost` using a `where`-construct. You may not use any if-then-else expression.

**Examples:**

```
ticketCostA ("Alice",17) == "Alice pays 7.50 euros for a ticket"
ticketCostB ("Bob",-1)   -- Causes a sensible error
```

3. Write a function `ageLookup :: [Age] -> Integer -> Maybe [String]` which takes a list of ages and a specific age. If there is at least one person with this age, then a list of the names of people with this age should be returned, otherwise `Nothing` should be returned. (1.5 points)  
*Hint: you might need a recursive call of `ageLookup`. Try using a `case ... of ...` to differentiate between the `Just` and `Nothing` cases rather than writing a separate auxiliary function.*

**Examples:**

```
ageLookup exampleAges 17 == Just ["Alice", "Clara"]
ageLookup exampleAges 10 == Nothing
```

4. Implement a Haskell function `bidirectionalLookup :: [(a, b)] -> Either a b -> Maybe (Either a b)` that takes a list of pairs of type `[(a,b)]` and a key `k :: Either a b`. For keys of shape `Left l`, perform a lookup on the left half of the pairs, and for keys `Right r` on the right half of the pairs. In both cases, return the other half of the first matching pair. If no match is found, the function should return `Nothing`. (2.5 points)

### Examples:

```
bidirectionalLookup (Left "Bob") exampleAges == Just (Right 35)
bidirectionalLookup (Right 17) exampleAges == Just (Left "Alice")
bidirectionalLookup (Right 10) exampleAges == Nothing
```

## Solution 1

```
type Age = (String, Integer)

exampleAges :: [Age]
exampleAges = [("Alice", 17), ("Bob", 35), ("Clara", 17)]

ticketCostA :: Age -> String
ticketCostA (n, a) =
  let formatCost c = n ++ " pays " ++ c ++ " euros for a ticket"
  in if a < 0
      then error "Age must be non-negative"
      else
        if a <= 12
          then formatCost "5"
          else if a <= 17 then formatCost "7.50" else formatCost "15"

ticketCostB :: Age -> String
ticketCostB (n, a)
  | a < 0 = error "Age must be non-negative"
  | a <= 12 = formatCost "5"
  | a <= 17 = formatCost "7.50"
  | otherwise = formatCost "15"
  where
    formatCost c = n ++ " pays " ++ c ++ " euros for a ticket"

ageLookup :: [Age] -> Integer -> Maybe [String]
ageLookup ((n, a) : rest) x =
  if a == x
    then case ageLookup rest x of
         Just ns -> Just (n : ns)
         Nothing -> Just [n]
    else ageLookup rest x
ageLookup _ _ = Nothing

bidirectionalLookup :: (Eq b, Eq a) => Either a b -> [(a, b)] -> Maybe (Either a b)
bidirectionalLookup key ((l, r) : rest) = case key of
  Left lVal -> if lVal == l then Just (Right r) else bidirectionalLookup key rest
  Right rVal -> if rVal == r then Just (Left l) else bidirectionalLookup key rest
bidirectionalLookup _ _ = Nothing
```


## Exercise 2 *Combined Recursion*

4 p.

Consider the following data type for binary trees:

```
data Tree a = Node a (Tree a) (Tree a) | X deriving Show
```

The data type is similar to the one from [Sheet 04](#) but with a constructor `X` instead of `Leaf` to represent an empty tree. For example, `exampleTree` from [template\\_05.hs](#) represents the following tree



where the different *levels* of the tree are indicated by dotted gray lines.

1. Implement a function `takeLevels :: Int -> Tree a -> Tree a` such that `takeLevels n t` results in a tree consisting of the upper `n` levels of the tree `t`. (1 point)

**Examples:**

```
takeLevels 2 exampleTree == Node 1 (Node 2 X X) (Node 3 X X)
takeLevels 0 exampleTree == X
```

2. Implement a function `dropLevels :: Int -> Tree a -> [Tree a]` such that `dropLevels n t` results in a list of trees consisting of the subtrees that remain after removing the `Nodes` of the upper `n` levels of the tree `t`. Since only `Nodes` are removed, `Xs` “hanging on” removed `Nodes` should “fall down,” which is achieved by fixing the equation `dropLevels _ X = [X]`. (1 point)

**Examples:**

```
dropLevels 2 exampleTree == [X, X, X, Node 4 X X]
dropLevels 0 exampleTree == [exampleTree]
```

3. Without using `takeLevels` and `dropLevels` from above, implement a function

```
splitAtLevel :: Int -> Tree a -> (Tree a, [Tree a])
```

that combines the functionality of `takeLevels` and `dropLevels` into a single recursive function. (1 point)

*Hint:* look at the similarities in the recursive structure of `takeLevels` and `dropLevels` and combine what you find using pattern matching on tuples.

**Example:**

```
splitAtLevel 2 exampleTree == (Node 1 (Node 2 X X) (Node 3 X X), [X,X,X,Node 4 X X])
```

4. Implement a function `fillXs :: Tree a -> [Tree a] -> (Tree a, [Tree a])` such that `fillXs t ts` uses the trees from the list `ts` to fill-in the `Xs` in the tree `t` and returns this result together with the remaining trees of `ts` that did not replace any `Xs`. (1 point)

*Hint:* Whenever `splitAtLevel i t == (s, ss)`, then the implementation should satisfy the equation `fillXs s ss == (t, [])`.

**Example:**

```
fillXs (Node 1 X X) [Node 2 X X, Node 3 X X, Node 4 X X] ==
  Node 1 (Node 2 X X) (Node 3 X X), [Node 4 X X]
```

## Solution 2

1. 

```
takeLevels :: Int -> Tree a -> Tree a
takeLevels _ X = X
takeLevels i (Node x l r)
  | i <= 0 = X
  | otherwise = Node x (takeLevels (i-1) l) (takeLevels (i-1) r)
```
2. 

```
dropLevels :: Int -> Tree a -> [Tree a]
dropLevels _ X = [X]
dropLevels i t@(Node _ l r)
  | i <= 0 = [t]
  | otherwise = dropLevels (i-1) l ++ dropLevels (i-1) r
```

```

3. splitAtLevel :: Int -> Tree a -> (Tree a, [Tree a])
   splitAtLevel _ X = (X, [X])
   splitAtLevel i t@(Node x l r)
     | i <= 0 = (X, [t])
     | otherwise = (Node x t1 t2, ts1 ++ ts2)
       where
         (t1, ts1) = splitAtLevel (i-1) l
         (t2, ts2) = splitAtLevel (i-1) r

4. fillXs :: Tree a -> [Tree a] -> (Tree a, [Tree a])
   fillXs t [] = (t, [])
   fillXs X (t:ts) = (t, ts)
   fillXs (Node x l r) ts = (Node x t1 t2, ts2)
     where
       (t1, ts1) = fillXs l ts
       (t2, ts2) = fillXs r ts1

```