

LSEG Quantitative Analytics

Database Schema for Compustat Global Data

Version 1.1.4



LSEG DATA &
ANALYTICS

Contents

1 Introduction.....	4
In This Document.....	4
Intended Readership.....	4
Table Name Conventions.....	4
Mapping Information	4
Pervasive and Oracle.....	5
Zero Values and Nulls.....	5
Accessing Standard & Poor's Compustat Documentation	5
Obsolete Tables.....	5
Service and Support	5
Feedback	6
Your Personal Information	6
2 Compustat Global Data Tables	7
CsgCad: Compustat Global Annual Period Description	7
CSGCAF1: Compustat Global Company Annual Fundamentals 1	9
CSGCAF2: Compustat Global Company Annual Fundamentals 2	10
CSGCAFNT: Compustat Global Company Annual Fundamentals Footnotes.....	11
CsgCau: Compustat Global Company Auditor Record	12
CsgCbd: Compustat Global Company Business Descriptions	13
CsgCin: Compustat Global Company Other Information	13
CsgCiv: Compustat Global Inventory Valuation Data.....	15
CsgCmp: Compustat Global Company Identification Information	16
CsgCof: Compustat Global Company Officers.....	17
CsgCoHGIC: Global GICS History	17
CSGCOIND: Compustat Global Company Industry Classification	18
CSGCOINDPRES: Compustat Global Company Industry Presentation	19
CsgCur: Compustat Global Currency.....	19
CSGIdx: Compustat Global Index	20
CSGIDXCSTHIS: Compustat Global Index Constituent History.....	20
CSGIdxCstHisSnP:SPDJI Index Constituent History	21
CsgItn: Compustat Global Data Items.....	21
CsgIdx: Compustat Global Index Daily Data	22
CsgIxm: Compustat Global Index Monthly Data	22
CSGNTRMCOAU: Compustat Global Interim Auditor Data	23
CsgNtrmCoFntQ: Compustat Global Company Quarterly Fundamental Footnotes	24

CsgNtrmCoFntSa: Compustat Global Company Semi-Annual Fundamental Footnotes.....	25
CsgNtrmCoFntYtd: Compustat Global Company Year-to-Date Fundamental Footnotes.....	26
CsgNtrmCoIDesc: Compustat Global Interim Company Description	27
CsgNtrmCoQ: Compustat Global Company Quarterly Fundamental Data	29
CsgNtrmCoSa: Compustat Global Semi-Annual Fundamentals	30
CsgNtrmCoYtd: Compustat Global Company Year-to-Date Fundamentals.....	31
CsgNtrmSec: Compustat Global Issue Fundamentals	32
CsgNtrmSecFnt: Compustat Global Issue Fundamental Footnotes.....	33
CsgNtrmSecIDesc: Compustat Global Issue Description	34
CsgRef: Compustat Global Code Reference	35
CsgSad: Compustat Global Security Annual Period Descriptors	36
CsgSaf: Compustat Global Security Annual Fundamentals.....	36
CsgSdp: Compustat Global Security Daily Price Data	36
CsgSdv: Compustat Global Security Dividend Data	37
CsgSec: Compustat Global Security Data	38
CSGSSPLIT: Compustat Global Security Stock Split Data.....	39
CsgXrd: Compustat Global Currency Daily Exchange Rate Data	39
CsgXrm: Compustat Global Currency Monthly Exchange Rate Data	40
CSKEYCODE: Compustat XF Security Information.....	40

1 Introduction

In This Document

This document provides schema information about the **Compustat Global** tables in Quantitative Analytics.

NOTE

For information about the other Quantitative Analytics tables, refer to the other Database Schema documents posted on the [Quantitative Analytics](#) product page on [MyAccount](#).

The documentation for each table includes these main elements:

- **Vendor Database or License Name** – This element provides the vendor database or license name. Vendor databases generally correspond to vendor licensing options.
- **Table Name: Table Title** – This element provides the table name and title, followed by a description of the table contents.
- **Update Cycle** – This element indicates the frequency of updates from the data vendor. (For specific information about when this update is posted for your use, refer to your update logs. The update log schema description is available in the Database Schema for Quantitative Analytics Core Tables document.)
- **Adjusted** – This element indicates whether the data is stored adjusted, unadjusted, or if adjustment is not applicable (N/A).
- **Indexes, Index Fields** – This element lists the table's index(es) (for example, pkey_CSGCAD) and the index fields. The primary index contains a "pkey_" or "PK_" prefix. Clustered indexes are noted.
- **Field, Type, Nullable, Definition** – This element describes the table's fields, including field names, data types, and whether each field is nullable. The data types in Snowflake have equivalents available. For example, an *int* in SQL Server is a *number* in Snowflake.

Intended Readership

This document is intended for Quantitative Analytics clients licensed to use **Compustat Global** data through LSEG. Note that the tables described in this document may be covered by several licenses; your access to the data in these tables is dependent on the licenses you have. Readers should have basic knowledge of Microsoft SQL Server 2016.

Table Name Conventions

In Quantitative Analytics, database tables are grouped by name. Generally, the first few letters of the table name refer to the data vendor or licensing group. For example, all tables beginning with **CSG*** are Compustat Global tables.

Mapping Information

When mapping Compustat Global content, use the VenType and VenCode values shown in the following table. (For more information about mapping or for other vendors' VenType and VenCode values, refer to the Database Schema for Quantitative Analytics Core Tables document, available on the [Quantitative Analytics](#) product page on [MyAccount](#)).

Security VenType Mapping for the SecMapX and GSecMapX Tables

Vendor	SecMapX/GSecMapX VenType	Vendor Table(s)	Vencode = [field]
Compustat Xpressfeed	4	CSVSecurity (domestic); CSGSec (global)	SecIntCode (domestic); SecID (global)

Pervasive and Oracle

This document is specific to Microsoft SQL Server 2016. If you are accessing the data directly through the Pervasive database, you may encounter slight differences in index names and data types. Please note that references to Pervasive and Actian are synonymous.

If you are accessing the data through Oracle, note that field names that correspond to Oracle reserved words are appended with an underscore. For example, field names “Number”, “Synonym”, and “UID” become “Number_”, “Synonym_”, and “UID_” in Oracle.

Zero Values and Nulls

Null values are usually recorded as “NULL”. Occasionally, a table may contain a value of “-99999” or “-9999”; in these cases, there is no recorded data for that period. (It is null.) If the table contains a “0” value, the data was reported as having a “0” value.

Accessing Standard & Poor’s Compustat Documentation

You may also want to refer to documentation provided for Compustat by Standard & Poor’s (S&P). Although this document describes database organization within Quantitative Analytics, it is not intended to replace Compustat documentation. Compustat data mnemonics, footnote codes, and reference items are described in detail in the online Compustat Data Guide.

You can access Compustat documentation at <http://www.compustat.com/>.

If you have a Compustat data license, but do not have a user name and password for the Compustat website, contact Compustat Customer Support:

- Phone: +1 800.523.4534
- Email: clientsupport@standardandpoors.com

Obsolete Tables

The following tables are no longer supported by Compustat and have been removed from the Quantitative Analytics database for Compustat Global.

- CsgCaf: Compustat Global Annual Fundamental Data
- CsgIad: Compustat Global Index Annual Period Description
- CsgIqd: Compustat Global Index Quarterly Period Descriptors
- CsgIxa: Compustat Global Index Annual Data
- CsgIqx: Compustat Global Index Quarterly Data
- CsgNtrmCo: Compustat Global Interim Company Records Data
- CsgNtrmColInfo: Compustat Global Interim Company Level Data
- CsgNtrmIs: Compustat Global Interim Issue Level Data
- CsgSpd: Compustat Global S&P Index Daily Data
- CsgSpi: Compustat Global S&P Index information
- CsgSpm: Compustat Global S&P Index Monthly Data

Service and Support

[MyAccount](#) is the LSEG portal that provides a single access point for timesaving support services, along with billing, user management, and information.

Statement of Service

The [Quantitative Analytics Service Description](#) is available on the [Quantitative Analytics](#) product page at [MyAccount](#).

Subscribe to Support Channels

You are encouraged to [subscribe](#) to the following support channels to keep informed of changes to products and data, and to be notified of any service issues or change. Please see the *Alerts and Notifications* section in the

Quantitative Analytics Service Description, available on the [Quantitative Analytics](#) product page at MyAccount for detailed instructions.

– Change Notifications

- **Product Change Notifications (PCNs)** detail new, enhanced, or changed functionality, which may require your action, in products that you use.
- **Data Notifications (DNs)** alert you to upcoming changes to real-time and historical data across all asset classes that are relevant to you.
- **RIC Change Events** inform you of planned changes to RICs. RIC is the market level identifier key unique to LSEG used to identify securities.

– Service Alerts

Alert you about planned maintenance and unplanned service issues affecting your products and services, and be notified via SMS or email.

Documentation

You can access product documentation on the [Quantitative Analytics](#) product page at [MyAccount](#).

Get Support

For support using Quantitative Analytics, please use one of the following methods:

Online

Access [Get Support](#) either via the blue **Get Support** button at the top right of each page or by selecting *Get Support* located under *Help and Support* on the left navigation pane at [MyAccount](#).

From the *Get Support* page, choose *Get Product and Content Support* and then select the appropriate category from the next page. Complete the request making sure to include the following:

- Under Product, select Quantitative Analytics from the dropdown list.
- In the **How can we help you?** text box, include the following information:
 - Content set name (i.e. Worldscope)
 - Date applicable to a content inquiry
 - Table names and relevant fields
 - Security code (i.e. QA-ID, PermID, Sedol, InfoCode, etc.)
 - Script used to generate the output
 - Any other supporting detail

Telephone

Region	Telephone	Options
AMERS	+01 866 427 8390	Option 1 – Product Support Option 2 – Technical Support
EMEA	+44 203 341 1036	
APAC	+65 6403 7436	

Feedback

We invite your comments, corrections, and suggestions about this document: access the [Feedback](#) option under [Get Support](#) at [MyAccount](#). Your feedback helps us continue to improve our user assistance.

Your Personal Information

LSEG is committed to the responsible handling and protection of personal information. We invite you to review our [Privacy and Cookie Statement](#), which describes how we collect, use, disclose, transfer, and store personal information when needed to provide our services and for our operational and business purposes.

2 Compustat Global Data Tables

Update Cycle: Compustat Global data is updated three times daily.

Adjusted: Compustat Global data is not adjusted (unless otherwise specified).

CsgCad: Compustat Global Annual Period Description

Use this table to retrieve period description data on an annual basis. This data includes adjustment factors, industry, and data formats, whether the data is consolidated or non-consolidated, currency translation exchange rate, and fiscal year data.

Indexes	Index Fields
pkey_CsgCad (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL
CsgCad_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CsgCad_2	GVKEY, DATAFMT, CONSOL, DATADATE
CsgCad_3	GVKEY, INDFMT, DATAFMT, DATADATE
CsgCad_4	GVKEY, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date, or for security-level data it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture)

Field	Type	Nullable	Description
			– 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
ACCTSTD	varchar(9)	Y	ACCTSTD is the accounting standard. ACCTSTD cross-references with CsgRef where CsgCad.acctstd = CsgRef.refcd1 and CsgRef.reftype = 2.
ACQMETH	varchar(3)	Y	ACQMETH is the acquisition method. It cross-references with CsgRef where CsgCad.acqmeth = CsgRef.refcd1 and CsgRef.reftype = 3.
ADRR	float	Y	ADRR is the company reported unweighted average of total demand deposits for the year, restated up to five years. If no average is reported, then this is the actual figure.
AJEX	float	Y	AJEX is the annual company adjustment factor; it is cumulative by ex-date.
AJP	float	Y	AJP is the annual company adjustment factor, as applied to the dividends per share by payable date; it is cumulative by payable date.
APDEDATE	datetime	Y	APDEDATE is the actual date the company closes accounting for the period.
BSPR	varchar(8)	Y	BSPR is the balance sheet presentation. BSPR cross-references with CsgRef where CsgCad.bspr = CsgRef.refcd1 and CsgRef.reftype = 5.
COMPST	varchar(8)	Y	COMPST is the comparability status. It cross-references with CsgRef where CsgCad.compst = CsgRef.refcd1 and CsgRef.reftype = 7.
CURCD	varchar(4)	Y	CURCD is company ISO currency code. Cross-reference CURCD with CsgRef where CsgCad.compst = CsgRef.refcd1 and CsgRef.reftype = 36.
CURNCD	varchar(4)	Y	CURNCD is the native currency in which the company reports its financial data.
CURRTR	float	Y	CURRTR is the exchange rate used to translate non-U.S. currency amounts into U.S. Dollars. The conversion rate is the rate as of the date of the company's balance sheet. When an international company reports in U.S. Dollars, the translation rate is 1.000.
CURUSCN	float	Y	CURUSCN is the exchange rate used to translate Canadian currency into U.S. Dollars, as published in the Federal Reserve period rates. This item is available only when a company reports in both U.S. and Canadian accounting standards.
FDATE	datetime	Y	FDATE is the date the data is finalized for the year.
FINAL	varchar(3)	Y	FINAL indicates that all annual fundamental items are available and have been delivered.
FYEAR	smallint	Y	FYEAR is the fiscal year of the current fiscal year-end month. If the current fiscal year-end month falls in January through May, this item is the current calendar year minus 1 year. If the current fiscal year-end month falls in June through December, this item is the current calendar year.
FYR	tinyint	Y	FYR is the fiscal year-end month. This item is a key field.
ISMOD	smallint	Y	ISMOD is the income statement model number. It cross-references with CsgRef where CsgCad.compst = CsgRef.refcd1 and CsgRef.reftype = 17.
OGM	varchar(9)	Y	OGM is the Oil and Gas Method. OGM refers to the method of revenue reporting used by the oil and gas company.
PDATE	datetime	Y	PDATE is the preliminary date the data for the company is updated for that year.
PDDUR	tinyint	Y	PDDUR is the period duration (number of months) covered by the company's annual report income statement. This figure may not be available for all companies.
SCF	smallint	Y	SCF is the cash flow format. Cross-reference with CsgRef where CsgCad.scf = CsgRef.refcd1 and CsgRef = 6.
SRC	smallint	Y	SRC is the source document. Cross-reference SRC with CsgRef where CsgCad.compst = CsgRef.refcd1 and CsgRef.reftype = 10.
STALT	varchar(3)	Y	STALT is the status alert. Cross-reference with CsgRef where CsgCad.compst = CsgRef.refcd1 and CsgRef.reftype = 30.
UDPL	varchar(9)	Y	UDPL is the liberalized depreciation code used by a utility company. This item identifies the method used to account for liberalized depreciation. If 51% of its liberalized depreciation is deferred, it is categorized as Normal. If 51% of its liberalized depreciation is flowed through, it is categorized as Flowed Through.

Field	Type	Nullable	Description
UPD	smallint	Y	UPD is the update code. Cross-reference with CsgRef where CsgCad.compst = CsgRef.refcd1 and CsgRef.reftype = 33.

CSGCAF1: Compustat Global Company Annual Fundamentals 1

Use CSGCAF1 in conjunction with [CsgCad](#) to retrieve annual fundamental company data. This table includes company information for mnemonics beginning with A through L.

Indexes	Index Fields
pkey_CSGCAF1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSGCAF1_1	GVKEY, Item, INDFMT, DATAFMT, CONSOL, DATADATE
CSGCAF1_2	GVKEY, Item, DATAFMT, CONSOL, DATADATE
CSGCAF1_3	GVKEY, Item, INDFMT, DATAFMT, DATADATE
CSGCAF1_4	GVKEY, Item, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
Item	smallint	N	Item identifies standardized fundamental data with related analyst notes or transparency. Cross reference Item with Csgltm. Item is a key field.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	smallint	Y	DATACODE indicates non-normal values. DATACODE values are: – 0 (Normal) – 1 (Not available) – 2 (Semi-annual figure) – 3 (Annual figure) – 4 (Combined figure)

Field	Type	Nullable	Description
			– 8 (Insignificant figure)

CSGCAF2: Compustat Global Company Annual Fundamentals 2

Use CSGCAF2 in conjunction with [CsgCad](#) to retrieve annual fundamental company data. This table includes company information for mnemonics beginning with M through Z.

Indexes	Index Fields
pkey_CSGCAF2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSGCAF2_1	GVKEY, Item, INDFMT, DATAFMT, CONSOL, DATADATE
CSGCAF2_2	GVKEY, Item, DATAFMT, CONSOL, DATADATE
CSGCAF2_3	GVKEY, Item, INDFMT, DATAFMT, DATADATE
CSGCAF2_4	GVKEY, Item, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
Item	smallint	N	Item identifies standardized fundamental data with related analyst notes or transparency. Cross reference Item with Csgltm. Item is a key field.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	smallint	Y	DATACODE indicates non-normal values. DATACODE values are: – 0 (Normal) – 1 (Not available)

Field	Type	Nullable	Description
			– 2 (Semi-annual figure) – 3 (Annual figure) – 4 (Combined figure) – 8 (Insignificant figure)

CSGCAFNT: Compustat Global Company Annual Fundamentals Footnotes

Use this table to retrieve footnotes for a value.

Indexes	Index Fields
pkey_CSGCAFNT (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSGCAFNT_1	GVKEY, Item

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
Item	smallint	N	Item identifies standardized fundamental data with related analyst notes or transparency. Cross reference Item with Csgltn. Item is a key field.
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

CsgCau: Compustat Global Company Auditor Record

Use this table to retrieve annual company statement auditor information, including auditor opinion.

Indexes	Index Fields
pkey_CsgCau (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CsgCau_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE
CsgCau_2	GVKEY, DATAFMT, CONSOL, RANK, DATADATE
CsgCau_3	GVKEY, INDFMT, DATAFMT, RANK, DATADATE
CsgCau_4	GVKEY, DATAFMT, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
RANK	int	N	RANK identifies hierarchy of auditors or of inventory valuation methods. For companies with more than one auditor, auditor hierarchy is ranked from 1 to 6, where 1 indicates the primary auditor. For companies using more than one inventory valuation method, 1 indicates the valuation method used most often.
AU	smallint	Y	AU is the auditor. Cross-reference AU with CsgRef where CsgCau.au = CsgRef.refcd1 and CsgRef.reftype = 4.
AUOP	smallint	Y	AUOP is the auditor opinion. It cross-references with CsgRef where CsgCau.auop = CsgRef.refcd1 and CsgRef.reftype = 22.
AUOPIC	char(1)	Y	AUOPIC is the auditor's opinion regarding whether the company's internal control over financial reporting is effective. Section 404 of the Sarbanes-Oxley Act of 2002 requires companies to report this opinion beginning with fiscal years ending after November 15, 2004.
CEOSO	char(1)	Y	CEOSO is the chief executive officer SOX certification. CEOSO indicates whether the company has filed documents certifying the CEO has reviewed the relevant

Field	Type	Nullable	Description
			report and that the information is reported fairly, as required by Section 302 of the Sarbanes-Oxley Act of 2002.
CFOSO	char(1)	Y	CFOSO is the chief financial officer SOX certification. CFOSO indicates whether the company has filed documents certifying the CFO has reviewed the relevant report and that the information is reported fairly, as required by Section 302 of the Sarbanes-Oxley Act of 2002.

CsgCbd: Compustat Global Company Business Descriptions

Use this table to retrieve generalized company descriptions.

Indexes	Index Fields
pkey_CsgCbd (Clustered)	GVKEY, SEQNO

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
SEQNO	smallint	N	SEQNO is the sequence number.
BUSDESC	varchar(101)	Y	BUSDESC is a textual description of the business.

CsgCin: Compustat Global Company Other Information

This table includes the company's current global classification and status. This table does not contain historical data.

Indexes	Index Fields
pkey_CsgCin (Clustered)	GVKEY

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
ADD1	varchar(66)	Y	ADD1 contains the company headquarters mailing address
ADD2	varchar(66)	Y	ADD2 contains the company headquarters mailing address
ADD3	varchar(66)	Y	ADD3 contain the company headquarters mailing address
ADD4	varchar(66)	Y	ADD4 contains the company headquarters mailing address
ADDZIP	varchar(21)	Y	ADDZIP contains the company zip or postal code.
CIK	varchar(11)	Y	CIK is the Central Index Key; it is used by the SEC to identify who has filed disclosures with the SEC.
CITY	varchar(101)	Y	CITY is the city of the company's headquarters.
CONML	varchar(101)	Y	CONML is the official company name, as filed in the company's EDGAR SEC filing.
COSTAT	char(1)	Y	COSTAT is the status marker. COSTAT can be A (Active) or I (Inactive).
COUNTY	varchar(101)	Y	COUNTY is the county of the company's headquarters.
DLDT	datetime	Y	DLDT is the date a research company was deleted.
DLRSN	varchar(9)	Y	DLRSN is the reason a research company was deleted. Cross-reference DLRSN with CsgRef where CsgCin.dlrsn = CsgRef.refcd1 and CsgRef.reftype = 16.
EIN	varchar(11)	Y	EIN is the Employer Identification Number issued by the IRS.
FAX	varchar(21)	Y	FAX is the fax number.
FIC	varchar(4)	Y	FIC is the ISO3 code of the country of incorporation. Cross-reference with CsgRef where CsgCin.fic = CsgRef.refcd1 and CsgRef.reftype = 8.

Field	Type	Nullable	Description
FYRC	tinyint	Y	FYRC is the fiscal year end month.
GGROUP	int	Y	GGROUP is the GICS group code. Cross-reference GGROUP with either – CsgRef where CsgCin.ggroup = CsgRef.refcd2, <i>and</i> CsgRef.reftype = 34, <i>and</i> CsgRef.refcd1 = 'GGROUP', <i>or</i> – CsgRef where CsgCin.ggroup = CsgRef.refcd1, <i>and</i> CsgRef.reftype = 15
GIND	int	Y	GIND is the GICS industry code. Cross-reference it with either – CsgRef where CsgCin.gind = CsgRef.refcd2, <i>and</i> CsgRef.reftype = 34, <i>and</i> CsgRef.refcd1 = 'GIND', <i>or</i> – CsgRef where CsgCin.gind = CsgRef.refcd1, <i>and</i> CsgRef.reftype = 15
GSECTOR	int	Y	GSECTOR is the GICS sector code. Cross-reference GSECTOR with either – CsgRef where CsgCin.gind = CsgRef.refcd2, <i>and</i> CsgRef.reftype = 34, <i>and</i> CsgRef.refcd1 = 'GSECTOR', <i>or</i> – CsgRef where CsgCin.gsectir = CsgRef.refcd1, <i>and</i> CsgRef.reftype = 15
GSUBIND	int	Y	GSUBIND is the GICS subindustry code. Cross-reference GSUBLND with either – CsgRef where CsgCin.gsubind = CsgRef.refcd2, <i>and</i> CsgRef.reftype = 34, <i>and</i> CsgRef.refcd1 = 'GSUBIND', <i>or</i> – CsgRef where CsgCin.gsubind = CsgRef.refcd1, <i>and</i> CsgRef.reftype = 15
IDBFLAG	char(1)	Y	IDBFLAG indicates whether the company is international (I), domestic (D), or both (B).
INCORP	varchar(9)	Y	INCORP is the state or province of incorporation. Cross-reference INCORP with CsgRef where CsgCin.incorp = CsgRef.refcd1 <i>and</i> CsgRef.reftype = 31.
IPODATE	datetime	Y	IPODATE is the date of the company's initial public stock offering. This date is available for some global companies, including companies from Japan (JPN), Hong-Kong (HKG), Malaysia (MYS), India (IDN), Philippines (PHL), China (CHN), and Singapore (SGP).
LOC	varchar(4)	Y	LOC is the ISO3 country code of the headquarters. It cross-references with CsgRef where CsgCin.loc = CsgRef.refcd1 <i>and</i> CsgRef.reftype = 8.
NAICS	int	Y	NAICS is the NAICS code. Cross-reference with CsgRef where CsgCin.naics = CsgRef.refcd1 <i>and</i> CsgRef.reftype = 21.
PHONE	varchar(20)	Y	PHONE is the phone number.
PRICAN	varchar(9)	Y	PRICAN is the primary issue tag for Canadian companies.

Field	Type	Nullable	Description
PRIROW	varchar(9)	Y	PRIROW identifies the primary issue for companies that trade outside of the United States and Canada.
PRIUSA	varchar(9)	Y	PRIUSA is the primary issue tag for U.S. companies.
SIC	smallint	Y	SIC is the SIC code (Standard Industrial Classification Code). Cross-reference with CsgRef where CsgCin.sic = CsgRef.refcd1 and CsgRef.reftype = 27.
SPCINDCD	smallint	Y	SPCINDCD is the S&P Industry Sector Code. Cross-reference with CsgRef where CsgCin.spcindcd = CsgRef.refcd1 and CsgRef.reftype = 18.
SPCSECCD	smallint	Y	SPCSECCD is the S&P Economic Sector Code. Cross-reference with CsgRef where CsgCin.spcseccd = CsgRef.refcd1 and CsgRef.reftype = 26.
SPCSRC	varchar(4)	Y	SPCSRC is the Standard & Poors appraisal of a stock's past performance including the stock's earnings and dividends, and the stock's standing as of a company's current fiscal year-end.
STATE	varchar(9)	Y	STATE is the state or province. Cross-reference with CsgRef where CsgCin.state = CsgRef.refcd1 and CsgRef.reftype = 31.
STKO	tinyint	Y	STKO indicates the company compensation in the form of company stock on a pre-tax basis, including stock bonuses, deferred compensation, amortization of deferred compensation, non-cash compensation expenses, and stock-based compensation to employees and non-employees.
WEBURL	varchar(61)	Y	WEBURL is the company's home page Internet address.

CsgCiv: Compustat Global Inventory Valuation Data

This table describes the company's inventory valuation method.

Indexes	Index Fields
pkey_CsgCiv (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CsgCiv_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE
CsgCiv_2	GVKEY, DATAFMT, CONSOL, RANK, DATADATE
CsgCiv_3	GVKEY, INDFMT, DATAFMT, RANK, DATADATE
CsgCiv_4	GVKEY, DATAFMT, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
RANK	int	N	RANK identifies hierarchy of auditors or of inventory valuation methods. For companies with more than one auditor, auditor hierarchy is ranked from 1 to 6, where 1 indicates the primary auditor. For companies using more than one inventory valuation method, 1 indicates the valuation method used most often.
INVVAL	int	Y	INVVAL is the inventory valuation method. Values may include: – 0 (No inventory) – 1 (FIFO) – 2 (LIFO) – 3 (Specific identification) – 4 (Average cost) – 5 (Retail method) – 6 (Standard cost) – 7 (Current or replacement cost) Cross-reference INVVAL with CsgRef where CsgCiv.invval = CsgRef.refcd1 and CsgRef.reftype = 19.

CsgCmp: Compustat Global Company Identification Information

This table is the primary company-level data table.

NOTE

For security-level data, use [CsgSec: Compustat Global Security Data](#) on page 38.

Indexes	Index Fields
pkey_CsgCmp (Clustered)	GVKEY
CsgCmp_1	SEDOL, GVKEY
CsgCmp_2	ISIN, GVKEY
CsgCmp_3	CONM, GVKEY

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
SEDOL	varchar(7)	Y	SEDOL is the Stock Exchange Daily Official List security ID, as determined by the International Stock Exchange in London.
ISIN	varchar(13)	Y	ISIN is the unique security identification number, as determined by the National Numbering Agency within a particular country is responsible for allocating ISIN codes.
CONM	varchar(250)	Y	CONM is the company name.
PRIMIID	varchar(4)	Y	PRIMIID identifies the primary issue id of the GVKEY, where 1 is the primary issue.
SECSTAT	varchar(2)	Y	SECSTAT is the security status marker. SECSTAT can be A (Active) or I (Inactive).

CsgCof: Compustat Global Company Officers

This table contains information on company officers.

Indexes		Index Fields	
pkey_CsgCmp (Clustered)		GVKEY, OFCD, OFID	
Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
OFCD	varchar(9)	N	OFCD is the officer title. OFCD cross-references with CsgRef where CsgCof.ofcd = CsgRef.refcd1 and CsgRef.reftype = 32.
OFID	int	N	OFID is the officer ID.
OFNM	varchar(40)	Y	OFNM is the officer name.

CsgCoHGIC: Global GICS History

This table contains global GICS history information.

Indexes		Index Fields	
pkey_CSGCOHGIC (Clustered)		GVKEY, INDTYPE, INDFROM	
Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
INDTYPE	varchar(9)	N	INDTYPE is the type of industry classification. GICS = Standard & Poor's Global Industry Classification System.
INDFROM	datetime	N	INDFROM is the date from which the GICS code was effective.
GGROUP	varchar(5)	Y	GGROUP is the GICS group code, the second level in the hierarchy of the Global Industry Classification Standard (GICS). The industry group is represented by the leftmost four digits of the total GICS code. Cross-reference GGROUP with either – CsgRef where CsgCoHGIC.GGROUP = CsgRef.refcd2, and CsgRef.reftype = 34, and CsgRef.refcd1 = 'GGROUP', or – CsgRef where CsgCoHGIC.GGROUP = CsgRef.refcd1, and CsgRef.reftype = 15
GIND	varchar(7)	Y	GIND is the GICS industry code, the third level in the hierarchy of the Global Industry Classification Standard (GICS). The industry is represented by the leftmost six digits of the total GICS code. Cross-reference GIND with either – CsgRef where CsgCoHGIC.gind = CsgRef.refcd2, and CsgRef.reftype = 34, and CsgRef.refcd1 = 'GIND', or – CsgRef where CsgCoHGIC.gind = CsgRef.refcd1, and CsgRef.reftype = 15

Field	Type	Nullable	Description
GSECTOR	varchar(3)	Y	GSECTOR is the GICS sector code, the first level in the hierarchy of the Global Industry Classification Standard (GICS). The sector is represented by the leftmost two digits of the total GICS code. Cross-reference GSECTOR with either – CsgRef where CsgCoHGIC.gind = CsgRef.refcd2, and CsgRef.reftype = 34, and CsgRef.refcd1 = 'GSECTOR', or – CsgRef where CsgCoHGIC.gsectir = CsgRef.refcd1, and CsgRef.reftype = 15
GSUBIND	varchar(9)	Y	GSUBIND is the GICS sub-industry code, the fourth level in the hierarchy of the Global Industry Classification Standard (GICS). The sub-industry is represented by all eight digits of the total GICS code. Cross-reference GSUBIND with either – CsgRef where CsgCoHGIC.gsubind = CsgRef.refcd2, and CsgRef.reftype = 34, and CsgRef.refcd1 = 'GSUBIND', or – CsgRef where CsgCoHGIC.gsubind = CsgRef.refcd1, and CsgRef.reftype = 15
INDTHRU	datetime	Y	INDTHRU is the date through which the GICS code was effective, if it is no longer effective.

CSGCOIND: Compustat Global Company Industry Classification

This table contains a company's historical SIC classification data.

Indexes	Index Fields
pkey_CSGCOIND (Clustered)	GVKEY, DATADATE, CONSOL
CSGCOIND_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	Y	FYR is the fiscal year-end month. This item is a key field.
NAICSH	int	Y	NAICSH is the historical NAICS code assigned to a company.
SICH	int	Y	SICH is the historical SIC code.
YEAR_	smallint	Y	YEAR indicates the year of the data.

CSGCOINDPRES: Compustat Global Company Industry Presentation

This table contains information on the company presentation format. This table cross-references with [CsgRef: Compustat Global Code Reference](#), described on page 35.

Indexes	Index Fields
pkey_CSGCOINDPRES (Clustered)	GVKEY, DATADATE, CONSOL, IPCD
CSGCOINDPRES_1	GVKEY, CONSOL, IPCD, DATADATE
CSGCOINDPRES_2	GVKEY, CONSOL, DATADATE
CSGCOINDPRES_3	GVKEY, IPCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
IPCD	char(1)	N	IPCD is the financial services company presentation format. Values are: – C (Combination of industry types) – B (Bank) – I (Insurance) – D (Broker/Dealer) – R (Real Estate) – O (Other)

CsgCur: Compustat Global Currency

Use this table to retrieve global currency data. For rate information, cross-reference this table with [CsgXrd: Compustat Global Currency Daily Exchange Rate Data](#), described on page 39, and [CsgXrm: Compustat Global Currency Monthly Exchange Rate Data](#), described on page 40.

Indexes	Index Fields
pkey_CsgCur (Clustered)	ISOCURCD
CsgCur_1	ISOCURNM, ISOCURCD

Field	Type	Nullable	Description
ISOCURCD	varchar(4)	N	ISOCURCD is the ISO currency code. ISOCURCD cross-references with CsgRef where CsgCur.isocurcd = CsgRef.refcd1 and CsgRef.reftype = 36.
ISOCURBD	datetime	Y	ISOCURBD is the ISO currency birth date.
ISOCURDD	datetime	Y	ISOCURDD is the ISO currency death date.
ISOCURLNK	smallint	Y	ISOCURLNK is the ISO currency link code. Different currencies used in the same country at different times share the same link code.
ISOCURNM	varchar(41)	Y	ISOCURNM is the ISO currency description.

Field	Type	Nullable	Description
ISOCURTR	smallint	Y	ISOCURTR is the ISO currency tier number. Tier number can be either 1 or 2. Tier 1 indicates the currency is translated directly into other currencies. Tier 2 indicates the currency is translated into one of four primary currencies, then translated from the primary currency into a target currency. The four primary currencies are U.S. Dollar, British Pound Sterling, Japanese Yen, and Swiss Francs.

CSGIdx: Compustat Global Index

This table is the general information table for Compustat indexes.

Indexes	Index Fields
pkey_CSGIdx (Clustered)	GVKEYX
CSGIdx_1	TIC, GVKEYX
CSGIdx_2	CONM, GVKEYX

Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is the index GVKEY. It is a primary key for all indexes across all Csgl* tables.
CONM	varchar(250)	Y	CONM is the index name.
IDX13KEY	varchar(14)	Y	IDX13KEY is the 13 character key.
IDXCSTFLG	varchar(2)	Y	IDXCSTFLG is the index constituent flag. This indicates that there are constituent markings available.
INDEXCAT	varchar(11)	Y	INDEXCAT is the index category code.
INDEXGEO	varchar(11)	Y	INDEXGEO is the index geographical area.
INDEXID	varchar(11)	Y	INDEXID is the S&P major index ID. Cross-reference INDEXID with CsgRef where CsgIdx.indexid = CsgRef.refcd1 and CsgIdx.indexcat = CsgRef.refcd2 and CsgRef.reftype = 35.
INDEXTYPE	varchar(11)	Y	INDEXTYPE is the index type.
INDEXVAL	varchar(11)	Y	INDEXVAL is the index value code. Cross-reference INDEXVAL with CsgRef where CsgIdx.indexval = CsgRef.refcd2, and CsgIdx.indextype = CsgRef.refcd1, and CsgRef.reftype = 34.
TIC	varchar(9)	Y	TIC is the ticker/trading symbol.
TICI	varchar(9)	Y	TICI is the issue trading ticker.
IDXSTAT	char(1)	Y	IDXSTAT is the status of the index (active or inactive).

CSGIDXCSTHIS: Compustat Global Index Constituent History

This table contains a history of components for every GVKEYX.

NOTE

As of July 22, 2020, S&P DJI historical constituent data is no longer available in this table where IndexCat in CSIdxIndex/CSGIdx = S&P.

Indexes	Index Fields
pkey_CSGIDXCSTHIS (Clustered)	GVKEYX, GVKEY, IID, FROM_
CSGIDXCSTHIS_1	GVKEY, IID, FROM_

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
IID	varchar(4)	N	IID is the global issue ID. The IID is an alphanumeric character code. IID consists of a security-identifying numeric component and a population-identifying alpha

Field	Type	Nullable	Description
			component. The numeric component distinguishes a security from other securities issued by a company. The alpha component W indicates that the security is traded on a non-Canadian, non-U.S. exchange; C indicates the issue is traded on a Canadian exchange; and no alpha character indicates the security is traded in the United States. This item is a key field. Cross reference IID with GVKEY to uniquely identify securities.
GVKEYX	int	N	GVKEYX is the index GVKEY. It is a primary key for all indexes across all Csgl* tables.
FROM_	datetime	N	FROM_ indicates the date from which the index mapping is effective.
THRU	datetime	Y	THRU indicates the date through which the index mapping is effective.

CSGIdxCstHisSnP:SPDJI Index Constituent History

This table contains S&P Dow Jones Index constituent history information.

Update cycle: Daily

Indexes		Index Fields	
pkey_CSGIDXCSTHISSNP (Clustered)		GVKEY, IID, GVKEYX, FROM_	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company. The combination of GVKEY and IID represents the index constituent.
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
FROM_	datetime	N	FROM_ represents the dates that the security was part of the index.
THRU	datetime	Y	THRU represents the dates that the security was part of the index.
LICFLAG	tinyint	N	LICFLAG represents the license flag value for the various Index constituents. The LICFLAG may be 8 = SPDJ Global Constituent History

Csgltn: Compustat Global Data Items

This table contains information for Compustat Global mnemonics

Indexes		Index Fields	
pkey_Csgltn (Clustered)		GROUP_, NUMBER	
Csgltn_1		GROUP_, MNEMONIC	
Csgltn_2		GROUP_, ANNSYN, MNEMONIC	
Csgltn_3		GROUP_, GBLSYN, MNEMONIC	
Csgltn_4		GROUP_, DESC_, MNEMONIC	

Field	Type	Nullable	Description
GROUP_	smallint	N	The combination of GROUP_ and NUMBER creates the key for linking Csg* data items to VALUE_. GROUP_ is defined by GNAME.
GNAME	varchar(50)	Y	GNAME defines GROUP_.
NUMBER	smallint	N	The combination of GROUP_ and NUMBER creates the key for linking Csg* data items to VALUE_.
MNEMONIC	varchar(20)	Y	MNEMONIC is the item mnemonic.
ANNSYN	varchar(7)	Y	ANNSYN is the annual synonym.
GBLSYN	varchar(7)	Y	GBLSYN is the global synonym.
DESC_	varchar(150)	Y	DESC_ is the item description.

Field	Type	Nullable	Description
IDBFLAG	varchar(2)	Y	IDBFLAG indicates if the company is international (I), domestic (D), or both (B).
ADJUST	tinyint	Y	ADJUST is the item adjustment method. ADJUST can be: – 0 (No adjustment) – 2 (Multiply) – 3 (Divide)
FREQ	tinyint	Y	FREQ is the item frequency. FREQ can be one either 1 (Annual) or 2 (Quarterly).
STMT	tinyint	Y	STMT is the item source statement. STMT can be one of the following: – 0 = None – 1 = Balance sheet – 2 = Income statement – 3 = Cash flow statement
UNITS	tinyint	Y	UNITS is the item units type. UNITS can be one of the following: – 1 = Currency – 2 = Units – 3 = Ratio
DATATYPE	tinyint	Y	DATATYPE is currently unused.
REFTYPE	tinyint	Y	REFTYPE is currently unused.

Csglxd: Compustat Global Index Daily Data

This table contains pricing and dividend information for daily indices.

Indexes	Index Fields
pkey_Csglxd (Clustered)	GVKEYX, DATADATE

Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is the index GVKEY. It is a primary key for all indexes across all Csgl* tables.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
DVPSXD	float	Y	DVPSXD is the daily cash (or cash equivalent), dividend payment amount. This item includes special dividends and spin-offs.
NEWNUM	int	Y	NEWNUM is the new index number.
OLDNUM	int	Y	OLDNUM is the old index number.
PRCCD	float	Y	PRCCD is the daily close index price.
PRCCDDIV	float	Y	PRCCDDIV is the daily close price for the index's rate of return.
PRCHD	float	Y	PRCHD is the daily high index price.
PRCLD	float	Y	PRCLD is the daily low index price.

Csglxm: Compustat Global Index Monthly Data

This table contains pricing and dividend information for monthly indices.

Indexes	Index Fields
pkey_Csglxd (Clustered)	GVKEYX, DATADATE

Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is the index GVKEY. It is a primary key for all indexes across all Csgl* tables.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.

Field	Type	Nullable	Description
DVPSXM	float	Y	DVPSXM is the monthly cash (or cash equivalent), dividend payment amount. This item includes special dividends and spin-offs.
PRCCM	float	Y	PRCCM is the monthly close index price.
PRCHM	float	Y	PRCHM is the monthly high index price.
PRCLM	float	Y	PRCLM is the monthly low index price.

CSGNTRMCOAU: Compustat Global Interim Auditor Data

Use this table to retrieve quarterly company statement auditor information, including auditor opinion.

Indexes	Index Fields
pkey_CSGNTRMCOAU (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CSGNTRMCOAU_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE
CSGNTRMCOAU_2	GVKEY, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
RANK	int	N	RANK identifies hierarchy of auditors or of inventory valuation methods. For companies with more than one auditor, auditor hierarchy is ranked from 1 to 6, where 1 indicates the primary auditor. For companies using more than one inventory valuation method, 1 indicates the valuation method used most often.
CEOSOQ	char(1)	Y	CEOSOQ is the chief executive officer SOX certification. CEOSOQ indicates whether the company has filed documents certifying the CEO has reviewed the relevant report and that the information is reported fairly, as required by Section 302 of the Sarbanes-Oxley Act of 2002.
CFOSOQ	char(1)	Y	CFOSOQ is the chief financial officer SOX certification. CFOSOQ indicates whether the company has filed documents certifying the CFO has reviewed the relevant

Field	Type	Nullable	Description
			report and that the information is reported fairly, as required by Section 302 of the Sarbanes-Oxley Act of 2002.

CsgNtrmCoFntQ: Compustat Global Company Quarterly Fundamental Footnotes

Use this table to retrieve quarterly fundamental footnotes.

Indexes	Index Fields
pkey_CsgNtrmCoFntQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmCoFntQ_1	GVKEY, ITEM
CsgNtrmCoFntQ_2	GVKEY, ITEM, DATADATE
CsgNtrmCoFntQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoFntQ_4	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with Csgltm. ITEM is a key field. Cross-reference ITEM with Csgltm where CsgNtrmCoFntQ.item = Csgltm.number and Csgltm.group_ = 1
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

CsgNtrmCoFntSa: Compustat Global Company Semi-Annual Fundamental Footnotes

Use this table to retrieve semi-annual fundamental footnotes.

Indexes	Index Fields
pkey_CsgNtrmCoFntSa (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmCoFntSa_1	GVKEY, ITEM
CsgNtrmCoFntSa_2	GVKEY, ITEM, DATADATE
CsgNtrmCoFntSa_3	GVKEY, INDFMT, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoFntSa_4	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference Item with CsgItrm. ITEM is a key field. Cross-reference ITEM with CsgItrm where CsgNtrmCoFntSa.item = CsgItrm.number and CsgItrm.group_ = 1
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

CsgNtrmCoFntYtd: Compustat Global Company Year-to-Date Fundamental Footnotes

Use this table to retrieve year-to-date fundamental footnotes.

Indexes	Index Fields
pkey_CsgNtrmCoFntYtd (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmCoFntYtd_1	GVKEY, ITEM
CsgNtrmCoFntYtd_2	GVKEY, ITEM, DATADATE
CsgNtrmCoFntYtd_3	GVKEY, INDFMT, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoFntYtd_4	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference Item with Csgltm. ITEM is a key field. Cross-reference ITEM with Csgltm where CsgNtrmCoFntYtd.item = Csgltm.number and Csgltm.group_ = 1
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

CsgNtrmColDesc: Compustat Global Interim Company Description

Use this table to retrieve period description data on a quarterly basis. This data includes adjustment factors, industry, and data formats, whether the data is consolidated or non-consolidated, currency translation exchange rate, and fiscal year data.

Indexes	Index Fields
pkey_CsgNtrmColDesc (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CsgNtrmColDesc_1	GVKEY, CONSOL, DATAFMT DATADATE
CsgNtrmColDesc_2	GVKEY, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ACCTSTDQ	varchar(9)	Y	ACCTSTDQ is the accounting standard for the quarter. ACCTSTD cross-references with CsgRef where CsgNtrmColDesc.acctstd = CsgRef.refcd1 and CsgRef.reftype = 2.
ADRRQ	float	Y	ADRRQ is the company reported unweighted average of total demand deposits for the quarter. If no average is reported, then this is the actual figure.
AJEXQ	float	Y	AJEXQ is the quarterly company adjustment factor; it is cumulative by ex-date.
AJPQ	float	Y	AJPQ is the quarterly company adjustment factor, as applied to the dividends per share by payable date; it is cumulative by payable date.

Field	Type	Nullable	Description
APDEDATEQ	datetime	Y	APDEDATEQ is the actual date the company closes accounting for the period.
BSPRQ	varchar(9)	Y	BSPRQ is the balance sheet presentation. BSPR cross-references with CsgRef where CsgNtrmColDesc.bspr = CsgRef.refcd1 and CsgRef.reftype = 5.
COMPSTQ	varchar(9)	Y	COMPSTQ is the comparability status. It cross-references with CsgRef where CsgNtrmColDesc.compst = CsgRef.refcd1 and CsgRef.reftype = 7.
CURCDQ	varchar(4)	Y	CURCDQ is company ISO currency code. Cross-reference CURCDQ with CsgRef where CsgNtrmColDesc.compst = CsgRef.refcd1 and CsgRef.reftype = 36.
CURNCDQ	varchar(4)	Y	CURNCDQ is the native currency in which the company reports its financial data.
CURRTRQ	float	Y	CURRTRQ is the exchange rate used to translate non-U.S. currency amounts into U.S. Dollars. The conversion rate is the rate as of the date of the company's balance sheet. When an international company reports in U.S. Dollars, the translation rate is 1.000.
CURUSCNQ	float	Y	CURUSCNQ is the exchange rate used to translate Canadian currency into U.S. Dollars, as published in the Federal Reserve period rates. This item is available only when a company reports in both U.S. and Canadian accounting standards.
DATAQTR	varchar(7)	Y	DATAQTR shows the calendar year and quarter as YYYYQQ, with the four calendar quarters defined as: – Q1 (February – April) – Q2 (May – July) – Q3 (August – October) – Q4 (November – January)
DATAFQTR	varchar(7)	Y	DATAFQTR shows the fiscal year and quarter as YYYYQQ, where 2007Q1 would represent the fiscal quarter July-September 2006 for a company whose fiscal year ends in June 2007.
FDATEQ	datetime	Y	FDATEQ is the date the data is finalized for the quarter.
FINALQ	varchar(3)	Y	FINALQ indicates that all quarterly fundamental items are available and have been delivered.
FQTR	tinyint	Y	FQTR is the fiscal quarter of the company, depending upon the quartile of the fiscal year in which the data falls.
FYEARQ	smallint	Y	FYEARQ is the fiscal year of the current fiscal end-of-quarter month.
OGMQ	varchar(9)	Y	OGMQ is the Quarterly Oil and Gas Method. OGM refers to the method of revenue reporting used by the oil and gas company.
PDATEQ	datetime	Y	PDATEQ is the preliminary date the data for the company is updated for that quarter.
PDQ	tinyint	Y	PDQ indicates the number of months in the quarter for the reporting period.
PDSA	tinyint	Y	PDSA indicates the number of months in the semi-annual reporting period.
PDYTD	tinyint	Y	PDYTD indicates the number of months in the year-to-date reporting period.
RDQ	datetime	Y	RDQ is the first public reporting date of the quarterly earnings per share.
RP	varchar(3)	Y	RP is the interim reporting periodicity of a company for a specific year. The reporting period will be either Q (quarterly) or (SA) semiannual.
SCFQ	int	Y	SCFQ is the cash flow format for the quarter.
SRCQ	int	Y	SRCQ is the source document for the quarter.
STALTQ	varchar(3)	Y	STALTQ is the status alert.
UPDQ	smallint	Y	UPDQ is the update code.

CsgNtrmCoQ: Compustat Global Company Quarterly Fundamental Data

This table contains quarterly company fundamental data.

Indexes		Index Fields	
pkey_CsgNtrmCoQ (Clustered)		GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM	
CsgNtrmCoQ_1		GVKEY, ITEM	
CsgNtrmCoQ_2		GVKEY, ITEM, DATADATE	
CsgNtrmCoQ_3		GVKEY, INDFMT, CONSOL, DATAFMT, ITEM, DATADATE	
CsgNtrmCoQ_4		GVKEY, CONSOL, DATAFMT, ITEM, DATADATE	
CsgNtrmCoQ_5		GVKEY, INDFMT, DATAFMT, ITEM, DATADATE	
CsgNtrmCoQ_6		GVKEY, DATAFMT, ITEM, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with Csgltm. ITEM is a key field.
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DATACODE indicates non-normal values. DATACODE values are: – 0 (Normal) – 1 (Not available)

Field	Type	Nullable	Description
			– 2 (Semi-annual figure) – 3 (Annual figure) – 4 (Combined figure) – 8 (Insignificant figure)

CsgNtrmCoSa: Compustat Global Semi-Annual Fundamentals

This table contains semi-annual company fundamental data.

Indexes	Index Fields
pkey_CsgNtrmCoSa (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmCoSa_1	GVKEY, ITEM
CsgNtrmCoSa_2	GVKEY, ITEM, DATADATE
CsgNtrmCoSa_3	GVKEY, INDFMT, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoSa_4	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoSa_5	GVKEY, INDFMT, DATAFMT, ITEM, DATADATE
CsgNtrmCoSa_6	GVKEY, DATAFMT, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	smallint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.

Field	Type	Nullable	Description
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with Csgltm. ITEM is a key field.
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DATACODE indicates non-normal values. DATACODE values are: – 0 (Normal) – 1 (Not available) – 2 (Semi-annual figure) – 3 (Annual figure) – 4 (Combined figure) – 8 (Insignificant figure)

CsgNtrmCoYtd: Compustat Global Company Year-to-Date Fundamentals

This table contains company year-to-date fundamental data.

Indexes	Index Fields
pkey_CsgNtrmCoYtd (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmCoYtd_1	GVKEY, ITEM
CsgNtrmCoYtd_2	GVKEY, ITEM, DATADATE
CsgNtrmCoYtd_3	GVKEY, INDFMT, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoYtd_4	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
CsgNtrmCoYtd_5	GVKEY, INDFMT, DATAFMT, ITEM, DATADATE
CsgNtrmCoYtd_6	GVKEY, DATAFMT, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with Csgltm. ITEM is a key field.
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DATACODE indicates non-normal values. DATACODE values are: – 0 (Normal) – 1 (Not available) – 2 (Semi-annual figure) – 3 (Annual figure) – 4 (Combined figure) – 8 (Insignificant figure)

CsgNtrmSec: Compustat Global Issue Fundamentals

This table contains security-level fundamental data.

Indexes	Index Fields
pkey_CsgNtrmSec (Clustered)	GVKEY, IID, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmSec_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE
CsgNtrmSec_2	GVKEY, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
IID	varchar(4)	N	IID is the global issue ID. The IID is an alphanumeric character code. IID consists of a security-identifying numeric component and a population-identifying alpha component. The numeric component distinguishes a security from other securities issued by a company. The alpha component W indicates that the security is traded on a non-Canadian, non-U.S. exchange; C indicates the issue is traded on a Canadian exchange; and no alpha character indicates the security is traded in the United States. This item is a key field. Cross reference IID with GVKEY to uniquely identify securities.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) – 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) – 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined)

Field	Type	Nullable	Description
			– 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: – 13 (HIST_STD Standardized data collected from the company's original filing.) – 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with Csgltm. ITEM is a key field.
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DATACODE indicates non-normal values. DATACODE values are: – 0 (Normal) – 1 (Not available) – 2 (Semi-annual figure) – 3 (Annual figure) – 4 (Combined figure) – 8 (Insignificant figure)

CsgNtrmSecFnt: Compustat Global Issue Fundamental Footnotes

This table contains footnotes for the security-level fundamental data.

Indexes	Index Fields
pkey_CsgNtrmSecFnt (Clustered)	GVKEY, IID, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, ITEM
CsgNtrmSecFnt_1	GVKEY, ITEM
CsgNtrmSecFnt_2	GVKEY, IID, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.venture = CsgCmp.gvkey where GSecMapX.venture = 3
IID	varchar(4)	N	IID is the global issue ID. The IID is an alphanumeric character code. IID consists of a security-identifying numeric component and a population-identifying alpha component. The numeric component distinguishes a security from other securities issued by a company. The alpha component W indicates that the security is traded on a non-Canadian, non-U.S. exchange; C indicates the issue is traded on a Canadian exchange; and no alpha character indicates the security is traded in the United States. This item is a key field. Cross reference IID with GVKEY to uniquely identify securities.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: – 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.)

Field	Type	Nullable	Description
			9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) 16 (ISSUE Issue-level fundamentals.) This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: 6 (C Consolidated – parent and subsidiary combined) 7 (P Pre-FASB) 8 (R Pro-forma) 10 (D Pre-divestiture) 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
DATAFMT	tinyint	N	DATAFMT describes the method of data reporting and collection. DATAFMT values for Compustat Global are: 13 (HIST_STD Standardized data collected from the company's original filing.) 15 (RST_STD Standardized restated data collected from the company's subsequent filings.) This item is a key field.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with Csgltn. ITEM is a key field.
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

CsgNtrmSecIDesc: Compustat Global Issue Description

Use this table to retrieve quarterly security description data including the adjustment factor and currency.

Indexes		Index Fields	
pkey_CsgNtrmSecIDesc (Clustered)		GVKEY, IID, DATADATE, INDFMT, CONSOL, FYR	
Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.vencode = CsgCmp.gvkey where GSecMapX.ventype = 3
IID	varchar(4)	N	IID is the global issue ID. The IID is an alphanumeric character code. IID consists of a security-identifying numeric component and a population-identifying alpha component. The numeric component distinguishes a security from other securities issued by a company. The alpha component W indicates that the security is traded on a non-Canadian, non-U.S. exchange; C indicates the issue is traded on a Canadian exchange; and no alpha character indicates the security is traded in the United States. This item is a key field. Cross reference IID with GVKEY to uniquely identify securities.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
INDFMT	tinyint	N	INDFMT denotes whether a company reports in a Financial Services or Industrial format. INDFMT cross-references with CSKEYCODE. INDFMT integer values are: 5 (INDL Industrial, including manufacturing, retail, construction and other commercial non-financial services.) 9 (FS Financial Services, including banks, insurance companies, broker or dealers, real estate, and other financial services.) 16 (ISSUE Issue-level fundamentals.)

Field	Type	Nullable	Description
			This item is a key field.
CONSOL	tinyint	N	CONSOL describes the level of consolidation in the company's financial statements. Levels of consolidation are: – 6 (C Consolidated – parent and subsidiary combined) – 7 (P Pre-FASB) – 8 (R Pro-forma) – 10 (D Pre-divestiture) – 14 (N Non-consolidated) This item is a key field. CONSOL cross-references with CSKEYCODE where CONSOL = CSKEYCODE.Code.
FYR	tinyint	N	FYR is the fiscal year-end month. This item is a key field.
AJEXIQ	float	Y	AJEXIQ is the quarterly security-level adjustment factor; it is cumulative by ex-date.
CURCDQ	varchar(4)	Y	CURCDQ is the ISO currency code. Cross-reference CURCDQ with CsgRef where CsgNtrmSecDesc.compst = CsgRef.refcd1 and CsgRef.reftype = 36.

CsgRef: Compustat Global Code Reference

This table contains values for the Compustat global code reference.

Indexes	Index Fields
pkey_CsgRef (Clustered)	REFTYPE, REFCD1, REFCD2

Field	Type	Nullable	Description
REFTYPE	smallint	N	The combination of REFTYPE and REFCD1 provides descriptions across all Csg* tables. REFTYPE is defined below, on page 35.
REFCD1	varchar(11)	N	The combination of REFTYPE and REFCD1 provides descriptions across all Csg* tables.
REFCD2	varchar(11)	N	
REFDESC	varchar(255)	Y	REFDESC is the textual description of the REFTYPE.
REFSTAT	varchar(2)	Y	

REFTYPE codes

code	definition	code	definition
1	sections	22	auditors opinion
2	accounting standard	23	price status
3	acquisition method	24	security status
4	auditors	25	security adjustment descriptions
5	balance sheet presentation	26	S&P sector codes
6	cash flow format	27	SIC codes
7	comparability status	28	S&P industry codes
8	country/FIC code	29	S&P major index code
9	data code	30	status alert
10	document source	31	state/province
11	exchange codes	32	officers titles
12	exchange rate report type	33	update codes
13	footnotes	34	index value code
14	Fortune industry codes	35	S&P major index code
15	GIC code	36	currency
16	reason for inactivation/deletion	37	consolidation
17	income statements	38	source document
18	industry	39	industry presentation

code	definition	code	definition
19	inventory valuation method	40	data format
20	issue type	41	fundamental footnote code
21	NAICS code	42	industry format

CsgSad: Compustat Global Security Annual Period Descriptors

This table contains information on annually-based security descriptors.

Indexes	Index Fields
pkey_CsgSad (Clustered)	SECID, DATADATE

Field	Type	Nullable	Description
SECID	int	N	SECID is synonymous to IID. SECID is the primary key across all CsgS* tables.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
AJEXI	float	Y	AJEXI is the annual cumulative adjustment factor on the ex-date.
CURCDI	varchar(4)	Y	CURCDI is the security-level ISO currency code. Cross-reference CURCDL with CsgRef where CsgSad.curcdi = CsgRef.refcd1 and CsgRef.reftype = 36.
FYR	smallint	Y	FYR is the fiscal year-end month. This item is a key field.

CsgSaf: Compustat Global Security Annual Fundamentals

This table contains security-level annual fundamental data.

Indexes	Index Fields
pkey_CsgSaf (Clustered)	SECID, ITEM, DATADATE

Field	Type	Nullable	Description
SECID	int	N	SECID is synonymous to IID. SECID is the primary key across all CsgS* tables.
ITEM	smallint	N	ITEM identifies standardized fundamental data with related analyst notes or transparency. Cross reference ITEM with CsgItn. ITEM is a key field.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
DATA CODE	tinyint	Y	DATA CODE indicates non-normal values. DATA CODE values are: 0 (Normal) 1 (Not available) 2 (Semi-annual figure) 3 (Annual figure) 4 (Combined figure) 8 (Insignificant figure)
FOOTNOTE	varchar(9)	Y	Cross-reference FOOTNOTE with CsgRef where CsgSaf.footnote = CsgRef.refcd1 and CsfRef.reftype = 13.
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.

CsgSdp: Compustat Global Security Daily Price Data

Use this table to retrieve security daily price data.

Indexes	Index Fields
pkey_CsgSdp (Clustered)	SECID, DATADATE, CURCDD

Field	Type	Nullable	Description
SECID	int	N	SECID is synonymous to IID. SECID is the primary key across all CsgS* tables.

Field	Type	Nullable	Description
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
CURCDD	varchar(4)	N	CURCDD is the ISO currency code. Cross-reference with CsgRef where CsgSdp.currdd = CsgRef.refcd1 and CsgRef.reftype = 36.
ADRRRC	float	Y	ADRRRC represents the number of an international company's common or ordinary shares equivalent to one American Depositary Receipt (ADR) or one American Depositary Share (ADS).
AJEXDI	float	Y	AJEXDI is the security-level cumulative adjustment factor on the ex-date.
CSHOC	float	Y	CSHOC is the shares outstanding.
CSHTRD	float	Y	CSHTRD is the daily trading volume.
DVI	float	Y	DVI is the indicated annual dividend (current).
EPS	float	Y	EPS is the earnings per share (current).
EPSMO	tinyint	Y	EPSMO is the earnings per share month (current).
PRCCD	float	Y	PRCCD is the daily closing price.
PRCHD	float	Y	PRCHD is the daily high price.
PRCLD	float	Y	PRCLD is the daily low price.
PRCOD	float	Y	PRCOD is the range of prices at which the first bids and offers were made or the first transactions were completed.
PRCSTD	smallint	Y	PRCSTD is the daily price status code. PRCSTD cross-references with CsgRef where CsgSdp.currdd = CsgRef.refcd1 and CsgRef.reftype = 23.
QUNIT	float	Y	QUNIT is the price quotation unit.

CsgSdv: Compustat Global Security Dividend Data

This table contains security dividend data.

Indexes	Index Fields
pkey_CsgSdv (Clustered)	SECID, DATADATE, CURCDDV

Field	Type	Nullable	Description
SECID	int	N	SECID is synonymous to IID. SECID is the primary key across all CsgS* tables.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
CURCDDV	varchar(4)	N	CURCDDV is the dividend ISO currency code. Cross-reference CURCDDV with CsgRef where CsgSdv.currdd = CsgRef.refcd1 and CsgRef.reftype = 36.
ANNCDATE	datetime	Y	ANNCDATE is the date the directors declare the next dividend in the format YYYYMMDD.
CAPGN	float	Y	CAPGN is the capital gain.
CHEQV	float	Y	CHEQV is the cash equivalent distributions per share.
DIV	float	Y	DIV is the daily dividends per share on the ex-date.
DIVD	float	Y	DIVD is the cash dividend paid to shareholders. This figure excludes special dividends, cash equivalents, and capital gains.
DIVOP	float	Y	DIVOP is the optional dividend.
DIVSP	float	Y	DIVSP is a non-recurring, special dividend.
DVRATED	float	Y	DVRATED is an approximate indicator of dividend performance.
PAYDATE	datetime	Y	PAYDATE is the date shareholders of record will be sent a check for the declared dividend.
RECORDDATE	datetime	Y	RECORDDATE is the date by which a shareholder must own shares to be entitled to a dividend.

CsgSec: Compustat Global Security Data

This table contains data on global securities.

Indexes	Index Fields
pkey_CsgSec (Clustered)	GVKEY, IID
CsgSec_1	SECID
CsgSec_2	SEDOL, SECID
CsgSec_3	ISIN, SECID
CsgSec_4	NAME, SECID

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key. It is a primary key for all companies in all Csg* tables. Use GVKEY with CsgCmp to obtain company-level information, or CsgSec to obtain security-level information. For example, for security mapping, to link to GSecMapX: GSecMapX.ventype = CsgCmp.gvkey where GSecMapX.ventype = 3
IID	varchar(4)	N	IID is the global issue ID. The IID is an alphanumeric character code. IID consists of a security-identifying numeric component and a population-identifying alpha component. The numeric component distinguishes a security from other securities issued by a company. The alpha component W indicates that the security is traded on a non-Canadian, non-U.S. exchange; C indicates the issue is traded on a Canadian exchange; and no alpha character indicates the security is traded in the United States. This item is a key field. Cross reference IID with GVKEY to uniquely identify securities.
CUSIP	varchar(10)	Y	CUSIP uniquely identifies a company. CUSIP is a nine-digit code: the first six digits identify the issuer, the seventh and eighth digit identify the security, and the ninth digit is the check digit. A CUSIP with an X as the last digit indicates that the security is inactive.
DLDEI	datetime	Y	DLDEI is the security inactivation date.
DLRSNI	varchar(9)	Y	DLRSNI is the security inactivation reason. DIRSNL cross-references with CsgRef where CsgSec.dlrsni = CsgRef.refcd1 and CsgRef.reftype = 16. DLRSNI is defined below on page 39.
DSCI	varchar(29)	Y	DSCI is the security description.
EPF	char(1)	Y	EPF indicates whether the security participates in the company's earnings. Y (Yes) indicates the security participates in earnings. If the security does not participate in the company's earnings, this item is blank.
EXCHG	smallint	Y	EXCHG is the stock exchange.
EXCNTRY	varchar(4)	Y	EXCNTRY is the stock exchange country code. Cross-reference EXCNTRY with CsgRef where CsgSec.excntry = CsgRef.refcd1 and CsgRef.reftype = 8.
IBTIC	varchar(7)	Y	IBTIC is the unique IBES security symbol.
ISIN	varchar(13)	Y	ISIN is the international security identification number.
SECSTAT	varchar(2)	Y	SECSTAT is the security status marker. SECSTAT cross-references with CsgRef where CsgSec.secstat = CsgRef.refcd1 and CsgRef.reftype = 24.
SEDOL	varchar(8)	Y	SEDOL is the Stock Exchange Daily Official List security ID, as determined by the International Stock Exchange in London.
TIC	varchar(21)	Y	TIC is the ticker/trading symbol.
TPCI	varchar(9)	Y	TPCI is the issue type. Cross-reference TPCI with CsgRef where CsgSec.tpci = CsgRef.refcd1 and CsgRef.reftype = 20.
SECID	int	Y	SECID is synonymous to IID. SECID is the primary key across all CsgS* tables.
NAME	varchar(250)	Y	NAME is the company name.

DLRSNI Codes

code	definition
01	Acquisition or merger
02	Bankruptcy
03	Liquidation
04	Reverse acquisition – 1983 forward
05	No longer fits original format – 1978 forward
06	Leveraged buyout – 1982 forward
07	Other – for example, no longer files with SEC – but pricing continues
09	Now a private company
10	Other – for example, no longer files with SEC
11	Local Settlement Code inactivated because the issue matured, expired or was called; there is no successor code
12	Local Settlement Code inactivated; a successor settlement code was established and the security was changed, as in a par value change
13	Price source for the SEDOL is no longer available and the security is now identified under a different SEDOL
14	Fully or partly paid issue was replaced by a subsequent installment; there is a successor code
20	Other – issue-level activity; company remains active on the file

CSGSSPLIT: Compustat Global Security Stock Split Data

This table contains information on security stock splits.

Indexes	Index Fields
pkey_CsgXrd (Clustered)	SECID, DATADATE

Field	Type	Nullable	Description
SECID	int	N	SECID is synonymous to IID. SECID is the primary key across all CsgS* tables.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
SPLIT	float	Y	SPLIT is the split ratio of the stock.

CsgXrd: Compustat Global Currency Daily Exchange Rate Data

Use this table to retrieve daily exchange rate data.

Indexes	Index Fields
pkey_CsgXrd (Clustered)	TOCURD, DATADATE

Field	Type	Nullable	Description
TOCURD	varchar(4)	N	TOCURD is the currency into which the daily translation rate translates. For example, in the translation from Euros into U.S. Dollars, the code for U.S. Dollars is the TOCURD. Use TOCURD in conjunction with FROMCURD. Cross-reference TOCURD with CsgRef, where CsgXrd.tocurd = CsgRef.refcd1 and CsgRef.reftype = 36.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
EXRATD	float	Y	EXRATD is the daily exchange rate.
EXRATTPD	varchar(3)	Y	EXRATTPD is the daily exchange rate report type. EXRATTPD cross-references with CsgRef where CsgXrd.exrattpd = CsgRef.refcd1 and CsgRef.reftype = 12.
FROMCURD	varchar(4)	Y	FROMCURD is the ISO currency code for the starting currency in a daily currency translation. For example, in the translation from Euros into U.S. Dollars, the code for Euros is the FROMCURD. Cross-reference FROMCURD with CsgRef, where CsgXrd.fromcurd = CsgRef.refcd1 and CsgRef.reftype = 36.

CsgXrm: Compustat Global Currency Monthly Exchange Rate Data

Use this table to retrieve monthly exchange rate data.

Indexes		Index Fields	
pkey_CsgXrm (Clustered)		TOCURM, DATADATE	

Field	Type	Nullable	Description
TOCURM	varchar(4)	N	TOCURM is the currency into which the monthly translation rate translates. For example, in the translation from Euros into U.S. Dollars, the code for U.S. Dollars is the TOCURM. Use TOCURM in conjunction with FROMCURM. Cross-reference TOCURM with CsgRef, where CsgXrm.tocurm = CsgRef.refcd1 and CsgRef.reftype = 36.
DATADATE	datetime	N	DATADATE is the company's fiscal period end date. For security-level data, it is the trade date for high, low, or close prices. This item is a key field.
EXRAT10M	float	Y	EXRAT10M is the average exchange rate, and 10 is the monthly duration.
EXRAT11M	float	Y	EXRAT11M is the average exchange rate, and 11 is the monthly duration.
EXRAT12M	float	Y	EXRAT12M is the average exchange rate, and 12 is the monthly duration.
EXRAT13M	float	Y	EXRAT13M is the average exchange rate, and 13 is the monthly duration.
EXRAT14M	float	Y	EXRAT14M is the average exchange rate, and 14 is the monthly duration.
EXRAT15M	float	Y	EXRAT15M is the average exchange rate, and 15 is the monthly duration.
EXRAT16M	float	Y	EXRAT16M is the average exchange rate, and 16 is the monthly duration.
EXRAT17M	float	Y	EXRAT17M is the average exchange rate, and 17 is the monthly duration.
EXRAT18M	float	Y	EXRAT18M is the average exchange rate, and is the monthly duration.
EXRAT1M	float	Y	EXRAT1M is the average exchange rate, and 1 is the monthly duration
EXRAT2M	float	Y	EXRAT2M is the average exchange rate, and 2 is the monthly duration.
EXRAT3M	float	Y	EXRAT3M is the average exchange rate, and 3 is the monthly duration.
EXRAT4M	float	Y	EXRAT4M is the average exchange rate, and 4 is the monthly duration.
EXRAT5M	float	Y	EXRAT5M is the average exchange rate, and 5 is the monthly duration.
EXRAT6M	float	Y	EXRAT6M is the average exchange rate, and 6 is the monthly duration.
EXRAT7M	float	Y	EXRAT7M is the average exchange rate, and 7 is the monthly duration.
EXRAT8M	float	Y	EXRAT8M is the average exchange rate, and 8 is the monthly duration.
EXRAT9M	float	Y	EXRAT9M is the average exchange rate, and 9 is the monthly duration.
EXRATM	float	Y	EXRATM is the month-end currency translation rate; it is the official pricing released at 4PM London closing.
FROMCURM	varchar(4)	Y	FROMCURM is the ISO currency code for the starting currency in a monthly currency translation. For example, in the translation from Euros into U.S. Dollars, the code for Euros is the FROMCURD. Cross-reference with CsgRef where CsgXrm.tocurm = CsgRef.refcd1 and CsgRef.reftype = 36.

CSKEYCODE: Compustat XF Security Information

This table is also part of the Compustat North American Xpressfeed schema. CSKEYCODE has been added to the Global schema due to Compustat's integer conversion. This table contains integer values for INDFMT, DATAFMT, and CONSOL..

Indexes		Index Fields	
pkey_CSKEYCODE (Clustered)		CODE	

Field	Type	Nullable	Description
Code	tinyint	N	Code is the numerical value for the field listed under FieldName.
StringValue	varchar(13)	Y	StringValue is the Compustat-provided value for the key field. Please consult the Compustat data guide for detailed explanation of the available values.
FieldName	varchar(31)	Y	FieldName contains the name of the field described (CONSOL, CURCD, DATAFMT, INDFMT)

Field	Type	Nullable	Description
Description	varchar(81)	Y	Description is currently unused.

NOTE

For more information on accessing Compustat documentation, see [Accessing Standard & Poor's Compustat Documentation](#) on page 5.

Copyright © 2024 London Stock Exchange Group plc and its group of companies (LSEG) and/or its affiliates. All rights reserved. The LSEG content received through this service is the intellectual property of LSEG or its third party suppliers. Republication or redistribution of content provided by LSEG is expressly prohibited without the prior written consent of LSEG, except where permitted by the terms of the relevant LSEG service agreement. Neither LSEG nor its third party suppliers shall be liable for any errors, omissions or delays in content, or for any actions taken in reliance thereon. LSEG and its logo are trademarks of LSEG.

For more information visit us at www.lseg.com



LSEG DATA &
ANALYTICS