

LSEG Quantitative Analytics

Database Schema for Compustat North America

Version 1.1.5



LSEG DATA &
ANALYTICS

Contents

1 Introduction.....	11
In This Document.....	11
Intended Readership.....	11
Table Name Conventions.....	11
Mapping Information	11
Pervasive and Oracle.....	12
Zero Values and Nulls.....	12
Accessing Standard & Poor's Compustat Documentation	12
Service and Support	12
Feedback	13
Your Personal Information	13
2 Compustat Schema Overview	14
Legacy Tables.....	14
3 Schema for Compustat Xpressfeed (All Subscriptions)	15
CSCoFileDate: Active Company File Dates	15
CSICoFileDate: Inactive Company File Dates	15
GCSKeyCode: Compustat XF Security Information.....	16
CSNAItem: Compustat XF Item Information	16
4 Schema for Compustat XF Daily	18
CSIdxIndex: Index Identifier Information	18
CSIdxCstHis: Index Constituent History.....	19
CSIdxCstHisSnP: SPDJI Index Constituent History.....	19
CSIdxDaily: Index Daily Market Values.....	20
CSIdxMth: Index Monthly Market Values	20
CSEcIndMth: Monthly Economic Industry	21
CSExRtDly: Daily Exchange Rate.....	21
CSExRtMth: Monthly Exchange Rate	21
CSSPInd: S&P Index Securities.....	22
CSSPIndDly: S&P Index Daily	22
CSSPIndMth: S&P Index Monthly	23
CSSecSPInd: S&P Index Securities	23
CSSPIdxCst: S&P Index Constituent Daily	24
CSCoAAudit: Compustat XF Audit Information	25
CSCoADesInd: Compustat XF Company Descriptions.....	26
CSCoAdjFact: Compustat XF Adjustment Factors.....	28

CSCoAFndDC1: Compustat XF Annual Fundamentals Data Codes 1	28
CSCoAFndDC2: Compustat XF Annual Fundamentals Data Codes 2	28
CSCoAFnd1: Compustat XF Annual Fundamentals 1	29
CSCoAFnd2: Compustat XF Annual Fundamentals 2	29
CSCoAlnvVal: Compustat XF Inventory Valuation Data	29
CSCoAMkt: Compustat XF Market Data	30
CSCoFortune: Fortune 500 Group	30
CSCoHGIC: GICS History	31
CSCoIAudit: Interim Auditor Group	31
CSCoIDesInd: Company Interim Descriptor Group	32
CSCoIFntYTD: Company Interim Fundamentals – Year-to-Date Footnotes	33
CSCoIFntQ: Company Quarterly Fundamental Footnotes	33
CSCoIFntSA: Company Quarterly Fundamental Footnotes	34
CSCoIMkt: Interim Market Group	35
CSCoIndstryPres: Company Industry Presentation	35
CSCoIndustry: Industry Classification Presentation	36
CSCoMth: Company Monthly	36
CSCoOffTitl: Company Officers	36
CSCoAFntInd: Company Annual Fundamental Footnotes	37
CSCoIFndQ: Company Interim Fundamentals – Quarterly	37
CSCoIFndYTD: Company Interim Fundamentals – Year to Date	38
CSCoIFndSA: Company Interim Fundamentals – Semi Annual	39
CSCurrency: Xpressfeed Currencies	40
CSRAccStd: Accounting Standards Reference Data	40
CSRAcqMeth: Acquisition Methods Reference Data	41
CSRAuditors: Auditors Reference Data	41
CSRAuopIC: Internal Control Auditor Reference Data	41
CSRBalPres: Balance Sheet Presentations Reference Data	41
CSRCFFormt: Cash Flow Formats Reference Data	42
CSRCoIndPre: Company Industry Presentation Reference Data	42
CSRCompStat: Comparability Stats Reference Data	42
CSRConsol: Level of Consolidation Reference Data	43
CSRCountry: Country Reference Data	43
CSRcstClsCd: Index Constituent Classification Reference Data	43
CSRDataCode: Data Codes Reference Data	43
CSRDataFmt: Data Format Reference Data	44
CSRDocSrc: Annual Source Document Codes Reference Data	44
CSRExCodes: Exchange Trading Sys Codes Reference Data	44
CSRExtTyp: Exchange Rate Types Reference Data	44

CSRfndFntCd: Fundamental Footnote Codes Reference Data	45
CSRFootnts: Footnote Codes	45
CSRForICd: Fortune Industry Code Reference Data	45
CSRGICCd: Global Industry Code Reference Data	46
CSRHCalendr: Holiday Calendar	46
CSRIIdxClsCd: Index Classification Reference Data	46
CSRInactvCd: Inactivation Code Reference Data	46
CSRIncStats: Income Statement Models Reference Data	47
CSRIndFmt: Industry Format Reference Data	47
CSRIndSec: S&P Industry Sector Codes Reference Data	47
CSRInvVal: Inventory Valuations Reference Data	48
CSRIssueTyp: Issue Types Reference Data	48
CSRMajIdxCl: Major Index—Classification Reference Data	48
CSRNAICCd: NAICS Code Reference Data	48
CSROffCRSO: Officer Sign-Off Reference Data	49
CSROGMethod: Oil and Gas Method Reference Data	49
CSROpinions: Opinions Reference Data	49
CSRPrStat: Price Status Codes Reference Data	49
CSRQSrcDoc: Quarterly Source Document Code Reference Data	50
CSRSecStat: Security Status Codes	50
CSRSEctors: S&P Sector Codes Reference Data	50
CSRSICCd: SIC Code Reference Data	51
CSRSPICd: S&P Industry Index Code Reference Data	51
CSRSPMICd: S&P Major Industry Codes Reference Data	51
CSRStatAlrt: Status Alerts Reference Data	51
CSRStates: States Reference Data	52
CSRStkO: Stock Ownership Reference Data	52
CSRTitles: Title Codes Reference Data	52
CSRUpdates: Update Codes Reference Data	52
CSSecMth: Monthly Descriptor	53
CSSecMthDiv: Monthly Dividend	53
CSSecMthPrc: Monthly Item	54
CSSecMthSpt: Monthly Stock Splits	54
CSSecMSptFn: Monthly Stock Split Footnotes	54
CSSecMDivFn: Monthly Dividend Footnotes	55
CSVCompany: Compustat XF Company Information	55
CSVSecurity: Compustat XF Security Information	57
5 Compustat XF Daily Historical	58
CSBkCoAFntInd: Annual Fundamental Footnotes Historical	58

CSBkCoAAudit: Compustat XF Audit Information Historical	58
CSBkCoADesInd: Compustat XF Company Descriptions Historical	59
CSBkCoAFndDC1: Compustat XF Annual Fundamentals Data Codes 1 Historical	61
CSBkCoAFndDC2: Compustat XF Annual Fundamentals Data Codes 2 Historical	61
CSBkCoAFnd1: Compustat XF Annual Fundamentals 1 Historical	62
CSBkCoAFnd2: Compustat XF Annual Fundamentals 2 Historical	62
CSBkCoAInvVal: Compustat XF Inventory Valuation Data Historical	63
CSBkCoAMkt: Compustat XF Market Data Historical	63
CSBkCoFortune: Fortune 500 Group Historical	64
CSBkCoIAudit: Interim Auditor Group Historical	64
CSBkCoIDesInd: Company Interim Descriptor Historical	65
CSBkCoIFntYTD: Company Interim Fundamentals – Year to Date Footnotes Historical	66
CSBkCoIFntQ: Company Quarterly Fundamental Footnotes Historical	66
CSBkCoIFntSA: Company Quarterly Fundamental Footnotes Historical	67
CSBkCoIMkt: Interim Market Group Historical	68
CSBkCoIndstryPres: Company Industry Presentation Historical	68
CSBkCoIndustry: Industry Classification Presentation Historical	69
CSBkCoMth: Company Monthly Historical	69
CSBkCoIFndQ: Company Interim Fundamentals – Quarterly Historical	69
CSBkCoIFndYTD: Company Interim Fundamentals – Year to Date Historical	70
CSBkCoIFndSA: Company Quarterly Fundamentals Historical	71
CSBkSecM: Monthly Descriptor Historical	72
CSBkSecMDv: Monthly Dividend Historical	72
CSBkSecMPrc: Monthly Item Historical	73
CSBkSecMSS: Monthly Stock Splits Historical	73
CSBkSecMSSF: Monthly Stock Split Footnotes	74
CSBkSecMDvFn: Monthly Dividend Footnotes	74
6 Compustat XF Daily Pension	75
CSACoPnFndQ: New Company Quarterly Pension and Post-Retirement Data	75
CSACoPnFndYTD: New Company Year-to-Date Pension and Post-Retirement Data	76
CSACoPnFntQ: Company Quarterly and Post-Retirement Footnotes	77
CSACoPnFntYTD: New Company Year-to-Date Pension and Post-Retirement Footnotes	77
CSACoPnFndA: Company Annual Pension and Post-Retirement Data	78
CSACoPnFntA: Company Annual and Post-Retirement Footnotes	79
7 Compustat XF Daily Pension Historical	80
CSBkCoPnFntA: Annual Pension Footnotes Historical	80
CSBkCoPnFndA: Company Annual Pension and Post-Retirement Data Historical	80
8 Compustat XF Daily Industry	82
CSACoIndStQC: Quarterly Industry Statistics	82

CSACoIndStQP: Company Quarterly Industry Statistics	82
CSACoIndStA: Annual Industry Statistics	83
CSACoIndFntQ: Quarterly Industry Statistics Footnotes	84
CSACoIndFntYTD: Year-to-Date Industry Statistics Footnotes	84
CSACoIndFntA: Annual Industry Statistics Footnotes	85
CSACoIndStYTD: Year-to-Date Industry Statistics	85
9 Compustat XF Daily Industry Historical.....	87
CSBkCoIndFntA: Annual Industry Statistics Footnotes Historical	87
CSBkCoIndStQC: Quarterly Industry Statistics Historical	87
CSBkCoIndStQP: Company Quarterly Industry Statistics Historical	88
CSBkCoIndStA: Annual Industry Statistics Historical.....	89
CSBkCoIndFntQ: Quarterly Industry Statistics Footnotes Historical	89
CSBKCOINDFNTYTD: Year-to-Date Industry Statistics Footnotes Historical	90
CSBkCoIndStYTD: Year-to-Date Industry Statistics Historical.....	90
10 Compustat Xpressfeed Banking	92
Compustat Banking Annual Descriptive Information	92
Compustat Banking Annual Data Values	94
Compustat Banking Annual Data Codes.....	94
Compustat Banking Annual Footnote Information.....	95
Compustat Banking Quarterly Bank Data Items.....	95
Compustat Banking Year-to-Date Bank Data Items.....	96
Compustat Banking Quarterly Footnote Information	97
Compustat Banking Year-to-Date Footnote Information	98
Compustat Banking Interim Descriptive Information	98
CSBnkAnn: Compustat Banking Annual	99
CSBnkItem: Compustat Banking Item Descriptions	100
CSBnkQtr: Compustat Banking Quarterly	101
11 Compustat XF Daily Issuer Credit Ratings	102
CSADSPRate: S&P Ratings – Monthly	102
12 Compustat XF Daily Current Issuer Credit Ratings	103
CSADSPRateC: S&P Ratings – Current.....	103
13 Compustat XF Index Fundamentals	104
CSADIdxADes: Annual Index Fundamental Descriptors.....	104
CSADIdxQDes: Quarterly Index Fundamental Descriptors.....	104
CSADIdxAnn: Annual Index Fundamentals	104
CSADIdxQtr: Quarterly Index Fundamentals	105
14 Compustat XF Daily Research	106
CSISecSPInd: S&P Index Inactive Securities	106
CSICoAAudit: Inactive Auditor Group	106

CSICoADesInd: Inactive Annual Descriptor	107
CSICoAdjFact: Inactive Cumulative Adjustment Factors	109
CSICoAFndDC1: Inactive Annual Fundamental Data Codes	109
CSICoAFndDC2: Inactive Annual Fundamental Data Codes	110
CSICoAFnd1: Inactive Annual Fundamental Data	110
CSICoAFnd2: Inactive Annual Fundamental Data	111
CSICoAlnvVal: Inactive Inventory Evaluation Group	111
CSICoAMkt: Inactive Annual Market Data Group	112
CSICoFortune: Inactive Fortune 500 Group.....	113
CSICoHGIC: Inactive GICS History	113
CSICoIAudit: Inactive Interim Auditor Group.....	114
CSICoIDesInd: Inactive Company Interim Descriptor Group	114
CSICoIFntYTD: Inactive Company Interim Fundamentals – Year-to-Date Footnotes.....	115
CSICoIFntQ: Inactive Company Interim Fundamentals – Quarterly Footnotes.....	116
CSICoIFntSA: Inactive Company Interim Fundamentals – Semiannual Footnotes.....	116
CSICoIMkt: Inactive Interim Market Group.....	117
CSICoIndustryPres: Inactive Company Industry Presentation	118
CSICoIndustry: Inactive Industry Classification Presentation.....	118
CSICOMth: Inactive Company Monthly	118
CSICoOffTitl: Inactive Company Officers.....	119
CSICoAFntIND: Inactive Company Annual Fundamental Footnotes	119
CSICoIFndQ: Inactive Company Interim Fundamentals – Quarterly.....	120
CSICoIFndYTD: Inactive Company Interim Fundamentals – Year to Date	120
CSICoIFndSA: Inactive Company Semi-Annual Fundamentals	121
CSISecMth: Inactive Monthly Descriptor.....	122
CSISecMthDiv: Inactive Monthly Dividend	123
CSISecMthPrc: Inactive Monthly Item.....	123
CSISecMthSpt: Inactive Monthly Stock Splits	123
CSISecMSptFn: Inactive Monthly Stock Split Footnotes.....	124
CSISecMDivFN: Inactive Monthly Dividend Footnotes	124
15 Compustat XF Daily Historical Research.....	126
CSIBkCoAFntInd: Inactive Annual Fundamental Footnotes Historical	126
CSIBkCoAAudit: Inactive Auditor Group Historical	126
CSIBkCoADesInd: Inactive Company Annual Descriptor - Industry Format Historical.....	127
CSIBkCoAFndDC1: Inactive Annual Fundamental Data Codes	129
CSIBkCoAFndDC2: Inactive Annual Fundamental Data Codes	129
CSIBkCoAFnd1: Inactive Annual Fundamental Data.....	130
CSIBkCoAFnd2: Inactive Annual Fundamental Data.....	130
CSIBkCoAlnvVal: Inactive Inventory Evaluation Group Historical.....	131

CSIBkCoAMkt: Inactive Annual Market Data Group Historical.....	131
CSIBkCoFortune: Inactive Fortune 500 Group Historical.....	132
CSIBkColAudit: Inactive Interim Auditor Group Historical.....	132
CSIBkColDesInd: Inactive Company Interim Descriptor Historical	133
CSIBkColFntYTD: Inactive Company Interim Fundamentals – Year-to-Date Footnotes Historical.....	134
CSIBkColFntQ: Inactive Company Interim Fundamentals – Quarterly Footnotes Historical.....	135
CSIBkColFntSA: Inactive Company Interim Fundamentals – Semiannual Footnotes Historical.....	135
CSIBkColMkt: Inactive Interim Market Group Historical.....	136
CSIBkColndstryPres: Inactive Company Industry Presentation Historical	136
CSIBkColndstry: Industry Classification Presentation Historical	137
CSIBkCoMth: Inactive Company Monthly Historical	137
CSIBkColFndQ: Inactive Company Interim Fundamentals – Quarterly Historical.....	138
CSIBkColFndYTD: Inactive Company Interim Fundamentals – Year to Date Historical	138
CSIBkColFndSA: Inactive Company Quarterly Fundamentals Historical.....	139
CSIBkSecM: Inactive Monthly Descriptor Historical.....	140
CSIBkSecMDv: Inactive Monthly Dividends Historical	141
CSIBkSecMPrc: Inactive Monthly Prices Historical	141
CSIBkSecMSS: Inactive Monthly Stock Split Factors Historical.....	141
CSIBkSecMSSFn: Inactive Monthly Stock Split Footnotes	142
CSIBkSecMDvFn: Inactive Monthly Dividend Footnotes	142
16 Compustat XF Daily Pension Research	144
CSIACoPnFndQ: Inactive Company Annual Pension and Post-Retirement Footnotes	144
CSIACoPnFndYTD: Inactive Company Year-to-Date Pension and Post-Retirement Data	145
CSIACoPnFntA: Inactive Company Annual and Post-Retirement Footnotes.....	146
CSIACoPnFntQ: Inactive Company Quarterly and Post-Retirement Footnotes.....	146
CSIACoPnFntYTD: Inactive Company Year-to-Date Pension and Post-Retirement Footnotes.....	147
CSIACoPnFndA: Inactive Company Annual and Post-Retirement Data	148
17 Compustat XF Daily Pension Historical Research.....	149
CSIBkCoPnFntA: Inactive Annual Pension Footnotes Historical	149
CSIBkCoPnFndA: Inactive Company Annual and Post-Retirement Data Historical.....	149
18 Compustat XF Daily Industry Research	151
CSIAColndFntA: Inactive Annual Industry Statistics Footnotes	151
CSIAColndStQC: Inactive Quarterly Industry Statistics	151
CSIAColndStQP: Inactive Company Quarterly Industry Statistics	152
CSIAColndStA: Inactive Annual Industry Statistics Historical	153
CSIAColndFntQ: Inactive Quarterly Industry Statistics Footnotes	153
CSIAColndFntYTD: Inactive Year-to-Date Industry Statistics Footnotes	154
CSIAColndStYTD: Inactive Year-to-Date Industry Statistics.....	154
19 Compustat XF Daily Industry Historical Research	156

CSIBkCoINDFNTA: Inactive Annual Industry Statistics Footnotes Historical	156
CSIBkCoINDSTQC: Inactive Quarterly Industry Statistics Historical	156
CSIBkCoINDSTQP: Inactive Company Quarterly Industry Statistics Historical	157
CSIBkCoINDFNTQ: Inactive Quarterly Industry Statistics Footnotes Historical	158
CSIBkCoINDFNTYTD: Inactive Year-to-Date Industry Statistics Footnotes Historical	158
CSIBkCoINDSTA: Inactive Annual Industry Statistics Historical	159
CSIBkCoINDSTYTD: Inactive Year-to-Date Industry Statistics Historical	159
20 Compustat XF Daily Issuer Credit Ratings Research	161
CSIADSPRate: Inactive S&P Ratings – Monthly	161
21 Compustat XF Daily Current Issuer Credit Ratings Research	162
CSIADSPRateC: S&P Ratings – Current	162
22 Compustat Xpressfeed Point-in-Time	163
CSPITAdj: Compustat PIT Adjustment	163
CSPITAdjC: Compustat PIT Adjustment—Canadian	163
CSPITCmp: Compustat PIT Companies	163
CSPITCmpC: Compustat PIT Companies—Canadian	164
CSPITDFnd: Compustat PIT As First Reported and Fully Restated Data	164
CSPITDFndC: Compustat PIT As First Reported and Fully Restated Data—Canadian	165
CSPITDHstFnd: Compustat PIT Historically Restated Data	166
CSPITDHstFndC: Compustat PIT Historically Restated Data—Canadian	166
CSPITFn: Compustat PIT Footnotes	167
CSPITFnC: Compustat PIT Footnotes—Canadian	167
CSPITFndInfo: Compustat PIT Fully Restated Dates Information	168
CSPITFndInfoC: Compustat PIT Fully Restated Dates Information—Canadian	168
CSPITHFndInfo: Compustat PIT Historical Dates Information	169
CSPITHFndInfoC: Compustat PIT Historical Dates Information—Canadian	169
CSPITId: Compustat PIT Historical Identification Information	170
CSPITIdC: Compustat PIT Historical Identification Information—Canadian	170
CSPITItem: Compustat PIT Item Information	171
CSPITMnt: Compustat PIT Monthly Tag Information	171
CSPITMntC: Compustat PIT Monthly Tag Information—Canadian	172
CSPITPQtr: Compustat PIT Quarterly Tag Information	172
CSPITPQtrC: Compustat PIT Quarterly Tag Information—Canadian	174
23 Compustat Xpressfeed Backtest	175
CSBData: Compustat Quarterly As First Reported Data	175
CSBFtn: Compustat AFR Footnotes	175
CSBItem: Compustat AFR Items	176
CSBPrD: Compustat AFR Period Dates	176
24 Compustat Xpressfeed Preliminary Data	178

CSPDesc: Compustat Preliminary Data Coded Item Descriptions.....	178
CSPItem: Compustat Preliminary Data Item Descriptions	178
CSPNData: Compustat Preliminary Numeric Data	179
CSPPrD: Compustat Preliminary Periods Data.....	179
CSPSData: Compustat Preliminary String Data.....	180
25 Compustat FTP Basic Data	181
CSDacPDE: Compustat U.S. Industrial Annual (with data codes)	181
CSCdnPDE: Compustat Canadian Price Dividends and Earnings.....	181
CSDescr: Compustat Business Descriptions	182
CSIndPDE: Compustat U.S. Industrial Price Dividends and Earnings	182
CSSgCmp: Compustat Segment Company	182
CSSgCst: Compustat Segment Customer	183
CSSgCur: Compustat Segment Currency Rate	183
CSSgDtl: Compustat Segment Detail	184
CSSgGeo: Compustat Segment Geographic Area Codes	184
CSSgItm: Compustat Segment Item Value	185
CSSgNAI: Compustat Segment NAICS	186
CSSgPrd: Compustat Segment Products	186
CSSgSrc: Compustat Segment Source	187
26 Compustat FTP Research (Legacy)	188
CSResPDE: Compustat Research Price Dividends and Earnings.....	188

1 Introduction

In This Document

This document provides schema information about the **Compustat North America** tables in Quantitative Analytics.

NOTE

For information about the other Quantitative Analytics tables, refer to the other Database Schema documents posted on the [Quantitative Analytics](#) product page on [MyAccount](#).

The documentation for each table includes these main elements:

- **Vendor Database or License Name** – This element provides the vendor database or license name. Vendor databases generally correspond to vendor licensing options.
- **Table Name: Table Title** – This element provides the table name and title, followed by a description of the table contents.
- **Update Cycle** – This element indicates the frequency of updates from the data vendor. (For specific information about when this update is posted for your use, refer to your update logs. The update log schema description is available in the Database Schema for Quantitative Analytics Core Tables document.)
- **Adjusted** – This element indicates whether the data is stored adjusted, unadjusted, or if adjustment is not applicable (N/A).
- **Indexes, Index Fields** – This element lists the table's index(es) (for example, pkey_CSGCAD) and the index fields. The primary index contains a "pkey_" or "PK_" prefix. Clustered indexes are noted.
- **Field, Type, Nullable, Definition** – This element describes the table's fields, including field names, data types, and whether each field is nullable. The data types in Snowflake have equivalents available. For example, an *int* in SQL Server is a *number* in Snowflake.

Intended Readership

This document is intended for Quantitative Analytics clients licensed to use **Compustat North America** data through LSEG. Note that the tables described in this document may be covered by several licenses; your access to the data in these tables is dependent on the licenses you have. Readers should have basic knowledge of Microsoft SQL Server 2016.

Table Name Conventions

In Quantitative Analytics, database tables are grouped by name. Generally, the first few letters of the table name refer to the data vendor or licensing group. For example, all tables beginning with **CS*** are Compustat North America tables.

Mapping Information

When mapping Compustat North America content, use the VenType and VenCode values shown in the following table. (For more information about mapping or for other vendors' VenType and VenCode values, refer to the Database Schema for Quantitative Analytics Core Tables document, available on the [Quantitative Analytics](#) product page on [MyAccount](#)).

Security VenType Mapping for the SecMapX and GSecMapX Tables

Vendor	SecMapX/GSecMapX VenType	Vendor Table(s)	Vencode = [field]
Compustat Xpressfeed	4	CSVSecurity (domestic); CSGSec (global)	SecIntCode (domestic); SecID (global)

Pervasive and Oracle

This document is specific to Microsoft SQL Server 2016. If you are accessing the data directly through the Pervasive database, you may encounter slight differences in index names and data types. Please note that references to Pervasive and Actian are synonymous.

If you are accessing the data through Oracle, note that field names that correspond to Oracle reserved words are appended with an underscore. For example, field names “Number”, “Synonym”, and “UID” become “Number_”, “Synonym_”, and “UID_” in Oracle.

Zero Values and Nulls

Null values are usually recorded as “NULL”. Occasionally, a table may contain a value of “-99999” or “-9999”; in these cases, there is no recorded data for that period. (It is null.) If the table contains a “0” value, the data was reported as having a “0” value.

Accessing Standard & Poor’s Compustat Documentation

You may also want to refer to documentation provided for Compustat by Standard & Poor’s (S&P). Although this document describes database organization within Quantitative Analytics, it is not intended to replace Compustat documentation. Compustat data mnemonics, footnote codes, and reference items are described in detail in the online Compustat Data Guide.

You can access Compustat documentation at <http://www.compustat.com/>.

If you have a Compustat data license, but do not have a user name and password for the Compustat website, contact Compustat Customer Support:

- Phone: +1 800.523.4534
- Email: clientsupport@standardandpoors.com

Service and Support

[MyAccount](#) is the LSEG portal that provides a single access point for timesaving support services, along with billing, user management, and information.

Statement of Service

The [Quantitative Analytics Service Description](#) is available on the [Quantitative Analytics](#) product page at [MyAccount](#).

Subscribe to Support Channels

You are encouraged to [subscribe](#) to the following support channels to keep informed of changes to products and data, and to be notified of any service issues or change. Please see the *Alerts and Notifications* section in the *Quantitative Analytics Service Description* available on the [Quantitative Analytics](#) product page at MyAccount for detailed instructions.

- **Change Notifications**
 - **Product Change Notifications (PCNs)** detail new, enhanced, or changed functionality, which may require your action, in products that you use.
 - **Data Notifications (DNs)** alert you to upcoming changes to real-time and historical data across all asset classes that are relevant to you.
 - **RIC Change Events** inform you of planned changes to RICs. RIC is the market level identifier key unique to LSEG used to identify securities.
- **Service Alerts**

Alert you about planned maintenance and unplanned service issues affecting your products and services, and be notified via SMS or email.

Documentation

You can access product documentation on the [Quantitative Analytics](#) product page at [MyAccount](#).

Get Support

For support using Quantitative Analytics, please use one of the following methods:

Online

Access [Get Support](#) either via the blue [Get Support](#) button at the top right of each page or by selecting *Get Support* located under *Help and Support* on the left navigation pane at [MyAccount](#).

From the *Get Support* page, choose *Get Product and Content Support* and then select the appropriate category from the next page. Complete the request making sure to include the following:

- Under Product, select Quantitative Analytics from the dropdown list.
- In the **How can we help you?** text box, include the following information:
 - Content set name (i.e. Worldscope)
 - Date applicable to a content inquiry
 - Table names and relevant fields
 - Security code (i.e. QA-ID, PermID, Sedol, InfoCode, etc.)
 - Script used to generate the output
 - Any other supporting detail

Telephone

Region	Telephone	Options
AMERS	+01 866 427 8390	Option 1 – Product Support Option 2 – Technical Support
EMEA	+44 203 341 1036	
APAC	+65 6403 7436	

Feedback

We invite your comments, corrections, and suggestions about this document: access the [Feedback](#) option under [Get Support](#) at [MyAccount](#). Your feedback helps us continue to improve our user assistance.

Your Personal Information

LSEG is committed to the responsible handling and protection of personal information. We invite you to review our [Privacy and Cookie Statement](#), which describes how we collect, use, disclose, transfer, and store personal information when needed to provide our services and for our operational and business purposes.

2 Compustat Schema Overview

Legacy Tables

The following obsolete tables have been replaced as described.

Obsolete Table (FTP)	Replaced by... (Xpressfeed)
CSItem	CSNAItem CSNAITEM: Compustat_XF
CSCdnAnn	CSCoAFnd1 and CSCoAFnd2
CSIndAnn	CSCoAFnd1 and CSCoAFnd2
CSResAnn	CSICoAFnd1 and CSICoAFnd2
CsBkdAnn (active)	CSBkCoAFnd1 and CSBkCoAFnd2
CsBkdAnn (inactive)	CSIBkCoAFnd1 and CSIBkCoAFnd2
CSCdnQtr	CSCoIFndQ
CSIndQtr	CSCoIFndQ
CSResQtr	CSICoIFndQ
CsBkdQtr (active)	CSBkCoIFndQ
CsBkdQtr (inactive)	CSIBkCoIFndQ
CSFYE	CSCoIDesInd (active) and CSICoIDesInd (inactive)
CsBkdFye	CSBkCoIDesInd (active) and CSIBkCoIDesInd (inactive)
CSDlyFnd	CSCoIFndQ , CSCoAFnd1 , and CSCoAFnd2
CSDlyPrc	Daily pricing is not available in Xpressfeed
CSIdxAnn	CSADIDXANN
CSIdxQtr	CSADIDXQTR
CSInfo	CSVCompany , CSVSecurity , and CSIdxIndex
CSAddr	CSVCompany
CSName	CSCoOffTitl
CSDacQtr	CSCoIFndQ (active) and CSICoIFndQ (inactive)
CSDacAnn	CSCoAFndDC1 (active) and CSICoAFndDC1 (inactive); CSCoAFndDC2 (active) and CSICoAFndDC2 (inactive)
CSDlyFDac	See CSDacQtr and CSDacAnn, above
CSDlyPDac	Daily pricing is not available in Xpressfeed
CSCode	All CSR* tables

3 Schema for Compustat Xpressfeed (All Subscriptions)

CSCoFileDate: Active Company File Dates

This table contains source information for the active named fundamentals for the specified period. It provides the name of the source as well as the date it was published.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_CSCOFILEDAT (Clustered)		GVKEY, CONSOL, SRCTYPE, DATADATE	
Field	Type	Nullable	Description
GVKEY	int	No	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	No	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	No	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
SRCTYPE	tinyint	No	SRCTYPE is the coded field for the source document. Descriptions are available in CSKeyCode , where SRCTYPE corresponds to CSKeyCode.Code 33 through 48.
FILEDATE	datetime	Yes	FILEDATE is the date for the corresponding file.

CSICoFileDate: Inactive Company File Dates

This table contains source information for the inactive named fundamentals for the specified period. It provides the name of the source as well as the date it was published.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_CSICOFILEDAT (Clustered)		GVKEY, CONSOL, SRCTYPE, DATADATE	
Field	Type	Nullable	Description
GVKEY	int	No	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	No	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	No	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
SRCTYPE	tinyint	No	SRCTYPE is the coded field for the source document. Descriptions are available in CSKeyCode , where SRCTYPE corresponds to CSKeyCode.Code 33 through 48.
FILEDATE	datetime	Yes	FILEDATE is the date for the corresponding file.

GCSKeyCode: Compustat XF Security Information

NOTE

This table is also part of the Compustat Global Xpressfeed schema. CSKeyCode is available in both the Global and North American schemas because of Compustat integer conversion. This table contains integer values and descriptions for DATAFMT, INDFMT, CONSOL, CURCD, and SRCTYPE.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_CSKEYCODE (Clustered)	CODE

Field	Type	Nullable	Description
Code	tinyint	N	Code is the numerical value for the field listed under FIELDNAME. For example, where Code = 6, and the FIELDNAME = CONSOL, the corresponding StringValue is C, indicating the related data is Consolidated.
StringValue	varchar(13)	Y	StringValue is the Compustat-provided value for the key field.
FieldName	varchar(31)	Y	FieldName contains the name of the field described.
Description	varchar(81)	Y	Description translation of FIELDNAME and CODE.

CSNAItem: Compustat XF Item Information

This table contains information for data items.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_CSNAITEM (Clustered)	GROUP_, NUMBER
CSNAITEM_1	GROUP_, MNEMONIC
CSNAITEM_2	GROUP_, ANNSYN, MNEMONIC
CSNAITEM_3	GROUP_, DESC_, MNEMONIC
CSNAITEM_4	GNAME, NUMBER
CSNAITEM_5	MNEMONIC, GROUP_
CSNAITEM_6	FTPMNEMONIC, GROUP_
CSNAITEM_7	GBLSYN, GROUP_
CSNAITEM_8	ANNSYN, GROUP_
CSNAITEM_9	RESTATED, GROUP_
CSNAITEM_10	GROUPID, MNEMONIC
CSNAITEM_11	GROUPID, DESC_, MNEMONIC

Field	Type	Nullable	Description
GROUP_	smallint	N	The combination of GROUP_ and NUMBER creates the key for linking Compustat data items to Value_.
NUMBER	smallint	N	The combination of GROUP_ and NUMBER creates the key for linking Compustat data items to Value_.
MNEMONIC	varchar(20)	Y	Mnemonic is the unique abbreviated name assigned by Standard & Poor's. Use Mnemonic to identify the data item within Standard & Poor's products and documentation.
ANNSYN	varchar(7)	Y	ANNSYN is the synonym for annual and quarterly items.
GBLSYN	varchar(7)	Y	GBLSYN is not currently used.
DESC_	varchar(150)	Y	DESC_ is the item description.

Field	Type	Nullable	Description
IDBFLAG	varchar(2)	Y	IDBFLAG indicates which database the item can be found in. The IDBFlag may be: – Domestic (D) – International (I) – Both (B)
ADJUST	tinyint	Y	Adjust is the adjustment method and can be: – 0 = No adjustment – 1 = Add adjustment factor – 2 = Increasing share count on split and decreasing on reverse split – 3 = Decreasing on split and increasing on reverse split – 4 = Increasing share count on split and decreasing on reverse split, restated – 5 = Decreasing on split and increasing on reverse split, restated – 6 = Increasing share count on split and decreasing on reverse split, pay date – 7 = Decreasing on split and increasing on reverse split, pay date
FREQ	tinyint	Y	FREQ is described in the FREQ section on page 17.
STMT	tinyint	Y	STMT is the item source statement. STMT can be: – 0 = None – 1 = Balance Sheet – 2 = Income Statement – 3 = Cash Flow Statement – 4 = Market Data
UNITS	tinyint	Y	UNITS is not currently used.
DATATYPE	tinyint	Y	DATATYPE describes the data type.
REFTYPE	tinyint	Y	REFTYPE is not currently used.
SCALE	float	Y	SCALE is the transparency scale value.
MONITEM	tinyint	Y	MONITEM is not currently used.
GNAME	varchar(50)	Y	GNAME is the description for Group_.
FTPMNEMONIC	varchar(20)	Y	FTPMNEMONIC is the mnemonic from the FTP product, when available.
RESTATED	varchar(21)	Y	RESTATED is the mnemonic for the corresponding restated item (for example, SALER for Sales).
GROUPID	smallint	Y	GROUPID identifies the group to which the item belongs.

FREQ

FREQ is the item frequency, and may be:

FREQ	Symbol	Description
0	N/A	Static
1	A	Annual
2	Q	Quarterly
3	M	Monthly
4	S	Semi annual
5	W	Weekly
6	D	Daily
7	C	Scalar
8	Y	Year to date
9	O	12 month moving

4 Schema for Compustat XF Daily

CSIdxIndex: Index Identifier Information

This table contains index identifier information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIdxIndex (Clustered)	GVKEYX
CSIdxIndex_1	CONM, GVKEYX
CSIdxIndex_2	INDEXID, GVKEYX
CSIdxIndex_3	TIC, GVKEYX

Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
CONM	varchar(200)	Y	CONM is the company name.
CONM2	varchar(57)	Y	CONM2 is the company name.
IDX13KEY	varchar(14)	Y	IDX13KEY is a company identifier comprised of the company's four-digit SIC code plus the nine digits of the company's primary issue CUSIP number.
INDEXCAT	varchar(11)	Y	INDEXCAT identifies the category of the index, such as S&P or Dow Jones.
INDEXGEO	varchar(110)	Y	INDEXGEO is the geographical coverage of an index.
INDEXID	varchar(11)	Y	INDEXID is the specific index within the index category.
INDEXTYPE	varchar(11)	Y	INDEXTYPE indicates the general type of the index.
INDEXVAL	varchar(11)	Y	INDEXVAL is the unique, numerical identifier representing a sub-classification of an index type.
TIC	varchar(9)	Y	TIC identifies the symbol associated with the trading of a particular issue on an exchange. For example, when a parent company symbol is appended with a number it indicates a subsidiary of a publicly traded company.
TICI	varchar(9)	Y	TICI is identical to TIC.
IDXCSTFLG	varchar(3)	Y	IDXCSTFLG is the index constituent flag. A value of Y (yes) indicates there are constituent marking for the index.
IDXSTAT	char(1)	Y	IDXSTAT is the status of the index (active or inactive).

CSIdxCstHis: Index Constituent History

This table contains index constituent history information.

NOTE

As of July 22, 2020, S&P DJI historical constituent data is no longer available in this table where **IndexCat** in CSIdxIndex/CSGIdx = S&P.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIDXCSTHIS (Clustered)	GVKEY, IID, GVKEYX, FROM_
CSIDXCSTHIS_1	GVKEY, FROM_
CSIDXCSTHIS_2	GVKEYX, GVKEY, IID, FROM_
CSIDXCSTHIS_3	GVKEY, FROM_
CSIDXCSTHIS_4	GVKEYX, FROM_
CSIDXCSTHIS_5	GVKEY, IID, FROM_

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company. The combination of GVKEY and IID represents the index constituent.
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
FROM_	smalldatetime	N	FROM_ represents the dates that the security was part of the index.
THRU	smalldatetime	Y	THRU represents the dates that the security was part of the index.

CSIdxCstHisSnP: SPDJ Index Constituent History

This table contains S&P Dow Jones Index constituent history information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIDXCSTHISSNP (Clustered)	GVKEY, IID, GVKEYX, FROM_

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company. The combination of GVKEY and IID represents the index constituent.
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
FROM_	datetime	N	FROM_ represents the dates that the security was part of the index.
THRU	datetime	Y	THRU represents the dates that the security was part of the index.
LICFLAG	tinyint	N	LICFLAG represents the license flag value for the various Index constituents. The LICFLAG may be 2 = SPDJ US Constituent History 4 = TSX Constituent History

CSIdxDaily: Index Daily Market Values

This table contains information for index daily market values.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSIdxDaily (Clustered)		GVKEYX, DATADATE	

Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
DATADATE	smalldatetime	N	DATADATE is the end date of the quarter for which the data was reported.
NEWNUM	int	Y	NEWNUM is the new index number. NEWNUM represents the number of constituents in the index for the current trade date.
OLDNUM	int	Y	OLDNUM is the old index number. OLDNUM represents the number of constituents in the index for the previous trade date.
PRCCD	float	Y	PRCCD is the close price for a given day of a company or index. For bid/ask pricing with no current volume, the close price is the last trade close price with volume.
PRCHD	float	Y	PRCHD is the highest trade price for the given date. For bid/ask pricing, high is the last asking price prior to market close, or the previous ask price when bid/ask is more than 50 percent of the latest ask price.
PRCLD	float	Y	PRCLD is the lowest trade price for the given date. For bid/ask pricing, low is the last bid prior to market close, or the previous bid price when bid/ask is more than 50 percent of the latest ask price.
DVPSXD	float	Y	DVPSXD is the amount of the cash or cash-equivalent dividend payment, or the ratio of a stock split or stock dividend.
PRCCDDIV	float	Y	PRCCDDIV is the daily close price rate of return of an index. PRCCDDIV reflects price appreciation plus the reinvestment of daily dividends and the compounding effect of dividends paid on reinvested dividends.

CSIdxMth: Index Monthly Market Values

This table contains information for index monthly market values.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSIdxMth (Clustered)		GVKEYX, DATADATE	

Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DVPSXM	float	Y	DVPSXM is the index monthly cash dividend paid per share by ex date. DVPSXM is adjusted for all stock splits and stock dividends that occurred during the period. This value does not include payments in preferred stock in lieu of cash, spin-offs, and stock of other corporations.
PRCCM	float	Y	PRCCM is the absolute close market price for each calendar month.
PRCHM	float	Y	PRCHM is the absolute high market price for each calendar month.
PRCLM	float	Y	PRCLM is the absolute low market price for each calendar month.
AJEXM	float	Y	AJEXM is the monthly cumulative adjustment factor. This is the monthly price adjustment factor used to adjust the security's price for corporate events.
BKVLPS	float	Y	BKVLPS is the book value per share, calculated annually from the calendar year-end index data.
EPSX12	float	Y	EPSX12 is the basic earnings per share (12 Months Moving) before extraordinary items and discontinued operations.

Field	Type	Nullable	Description
CSHTRM	float	Y	CSHTRM is the monthly number of shares traded for companies listed on national stock exchanges and over-the-counter companies in the NASDAQ system.
DVRATE	float	Y	DVRATE is the monthly indicated annual dividend rate.

CSecIndMth: Monthly Economic Industry

This table contains monthly economic industry information.h

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_CSECINDMTH (Clustered)	ECONISO, DATADATE, ITEM
CSECINDMTH_1	ECONISO, ITEM, DATADATE

Field	Type	Nullable	Description
ECONISO	varchar(4)	N	ECONISO is the ISO country code of the country to which the data applies.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
Item	smallint	N	Item is the Compustat item. Item cross-references CSNAItem where CSNAItem.Number = CSecIndMth.Item and Group_ = 80.
Value_	float	Y	Value_ is the raw value provided by Compustat.

CSExRtDly: Daily Exchange Rate

This table contains daily exchange rate information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSEXRTDLY (Clustered)	TOCURD, DATADATE

Field	Type	Nullable	Description
TOCURD	varchar(4)	N	TOCURD is the ISO currency code for the currency to which the daily exchange rate translates. For example, in the exchange from USD to GBP, TOCURD returns GBP.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
EXRATD	float	Y	EXRATD is the daily exchange rate. EXRATD is based on official pricing at London market close.
EXRATTPD	varchar(3)	Y	EXRATTPD is the exchange rate type, indicating whether the reported exchange rate is As Reported (AR), or if no rate was available for a given date, Copied Forward (CF).
FROMCURD	varchar(4)	Y	FROMCURD is the ISO currency code for the currency from which the daily exchange rate translates. For example, in the exchange from USD to GBP, TOCURD returns USD.

CSExRtMth: Monthly Exchange Rate

This table contains monthly exchange rate information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSEXRTMTH (Clustered)	TOCURM, DATADATE

Field	Type	Nullable	Description
TOCURM	varchar(4)	N	TOCURM is the ISO currency code for the currency to which the monthly exchange rate translates. For example, in the exchange from USD to GBP, TOCURM returns GBP.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
EXRAT1M - EXRAT18M	float	Y	EXRAT1M through EXRAT18M is the average foreign currency exchange rate for the range of months indicated by the numeric value of the mnemonic. For example, EXRAT6 indicates the average foreign currency exchange rate for the past six months.
EXRATM	float	Y	EXRATM is the month-end currency exchange rate.
FROMCURM	varchar(4)	Y	FROMCURM is the ISO currency code for the currency from which the monthly exchange rate translates. For example, in the exchange from USD to GBP, FROMCURM returns GBP.

CSSPInd: S&P Index Securities

This table contains information for S&P index securities.

NOTE

As of March 22, 2002, this table is no longer updated. Updated data is available in tables with a CSIDX prefix.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSPIND (Clustered)	GVKEY
CSSPIND_1	SPITIC
CSSPIND_2	SPITIC, GVKEY

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
SPIDESC	varchar(255)	Y	SPIDESC is the Standard & Poor's industry index description.
SPIDESC2	varchar(2)	Y	SPIDESC2 is not currently used.
SPIIID	smallint	Y	SPIIID is the S&P industry index ID. SPIIID identifies industry groupings within the major S&P indexes.
SPIMID	smallint	Y	SPIMID is the S&P major index ID and identifies the major S&P index. The codes for this item are: – 400 = S&P MidCap 400 – 500 = S&P 500 – 600 = S&P SmallCap 600 – 1500 = S&P Super Composite 1500
SPITIC	varchar(9)	Y	SPITIC is the S&P index ticker. This is the pseudo ticker symbol for the industry index.

CSSPIndDly: S&P Index Daily

This table contains S&P index daily information.

NOTE

As of March 22, 2002, this table is no longer updated. Updated data is available in tables with a CSIDX prefix.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSPINDDLY (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
SPIHI	float	Y	SPIHI is the calculated high S&P index price for the trading day.
SPILO	float	Y	SPILO is the S&P calculated low index price for the trading day.
SPINUMN	int	Y	SPINUMN is the new number of holdings for the S&P index. This number includes any changes in the index holdings after the close of the day, such as replacing one company with another.
SPINUMO	int	Y	SPINUMO is the S&P old index number. It is the number of holdings as of the market close, before changes are made in the index.
SPIPRC	float	Y	SPIPRC is the calculated closing index price for the trading day.

CSSPIndMth: S&P Index Monthly

This table contains S&P index monthly information.

NOTE

As of March 22, 2002, this table is no longer updated. Updated data is available in tables with a CSIDX prefix.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSPINDMTH (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	smalldatetime	N	DATADATE is the end date of the quarter for which the data was reported.
DIVXM	float	Y	DIVXM is the S&P monthly index dividend and represents the cash dividends per share for the index where ex-dates occurred during the reporting period. This item is adjusted for stock splits and stock dividends that occurred during the period, and excludes spin-offs, stock of other corporations, and payments in preferred stock in lieu of cash.

CSSECSPInd: S&P Index Securities

This table contains information for S&P index securities.

NOTE

As of 22 March 2002, this table is no longer updated. Updated data is available in tables with a CSIDX prefix.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSECSPIND	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
SPH100	varchar(9)	Y	SPH100 flags companies comprising the S&P 100 Index. An asterisk (*) indicates the company is in the index.
SPHCUSIP	varchar(9)	Y	SPHCUSIP is the S&P holdings CUSIP. It gives the CUSIP security identification number for an index holding.
SPHIID	smallint	Y	SPHIID is the S&P holdings industry index ID. It identifies the industry grouping an S&P major index company is assigned to.

Field	Type	Nullable	Description
SPHMID	smallint	Y	SPHMID is the S&P holdings major index ID. The companies in the S&P indexes are identified as: – 400 = S&P MidCap 400 – 500 = S&P 500 – 600 = S&P SmallCap 600 – 1500 = S&P Super Composite 1500
SPHNAME	varchar(32)	Y	SPHNAME gives the name of the company that is a member of an S&P index.
SPHSEC	smallint	Y	SPHSEC is described in the SPHSEC section on page 24.
SPHTIC	varchar(9)	Y	SPHTIC is the S&P holdings ticker. It is the ticker symbol for a company that is a member of an S&P index.
SPHVG	char(1)	Y	SPHVG is the S&P holdings value and growth indicator. SPHVG compares the price-to-book ratio of an index to the median price-to-book ratio for its industry sector, calculated using all active U.S. companies in the database. If the ratio is greater than or equal to the industry median, it is G (a growth index). If the ratio is less than the industry median, it is V (a value index).

SPHSEC

SPHSEC is the code indicating the economic sector to which a company in an S&P index belongs. SPHSEC can be:

Code	S&P Description
600	Transportation
700	Utility
800	Financials
905	Health Care
925	Capital Goods
935	Energy
940	Technology
970	Basic Materials
974	Communication Services
976	Consumer Cyclical
978	Consumer Staples

CSSPIdxCst: S&P Index Constituent Daily

This table contains S&P index constituent daily information.

NOTE

The items in this table were discontinued in 2009. Updated data is available in tables with a CSIDX prefix. Effective July 2020, the historical data for the contype='SPGICX' are removed from this table.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSSPIDXCST (Clustered)	GVKEY, IID, DATADATE, INDEXID
CSSPIDXCST_1	GVKEY, IID, INDEXID, DATADATE
CSSPIDXCST_2	INDEXID, DATADATE
CSSPIDXCST_3	INDEXID, DATADATE, GVKEY

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.

Field	Type	Nullable	Description
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDEXID	varchar(11)	N	INDEXID identifies a specific index within an Index Category. For example, 500 is the INDEXID for the S&P 500 index.
CONMX	varchar(41)	Y	CONMX is the constituent name. This field may contain special characters.
CONTYPE	varchar(11)	Y	CONTYPE is the constituent type.
CONVAL	varchar(11)	Y	CONVAL is the constituent value. This field contains the GICS sub-industry code the index constituent.
CUSIPX	varchar(9)	Y	CUSIPX is the constituent CUSIP. An X in the last digit indicates the issue is inactive.
EXCHGX	varchar(5)	Y	EXCHGX is described in the EXCHGX section on page 25.
TICX	varchar(11)	Y	TICX is the constituent ticker. Not all issues have a ticker symbol.
SPFLOAT	float	Y	SPFLOAT is the S&P Float Shares value. This value is obtained by taking the last Compustat quarterly shares outstanding value and multiplying it by the S&P Index Services Investable Weight Factor (IWF), producing an approximate company float shares figure. This calculation may differ from published S&P Index Float Shares data.

EXCHGX

EXCHGX is the constituent exchange. EXCHGX translates as:

Code	Exchange	Effective
AS	American	prior to March 2005
NY	New York	prior to March 2005
OT	NASDAQ and Other	prior to March 2005
XASE	American	March 2005 forward
XNAS	NASDAQ	March 2005 forward
XNYS	New York	March 2005 forward

CSCoAAudit: Compustat XF Audit Information

This table contains audit information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoAAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, POPSRC, RANK
CSCoAAUDIT_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.

Field	Type	Nullable	Description
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
AU	varchar(9)	Y	AU lists the auditing firms that audited a company's financial statements. AU is translated by CSRAuditors where CSRAuditors.AUCD = CSCoAAudit.AU.
AUOP	varchar(9)	Y	AUOP is the auditor opinion. AUOP is translated by CSROPINIONS where CSROPINIONS.AUOPCD = CSCoAAudit.AUOP.
AUOPIC	char(1)	Y	AUOP is the auditor opinion of internal control. AUOPIC is translated by CSRAuopIC where CSRAuopIC.AUOPICCD = CSCoAAudit.AUOPIC.
CEOSO	char(1)	Y	CEOSO is the Chief Executive Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.
CFOSO	char(1)	Y	CFOSO is the Chief Financial Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.

CSCoADesInd: Compustat XF Company Descriptions

This table contains company description information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOADESIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL
CSCOADESIND_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSCOADESIND_2	GVKEY, FYEAR, INDFMT, DATAFMT, CONSOL
CSCOADESIND_3	DATADATE, GVKEY, INDFMT, DATAFMT, CONSOL

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ACCTSTD	varchar(9)	Y	ACCTSTD identifies the accounting standard a company uses when preparing its financial statements. If a company does not reference a specific standard, a domestic standard is assumed. ACCTSTD is translated by CSRAccStd where CSRAccStd.ACCTSTD = CSCoADesInd.ACCTSTD.
ACQMETH	varchar(3)	Y	ACQMETH is the code that identifies the method a company uses to account for acquisitions. ACQMETH is translated by CSRAcqMeth where CSRAcqMeth.ACQMETHCD = CSCoADesInd.ACQMETH.
ADRR	float	Y	ADRR is the ADR (American Depositary Receipt) Ratio. This indicates the number of a foreign company's common or ordinary shares that are equivalent to one ADR or one ADS (American Depositary Share). This ratio is usually a whole number, and is available only for foreign companies that trade ADR or ADS in the U.S. ADRR is on an annual basis.
AJEX	float	Y	AJEX is the adjustment factor you use to adjust per-share data (such as price, earnings per share, and dividends per share) and share data (such as shares outstanding and shares traded) for all stock splits and stock dividends occurring subsequent to the end of a given period. The ex-dividend date is used to determine the adjustment of per-share data. The cumulative adjustment factor

Field	Type	Nullable	Description
			changes whenever a stock split or stock dividend occurs. AJEX is on an annual basis.
AJP	float	Y	AJP is the adjustment factor you use to adjust dividends per share for all stock dividends occurring subsequent to the end of a given period. The payable date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock dividend occurs. AJP is on an annual basis.
APDEDATE	datetime	Y	APDEDATE is the actual date the company closes their accounting period, which may be different from the last day of the month in the period. APDEDATE is in the form YYYY-MM-DD.
BSPR	varchar(9)	Y	BSPR is the balance sheet presentation method. BSPR is translated by CSRBalPres where CSRBalPres.BSPRCD = CSCoADesInd.BSPR.
COMPST	varchar(9)	Y	COMPST is the comparability status which describes conditions under which data in one period may not be comparable to data in another period. COMPST is translated by CSRCompStat where CSRCompStat.COMPSTCD = CSCoADesInd.COMPST.
CURCD	varchar(4)	Y	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURNCD	varchar(4)	Y	CURNCD is the native currency code and identifies the currency in which the company reports its financial data. When CURNCD is not the same as CURCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURRTR	float	Y	CURRTR is the currency translation rate. This is the rate of exchange used to translate international currency into U.S. dollars. The rate used is the rate in effect as of the date of the company's balance sheet. If an international company reports in U.S. dollars, the translation rate is 1.000.
CURUSCN	float	Y	CURUSCN is the rate of exchange used to translate Canadian currency amounts into U.S. dollar amounts. This is available only when a company reports in both U.S. and Canadian accounting standards.
FDATE	datetime	Y	FDATE is the date the data was finalized for that year or quarter.
FYEAR	smallint	Y	FYEAR represents the fiscal year of the current fiscal year-end month.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
ISMOD	smallint	Y	ISMOD is the income statement model number.
OGM	varchar(9)	Y	OGM is the method of reporting revenue used by the Oil & Gas company.
PDATE	datetime	Y	PDATE is the date the data for the company is updated on a preliminary basis for that year or quarter.
PDDUR	smallint	Y	PDDUR is a unique integer code that identifies the source of the data. PDDUR is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as PDDUR.
SCF	smallint	Y	SCF contains the numeric code that identifies the format of a company's flow of funds statement, statement of changes, or statement of cash flow.
SRC	smallint	N	SRC contains code that indicates the most recent source from which S&P obtained data for each fiscal period.
STALT	varchar(3)	Y	STALT is a unique integer code that identifies the source of the data. STALT is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as STALT.
UDPL	varchar(9)	Y	UDPL designates the method used by the utility company to account for Liberalized Depreciation.
UPD	smallint	Y	UPD contains the code that identifies the updated status of the data for the period. UPD consists of a one-character numeric code.

CSCoAdjFact: Compustat XF Adjustment Factors

This table contains information for adjustment factors.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOADJFACT (Clustered)	GVKEY, EFFDATE, THRUDATE
CSCOADJFACT_1	GVKEY, THRUDATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
EFFDATE	datetime	N	EFFDATE is the date from which the cumulative adjustment factor is effective.
THRUDATE	datetime	N	THRUDATE is the date through which the daily total return factor is effective. A NULL value indicates current daily total return factor.
ADJEX	float	Y	ADJEX is the multiplication of all Ex-Date adjustment factors going back in time.
ADJPAY	float	Y	ADJPAY is the multiplication of all Pay-Date adjustment factors going back in time.

CSCoAFndDC1: Compustat XF Annual Fundamentals Data Codes 1

CSCoAFndDC2: Compustat XF Annual Fundamentals Data Codes 2

These tables contain information for annual fundamentals data codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoAFNDDC[n] (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSCoAFNDDC[n]_1	GVKEY, Item, DATADATE
CSCoAFNDDC[n]_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSCoAFNDDC[n]_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item. Item cross-references with CSNAItem where: For CSCoAFndDC1, CSNAItem.Number = CSCoAFndDC1.Item and Group_ = 202. For CSCoAFndDC2, CSNAItem.Number = CSCoAFndDC2.Item and Group_ = 203.
Value_	smallint	Y	Value_ is the raw value provided by Compustat.

CSCoAFnd1: Compustat XF Annual Fundamentals 1

CSCoAFnd2: Compustat XF Annual Fundamentals 2

This table contains information on annual fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSCoAFND[n] (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSCoAFND[n]_1	GVKEY, Item, DATADATE
CSCoAFND[n]_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSCoAFND[n]_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSCoAFND[n]_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item. Item cross-references with CSNAItem where: For CsCoAFnd1, CSNAItem.Number = CsCoAFnd1.Item and Group_ = 204. For CsCoAFnd2, CSNAItem.Number = CsCoAFnd2.Item and Group_ = 205.
Value_	float	Y	Value_ is the raw value provided by Compustat.

CSCoAInvVal: Compustat XF Inventory Valuation Data

This table contains inventory valuation data information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoAINVVAL (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CSCoAINVVAL_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSCoAINVVAL_2	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.

Field	Type	Nullable	Description
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
INVVAL	int	Y	INVVAL contains the code that identifies the method used to value inventory.

CSCoAMkt: Compustat XF Market Data

This table contains market data information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSCOAMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD
CSCOAMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
CLSM	smallint	Y	CLSM is the month of the company's last close price.
CSHTR	float	Y	CSHTR is the number of shares traded for companies listed on national stock exchanges and over-the-counter companies in the NASDAQ system on a fiscal, rather than calendar, basis.
DVPSP	float	Y	DVPSP is the cash dividends per share for which the payable dates occurred during the reporting period, unadjusted for all stock splits and stock dividends that occurred during the period.
DVPSX	float	Y	DVPSX is the cash dividends per share for which the ex-dividend dates occurred during the reporting period, adjusted for all stock splits and stock dividends that occurred during the period.
PRCC	float	Y	PRCC is the absolute close transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCH	float	Y	PRCH is the absolute high transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCL	float	Y	PRCL is the absolute low transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSCoFortune: Fortune 500 Group

This table contains information for the Fortune 500 Group.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOFORTUNE (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.

Field	Type	Nullable	Description
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
FORI	smallint	Y	FORI contains the code that identifies the industry group of a Fortune 1000 company.
FORRK	smallint	Y	FORRK is the fortune rank.

CSCoHGIC: GICS History

This table contains GICS history information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoHGIC (Clustered)	GVKEY, INDTYPE, INDFROM

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
INDTYPE	varchar(9)	N	INDTYPE is the type of industry classification. GICS = Standard & Poor's Global Industry Classification System (GICS)
INDFROM	datetime	N	INDFROM is the date from which the GICS code was effective.
GGROUP	varchar(5)	Y	GGROUP is the second level in the hierarchy of the Global Industry Classification Standard (GICS). The Industry Group is represented by the leftmost four digits of the total GICS code.
GIND	varchar(7)	Y	GIND is the third level in the hierarchy of the Global Industry Classification Standard (GICS). Industry is represented by the leftmost six digits of the total GICS code.
GSECTOR	varchar(3)	Y	GSECTOR is the first level in the hierarchy of the Global Industry Classification Standard (GICS). The Sector is represented by the leftmost two digits of the total GICS code.
GSUBIND	varchar(9)	Y	GSUBIND is fourth level in the hierarchy of the Global Industry Classification Standard (GICS). The Sub-industry is represented by all eight digits of the total GICS code.
INDTHRU	datetime	Y	INDTHRU is the date through which the GICS code was effective, if it is no longer effective.

CSCoIAudit: Interim Auditor Group

This table contains interim auditor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoIAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, RANK
CSCoIAUDIT_1	GVKEY, INDFMT, CONSOL, DATAFMT, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
CEOSOQ	char(1)	Y	CEOSOQ is the same as CEOSO , but is on a quarterly basis.
CFOSOQ	char(1)	Y	CFOSOQ is the same as CFOSO , but is on a quarterly basis.

CSCoIdesInd: Company Interim Descriptor Group

This table contains company interim descriptor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOIDESIND (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSCOIDESIND_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSCOIDESIND_2	GVKEY, FQTR, FYEARQ, INDFMT, CONSOL, DATAFMT
CSCOIDESIND_3	DATADATE, GVKEY, INDFMT, CONSOL, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ACCTSTDQ	varchar(9)	Y	ACCTSTDQ is the same as ACCTSTD , but is on a quarterly basis.
ADRRQ	float	Y	ADRRQ is the same as ADRR , but is on a quarterly basis.
AJEXQ	float	Y	AJEXQ is the same as AJEX , but is on a quarterly basis.
AJPQ	float	Y	AJPQ is the same as AJP , but is on a quarterly basis.
APDEDATEQ	datetime	Y	APDEDATEQ is the same as APDEDATE, but is on a quarterly basis.
BSPRQ	varchar(9)	Y	BSPRQ is the same as BSPR , but is on a quarterly basis.
COMPSTQ	varchar(9)	Y	COMPSTQ is the same as COMPST , but is on a quarterly basis.
CURCDQ	varchar(4)	Y	CURCDQ is the same as CURCD , but is on a quarterly basis.
CURNCDQ	varchar(4)	Y	CURNCDQ is the same as CURNCD , but is on a quarterly basis.
CURRTRQ	float	Y	CURRTRQ is the same as CURRTR , but is on a quarterly basis.
CURUSCNQ	float	Y	CURUSCNQ is the same as CURUSCN , but is on a quarterly basis.
DATAQTR	varchar(7)	Y	DATAQTR is the calendar year and quarter.
DATAFQTR	varchar(7)	Y	DATAFQTR is the fiscal year and quarter.
FDATEQ	datetime	Y	FDATEQ is the same as FDATE , but is on a quarterly basis.
FQTR	smallint	Y	FQTR is the fiscal quarter of the company.
FYEARQ	smallint	Y	FYEARQ is the same as FYEAR , but is on a quarterly basis.
OGMQ	varchar(9)	Y	OGMQ is the same as OGM , but is on a quarterly basis.

Field	Type	Nullable	Description
PDATEQ	datetime	Y	PDATEQ is the same as PDATE , but is on a quarterly basis.
PDQ	smallint	Y	PDQ is the number of months in a quarterly, interim reporting period.
PDSA	smallint	Y	PDSA is the number of months in a semiannual, interim reporting period.
PDYTD	smallint	Y	PDYTD is the number of months in a year-to-date, interim reporting period.
RDQ	datetime	Y	RDQ is the date on which quarterly earnings per share are first publicly reported.
RP	varchar(3)	Y	RP is the interim reporting periodicity of a company for a specific year.
SCFQ	int	Y	SCFQ is the same as SCF , but is on a quarterly basis.
SRCQ	int	Y	SRCQ is the same as SRC , but is on a quarterly basis.
STALTQ	varchar(3)	Y	STALTQ is the same as STALT , but is on a quarterly basis.
UPDQ	smallint	Y	UPDQ is the same as UPD , but is on a quarterly basis.

CSCoIFntYTD: Company Interim Fundamentals – Year-to-Date Footnotes

This table contains information for company interim fundamentals - year-to-date footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoIFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSCoIFNTYTD_1	GVKEY, Item, DATADATE
CSCoIFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSCoIFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSCoIFntYTD.Item and Group_ = 211.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSCoIFntQ: Company Quarterly Fundamental Footnotes

This table contains information for company quarterly fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoIFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSCoIFNTQ_1	GVKEY, Item, DATADATE

Indexes	Index Fields
CSCOIFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE
CSCOIFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSCoIFntQ.Item and Group_ = 212.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSCoIFntSA: Company Quarterly Fundamental Footnotes

This table contains information for company quarterly fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOIFNTSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSCOIFNTSA_1	GVKEY, Item, DATADATE
CSCOIFNTSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSCOIFNTSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSCoIFntSA.Item and Group_ = 213.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSCoIMkt: Interim Market Group

This table contains interim market group information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSCoIMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD, YEM
CSCoIMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
YEM	smallint	N	YEM works with CFFLAG to represent the month of the company's year-end price.
CLSMQ	smallint	Y	CLSMQ is the same as CLSM , but is on a quarterly basis.
CSHTRQ	float	Y	CSHTRQ is the same as CSHTR , but is on a quarterly basis.
DVPSPQ	float	Y	DVPSPQ is the same as DVPSP , but is on a quarterly basis.
DVPSXQ	float	Y	DVPSXQ is the same as DVPSX , but is on a quarterly basis.
PRCCQ	float	Y	PRCCQ is the same as PRCC , but is on a quarterly basis.
PRCHQ	float	Y	PRCHQ is the same as PRCH , but is on a quarterly basis.
PRCLQ	float	Y	PRCLQ is the same as PRCL , but is on a quarterly basis.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSCoIndstPres: Company Industry Presentation

This table contains company industry presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoINDSTRYPRES (Clustered)	GVKEY, DATADATE, CONSOL, IPCD
CSCoINDSTRYPRES_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CsKeyCode where FIELDNAME = CONSOL.
IPCD	char(1)	N	IPCD identifies the industry presentation of financial services companies trading outside of the United States and Canada.

CSCoIndustry: Industry Classification Presentation

This table contains industry classification presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOINDUSTRY (Clustered)	GVKEY, DATADATE, CONSOL
CSCOINDUSTRY_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
NAICSH	int	Y	NAICSH contains the historical NAICS code assigned to a company.
SICH	int	Y	SICH contains the SIC code that identifies the company's SIC Code in prior years.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSCoMth: Company Monthly

This table contains company monthly information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOMTH (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
BETA	float	Y	BETA is a measurement of the sensitivity of a company's stock price to the overall fluctuation in the Standard & Poor's 500 (S&P 500) Index Price for U.S. Companies, or the Toronto Stock Exchange 300 (TSE 300) Index Price for Canadian Companies.
SPCSRM	varchar(4)	Y	SPCSRM is an appraisal of the past performance of a stock's earnings and dividends and the stock's relative standing as of a company's current fiscal year-end.

CSCoOffTitl: Company Officers

This table contains information for company officers.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCOOFFTITL (Clustered)	GVKEY, OFID, OFCD
CSCOOFFTITL_1	GVKEY, OFCD
CSCOOFFTITL_2	GVKEY, OFID

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.

Field	Type	Nullable	Description
OFID	int	N	OFID is a unique identifying number assigned to a person holding the position of company officer. The Officer ID remains consistent for that person, even if the person holds more than one officer title.
OFCD	varchar(9)	N	OFCD represents one or more officers of a company.
OFNM	varchar(40)	Y	OFNM is the first two initials and the last name(s) of the officer(s) for a company.

CSCoAFntInd: Company Annual Fundamental Footnotes

This table contains information for company annual fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCoAFNTIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSCoAFNTIND_1	GVKEY, Item, DATADATE
CSCoAFNTIND_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSCoAFNTIND_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem CSNAITEM: Compustat where CSNAItem.Number = CSCoAFntInd.Item and Group_ = 217.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSCoIFndQ: Company Interim Fundamentals – Quarterly

This table contains quarterly company interim fundamentals information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSCoIFNDQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSCoIFNDQ_1	GVKEY, Item, DATADATE
CSCoIFNDQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSCoIFNDQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSCoIFNDQ_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.

Field	Type	Nullable	Description
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem CSNAITEM: Compustat where CSNAItem.Number = CSColFndQ.Item and Group_ = 218.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSCoIFndYTD: Company Interim Fundamentals – Year to Date

This table contains year-to-date company interim fundamentals information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSCoIFNDYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSCoIFNDYTD_1	GVKEY, Item, DATADATE
CSCoIFNDYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSCoIFNDYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSCoIFNDYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.

Field	Type	Nullable	Description
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSCoIFndQ.Item and Group_ = 219.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSCoIFndSA: Company Interim Fundamentals – Semi Annual

This table contains semi-annual company interim fundamentals information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSCoIFndSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSCoIFndSA_1	GVKEY, Item, DATADATE
CSCoIFndSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSCoIFndSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSCoIFndSA_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSCoIFndSA.Item and Group_ = 220.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue

Field	Type	Nullable	Description
			– 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSCurrency: Xpressfeed Currencies

This table contains information for Xpressfeed currencies.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSCURRENCY (Clustered)	ISOCURCD

Field	Type	Nullable	Description
ISOCURCD	varchar(4)	N	ISOCURCD represents the ISO names of countries and their respective currencies.
ISOCURBD	datetime	Y	ISOCURBD is the ISO currency birth date. It identifies the date that a particular currency was first used within a particular country.
ISOCURDD	datetime	Y	ISOCURDD is the ISO currency death date. It identifies the date that a particular currency was last used within a particular country.
ISOCURLNK	smallint	Y	ISOCURLNK is the ISO currency link code. It associates two or more currencies that have been used in the same country at different times.
ISOCURNM	varchar(101)	Y	ISOCURNM is the ISO currency code name. It is the name of the currency in which daily or monthly prices are reported.
ISOCURTR	tinyint	Y	ISOCURTR is the ISO currency tier number. Currencies are classified as Tier 1 or Tier 2. Tier 1 currencies can be translated directly into other currencies. Tier 2 currencies are first translated into one of four primary currencies, then translated from the primary currency into the target currency. The four primary currencies are U.S. Dollar, British Pound Sterling, Japanese Yen, and Swiss Francs.

CSRAccStd: Accounting Standards Reference Data

This table contains reference data for accounting standards.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRACCSTD (Clustered)	ACCTSTD CD

Field	Type	Nullable	Description
ACCTSTD CD	varchar(3)	N	ACCTSTD CD is the Accounting Standard code.
ACCTSTD DESC	varchar(255)	Y	ACCTSTD DESC is the Accounting Standard description.
ACCTSTD DESC2	varchar(2)	Y	ACCTSTD DESC is additional Accounting Standard description information.

CSRAcqMeth: Acquisition Methods Reference Data

This table contains reference data for acquisition methods.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRAcqMETH (Clustered)		ACCTSTD CD	
Field	Type	Nullable	Description
ACQMETHCD	varchar(3)	N	ACQMETHCD is the Acquisition Method code.
ACQMETHDESC	varchar(255)	Y	ACQMETHDESC is the Acquisition Method description.
ACQMETHDESC2	varchar(2)	Y	ACQMETHDESC2 is additional Acquisition Method description information.

CSRAuditors: Auditors Reference Data

This table contains reference data for auditors.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRAUDITORS (Clustered)		AU CD	
Field	Type	Nullable	Description
AU CD	smallint	N	AU CD is the Auditor code.
AUDESC	varchar(255)	Y	AUDESC is the Auditor description.
AUDESC2	varchar(2)	Y	AUDESC2 is additional Auditor description information.

CSRAuopIC: Internal Control Auditor Reference Data

This table contains internal control auditor reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRAUOPIC (Clustered)		AUOPIC CD	
Field	Type	Nullable	Description
AUOPIC CD	smallint	N	AUOPIC CD is the Internal Control Auditor Opinion code.
AUOPICDESC	varchar(255)	Y	AUOPICDESC is the Internal Control Auditor Opinion description.
AUOPICDESC1	varchar(2)	Y	AUOPICDESC1 is additional Internal Control Auditor Opinion description information.

CSRBalPres: Balance Sheet Presentations Reference Data

This table contains reference data for balance sheet presentations.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRBALPRES (Clustered)		BSPR CD	

Field	Type	Nullable	Description
BSPRCD	varchar(3)	N	BSPRCD is the Balance Sheet Presentation code.
BSPRDESC	varchar(255)	Y	BSPRDESC is the Balance Sheet Presentation description.
BSPRDESC2	varchar(2)	Y	BSPRDESC2 is additional Balance Sheet Presentation description information.

CSRCFFormt: Cash Flow Formats Reference Data

This table contains reference data for cash flow formats.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRCFFORMT (Clustered)	SCFCD

Field	Type	Nullable	Description
SCFCD	varchar(3)	N	SCFCD is the Cash Flow Format code.
SCFDESC	varchar(255)	Y	SCFDESC is the Cash Flow Format description.
SCFDESC2	varchar(2)	Y	SCFDESC2 is additional Cash Flow Format description information.

CSRCoIndPre: Company Industry Presentation Reference Data

This table contains company industry presentation reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRCOINDPRE (Clustered)	IPCD CD

Field	Type	Nullable	Description
IPCD CD	char(1)	N	IPCD CD is the Industry Presentation code.
IPCDDESC	varchar(51)	Y	IPCDDESC is the Industry Presentation description.

CSRCompStat: Comparability Stats Reference Data

This table contains reference data for comparability stats.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRCOMPSTAT (Clustered)	COMPSTCD

Field	Type	Nullable	Description
COMPSTCD	varchar(3)	N	COMPSTCD is the Comparability Status code.
COMPSTDESC	varchar(255)	Y	COMPSTDESC is the Comparability Status description.
COMPSTDESC2	varchar(2)	Y	COMPSTDESC2 is additional Comparability Status description information.

CSRConsol: Level of Consolidation Reference Data

This table contains level of consolidation reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRCONSOL (Clustered)		CONSOLCD	
Field	Type	Nullable	Description
CONSOLCD	varchar(3)	N	CONSOLCD is the Level of Consolidation code.
CONSOLDESC	varchar(200)	Y	CONSOLDESC is the Level of Consolidation description.
CONSOLDESC1	varchar(57)	Y	CONSOLDESC1 is additional Level of Consolidation description information.

CSRCountry: Country Reference Data

This table contains country reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRCOUNTRY (Clustered)		ISOCNTRYCD	
Field	Type	Nullable	Description
ISOCNTRYCD	varchar(4)	N	ISOCNTRYCD is the ISO Country code.
ISOCNTRYDESC	varchar(101)	Y	ISOCNTRYDESC is the ISO Country description.

CSRCstClsCd: Index Constituent Classification Reference Data

This table contains index constituent classification reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRCSTCLSCD (Clustered)		CONTYPECD, CONVALCD	
CSRCSTCLSCD_1		CONVALCD, CONTYPECD	
Field	Type	Nullable	Description
CONTYPECD	varchar(11)	N	CONTYPECD is the Constituent Type.
CONVALCD	varchar(11)	N	CONVALCD is the Constituent Value code.
CONVALDESC	varchar(255)	Y	CONVALDESC is the Constituent Value description.
CONVALDESC2	varchar(2)	Y	CONVALDESC2 is additional Constituent Value description information.

CSRDataCode: Data Codes Reference Data

This table contains reference data for data codes.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRDATACODE (Clustered)		DATCD	

Field	Type	Nullable	Description
DATCD	smallint	N	DATCD is the Data code.
DATCDESC	varchar(51)	Y	DATCDESC is the Data description.

CSRDataFmt: Data Format Reference Data

This table contains data format reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRDATAFMT (Clustered)	DATAFMTCD

Field	Type	Nullable	Description
DATAFMTCD	varchar(13)	N	DATAFMTCD is the Data Format code.
DATAFMTDESC	varchar(200)	Y	DATAFMTDESC is the Data Format description.
DATAFMTDESC1	varchar(57)	Y	DATAFMTDESC1 is additional Data Format description information.

CSRDocSrce: Annual Source Document Codes Reference Data

This table contains annual source document codes reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRDOCSRCE (Clustered)	SRCCD

Field	Type	Nullable	Description
SRCCD	smallint	N	SRCCD is the Source Document code.
SRDESC	varchar(255)	Y	SRDESC is the Source Document description.
SRDESC2	varchar(2)	Y	SRDESC2 is additional Source Document description information.

CSRExCodes: Exchange Trading Sys Codes Reference Data

This table contains reference data for exchange trading sys codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSREXCODES (Clustered)	EXCHGCD

Field	Type	Nullable	Description
EXCHGCD	smallint	N	EXCHGCD is the Stock Exchange.
EXCHGDESC	varchar(101)	Y	EXCHGDESC is the Stock Exchange description.

CSRExrtTyp: Exchange Rate Types Reference Data

This table contains reference data for exchange rate types.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSREXRTTYP (Clustered)	EXRATTPCD

Field	Type	Nullable	Description
EXRATTPDCD	varchar(3)	N	EXRATTPDCD is the Exchange Rate Type code.
EXCHGDESC	varchar(255)	Y	EXCHGDESC is the Exchange description.
EXCHGDESC2	varchar(2)	Y	EXCHGDESC2 is additional Exchange description information.

CSRFnDfntCd: Fundamental Footnote Codes Reference Data

This table contains reference data for fundamental footnote codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRFNDFNTCD (Clustered)	FNCD

Field	Type	Nullable	Description
FNCD	varchar(9)	N	FNCD is the Footnote code.
FNDESC	varchar(255)	Y	FNDESC is the Footnote description.
FNDESC2	varchar(2)	Y	FNDESC2 is additional Footnote description information.

CSRFootnts: Footnote Codes

This table contains footnote codes information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRFOOTNTS (Clustered)	FNCD

Field	Type	Nullable	Description
FNCD	varchar(9)	N	FNCD is the Footnote code.
FNDESC	varchar(254)	Y	FNDESC is the Footnote description.
FNDESC2	varchar(2)	Y	FNDESC2 is additional Footnote description information.

CSRForICd: Fortune Industry Code Reference Data

This table contains fortune industry code reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRFORICD (Clustered)	FORICD

Field	Type	Nullable	Description
FORICD	tinyint	N	FORICD is the Fortune Industry code.
FORIDESC	varchar(101)	Y	FORIDESC is the Fortune Industry description.
FORISTAT	char(1)	Y	FORISTAT is additional Fortune Industry description information.

CSRGICCd: Global Industry Code Reference Data

This table contains global industry code reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRGICCD (Clustered)		GICCD	
Field	Type	Nullable	Description
GICCD	int	N	GICCD is the GIC code.
GICDESC	varchar(101)	Y	GICDESC is the GIC description.
GICSTAT	char(1)	Y	GICSTAT is the GIC status (active or inactive).
GICTYPE	varchar(9)	Y	GICTYPE is the GIC type.

CSRHCalendr: Holiday Calendar

This table contains holiday calendar information.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRHCALENDR (Clustered)		ISOCD, DATADATE	
Field	Type	Nullable	Description
ISOCD	varchar(4)	N	ISOCD is the ISO Country Code - Market Holidays.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.

CSRIIdxClsCd: Index Classification Reference Data

This table contains index classification reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRIIDXCLSCD (Clustered)		IDXVALCD, IDXTYPECD	
CSRIIDXCLSCD_1		IDXTYPECD, IDXVALCD	
Field	Type	Nullable	Description
IDXVALCD	varchar(11)	N	IDXVALCD is the Index Value code.
IDXTYPECD	varchar(11)	N	IDXTYPECD is the Index type.
IDXVALDESC	varchar(255)	Y	IDXVALDESC is the Index Value description.
IDXVALDESC2	varchar(2)	Y	IDXVALDESC2 is additional Index Value description information.

CSRInactvCd: Inactivation Code Reference Data

This table contains inactivation code reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRINACTVCD (Clustered)		DLRSNCD	

Field	Type	Nullable	Description
DLRSNCD	varchar(9)	N	DLRSNCD is the Research Company Reason for Deletion code.
DLRSNDESC	varchar(255)	Y	DLRSNDESC is the Research Company Reason for Deletion description.
DLRSNDESC2	varchar(3)	Y	DLRSNDESC2 is additional Research Company Reason for Deletion description information.

CSRIncStats: Income Statement Models Reference Data

This table contains reference data for income statement models.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRIINCSTATS (Clustered)	ISMODCD

Field	Type	Nullable	Description
ISMODCD	smallint	N	ISMODCD is the Income Statement Model Number code.
ISMODDESC	varchar(255)	Y	ISMODDESC is the Income Statement Model Number description.
ISMODDESC2	varchar(2)	Y	ISMODDESC2 is additional Income Statement Model Number description information.

CSRIndFmt: Industry Format Reference Data

This table contains industry format reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRINDFMT (Clustered)	INDFMTCD

Field	Type	Nullable	Description
INDFMTCD	varchar(13)	N	INDFMTCD is the Industry Format code.
INDFMTDESC	varchar(200)	Y	INDFMTDESC is the Industry Format description.
INDFMTDESC1	varchar(57)	Y	INDFMTDESC1 is additional Industry Format description information.

CSRIndSec: S&P Industry Sector Codes Reference Data

This table contains reference data for S&P industry sector codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRINDSEC (Clustered)	SPINDCD

Field	Type	Nullable	Description
SPINDCD	smallint	N	SPINDCD is the S&P Industry Sector code.
SPINDDESC	varchar(255)	Y	SPINDDESC is the S&P Industry Sector description.
SPINDDESC2	varchar(2)	Y	SPINDDESC2 is additional S&P Industry Sector description information.

CSRInvVal: Inventory Valuations Reference Data

This table contains reference data for inventory valuations.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRINVVAL (Clustered)		INVVALCD	
Field	Type	Nullable	Description
INVVALCD	smallint	N	INVVALCD is the Inventory Valuation Method code.
INVVALDESC	varchar(51)	Y	INVVALDESC is the Inventory Valuation Method description.

CSRIssueTyp: Issue Types Reference Data

This table contains reference data for issue types.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRISSUETYP (Clustered)		TPCICD	
Field	Type	Nullable	Description
TPCICD	varchar(8)	N	TPCICD is the Issue type. CSRIssueTyp.TPCICD cross-references with CSVSecurity.TPCI .
TPCIDESC	varchar(255)	Y	TPCIDESC is the Issue description.
TPCIDESC2	varchar(2)	Y	TPCIDESC2 is additional Issue description information.

CSRMajIdxCl: Major Index—Classification Reference Data

This table contains major index – classification reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRMAJIDXCL (Clustered)		IDXCAT, IDXIDCD	
CSRMAJIDXCL_1		IDXIDCD, IDXCAT	
Field	Type	Nullable	Description
IDXCAT	varchar(11)	N	IDXCAT is the Index Category.
IDXIDCD	varchar(11)	N	IDXIDCD is the Major Index ID code.
IDXIDDESC	varchar(255)	Y	IDXIDDESC is the Major Index ID description.
IDXIDDESC2	varchar(2)	Y	IDXIDDESC2 is additional Major Index ID description information.

CSRNAICCd: NAICS Code Reference Data

This table contains NAICS code reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRNAICCD (Clustered)		NAICSCD	

Field	Type	Nullable	Description
NAICSCD	int	N	NAICSCD is the NAICS code.
NAICSDESC	varchar(255)	Y	NAICSDESC is the NAICS description.
NAICSDESC2	varchar(2)	Y	NAICSDESC2 is additional NAICS description information.
NAICSTAT	char(1)	Y	NAICSTAT is the NAICS status.

CSROffCRSO: Officer Sign-Off Reference Data

This table contains officer sign-off reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSROFFCRSO (Clustered)	OSOCD

Field	Type	Nullable	Description
OSOCD	char(1)	N	OSOCD is the Officer SOX Certification code.
OSODESC	varchar(200)	Y	OSODESC is the Officer SOX Certification description.
OSODESC1	varchar(57)	Y	OSODESC1 is additional Officer SOX Certification description information.

CSROGMethod: Oil and Gas Method Reference Data

This table contains oil & gas method reference data.

Update Cycle: Daily **Adjusted:** No

Indexes	Index Fields
pkey_CSROGMETHOD (Clustered)	OGMCD

Field	Type	Nullable	Description
OGMCD	char(1)	N	OGMCD is the Oil and Gas Method code.
OGMDESC	varchar(200)	Y	OGMDESC is the Oil and Gas Method description.
OGMDESC1	varchar(57)	Y	OGMDESC1 is additional Oil and Gas Method description information.

CSROpinions: Opinions Reference Data

This table contains opinions reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSROPINIONS (Clustered)	AUOPCD

Field	Type	Nullable	Description
AUOPCD	smallint	N	AUOPCD is the Auditor Opinion code.
AUOPDESC	varchar(51)	Y	AUOPDESC is the Auditor Opinion description.

CSRPrStat: Price Status Codes Reference Data

This table contains reference data for price status codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRPRCSTAT (Clustered)	PRCSTDCD

Field	Type	Nullable	Description
PRCSTDCD	smallint	N	PRCSTDCD is the Price Status code.
PRCSTDDESC	varchar(255)	Y	PRCSTDDESC is the Price Status description.
PRCSTDDESC2	varchar(2)	Y	PRCSTDDESC2 is additional Price Status description information.

CSRQSrcDoc: Quarterly Source Document Code Reference Data

This table contains quarterly source document code reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRQSRCDOC (Clustered)	SRCQCD

Field	Type	Nullable	Description
SRCQCD	smallint	N	SRCQCD is the Source Document quarterly code.
SRCQDESC	varchar(255)	Y	SRCQDESC is the Source Document description.
SRCQDESC2	varchar(2)	Y	SRCQDESC2 is additional Source Document quarterly description information.

CSRSecStat: Security Status Codes

This table contains information for security status codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRSECSTAT (Clustered)	ISALRTCD

Field	Type	Nullable	Description
ISALRTCD	varchar(9)	N	ISALRTCD is the Issue Status Alert code.
ISALRTDESC	varchar(255)	Y	ISALRTDESC is the Issue Status Alert description.
ISALRTDESC2	varchar(2)	Y	ISALRTDESC2 is additional Issue Status Alert description information.

CSRSEctors: S&P Sector Codes Reference Data

This table contains reference data for S&P sector codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRSECTORS (Clustered)	SPSECCD

Field	Type	Nullable	Description
SPSECCD	smallint	N	SPSECCD is the S&P Economic Sector code.
SPSECDDESC	varchar(255)	Y	SPSECDDESC is the S&P Economic Sector description.
SPSECDDESC2	varchar(2)	Y	SPSECDDESC2 is additional S&P Economic Sector description information.

CSRSICCD: SIC Code Reference Data

This table contains SIC code reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRSICCD (Clustered)		SICCD	
Field	Type	Nullable	Description
SICCD	smallint	N	SICCD is the SIC code.
SICDESC	varchar(255)	Y	SICDESC is the SIC description.
SICDESC2	varchar(2)	Y	SICDESC2 is additional SIC description information.
SICSTAT	char(1)	Y	SICSTAT is the SIC status (active or inactive).

CSRSPICD: S&P Industry Index Code Reference Data

This table contains S&P industry index code reference data.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRSPICD (Clustered)		SPIICD	
Field	Type	Nullable	Description
SPIICD	smallint	N	SPIICD is the S&P Industry Index code.
SPIIDESC	varchar(255)	Y	SPIIDESC is the S&P Industry Index description.
SPIIDESC2	varchar(2)	Y	SPIIDESC2 is additional S&P Industry Index description information.
SPIISTAT	char(1)	Y	SPIISTAT is the status of the S&P Industry Index code (active or inactive).

CSRSPMICD: S&P Major Industry Codes Reference Data

This table contains reference data for S&P major industry codes.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRSPMICD (Clustered)		SPMICD	
Field	Type	Nullable	Description
SPMICD	tinyint	N	SPMICD is the S&P Major Index code.
SPMIDESC	varchar(255)	Y	SPMIDESC is the S&P Major Index description.
SPMIDESC2	varchar(2)	Y	SPMIDESC2 is additional S&P Major Index description information.
SPMISTAT	char(1)	Y	SPMISTAT is the S&P Major Index status (active or inactive).

CSRStatAlrt: Status Alerts Reference Data

This table contains reference data for status alerts.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSRSTATALRT (Clustered)		STALTC	

Field	Type	Nullable	Description
STALTCOD	varchar(3)	N	STALTCOD is the Status Alert code.
STALTDESC	varchar(254)	Y	STALTDESC is the Status Alert description.
STALTDESC2	varchar(2)	Y	STALTDESC2 is additional Status Alert description information.

CSRStates: States Reference Data

This table contains reference data for states and province codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRSTATES (Clustered)	STATECD

Field	Type	Nullable	Description
STATECD	varchar(9)	N	STATECD is the State/Province code.
STATEDESC	varchar(51)	Y	STATEDESC is the State/Province description.

CSRStkO: Stock Ownership Reference Data

This table contains stock ownership reference data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRSTKO (Clustered)	STKOCOD

Field	Type	Nullable	Description
STKOCOD	char(1)	N	STKOCOD is the Stock Ownership code.
STKODESC	varchar(200)	Y	STALTDESC is the Stock Ownership description.
STKODESC1	varchar(57)	Y	STKODESC1 is additional Stock Ownership description information.

CSRTitles: Title Codes Reference Data

This table contains reference data for title codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRTITLES (Clustered)	OFCDCD

Field	Type	Nullable	Description
OFCDCD	varchar(9)	N	OFCDCD is the Officer Title code.
OFCDESC	varchar(51)	Y	OFCDESC is the Officer Title description.

CSRUpdates: Update Codes Reference Data

This table contains reference data for update codes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSRUPDATES (Clustered)	UPDCD

Field	Type	Nullable	Description
UPDCD	smallint	N	UPDCD is the Update code
UPDESC	varchar(51)	Y	UPDESC is the Update description.

CSecMth: Monthly Descriptor

This table contains monthly descriptor information.

NOTE

As of 21 July 2020, SPGIM, SPIIM and SPMIM fields are no longer populated. These fields are set to NULL.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSECMTH (Clustered)	GVKEY, IID, DATADATE
CSSECMTH_1	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
AJEXM	float	Y	AJEXM is the monthly adjustment factor - cumulative by ex-date.
AJPM	float	Y	AJPM is the monthly adjustment factor - cumulative by payable date.
ISALRT	varchar(9)	Y	ISALRT is the issue status alert. It contains the two-character code that indicates when issue trading has been suspended.
PRIMISS	char(1)	Y	PRIMISS is a monthly market data descriptor that identifies the issue with the highest market presence.
SPGIM	varchar(9)	Y	SPGIM is the S&P Global Industry Classification Index code – historical.
SPIIM	varchar(9)	Y	SPIIM is the S&P Industry Index code –historical.
SPMIM	varchar(9)	Y	SPMIM is the S&P Major Index code – historical.

CSecMthDiv: Monthly Dividend

This table contains monthly dividend information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSSECMTHDIV (Clustered)	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CHEQVM	float	Y	CHEQVM is the monthly cash equivalent distributions per share - ex-date.
CURCDDVM	varchar(4)	Y	CURCDDVM is the monthly ISO currency code – dividend.
DVPSPM	float	Y	DVPSPM is the monthly dividends per share –pay date.
DVPSXM	float	Y	DVPSXM is the index monthly cash dividend paid per share by ex date. DVPSXM is adjusted for all stock splits and stock dividends that occurred during the period. This value does not include payments in preferred stock in lieu of cash, spin-offs, and stock of other corporations.
DVRATE	float	Y	DVRATE is the monthly indicated annual dividend rate.

CSecMthPrc: Monthly Item

This table contains monthly item information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSSECMTHPRC (Clustered)	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CSFSM	float	Y	CSFSM is the monthly common stock float shares – Canada.
CSHTRM	float	Y	CSHTRM is the monthly trading volume.
CURCDM	varchar(4)	Y	CURCDM is the monthly ISO currency code.
NAVM	float	Y	NAVM is the monthly net asset value.
PRCCM	float	Y	PRCCM is the absolute close market price for each calendar month.
PRCHM	float	Y	PRCHM is the absolute high market price for each calendar month.
PRCLM	float	Y	PRCLM is the absolute low market price for each calendar month.

CSecMthSpt: Monthly Stock Splits

This table contains information for monthly stock splits.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSECMTHSPT (Clustered)	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
RAWPM	float	Y	RAWPM is the monthly raw adjustment factor – pay date.
RAWXM	float	Y	RAWXM is the monthly raw adjustment factor – ex date.

CSecMSptFn: Monthly Stock Split Footnotes

This table contains information for monthly stock split footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSECMSPTFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSSECMSPTFN_1	GVKEY, Item, DATADATE
CSSECMSPTFN_2	GVKEY, DATADATE
CSSECMSPTFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSSECMSPTFN_4	GVKEY, IID, DATADATE
CSSECMSPTFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSSECMSptFn.Item and Group_ = 145.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSSECMDivFn: Monthly Dividend Footnotes

This table contains information for monthly dividend footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSSECMDIVFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSSECMDIVFN_1	GVKEY, Item, DATADATE
CSSECMDIVFN_2	GVKEY, DATADATE
CSSECMDIVFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSSECMDIVFN_4	GVKEY, IID, DATADATE
CSSECMDIVFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSSECMDivFn.Item and Group_ = 81.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSVCompany: Compustat XF Company Information

This table contains Compustat XF company information.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_CSVCOMPANY (Clustered)	GVKEY
CSVCOMPANY_1	CONM, GVKEY
CSVCOMPANY_2	CITY, GVKEY
CSVCOMPANY_3	STATE, GVKEY

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the primary link for all CS* tables.
ADD1	varchar(66)	Y	ADD1 is the Company's address.
ADD2	varchar(66)	Y	ADD2 is the Company's address.
ADD3	varchar(66)	Y	ADD3 is the Company's address.
ADD4	varchar(66)	Y	ADD4 is the Company's address.

Field	Type	Nullable	Description
BUSDESC	varchar(255)	Y	BUSDESC[2 through 8] is a textual description of a company's business operations.
BUSDESC2	varchar(255)	Y	
BUSDESC3	varchar(255)	Y	
BUSDESC4	varchar(255)	Y	
BUSDESC5	varchar(255)	Y	
BUSDESC6	varchar(255)	Y	
BUSDESC7	varchar(255)	Y	
BUSDESC8	varchar(223)	Y	
ADDZIP	varchar(21)	Y	ADDZIP is the postal code or zip code of the company's corporate headquarters or home office.
CITY	varchar(101)	Y	CITY is the city where a company's corporate headquarters or home office is located.
CONM	varchar(200)	Y	CONM is the company name.
CONM2	varchar(57)	Y	CONM2 is the company name.
COSTAT	char(1)	Y	COSTAT is the company status and can be either A = Active or I = Inactive.
DLDTE	datetime	Y	DLDTE is the research company deletion date.
DLRSN	varchar(9)	Y	DLRSN is the research company deletion reason.
FAX	varchar(21)	Y	FAX is the area code and facsimile (fax) number for a company.
FIC	varchar(4)	Y	FIC is the ISO country code – incorporation.
FYRC	tinyint	Y	FYRC is the fiscal year end month – current.
GGROUP	varchar(5)	Y	GGROUP is the second level in the hierarchy of the Global Industry Classification Standard (GICS).
GIND	varchar(7)	Y	GIND is the third level in the hierarchy of the Global Industry Classification Standard (GICS).
GSECTOR	varchar(3)	Y	GSECTOR is the first level in the hierarchy of the Global Industry Classification Standard (GICS).
GSUBIND	varchar(9)	Y	GSUBIND is the fourth level in the hierarchy of the Global Industry Classification Standard (GICS).
IDBFLAG	char(1)	Y	IDBFLAG indicates which database the item can be found in. The IDBFlag may be: – D (Domestic) – I (International) – B (Both)
INCORP	varchar(9)	Y	INCORP contains the code that indicates the U.S. state in which a company is incorporated.
LOC	varchar(4)	Y	LOC is the ISO country code of the headquarters.
NAICS	varchar(7)	Y	NAICS is a six-digit coding system for classifying establishments on a production/process-oriented basis.
PHONE	varchar(21)	Y	PHONE is the area code and telephone number of the company's corporate headquarters or home office.
PRICAN	varchar(9)	Y	PRICAN identifies the current primary issue for a Canadian company.
PRIROW	varchar(9)	Y	PRIROW identifies the primary issue for companies that trade outside of the U.S. and Canada.
PRIUSA	varchar(9)	Y	PRIUSA identifies the current primary issue for a U.S. company.
SIC	varchar(5)	Y	SIC contains the code that identifies the line of business best representative of the company as a whole.
SPCINDCD	smallint	Y	SPCINDCD contains the code that identifies all companies in any of the specific S&P industry groups.
SPCSECCD	smallint	Y	SPCSECCD is an S&P economic sector code.
STATE	varchar(9)	Y	STATE contains the code that indicates the U.S. state or territory or the Canadian province of a company's address.

Field	Type	Nullable	Description
CIK	varchar(11)	Y	CIK is the Central Index Key.
CONML	varchar(101)	Y	CONML is the company's legal name.
EIN	varchar(11)	Y	EIN is the employer identification number.
IPODATE	datetime	Y	IPODATE is the date of a company's initial public stock offering.
WEBURL	varchar(61)	Y	WEBURL is the address for a company's home page on the Internet.
COUNTY	varchar(101)	Y	COUNTY is the county where a company's corporate headquarters or home office is located.
STKO	tinyint	Y	STKO is the stock ownership of the company.

CSVSecurity: Compustat XF Security Information

This table contains Compustat XF security information.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_CSVSECURITY (Clustered)	GVKEY, IID
CSVSECURITY_1	TIC, GVKEY, IID
CSVSECURITY_2	CUSIP, GVKEY, IID
CSVSECURITY_3	SEDOL, GVKEY, IID
CSVSECURITY_4	ISIN, GVKEY, IID
CSVSECURITY_5	CUSIP
CSVSECURITY_6	SECINTCODE
CSVSECURITY_7	SECID
CSVSECURITY_8	GVKEY, EXCNTRY

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the primary link for all CS* tables.
IID	varchar(4)	N	IID is the issue id and uniquely identifies each issue of a company.
SECID	varchar(14)	Y	SECID is the combination of the GvKey and IId.
CUSIP	varchar(9)	Y	CUSIP is a unique identifier for each company on Compustat.
DLDEI	datetime	Y	DLDEI is the security deletion date.
DLRSNI	varchar(9)	Y	DLRSNI is the security inactivation code.
DSCI	varchar(29)	Y	DSCI is the security description.
EPF	Char(1)	Y	EPF is the earnings participation flag, and signals if the security is part of the company's earnings. It has two values: Y = Yes and Blank = No.
EXCHG	smallint	Y	EXCHG identifies the major exchange on which the company's Common/Ordinary Stock (Capital) is traded.
EXCNTRY	varchar(4)	Y	EXCNTRY is the three-digit ISO country code that identifies the country of the exchange for the market data presented in the issue record.
ISIN	varchar(13)	Y	ISIN is an identification number developed from an internationally accepted standard for uniquely identifying securities worldwide.
SECSTAT	Char(1)	Y	SECSTAT is the security status marker, and is either A = Active or I = Inactive
SEDOL	varchar(8)	Y	SEDOL is used primarily to identify issues listed outside of North America.
TIC	varchar(9)	Y	TIC identifies the symbol associated with the trading of a particular issue on an exchange. For example, when a parent company symbol is appended with a number it indicates a subsidiary of a publicly traded company.
TPCI	varchar(9)	Y	TPCI is the security type. CSVSecurity.TPCI cross-references with CSRIssueTyp .TPCICD.
SECINTCODE	int	Y	SECINTCODE is the security integer code.

5 Compustat XF Daily Historical

CSBkCoAFntInd: Annual Fundamental Footnotes Historical

This table contains historical information for annual fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOAFNTIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOAFNTIND_1	GVKEY, Item, DATADATE
CSBKCOAFNTIND_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKCOAFNTIND_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoAFntInd.Item and Group_ = 246.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBkCoAAudit: Compustat XF Audit Information Historical

This table contains Compustat XF audit historical information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOAAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CSBKCOAAUDIT_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.

Field	Type	Nullable	Description
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
AU	varchar(9)	Y	AU lists the auditing firms that audited a company's financial statements. AU is translated by CSRAuditors where CSRAuditors.AUCD = CSBkCoAAudit.AU.
AUOP	varchar(9)	Y	AUOP is the auditor opinion. AUOP is translated by CSROPINIONS where CSROPINIONS.AUOPCD = CSBkCoAAudit.AUOP.
AUOPIC	char(1)	Y	AUOP is the auditor opinion of internal control. AUOPIC is translated by CSRAuopIC where CSRAuopIC.AUOPICCD = CSBkCoAAudit.AUOPIC.
CEOSO	char(1)	Y	CEOSO is the Chief Executive Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.
CFOSO	char(1)	Y	CFOSO is the Chief Financial Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.

CSBkCoADesInd: Compustat XF Company Descriptions Historical

This table contains historical information for Compustat XF company descriptions.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOADESIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL
CSBKCOADESIND_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSBKCOADESIND_2	GVKEY, FYEAR, INDFMT, DATAFMT, CONSOL
CSBKCOADESIND_3	DATADATE, GVKEY, INDFMT, DATAFMT, CONSOL

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ACCTSTD	varchar(9)	Y	ACCTSTD identifies the accounting standard a company uses when preparing its financial statements. If a company does not reference a specific standard, a domestic standard is assumed. ACCTSTD is translated by CSRAccStd where CSRAccStd.ACCTSTDCD = CSBkCoADesInd.ACCTSTD.
ACQMETH	varchar(3)	Y	ACQMETH is the code that identifies the method a company uses to account for acquisitions. ACQMETH is translated by CSRAcqMeth where CSRAcqMeth.ACQMETHCD = CSBkCoADesInd.ACQMETH.
ADRR	float	Y	ADRR is the ADR (American Depositary Receipt) Ratio. This indicates the number of a foreign company's common or ordinary shares that are equivalent to one ADR or one ADS (American Depositary Share). This ratio is usually a whole number, and is available only for foreign companies that trade ADR or ADS in the U.S. ADRR is on an annual basis.
AJEX	float	Y	AJEX is the adjustment factor you use to adjust per-share data (such as price, earnings per share, and dividends per share) and share data (such as shares outstanding and shares traded) for all stock splits and stock dividends occurring subsequent to the end of a given period. The ex-dividend date is used to

Field	Type	Nullable	Description
			determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock split or stock dividend occurs. AJEX is on an annual basis.
AJP	float	Y	AJP is the adjustment factor you use to adjust dividends per share for all stock dividends occurring subsequent to the end of a given period. The payable date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock dividend occurs. AJP is on an annual basis.
APDEDATE	datetime	Y	APDEDATE is the actual date the company closes their accounting period, which may be different from the last day of the month in the period. APDEDATE is in the form YYYY-MM-DD.
BSPR	varchar(9)	Y	BSPR is the balance sheet presentation method. BSPR is translated by CSRBalPres where CSRBalPres.BSPRCD = CSBkCoAdesInd.BSPR.
COMPST	varchar(9)	Y	COMPST is the comparability status which describes conditions under which data in one period may not be comparable to data in another period. COMPST is translated by CSRCompStat where CSRCompStat.COMPSTCD = CSBkCoAdesInd.COMPST.
CURCD	varchar(4)	Y	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURNCD	varchar(4)	Y	CURNCD is the native currency code and identifies the currency in which the company reports its financial data. When CURNCD is not the same as CURCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURRTR	float	Y	CURRTR is the currency translation rate. This is the rate of exchange used to translate international currency into U.S. dollars. The rate used is the rate in effect as of the date of the company's balance sheet. If an international company reports in U.S. dollars, the translation rate is 1.000.
CURUSCN	float	Y	CURUSCN is CURUSCN is the rate of exchange used to translate Canadian currency amounts into U.S. dollar amounts. This is available only when a company reports in both U.S. and Canadian accounting standards.
FDATE	datetime	Y	FDATE is the date the data was finalized for that year or quarter.
FYEAR	smallint	Y	FYEAR represents the fiscal year of the current fiscal year-end month.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
ISMOD	smallint	Y	ISMOD is the income statement model number.
OGM	varchar(9)	Y	OGM is the method of reporting revenue used by the Oil & Gas company.
PDATE	datetime	Y	PDATE is the date the data for the company is updated on a preliminary basis for that year or quarter.
PDDUR	smallint	Y	PDDUR is a unique integer code that identifies the source of the data. PDDUR is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as PDDUR.
SCF	smallint	Y	SCF contains the numeric code that identifies the format of a company's flow of funds statement, statement of changes, or statement of cash flow.
SRC	smallint	Y	SRC contains code that indicates the most recent source from which S&P obtained data for each fiscal period.
STALT	varchar(3)	Y	STALT is a unique integer code that identifies the source of the data. STALT is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as STALT.
UDPL	varchar(9)	Y	UDPL designates the method used by the utility company to account for Liberalized Depreciation.
UPD	smallint	Y	UPD contains the code that identifies the updated status of the data for the period. UPD consists of a one-character numeric code.

CSBkCoAFndDC1: Compustat XF Annual Fundamentals Data Codes 1 Historical

This table contains historical information for Compustat XF annual fundamentals data codes 1.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOAFNDDC1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOAFNDDC1_1	GVKEY, Item, DATADATE
CSBKCOAFNDDC1_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKCOAFNDDC1_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoAFndDC1.Item and Group_ = 231.
Value_	smallint	Y	Value_ is the raw value provided by Compustat.

CSBkCoAFndDC2: Compustat XF Annual Fundamentals Data Codes 2 Historical

This table contains historical information for Compustat XF annual fundamentals data codes 2.

Update Cycle: Daily **Adjusted:** No

Indexes	Index Fields
pkey_CSBKCOAFNDDC2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOAFNDDC2_1	GVKEY, Item, DATADATE
CSBKCOAFNDDC2_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKCOAFNDDC2_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoAFndDC2.Item and Group_ = 232.
Value_	smallint	Y	Value_ is the raw value provided by Compustat.

CSBkCoAFnd1: Compustat XF Annual Fundamentals 1 Historical

This table contains historical information for Compustat XF annual fundamentals 1.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOAFND1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOAFND1_1	GVKEY, Item, DATADATE
CSBKCOAFND1_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKCOAFND1_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSBKCOAFND1_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoAFnd1.Item and Group_ = 233.
Value_	float	Y	Value_ is the raw value provided by Compustat.

CSBkCoAFnd2: Compustat XF Annual Fundamentals 2 Historical

This table contains historical information for Compustat XF annual fundamentals 2.

Update Cycle: Daily **Adjusted:** Yes

Indexes	Index Fields
pkey_CSBKCOAFND2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOAFND2_1	GVKEY, Item, DATADATE
CSBKCOAFND2_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKCOAFND2_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSBKCOAFND2_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoAFnd2.Item and Group_ = 234.
Value_	float	Y	Value_ is the raw value provided by Compustat.

CSBkCoAInvVal: Compustat XF Inventory Valuation Data Historical

This table contains historical Compustat XF inventory valuation data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOAINVVAL (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CSBKCOAINVVAL_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSBKCOAINVVAL_2	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
INVVAL	int	Y	INVVAL contains the code that identifies the method used to value inventory.

CSBkCoAMkt: Compustat XF Market Data Historical

This table contains historical Compustat XF market data.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOAMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD
CSBKCOAMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
CLSM	smallint	Y	CLSM is the month of the company's last close price.
CSHTR	float	Y	CSHTR is the number of shares traded for companies listed on national stock exchanges and over-the-counter companies in the NASDAQ system on a fiscal, rather than calendar, basis.

Field	Type	Nullable	Description
DVPSP	float	Y	DVPSP is the cash dividends per share for which the payable dates occurred during the reporting period, unadjusted for all stock splits and stock dividends that occurred during the period.
DVPSX	float	Y	DVPSX is the cash dividends per share for which the ex-dividend dates occurred during the reporting period, adjusted for all stock splits and stock dividends that occurred during the period.
PRCC	float	Y	PRCC is the absolute close transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCH	float	Y	PRCH is the absolute high transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCL	float	Y	PRCL is the absolute low transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSBkCoFortune: Fortune 500 Group Historical

This table contains historical Fortune 500 group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOFORTUNE (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
FORI	smallint	Y	FORI contains the code that identifies the industry group of a Fortune 1000 company.
FORRK	smallint	Y	FORRK is the fortune rank.

CSBkCoAudit: Interim Auditor Group Historical

This table contains historical interim auditor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOIAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, RANK
CSBKCOIAUDIT_1	GVKEY, INDFMT, CONSOL, DATAFMT, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.

Field	Type	Nullable	Description
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
CEOSOQ	char(1)	Y	CEOSOQ is the same as CEOSO , but is on a quarterly basis.
CFOSOQ	char(1)	Y	CFOSOQ is the same as CFOSO , but is on a quarterly basis.

CSBkColDesInd: Company Interim Descriptor Historical

This table contains historical company interim descriptor information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOIDESIND (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSBKCOIDESIND_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSBKCOIDESIND_2	GVKEY, FQTR, FYEARQ, INDFMT, CONSOL, DATAFMT
CSBKCOIDESIND_3	DATADATE, GVKEY, INDFMT, CONSOL, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ACCTSTDQ	varchar(9)	Y	ACCTSTDQ is the same as ACCTSTD , but is on a quarterly basis.
ADRRQ	float	Y	ADRRQ is the same as ADRR , but is on a quarterly basis.
AJEXQ	float	Y	AJEXQ is the same as AJEX , but is on a quarterly basis.
AJPQ	float	Y	AJPQ is the same as AJP , but is on a quarterly basis.
APDEDATEQ	datetime	Y	APDEDATEQ is the same as APDEDATE , but is on a quarterly basis.
BSPRQ	varchar(9)	Y	BSPRQ is the same as BSPR , but is on a quarterly basis.
COMPSTQ	varchar(9)	Y	COMPSTQ is the same as COMPST , but is on a quarterly basis.
CURCDQ	varchar(4)	Y	CURCDQ is the same as CURCD , but is on a quarterly basis.
CURNCDQ	varchar(4)	Y	CURNCDQ is the same as CURNCD , but is on a quarterly basis.
CURRTRQ	float	Y	CURRTRQ is the same as CURRTR , but is on a quarterly basis.
CURUSCNQ	float	Y	CURUSCNQ is the same as CURUSCN , but is on a quarterly basis.
DATAQTR	varchar(7)	Y	DATAQTR is the calendar year and quarter.
DATAFQTR	varchar(7)	Y	DATAFQTR is the fiscal year and quarter.
FDATEQ	datetime	Y	FDATEQ is the same as FDATE , but is on a quarterly basis.
FQTR	smallint	Y	FQTR is the fiscal quarter of the company.
FYEARQ	smallint	Y	FYEARQ is the same as FYEAR , but is on a quarterly basis.
OGMQ	varchar(9)	Y	OGMQ is the same as OGM , but is on a quarterly basis.
PDATEQ	datetime	Y	PDATEQ is the same as PDATE , but is on a quarterly basis.
PDQ	smallint	Y	PDQ is the number of months in a quarterly, interim reporting period.

Field	Type	Nullable	Description
PDSA	smallint	Y	PDSA is the number of months in a semiannual, interim reporting period.
PDYTD	smallint	Y	PDYTD is the number of months in a year-to-date, interim reporting period.
RDQ	datetime	Y	RDQ is the date on which quarterly earnings per share are first publicly reported.
RP	varchar(3)	Y	RP is the interim reporting periodicity of a company for a specific year.
SCFQ	int	Y	SCFQ is the same as SCF , but is on a quarterly basis.
SRCQ	int	Y	SRCQ is the same as SRC , but is on a quarterly basis.
STALTQ	varchar(3)	Y	STALTQ is the same as STALT , but is on a quarterly basis.
UPDQ	smallint	Y	UPDQ is the same as UPD , but is on a quarterly basis.

CSBkColFntYTD: Company Interim Fundamentals – Year to Date Footnotes Historical

This table contains historical year-to-date company interim fundamentals information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOIFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOIFNTYTD_1	GVKEY, Item, DATADATE
CSBKCOIFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE
CSBKCOIFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColFntYTD.Item and Group_ = 240.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBkColFntQ: Company Quarterly Fundamental Footnotes Historical

This table contains historical information for company quarterly fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOIFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOIFNTQ_1	GVKEY, Item, DATADATE

Indexes	Index Fields
CSBKCOIFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE
CSBKCOIFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBKColFntQ.Item and Group_ = 241.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBKColFntSA: Company Quarterly Fundamental Footnotes Historical

This table contains historical information for company quarterly fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOIFNTSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOIFNTSA_1	GVKEY, Item, DATADATE
CSBKCOIFNTSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE
CSBKCOIFNTSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBKColFntSA.Item and Group_ = 242.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBkColMkt: Interim Market Group Historical

This table contains historical interim market group information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOIMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD, YEM
CSBKCOIMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
YEM	smallint	N	YEM works with CFFLAG to represent the month of the company's year-end price.
CLSMQ	smallint	Y	CLSMQ is the same as CLSM , but is on a quarterly basis.
CSHTRQ	float	Y	CSHTRQ is the same as CSHTR , but is on a quarterly basis.
DVPSPQ	float	Y	DVPSPQ is the same as DVPSP , but is on a quarterly basis.
DVPSXQ	float	Y	DVPSXQ is the same as DVPSX , but is on a quarterly basis.
PRCCQ	float	Y	PRCCQ is the same as PRCC , but is on a quarterly basis.
PRCHQ	float	Y	PRCHQ is the same as PRCH , but is on a quarterly basis.
PRCLQ	float	Y	PRCLQ is the same as PRCL , but is on a quarterly basis.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSBkColIndustryPres: Company Industry Presentation Historical

This table contains historical company industry presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOINDSTRYPRES (Clustered)	GVKEY, DATADATE, CONSOL, IPCD
CSBKCOINDSTRYPRES_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CsKeyCode where FIELDNAME = INDFMT.
IPCD	char(1)	N	IPCD identifies the industry presentation of financial services companies trading outside of the United States and Canada.

CSBkCoIndustry: Industry Classification Presentation Historical

This table contains historical industry classification presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOINDUSTRY (Clustered)	GVKEY, DATADATE, CONSOL
CSBKCOINDUSTRY_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
NAICSH	int	Y	NAICSH contains the historical NAICS code assigned to a company.
SICH	int	Y	SICH contains the SIC code that identifies the company's SIC Code in prior years.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSBkCoMth: Company Monthly Historical

This table contains historical monthly company information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOMTH (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
BETA	float	Y	BETA is a measurement of the sensitivity of a company's stock price to the overall fluctuation in the Standard & Poor's 500 (S&P 500) Index Price for U.S. Companies, or the Toronto Stock Exchange 300 (TSE 300) Index Price for Canadian Companies.
SPCSR	varchar(4)	Y	SPCSR is an appraisal of the past performance of a stock's earnings and dividends and the stock's relative standing as of a company's current fiscal year-end.

CSBkCoIFndQ: Company Interim Fundamentals – Quarterly Historical

This table contains quarterly historical information for company interim fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOIFNDQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOIFNDQ_1	GVKEY, Item, DATADATE
CSBKCOIFNDQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE

Indexes		Index Fields	
CSBKCOIFNDQ_3		GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE	
CSBKCOIFNDQ_4		GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBKColFndQ.Item and Group_ = 247.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSBKColFndYTD: Company Interim Fundamentals – Year to Date Historical

This table contains year-to-date historical information for company interim fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes		Index Fields	
pkey_CSBKCOIFNDYTD (Clustered)		GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item	
CSBKCOIFNDYTD_1		GVKEY, Item, DATADATE	
CSBKCOIFNDYTD_2		GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE	
CSBKCOIFNDYTD_3		GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE	
CSBKCOIFNDYTD_4		GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColFndYTD.Item and Group_ = 248.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSBkColFndSA: Company Quarterly Fundamentals Historical

This table contains historical information for company quarterly fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOIFNDSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOIFNDSA_1	GVKEY, Item, DATADATE
CSBKCOIFNDSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSBKCOIFNDSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSBKCOIFNDSA_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

g

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColFndSA.Item and Group_ = 249.

Field	Type	Nullable	Description
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSBKSecM: Monthly Descriptor Historical

This table contains historical monthly descriptor information.

NOTE

As of 21 July 2020, SPGIM, SPIIM and SPMIM fields are no longer populated. These fields are set to NULL.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSbkSECM (Clustered)	GVKEY, IID, DATADATE
CSBKSECM_1	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
AJEXM	float	Y	AJEXM is the monthly adjustment factor - cumulative by ex-date.
AJPM	float	Y	AJPM is the monthly adjustment factor - cumulative by payable date.
ISALRT	varchar(9)	Y	ISALRT is the issue status alert. It contains the two-character code that indicates when issue trading has been suspended.
PRIMISS	char(1)	Y	PRIMISS is a monthly market data descriptor that identifies the issue with the highest market presence.
SPGIM	varchar(9)	Y	SPGIM is the S&P Global Industry Classification Index code – historical.
SPIIM	varchar(9)	Y	SPIIM is the S&P Industry Index code – historical.
SPMIM	varchar(9)	Y	SPMIM is the S&P Major Index code – historical.

CSBKSecMDv: Monthly Dividend Historical

This table contains historical monthly dividend information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSbkSECMDV (Clustered)	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.

Field	Type	Nullable	Description
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CHEQVM	float	Y	CHEQVM is the monthly cash equivalent distributions per share - ex-date.
CURCDDVM	varchar(4)	Y	CURCDDVM is the monthly ISO currency code – dividend.
DVPSPM	float	Y	DVPSPM is the monthly dividends per share –pay date.
DVPSXM	float	Y	DVPSXM is the index monthly cash dividend paid per share by ex date. DVPSXM is adjusted for all stock splits and stock dividends that occurred during the period. This value does not include payments in preferred stock in lieu of cash, spin-offs, and stock of other corporations.
DVRATE	float	Y	DVRATE is the monthly indicated annual dividend rate.

CSBkSecMPrc: Monthly Item Historical

This table contains historical monthly item information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKSECMPC (Clustered)	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CSFSM	float	Y	CSFSM is the monthly common stock float shares – Canada.
CSHTRM	float	Y	CSHTRM is the monthly trading volume.
CURCDM	varchar(4)	Y	CURCDM is the monthly ISO currency code.
NAVM	float	Y	NAVM is the monthly net asset value.
PRCCM	float	Y	PRCCM is the absolute close market price for each calendar month.
PRCHM	float	Y	PRCHM is the absolute high market price for each calendar month.
PRCLM	float	Y	PRCLM is the absolute low market price for each calendar month.

CSBkSecMSS: Monthly Stock Splits Historical

This table contains historical monthly stock splits information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKSECMSS (Clustered)	GVKEY, IID, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
RAWPM	float	Y	RAWPM is the monthly raw adjustment factor – pay date.
RAWXM	float	Y	RAWXM is the monthly raw adjustment factor – ex date.

CSBkSecMSSFn: Monthly Stock Split Footnotes

This table contains information for monthly stock split footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKSECMSSFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSBKSECMSSFN_1	GVKEY, Item, DATADATE
CSBKSECMSSFN_2	GVKEY, DATADATE
CSBKSECMSSFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSBKSECMSSFN_4	GVKEY, IID, DATADATE
CSBKSECMSSFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkSecMSSFn.Item and Group_ = 164.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBkSecMDvFn: Monthly Dividend Footnotes

This table contains information for monthly dividend footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKSECMDVFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSBKSECMDVFN_1	GVKEY, Item, DATADATE
CSBKSECMDVFN_2	GVKEY, DATADATE
CSBKSECMDVFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSBKSECMDVFN_4	GVKEY, IID, DATADATE
CSBKSECMDVFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkSecMDvFn.Item and Group_ = 81.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

6 Compustat XF Daily Pension

CSACoPnFndQ: New Company Quarterly Pension and Post-Retirement Data

This table contains new company quarterly pension and post-retirement data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOPNFNDQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSACOPNFNDQ_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERQ	float	Y	PBECERQ is the amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECERQ_DC	smallint	Y	PBECERQ_DC is the data code of the amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECQ	float	Y	PBECQ is the quarterly amount of contributions the company made to its pension plans during the current period.
PBECQ_DC	smallint	Y	PBECQ_DC is the data code of the quarterly amount of contributions the company made to its pension plans during the current period.
PPCQ	float	Y	PPCQ is the periodic pension cost on a quarterly basis.
PPCQ_DC	smallint	Y	PPCQ_DC is the data code of the periodic pension cost on a quarterly basis.
PPICQ	float	Y	PPICQ is the accrual of interest for the year on the projected pension benefit obligation on a quarterly basis.
PPICQ_DC	smallint	Y	PPICQ_DC is the data code of the accrual of interest for the year on the projected pension benefit obligation on a quarterly basis.
PPOPCCQ	float	Y	PPOPCCQ is all quarterly additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPORCCQ_DC	smallint	Y	PPORCCQ_DC is the data code of all quarterly additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPRPAQ	float	Y	PPRPAQ is the quarterly expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPRPAQ_DC	smallint	Y	PPRPAQ_DC is the data code of the quarterly expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPSCQ	float	Y	PPSCQ is the quarterly present value of expected future pension payments attributed to employee services performed during the current year.

Field	Type	Nullable	Description
PPSCQ_DC	smallint	Y	PPSCQ_DC is the data code of the present value of expected future pension payments attributed to employee services performed during the current year.

CSACoPnFndYTD: New Company Year-to-Date Pension and Post-Retirement Data

This table contains new company year-to-date pension and post-retirement data.

Update Cycle: Daily **Adjusted:** No

Indexes	Index Fields
pkey_CSACOPNFNDYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSACOPNFNDYTD_1	GVKEY, -INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERY	float	Y	PBECERY is the year-to-date amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECERY_DC	smallint	Y	PBECERY_DC is the data code of the year-to-date amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECY	float	Y	PBECY is the year-to-date amount of contributions the company made to its pension plans during the current period.
PBECY_DC	smallint	Y	PBECY_DC is the data code of the year-to-date amount of contributions the company made to its pension plans during the current period.
PPCY	float	Y	PPCY is the year-to-date periodic pension cost.
PPCY_DC	smallint	Y	PPCY_DC is the data code of the year-to-date periodic pension cost.
PPICY	float	Y	PPICY is the year-to-date accrual of interest for the year on the projected pension benefit obligation.
PPICY_DC	smallint	Y	PPICY_DC is the data code of the year-to-date accrual of interest for the year on the projected pension benefit obligation.
PPOPCCY	float	Y	PPOPCCY is all year-to-date additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPORCCY_DC	smallint	Y	PPORCCY_DC is the data code of all year-to-date additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPRPAY	float	Y	PPRPAY is the year-to-date expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPRPAY_DC	smallint	Y	PPRPAY_DC is the data code of the year-to-date expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPSCY	float	Y	PPSCY is the year-to-date present value of expected future pension payments attributed to employee services performed during the current year.
PPSCY_DC	smallint	Y	PPSCY_DC is the data code of the year-to-date present value of expected future pension payments attributed to employee services performed during the current year.

CSACoPnFntQ: Company Quarterly and Post-Retirement Footnotes

This table contains information for company quarterly and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOPNFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSACOPNFNTQ_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERQ_FN	varchar(9)	Y	PBECERQ_FN is the additional contributions expected remainder of the year footnote.
PBECQ_FN	varchar(9)	Y	PBECQ_FN is the pension employer contribution footnote.
PPCQ_FN	varchar(9)	Y	PPCQ_FN is the periodic pension cost footnote.
PPICQ_FN	varchar(9)	Y	PPICQ_FN is the pension plans interest cost footnote.
PPOPCCQ_FN	varchar(9)	Y	PPOPCCQ_FN is the pension plans other periodic cost components footnote.
PPRPAQ_FN	varchar(9)	Y	PPRPAQ_FN is the expected change in market value of pension plan assets footnote.
PPSCQ_FN	varchar(9)	Y	PPSCQ_FN is the pension plans service cost footnote.

CSACoPnFntYTD: New Company Year-to-Date Pension and Post-Retirement Footnotes

This table contains information for new company year-to-date pension and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOPNFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSACOPNFNTYTD_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERY_FN	varchar(9)	Y	PBECERY_FN is the year-to-date footnote amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECY_FN	varchar(9)	Y	PBECY_FN is the year-to-date footnote amount of contributions the company made to its pension plans during the current period.
PPCY_FN	varchar(9)	Y	PPCY_FN is the year-to-date periodic pension cost footnote.
PPICY_FN	varchar(9)	Y	PPICY_FN is the year-to-date footnote accrual of interest for the year on the projected pension benefit obligation.
PPOPCCY_FN	varchar(9)	Y	PPOPCCY_FN is all year-to-date footnote additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPRPAY_FN	varchar(9)	Y	PPRPAY_FN is the year-to-date footnote expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPSCY_FN	varchar(9)	Y	PPSCY_FN is the year-to-date footnote present value of expected future pension payments attributed to employee services performed during the current year.

CSACoPnFndA: Company Annual Pension and Post-Retirement Data

This table contains company annual pension and post-retirement data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOPNFNDA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSACOPNFNDA_1	GVKEY, Item, DATADATE
CSACOPNFNDA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoPnFndA.Item and Group_ = 268.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSACoPnFntA: Company Annual and Post-Retirement Footnotes

This table contains information for company annual and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOPNFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSACOPNFNTA_1	GVKEY, Item, DATADATE
CSACOPNFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSACOPNFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoPnFntA.Item and Group_ = 269.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

7 Compustat XF Daily Pension Historical

CSBkCoPnFntA: Annual Pension Footnotes Historical

This table contains information for historical annual pension footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKOPNFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKOPNFNTA_1	GVKEY, Item, DATADATE
CSBKOPNFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKOPNFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoPnFntA.Item and Group_ = 271.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBkCoPnFndA: Company Annual Pension and Post-Retirement Data Historical

This table contains historical company annual pension and post-retirement data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKOPNFNDA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKOPNFNDA_1	GVKEY, Item, DATADATE
CSBKOPNFNDA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkCoPnFndA.Item and Group_ = 270.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

8 Compustat XF Daily Industry

CSACoIndStQC: Quarterly Industry Statistics

This table contains information for quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSACOINDSTQC (Clustered)	KeyCode, Item
CSACOINDSTQC_1	KeyCode

Field	Type	Nullable	Description
KeyCode	int	N	
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoIndStQC.Item and Group_ = 251.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSACoIndStQP: Company Quarterly Industry Statistics

This table contains information for company quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSACOINDSTQP (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, KEYCODE
CSACOINDSTQP_1	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSACOINDSTQP_2	KEYCODE
CSACOINDSTQP_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE, KEYCODE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
KEYCODE	int	N	
UEDODF	datetime	Y	UEDODF is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODF_DC	tinyint	Y	UEDODF_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).

Field	Type	Nullable	Description
UEDODS	datetime	Y	UEDODS is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODS_DC	tinyint	Y	UEDODS_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODT	datetime	Y	UEDODT is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UEDODT_DC	tinyint	Y	UEDODT_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UGDODF	datetime	Y	UGDODF is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODF_DC	tinyint	Y	UGDODF_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODS	datetime	Y	UGDODS is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODS_DC	tinyint	Y	UGDODS_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODT	datetime	Y	UGDODT is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).
UGDODT_DC	tinyint	Y	UGDODT_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).

CSACoIndStA: Annual Industry Statistics

This table contains information for annual industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOINDSTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSACOINDSTA_1	GVKEY, Item, DATADATE
CSACOINDSTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoIndStA.Item and Group_ = 252.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSACoIndFntQ: Quarterly Industry Statistics Footnotes

This table contains information for quarterly industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOINDFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSACOINDFNTQ_1	GVKEY, Item, DATADATE
CSACOINDFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSACOINDFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoIndFntQ.Item and Group_ = 253.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSACoIndFntYTD: Year-to-Date Industry Statistics Footnotes

This table contains information for year-to-date industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOINDFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSACOINDFNTYTD_1	GVKEY, Item, DATADATE
CSACOINDFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSACOINDFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.

Field	Type	Nullable	Description
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoIndFntYTD.Item and Group_ = 254.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSACoIndFntA: Annual Industry Statistics Footnotes

This table contains information for annual industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOINDFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSACOINDFNTA_1	GVKEY, Item, DATADATE
CSACOINDFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSACOINDFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSACoIndFntA.Item and Group_ = 255.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSACoIndStYTD: Year-to-Date Industry Statistics

This table contains information for year-to-date industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSACOINDSTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSACOINDSTYTD_1	GVKEY, Item, DATADATE
CSACOINDSTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSACOINDSTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSACOINDSTYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSAColndStYTD.Item and Group_ = 256.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

9 Compustat XF Daily Industry Historical

CSBkColndFntA: Annual Industry Statistics Footnotes Historical

This table contains information for historical annual industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOINDFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOINDFNTA_1	GVKEY, Item, DATADATE
CSBKCOINDFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSBKCOINDFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColndFntA.Item and Group_ = 262.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBkColndStQC: Quarterly Industry Statistics Historical

This table contains information for historical quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOINDSTQC (Clustered)	KeyCode, Item
CSBKCOINDSTQC_1	KeyCode

Field	Type	Nullable	Description
KeyCode	int	N	
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColndStQC.Item and Group_ = 256.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSBkCoIndStQP: Company Quarterly Industry Statistics Historical

This table contains information for historical company quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSBKCOINDSTQP (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, KEYCODE
CSBKCOINDSTQP_1	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSBKCOINDSTQP_2	KEYCODE
CSBKCOINDSTQP_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE, KEYCODE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
KEYCODE	int	N	
UEDODF	datetime	Y	UEDODF is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODF_DC	tinyint	Y	UEDODF_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODS	datetime	Y	UEDODS is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODS_DC	tinyint	Y	UEDODS_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODT	datetime	Y	UEDODT is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UEDODT_DC	tinyint	Y	UEDODT_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UGDODF	datetime	Y	UGDODF is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODF_DC	tinyint	Y	UGDODF_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODS	datetime	Y	UGDODS is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODS_DC	tinyint	Y	UGDODS_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODT	datetime	Y	UGDODT is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).
UGDODT_DC	tinyint	Y	UGDODT_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).

CSBkColIndStA: Annual Industry Statistics Historical

This table contains information for historical annual industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOINDSTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSBKCOINDSTA_1	GVKEY, Item, DATADATE
CSBKCOINDSTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColIndStA.Item and Group_ = 259.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSBkColIndFntQ: Quarterly Industry Statistics Footnotes Historical

This table contains information for historical quarterly industry statistics footnotes.

Update Cycle: Daily **Adjusted:** No

Indexes	Index Fields
pkey_CSBKCOINDFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOINDFNTQ_1	GVKEY, Item, DATADATE
CSBKCOINDFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSBKCOINDFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColIndFntQ.Item and Group_ = 260.
Value_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBKCOINDFNTYTD: Year-to-Date Industry Statistics Footnotes Historical

This table contains information for historical year-to-date industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOINDFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOINDFNTYTD_1	GVKEY, Item, DATADATE
CSBKCOINDFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSBKCOINDFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBKCOINDFNTYTD.Item and Group_ = 261.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSBKCoIndStYTD: Year-to-Date Industry Statistics Historical

This table contains information for historical year-to-date industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSBKCOINDSTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSBKCOINDSTYTD_1	GVKEY, Item, DATADATE
CSBKCOINDSTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSBKCOINDSTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSBKCOINDSTYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSBkColndStYTD.Item and Group_ = 263.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

10 Compustat Xpressfeed Banking

Compustat Banking Annual Descriptive Information

The following tables provide annual descriptive information for each company and period date, including the accounting method and source documents:

- CSBnkADesInd
- CSBnkIADesInd – Inactive
- CSBnkBKADesInd – History Active
- CSBnkBKIADesInd – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, DATAFMT
[table name]_1	GVKEY, CONSOL, DATAFMT, DATADATE
[table name]_2	GVKEY, FYEAR, DATAFMT, CONSOL
[table name]_3	DATADATE, GVKEY, CONSOL, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ACCTCHG	varchar(9)	Y	ACCTCHG captures the effective date of accounting changes that have a substantive impact on the measurement and presentation of financial data, or which require significant new disclosures.
ACCTSTD	varchar(9)	Y	ACCTSTD is a unique integer code that identifies the source of the data. ACCTSTD is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. The vendor provides a character value and is represented in the feed files as ACCTSTD.
ACQMETH	varchar(3)	Y	ACQMETH is the code that identifies the method a company uses to account for acquisitions. ACQMETH is translated by CSRAcqMeth where CSRAcqMeth.ACQMETHCD = [table name].ACQMETH.
ADRR	float	Y	ADRR is the ADR (American Depositary Receipt) Ratio. This indicates the number of a foreign company's common or ordinary shares that are equivalent to one ADR or one ADS (American Depositary Share). This ratio is usually a whole number, and is available only for foreign companies that trade ADR or ADS in the U.S. ADRR is on an annual basis.
AJEX	float	Y	AJEX is the adjustment factor you use to adjust per-share data (such as price, earnings per share, and dividends per share) and share data (such as shares outstanding and shares traded) for all stock splits and stock dividends occurring subsequent to the end of a given period. The ex-dividend date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock split or stock dividend occurs. AJEX is on an annual basis.

Field	Type	Nullable	Description
AJP	float	Y	AJP is the adjustment factor you use to adjust dividends per share for all stock dividends occurring subsequent to the end of a given period. The payable date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock dividend occurs. AJP is on an annual basis.
APDEDATE	datetime	Y	APDEDATE is the actual date the company closes their accounting period, which may be different from the last day of the month in the period. APDEDATE is in the form YYYY-MM-DD.
BSPR	varchar(9)	Y	BSPR is the balance sheet presentation method. BSPR is translated by CSRBalPres where CSRBalPres.BSPRCD = [table name].BSPR.
COMPST	varchar(9)	Y	COMPST is the comparability status that describes conditions under which data in one period may not be comparable to data in another period. COMPST is translated by CSRCompStat where CSRCompStat.COMPSTCD = [table name].COMPST.
CURCD	varchar(4)	Y	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURNCD	varchar(4)	Y	CURNCD is the native currency code and identifies the currency in which the company reports its financial data. When CURNCD is not the same as CURCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURRTR	float	Y	CURRTR is the currency translation rate. This is the rate of exchange used to translate international currency into U.S. dollars. The rate used is the rate in effect as of the date of the company's balance sheet. If an international company reports in U.S. dollars, the translation rate is 1.000.
FDATE	datetime	Y	FDATE is the date the data was finalized for that year or quarter.
FINAL	varchar(3)	Y	FINAL is the date the data was finalized for that year or quarter.
FYEAR	smallint	Y	FYEAR represents the fiscal year of the current fiscal year-end month.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
LTDD	varchar(9)	Y	LTDD is a unique integer code that identifies the source of the data. LTDD is defined in TDW and is not received from the vendor. The vendor provides a character value and is represented in the feed files as LTDD.
PDATE	datetime	Y	PDATE is the date the data for the company is updated on a preliminary basis for that year or quarter.
PDDUR	smallint	Y	PDDUR is a unique integer code that identifies the source of the data. PDDUR is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as PDDUR.
SCF	smallint	Y	SCF contains the numeric code that identifies the format of a company's flow of funds statement, statement of changes, or statement of cash flow.
SRC	smallint	Y	SRC contains code that indicates the most recent source from which S&P obtained data for each fiscal period.
STALT	varchar(3)	Y	STALT is a unique integer code that identifies the source of the data. STALT is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as STALT.
UPD	smallint	Y	UPD contains the code that identifies the updated status of the data for the period. UPD consists of a one-character numeric code.

Compustat Banking Annual Data Values

The following tables contain the data values for annual items provided by Compustat:

- CSBnkAFnd1
- CSBnkAFnd2
- CSBnkIAFnd1 – Inactive
- CSBnkIAFnd2 – Inactive
- CSBnkBkAFnd1 – History Active
- CSBnkBkAFnd2 – History Active
- CSBnkBkIAFnd1 – History Inactive
- CSBnkBkIAFnd2 – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where – CSNAItem.group_ = 276 (CSBnkAFnd1 and CSBnkIAFnd1) – CSNAItem.group_ = 278 (CSBnkAFnd2 and CSBnkIAFnd2) – CSNAItem.group_ = 288 (CSBnkBkAFnd1 and CSBnkBkIAFnd1) – CSNAItem.group_ = 289 (CSBnkBkAFnd2 and CSBnkBkIAFnd2)
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.

Compustat Banking Annual Data Codes

The following tables contain the annual data codes for any item:

- CSBnkAFndDC1
- CSBnkAFndDC2
- CSBnkIAFndDC1 – Inactive
- CSBnkIAFndDC2 – Inactive
- CSBnkBkAFndDC1 – History Active
- CSBnkBkAFndDC2 – History Active
- CSBnkBkIAFndDC1 – History Inactive
- CSBnkBkIAFndDC2 – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where CSNAItem.GName = 'bank_afnddc1' or 'bank_afnddc2'.
VALUE_	smallint	Y	VALUE_ is the raw value provided by Compustat.

Compustat Banking Annual Footnote Information

The following tables contain the annual footnote information for each company:

- CSBnkAFntInd
- CSBnkIAFntInd – Inactive
- CSBnkBkAFntIND – History Active
- CSBnkBkIAFntIND – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where CSNAItem.GName = 'bank_afntind'.
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

Compustat Banking Quarterly Bank Data Items

The following tables contain the quarterly bank data items:

- CSBnkIFndQ
- CSBnkIIFndQ – Inactive
- CSBnkBkIFndQ – History Active
- CSBnkBkIIFndQ – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, FYR, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where - CSNAItem.group_ = 283 (CSBnkIFndQ and CSBnkIIFndQ) - CSNAItem.group_ = 294 (CSBnkBkIFndQ and CSBnkBkIIFndQ)
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DATACODE flags non-normal values; descriptions can be found in CSRDataCode .
DVALUE	float	Y	DVALUE is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FYRFLAG identifies values affected by FYR changes or DataCode adjustments; the possible values are below: 0 = No FYR or Datacode adjustment 1 = Fyr adjusted, the DValue is derived from raw data of a different record 2 = Datacode adjusted, the original value is 2x DValue 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record 4 = DataCode adjusted, the original value is 4x DValue 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

Compustat Banking Year-to-Date Bank Data Items

The following tables contain the year-to-date bank data items:

- CSBnkIFndYTD
- CSBnkIIFndYTD – Inactive
- CSBnkBkIFndYTD – History Active
- CSBnkBkIIFndYTD – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, FYR, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where CSNAItem.group_ = 284 (CSBnkIFndYTD and CSBnkIIFndYTD)

Field	Type	Nullable	Description
			– CSNAItem. group_ = 295 (CSBnkBkIFndYTD and CSBnkBkIIFndYTD)
VALUE_	float	Y	VALUE_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DATACODE flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DVALUE is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FYRFLAG identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

Compustat Banking Quarterly Footnote Information

The following tables contain the quarterly footnote information for each company:

- CSBnkIFntQ
- CSBnkIIFntQ – Inactive
- CSBnkBkIFntQ – History Active
- CSBNKBKIIFNTQ – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, FYR, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where CSNAItem.GName = 'bank_ifntq'.
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

Compustat Banking Year-to-Date Footnote Information

The following tables contain the year-to-date footnote information for each company:

- CSBnkIFntYTD
- CSBnkIIIFntYTD – Inactive
- CSBnkBKIFntYTD – History Active
- CSBnkBKIIIFntYTD – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, FYR, DATAFMT, ITEM
[table name]_1	GVKEY, CONSOL, DATAFMT, ITEM, DATADATE
[table name]_2	GVKEY, ITEM

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	ITEM can be cross-referenced with CSNAItem where CSNAItem.GName = 'bank_ifntytd'.
VALUE_	varchar(9)	Y	VALUE_ is the raw value provided by Compustat.

Compustat Banking Interim Descriptive Information

The following tables provide interim descriptive information for each company and period date, such as the accounting method and source documents:

- CSBnkIDesInd
- CSBnkIIDesInd – Inactive
- CSBnkBKIDesInd – History Active
- CSBnkBKIIDesInd – History Inactive

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_[table name] (Clustered)	GVKEY, DATADATE, CONSOL, DATAFMT, FYR
[table name]_1	GVKEY, CONSOL, DATAFMT, DATADATE
[table name]_2	GVKEY, FQTR, FYEARQ, CONSOL, DATAFMT
[table name]_3	DATADATE, GVKEY, CONSOL, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.

Field	Type	Nullable	Description
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
ACCTCHGQ	varchar(9)	Y	ACCTCHGQ is the same as ACCTCHG , but is on a quarterly basis.
ACCTSTDQ	varchar(9)	Y	ACCTSTDQ is the same as ACCTSTD , but is on a quarterly basis.
ADRRQ	float	Y	ADRRQ is the same as ADRR , but is on a quarterly basis.
AJEXQ	float	Y	AJEXQ is the same as AJEX , but is on a quarterly basis.
AJPQ	float	Y	AJPQ is the same as AJP , but is on a quarterly basis.
APDEDATEQ	datetime	Y	APDEDATEQ is the same as APDEDATE , but is on a quarterly basis.
BSPRQ	varchar(9)	Y	BSPRQ is the same as BSPR , but is on a quarterly basis.
COMPSTQ	varchar(9)	Y	COMPSTQ is the same as COMPST , but is on a quarterly basis.
CURCDQ	varchar(4)	Y	CURCDQ is the same as CURCD , but is on a quarterly basis.
CURNCDQ	varchar(4)	Y	CURNCDQ is the same as CURNCD , but is on a quarterly basis.
CURRTRQ	float	Y	CURRTRQ is the same as CURRTR , but is on a quarterly basis.
DATAQTR	varchar(7)	Y	DATAQTR is the calendar year and quarter.
DATAFQTR	varchar(7)	Y	DATAFQTR is the fiscal year and quarter.
FDATEQ	datetime	Y	FDATEQ is the same as FDATE , but is on a quarterly basis.
FINALQ	varchar(3)	Y	FINALQ is the same as FINAL , but is on a quarterly basis.
FQTR	smallint	Y	FQTR is the fiscal quarter of the company.
FYEARQ	smallint	Y	FYEARQ is the same as FYEAR , but is on a quarterly basis.
LTDDQ	varchar(9)	Y	LTDDQ is the same as LTDD , but is on a quarterly basis.
PDATEQ	datetime	Y	PDATEQ is the same as PDATE , but is on a quarterly basis.
PDQ	smallint	Y	PDQ is the number of months in a quarterly, interim reporting period.
PDSA	smallint	Y	PDSA is the number of months in a semiannual, interim reporting period.
PDYTD	smallint	Y	PDYTD is the number of months in a year-to-date, interim reporting period.
RDQ	datetime	Y	RDQ is the date on which quarterly earnings per share are first publicly reported.
RP	varchar(3)	Y	RP is the interim reporting periodicity of a company for a specific year.
SCFQ	int	Y	SCFQ is the same as SCF , but is on a quarterly basis.
SRCQ	int	Y	SRCQ is the same as SRC , but is on a quarterly basis.
STALTQ	varchar(3)	Y	STALTQ is the same as STALT , but is on a quarterly basis.
UPDQ	smallint	Y	UPDQ is the same as UPD , but is on a quarterly basis.

CSBnkAnn: Compustat Banking Annual

This table contains annual banking information.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_csbnnkann (Clustered)	Item, Code, Date_

Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross-references with CSBnkItem where Item = CSBnkItem.Number and CSBnkItem.Group_ = 5.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

NOTE

For items on a fiscal basis, cross-reference Date_ with CSFYE where Code = CSFYE.Code, Date_ = CSFYE.Date_, and CSFYE.Type_ = 5.

CSBnkItem: Compustat Banking Item Descriptions

This table contains descriptions for each item.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_csbnkitem (Clustered)	Mnemonic
csbnkitem_Group	Group_, Number
csbnkitem_Mnemonic	Mnemonic
csbnkitem_Name	Name
csbnkitem_Synonym	Synonym

Field	Type	Nullable	Description
MNEMONIC	varchar(32)	N	Mnemonic is a method of identifying a particular data item. You can directly relate the Mnemonic to the Compustat data documentation.
SYNONYM	varchar(7)	Y	Synonym is a method of identifying a particular data item.
NAME	varchar(69)	Y	Name is the index corporation action name.
GROUP_	smallint	Y	The combination of Group_ and Number creates the key for linking Compustat data items to Value_. Group_ can contain one of the following: – 6 = Bank Annual – 7 = Bank Qtr
NUMBER	smallint	Y	Number is a method of identifying a particular data item. You can directly relate the Number to the Compustat data documentation.
PERIODICITY	smallint	Y	Periodicity can be: – 0 = annual – 1 = quarterly – 2 = monthly – 4 = daily – 5 = scalar
BASIS	smallint	Y	Basis represents the reporting method of data; Basis can be: – 0 = fiscal year basis – 1 = calendar basis.
DATATYPE	smallint	Y	DataType can contain one of the following: – 0 = Double – 1 = int – 3 = String – 5 = Date
ADJMETHOD	smallint	Y	AdjMethod can contain one of the following: – 0 = No adjustment – 1 = Add adjustment factor – 2 = Increasing share count on split and decreasing on reverse split – 3 = Decreasing on split and increasing on reverse split – 4 = Increasing share count on split and decreasing on reverse split, restated – 5 = Decreasing on split and increasing on reverse split, restated

Field	Type	Nullable	Description
			– 6 = Increasing share count on split and decreasing on reverse split, pay date – 7 = Decreasing on split and increasing on reverse split, pay date
CODENUMB	smallint	Y	CodeNumb cross-references with CSCode for translation (see CSCode notes for example of usage).

NOTE

Compustat data is stored adjusted. To unadjust the data, use Mnemonics AJEX and AJEXQ for methods 2, 3, 4 and 5. Use Mnemonics AJP and AJPQ for methods 6 and 7.

CSBnkQtr: Compustat Banking Quarterly

This table contains quarterly information for each company.

Update Cycle: N/A

Adjusted: N/A

Indexes		Index Fields	
pkey_csbkqtr (Clustered)		Item, Code, Date_	

Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross-references with CSBnkItem where Item = CSBnkItem.Number and CSBnkItem.Group_ = 5.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

NOTE

For items on a fiscal basis, cross-reference Date_ with [CSFYE](#) where Code = CSFYE.Code and Date_ = CSFYE.Date_ and CSFYE.Type_ = 6.

11 Compustat XF Daily Issuer Credit Ratings

CSADSPRate: S&P Ratings – Monthly

This table contains monthly S&P ratings information.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSADSPRATE (Clustered)		GVKEY, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
SPLTICRM	varchar(11)	Y	SPLTICRM is the S&P domestic long-term issuer credit rating.
SPSDRM	varchar(11)	Y	SPSDRM is the monthly S&P subordinated debt rating.
SPSTICRM	varchar(11)	Y	SPSTICRM is the S&P domestic short-term issuer credit rating.

12 Compustat XF Daily Current Issuer Credit Ratings

CSADSPRateC: S&P Ratings – Current

This table contains current S&P ratings information.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSADSPRATEC (Clustered)		GVKEY	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
SPLTICRC	varchar(11)	Y	SPLTICRC is the current S&P domestic long-term issuer credit rating.
SPSTICRC	varchar(11)	Y	SPSTICRC is the current S&P domestic short-term issuer credit rating.

13 Compustat XF Index Fundamentals

CSADIdxADes: Annual Index Fundamental Descriptors

This table contains information for annual index fundamental descriptors.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSADIDXADES (Clustered)		GVKEYX, DATADATE	
Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
SPEQA	float	Y	SPEQA is the annual percentage of equity updated.
SPNOA	int	Y	SPNOA is the annual total number of companies in the index for the period.
YEAR_	smallint	Y	YEAR_ is the fiscal year of the data date.

CSADIdxQDes: Quarterly Index Fundamental Descriptors

This table contains information for quarterly index fundamental descriptors.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSADIDXQDES (Clustered)		GVKEYX, DATADATE	
CSADIDXQDES_1		GVKEYX, QTR, DATADATE	
Field	Type	Nullable	Description
GVKEYX	int	N	GVKEYX is a unique identifier and primary key for each index.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
QTR	tinyint	Y	Qtr is the calendar quarter of the data date. For example, Q1, Q2, Q3, and Q4.
SPEQQ	float	Y	SPEQQ is the quarterly percentage of equity updated.
SPNOQ	int	Y	SPNOQ is the quarterly total number of companies in the index for the period.
YEAR_	smallint	Y	YEAR_ is the fiscal year of the data date.

CSADIdxAnn: Annual Index Fundamentals

This table contains information for annual index fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSADIDXANN (Clustered)		GVKEYX, DATADATE, Item	
CSADIDXANN_1		GVKEYX, Item, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSADIdxAnn.Item and Group_ = 179.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSADIdxQtr: Quarterly Index Fundamentals

This table contains information for quarterly index fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSADIDXQTR (Clustered)	GVKEYX, DATADATE, Item
CSADIDXQTR_1	GVKEYX, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSADIdxQtr.Item and Group_ = 180.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

14 Compustat XF Daily Research

CSISecSPInd: S&P Index Inactive Securities

This table contains information for inactive S&P index securities.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSISECSPIND (Clustered)		GVKEYX, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
SPH100	varchar(9)	Y	SPH100 flags companies comprising the S&P 100 Index. An asterisk (*) indicates the company is in the index.
SPHCUSIP	varchar(9)	Y	SPHCUSIP is the S&P holdings CUSIP. It gives the CUSIP security identification number for an index holding.
SPHIID	smallint	Y	SPHIID is the S&P holdings industry index ID. It identifies the industry grouping an S&P major index company is assigned to.
SPHMID	smallint	Y	SPHMID is the S&P holdings major index ID. The companies in the S&P indexes are identified as: – 400 = S&P MidCap 400 – 500 = S&P 500 – 600 = S&P SmallCap 600 – 1500 = S&P Super Composite 1500
SPHNAME	varchar(32)	Y	SPHNAME gives the name of the company that is a member of an S&P index.
SPHSEC	smallint	Y	SPHSEC is described in the SPHSEC section on page 24.
SPHTIC	varchar(9)	Y	SPHTIC is the S&P holdings ticker. It is the ticker symbol for a company that is a member of an S&P index.
SPHVG	char(1)	Y	SPHVG is the S&P holdings value and growth indicator. SPHVG compares the price-to-book ratio of an index to the median price-to-book ratio for its industry sector, calculated using all active U.S. companies in the database. If the ratio is greater than or equal to the industry median, it is G (a growth index). If the ratio is less than the industry median, it is V (a value index).

CSICoAAudit: Inactive Auditor Group

This table contains inactive auditor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOOAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK

Indexes	Index Fields
CSICOOAUDIT_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
AU	varchar(9)	Y	AU lists the auditing firms that audited a company's financial statements. AU is translated by CSRAuditors where CSRAuditors.AUCD = CSICoAAudit.AU.
AUOP	varchar(9)	Y	AUOP is the auditor opinion. AUOP is translated by CSROPINIONS where CSROPINIONS.AUOPCD = CSICoAAudit.AUOP.
AUOPIC	char(1)	Y	AUOP is the auditor opinion of internal control. AUOPIC is translated by CSRAuopIC where CSRAuopIC.AUOPICCD = CSICoAAudit.AUOPIC.
CEOSO	char(1)	Y	CEOSO is the Chief Executive Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.
CFOSO	char(1)	Y	CFOSO is the Chief Financial Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.

CSICoADesInd: Inactive Annual Descriptor

This table contains inactive annual descriptor information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOADESIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL
CSICOADESIND_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSICOADESIND_2	GVKEY, FYEAR, INDFMT, DATAFMT, CONSOL
CSICOADESIND_3	DATADATE, GVKEY, INDFMT, DATAFMT, CONSOL

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.

Field	Type	Nullable	Description
ACCTSTD	varchar(9)	Y	ACCTSTD identifies the accounting standard a company uses when preparing its financial statements. If a company does not reference a specific standard, a domestic standard is assumed. ACCTSTD is translated by CSRAccStd where <code>CSRAccStd.ACCTSTD</code> = <code>CSICoADesInd.ACCTSTD</code> .
ACQMETH	varchar(3)	Y	ACQMETH is the code that identifies the method a company uses to account for acquisitions. ACQMETH is translated by CSRAcqMeth where <code>CSRAcqMeth.ACQMETH</code> = <code>CSICoADesInd.ACQMETH</code> .
ADRR	float	Y	ADRR is the ADR (American Depositary Receipt) Ratio. This indicates the number of a foreign company's common or ordinary shares that are equivalent to one ADR or one ADS (American Depositary Share). This ratio is usually a whole number, and is available only for foreign companies that trade ADR or ADS in the U.S. ADRR is on an annual basis.
AJEX	float	Y	AJEX is the adjustment factor you use to adjust per-share data (such as price, earnings per share, and dividends per share) and share data (such as shares outstanding and shares traded) for all stock splits and stock dividends occurring subsequent to the end of a given period. The ex-dividend date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock split or stock dividend occurs. AJEX is on an annual basis.
AJP	float	Y	AJP is the adjustment factor you use to adjust dividends per share for all stock dividends occurring subsequent to the end of a given period. The payable date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock dividend occurs. AJP is on an annual basis.
APDEDATE	datetime	Y	APDEDATE is the actual date the company closes their accounting period, which may be different from the last day of the month in the period. APDEDATE is in the form YYYY-MM-DD.
BSPR	varchar(9)	Y	BSPR is the balance sheet presentation method. BSPR is translated by CSRBalPres where <code>CSRBalPres.BSPR</code> = <code>CSICoADesInd.BSPR</code> .
COMPST	varchar(9)	Y	COMPST is the comparability status which describes conditions under which data in one period may not be comparable to data in another period. COMPST is translated by CSRCompStat where <code>CSRCompStat.COMPST</code> = <code>CSICoADesInd.COMPST</code> .
CURCD	varchar(4)	Y	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURNCD	varchar(4)	Y	CURNCD is the native currency code and identifies the currency in which the company reports its financial data. When CURNCD is not the same as CURCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURRTR	float	Y	CURRTR is the currency translation rate. This is the rate of exchange used to translate international currency into U.S. dollars. The rate used is the rate in effect as of the date of the company's balance sheet. If an international company reports in U.S. dollars, the translation rate is 1.000.
CURUSCN	float	Y	CURUSCN is the rate of exchange used to translate Canadian currency amounts into U.S. dollar amounts. This is available only when a company reports in both U.S. and Canadian accounting standards.
FDATE	datetime	Y	FDATE is the date the data was finalized for that year or quarter.
FYEAR	smallint	Y	FYEAR represents the fiscal year of the current fiscal year-end month.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
ISMOD	smallint	Y	ISMOD is the income statement model number.
OGM	varchar(9)	Y	OGM is the method of reporting revenue used by the Oil & Gas company.
PDATE	datetime	Y	PDATE is the date the data for the company is updated on a preliminary basis for that year or quarter.
PDDUR	smallint	Y	PDDUR is a unique integer code that identifies the source of the data. PDDUR is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as PDDUR.
SCF	smallint	Y	SCF contains the numeric code that identifies the format of a company's flow of funds statement, statement of changes, or statement of cash flow.

Field	Type	Nullable	Description
SRC	smallint	N	SRC contains code that indicates the most recent source from which S&P obtained data for each fiscal period.
STALT	varchar(3)	Y	STALT is a unique integer code that identifies the source of the data. STALT is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as STALT.
UDPL	varchar(9)	Y	UDPL designates the method used by the utility company to account for Liberalized Depreciation.
UPD	smallint	Y	UPD contains the code that identifies the updated status of the data for the period. UPD consists of a one-character numeric code.

CSICoAdjFact: Inactive Cumulative Adjustment Factors

This table contains information for inactive cumulative adjustment factors.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOADJFACT (Clustered)	GVKEY, EFFDATE, THRUDATE
CSICOADJFACT_1	GVKEY, THRUDATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
EFFDATE	datetime	N	EFFDATE indicates the date from which the cumulative adjustment factor is effective.
THRUDATE	datetime	N	THRUDATE is the date through which the cumulative adjustment factor is effective.
ADJEX	float	Y	ADJEX is the multiplication of all Ex-Date adjustment factors going back in time.
ADJPAY	float	Y	ADJPAY is the multiplication of all Pay-Date adjustment factors going back in time.

CSICoAFndDC1: Inactive Annual Fundamental Data Codes

This table contains information for inactive annual fundamental data codes.

NOTE

Data group will provide industrial and financial service formats.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoAFNDDC1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSICoAFNDDC1_1	GVKEY, Item, DATADATE
CSICoAFNDDC1_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSICoAFNDDC1_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSICoAFndDC1.Item and Group_ = 202.
VALUE_	smallint	Y	Value_ is the raw value provided by Compustat.

CSICoAFndDC2: Inactive Annual Fundamental Data Codes

This table contains information for inactive annual fundamental data codes.

NOTE

Data group will provide industrial and financial service formats.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoAFND2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSICoAFND2_1	GVKEY, Item, DATADATE
CSICoAFND2_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSICoAFND2_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSICoAFndDC2.Item and Group_ = 203.
VALUE_	smallint	Y	Value_ is the raw value provided by Compustat.

CSICoAFnd1: Inactive Annual Fundamental Data

This table contains information for inactive annual fundamental data.

NOTE

Data group will provide industrial and financial service formats.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICoAFND1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSICoAFND1_1	GVKEY, Item, DATADATE
CSICoAFND1_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSICoAFND1_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSICoAFND1_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSICoAFnd1.Item and Group_ = 204.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSICoAFnd2: Inactive Annual Fundamental Data

This table contains information for inactive annual fundamental data.

NOTE

Data group will provide industrial and financial service formats.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICoAFND2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSICoAFND2_1	GVKEY, Item, DATADATE
CSICoAFND2_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSICoAFND2_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSICoAFND2_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSICoAFnd2.Item and Group_ = 205.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSICoAInvVal: Inactive Inventory Evaluation Group

This table contains inactive inventory evaluation group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoAINVVAL (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK

Indexes	Index Fields
CSICOAINVVAL_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSICOAINVVAL_2	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
INVVAL	int	Y	INVVAL contains the code that identifies the method used to value inventory.

CSiCoAMkt: Inactive Annual Market Data Group

This table contains inactive annual market data group information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICOAMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD
CSICOAMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
CLSM	smallint	Y	CLSM is the month of the company's last close price.
CSHTR	float	Y	CSHTR is the number of shares traded for companies listed on national stock exchanges and over-the-counter companies in the NASDAQ system on a fiscal, rather than calendar, basis.
DVPSP	float	Y	DVPSP is the cash dividends per share for which the payable dates occurred during the reporting period, unadjusted for all stock splits and stock dividends that occurred during the period.
DVPSX	float	Y	DVPSX is the cash dividends per share for which the ex-dividend dates occurred during the reporting period, adjusted for all stock splits and stock dividends that occurred during the period.
PRCC	float	Y	PRCC is the absolute close transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCH	float	Y	PRCH is the absolute high transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.

Field	Type	Nullable	Description
PRCL	float	Y	PRCL is the absolute low transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSiCoFortune: Inactive Fortune 500 Group

This table contains inactive Fortune 500 group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOFORTUNE (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
FORI	smallint	Y	FORI contains the code that identifies the industry group of a Fortune 1000 company.
FORRK	smallint	Y	FORRK is the fortune rank.

CSiCoHGIC: Inactive GICS History

This table contains inactive GICS history information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOHGIC (Clustered)	GVKEY, INDTYPE, INDFROM

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
INDTYPE	varchar(9)	N	INDTYPE indicates the type of industry classification. GICS = Standard & Poor's Global Industry Classification System (GICS)
INDFROM	datetime	N	INDFROM indicates the date from which the GICS code was effective.
GGROUP	varchar(5)	Y	GGROUP is the second level in the hierarchy of the Global Industry Classification Standard (GICS). The Industry Group is represented by the leftmost four digits of the total GICS code.
GIND	varchar(7)	Y	GIND is the third level in the hierarchy of the Global Industry Classification Standard (GICS). Industry is represented by the leftmost six digits of the total GICS code.
GSECTOR	varchar(3)	Y	GSECTOR is the first level in the hierarchy of the Global Industry Classification Standard (GICS). The Sector is represented by the leftmost two digits of the total GICS code.
GSUBIND	varchar(9)	Y	GSUBIND is fourth level in the hierarchy of the Global Industry Classification Standard (GICS). The Sub-industry is represented by all eight digits of the total GICS code.
INDTHRU	datetime	Y	INDTHRU is the date through which the GICS code was effective, if it is no longer effective.

CSICoIAudit: Inactive Interim Auditor Group

This table contains inactive interim auditor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoIAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, RANK
CSICoIAUDIT_1	GVKEY, INDFMT, CONSOL, DATAFMT, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
CEOSOQ	char(1)	Y	CEOSOQ is the same as CEOSO , but is on a quarterly basis.
CFOSOQ	char(1)	Y	CFOSOQ is the same as CFOSO , but is on a quarterly basis.

CSICoDesInd: Inactive Company Interim Descriptor Group

This table contains inactive company interim descriptor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoIDESIND (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSICoIDESIND_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSICoIDESIND_2	GVKEY, FQTR, FYEARQ, INDFMT, CONSOL, DATAFMT
CSICoIDESIND_3	DATADATE, GVKEY, INDFMT, CONSOL, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ACCTSTDQ	varchar(9)	Y	ACCTSTDQ is the same as ACCTSTD , but is on a quarterly basis.

Field	Type	Nullable	Description
ADRRQ	float	Y	ADRRQ is the same as ADRR , but is on a quarterly basis.
AJEXQ	float	Y	AJEXQ is the same as AJEX , but is on a quarterly basis.
AJPQ	float	Y	AJPQ is the same as AJP , but is on a quarterly basis.
APDEDATEQ	datetime	Y	APDEDATEQ is the same as APDEDATE , but is on a quarterly basis.
BSPRQ	varchar(9)	Y	BSPRQ is the same as BSPR , but is on a quarterly basis.
COMPSTQ	varchar(9)	Y	COMPSTQ is the same as COMPST , but is on a quarterly basis.
CURCDQ	varchar(4)	Y	CURCDQ is the same as CURCD , but is on a quarterly basis.
CURNCDQ	varchar(4)	Y	CURNCDQ is the same as CURNCD , but is on a quarterly basis.
CURRTRQ	float	Y	CURRTRQ is the same as CURRTR , but is on a quarterly basis.
CURUSCNQ	float	Y	CURUSCNQ is the same as CURUSCN , but is on a quarterly basis.
DATAQTR	varchar(7)	Y	DATAQTR is the calendar year and quarter.
DATAFQTR	varchar(7)	Y	DATAFQTR is the fiscal year and quarter.
FDATEQ	datetime	Y	FDATEQ is the same as FDATE , but is on a quarterly basis.
FQTR	smallint	Y	FQTR is the fiscal quarter of the company.
FYEARQ	smallint	Y	FYEARQ is the same as FYEAR , but is on a quarterly basis.
OGMQ	varchar(9)	Y	OGMQ is the same as OGM , but is on a quarterly basis.
PDATEQ	datetime	Y	PDATEQ is the same as PDATE , but is on a quarterly basis.
PDQ	smallint	Y	PDQ is the number of months in a quarterly, interim reporting period.
PDSA	smallint	Y	PDSA is the number of months in a semiannual, interim reporting period.
PDYTD	smallint	Y	PDYTD is the number of months in a year-to-date, interim reporting period.
RDQ	datetime	Y	RDQ is the date on which quarterly earnings per share are first publicly reported.
RP	varchar(3)	Y	RP is the interim reporting periodicity of a company for a specific year.
SCFQ	int	Y	SCFQ is the same as SCF , but is on a quarterly basis.
SRCQ	int	Y	SRCQ is the same as SRC , but is on a quarterly basis.
STALTQ	varchar(3)	Y	STALTQ is the same as STALT , but is on a quarterly basis.
UPDQ	smallint	Y	UPDQ is the same as UPD , but is on a quarterly basis.

CSICoIFntYTD: Inactive Company Interim Fundamentals – Year-to-Date Footnotes

This table contains year-to-date footnotes information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoIFntYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSICoIFntYTD_1	GVKEY, Item, DATADATE
CSICoIFntYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSICoIFntYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIColFntYTD.Item and Group_ = 211.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIColFntQ: Inactive Company Interim Fundamentals – Quarterly Footnotes

This table contains quarterly footnotes information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSICOFNTQ_1	GVKEY, Item, DATADATE
CSICOFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSICOFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIColFntQ.Item and Group_ = 212.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIColFntSA: Inactive Company Interim Fundamentals – Semiannual Footnotes

This table contains semiannual footnotes information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOFNTSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSICOFNTSA_1	GVKEY, Item, DATADATE
CSICOFNTSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSICOFNTSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIColFntSA.Item and Group_ = 213.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIColMkt: Inactive Interim Market Group

This table contains inactive interim market group information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICOLMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD, YEM
CSICOLMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
YEM	smallint	N	YEM works with CFFLAG to represent the month of the company's year-end price.
CLSMQ	smallint	Y	CLSMQ is the same as CLSM , but is on a quarterly basis.
CSHTRQ	float	Y	CSHTRQ is the same as CSHTR , but is on a quarterly basis.
DVPSPQ	float	Y	DVPSPQ is the same as DVPSP , but is on a quarterly basis.
DVPSXQ	float	Y	DVPSXQ is the same as DVPSX , but is on a quarterly basis.
PRCCQ	float	Y	PRCCQ is the same as PRCC , but is on a quarterly basis.
PRCHQ	float	Y	PRCHQ is the same as PRCH , but is on a quarterly basis.
PRCLQ	float	Y	PRCLQ is the same as PRCL , but is on a quarterly basis.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSICoIndustryPres: Inactive Company Industry Presentation

This table contains inactive company industry presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOINDSTRYPRES (Clustered)	GVKEY, DATADATE, CONSOL, IPCD
CSICOINDSTRYPRES_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
IPCD	char(1)	N	IPCD identifies the industry presentation of financial services companies trading outside of the United States and Canada.

CSICoIndustry: Inactive Industry Classification Presentation

This table contains inactive industry classification presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOINDUSTRY (Clustered)	GVKEY, DATADATE, CONSOL
CSICOINDUSTRY_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
NAICSH	int	Y	NAICSH contains the historical NAICS code assigned to a company.
SICH	int	Y	SICH contains the SIC code that identifies the company's SIC Code in prior years.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSICOMth: Inactive Company Monthly

This table contains monthly inactive company information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOMTH (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
BETA	float	Y	BETA is a measurement of the sensitivity of a company's stock price to the overall fluctuation in the Standard & Poor's 500 (S&P 500) Index Price for U.S.

Field	Type	Nullable	Description
			Companies, or the Toronto Stock Exchange 300 (TSE 300) Index Price for Canadian Companies.
SPCSRM	varchar(4)	Y	SPCSRM is an appraisal of the past performance of a stock's earnings and dividends and the stock's relative standing as of a company's current fiscal year-end.

CSICoOffTitl: Inactive Company Officers

This table contains information for inactive company officers.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICOOFFTITL (Clustered)	GVKEY, OFID, OFCD
CSICOOFFTITL_1	GVKEY, OFCD
CSICOOFFTITL_2	GVKEY, OFID

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
OFID	int	N	OFID is a unique identifying number assigned to a person holding the position of company officer. The Officer ID remains consistent for that person, even if the person holds more than one officer title.
OFCD	varchar(9)	N	OFCD represents one or more officers of a company.
OFNM	varchar(40)	Y	OFNM is the first two initials and the last name(s) of the officer(s) for a company.

CSICoAFntIND: Inactive Company Annual Fundamental Footnotes

This table contains information for inactive company annual fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSICoAFNTIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSICoAFNTIND_1	GVKEY, Item, DATADATE
CSICoAFNTIND_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item DATADATE
CSICoAFNTIND_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSICoAFntIND.Item and Group_ = 217.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSICoIFndQ: Inactive Company Interim Fundamentals – Quarterly

This table contains quarterly information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICoIFNDQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSICoIFNDQ_1	GVKEY, Item, DATADATE
CSICoIFNDQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSICoIFNDQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSICoIFNDQ_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSICoIFndQ.Item and Group_ = 218.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSICoIFndYTD: Inactive Company Interim Fundamentals – Year to Date

This table contains year-to-date information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICoIFNDYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSICoIFNDYTD_1	GVKEY, Item, DATADATE

Indexes	Index Fields
CSICOIFNDYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSICOIFNDYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSICOIFNDYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIColFndYTD.Item and Group_ = 219.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSIColFndSA: Inactive Company Semi-Annual Fundamentals

This table contains information for inactive company semi-annual fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSICOFNDSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSICOFNDSA_1	GVKEY, Item, DATADATE
CSICOFNDSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSICOFNDSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSICOFNDSA_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIColFndSA.Item and Group_ = 220.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSISecMth: Inactive Monthly Descriptor

This table contains inactive monthly descriptor information.

NOTE

As of 21 July 2020, SPGIM, SPIIM and SPMIM fields are no longer populated. These fields are set to NULL.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSISECMTH (Clustered)	GVKEY, IID, DATADATE
CSISECMTH_1	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
AJEXM	float	Y	AJEXM is the monthly adjustment factor - cumulative by ex-date.
AJPM	float	Y	AJPM is the monthly adjustment factor - cumulative by payable date.
ISALRT	varchar(9)	Y	ISALRT is the issue status alert. It contains the two-character code that indicates when issue trading has been suspended.
PRIMISS	char(1)	Y	PRIMISS is a monthly market data descriptor that identifies the issue with the highest market presence.
SPGIM	varchar(9)	Y	SPGIM is the S&P Global Industry Classification Index code – historical.
SPIIM	varchar(9)	Y	SPIIM is the S&P Industry Index code –historical.
SPMIM	varchar(9)	Y	SPMIM is the S&P Major Index code – historical.

CSISecMthDiv: Inactive Monthly Dividend

This table contains inactive monthly dividend information.

Update Cycle: Daily

Adjusted: Yes

Indexes		Index Fields	
pkey_CSISECMTHDIV (Clustered)		GVKEY, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CHEQVM	float	Y	CHEQVM is the monthly cash equivalent distributions per share - ex-date.
CURCDDVM	varchar(4)	Y	CURCDDVM is the monthly ISO currency code – dividend.
DVPSPM	float	Y	DVPSPM is the monthly dividends per share –pay date.
DVPSXM	float	Y	DVPSXM is the index monthly cash dividend paid per share by ex date. DVPSXM is adjusted for all stock splits and stock dividends that occurred during the period. This value does not include payments in preferred stock in lieu of cash, spin-offs, and stock of other corporations.
DVRATE	float	Y	DVRATE is the monthly indicated annual dividend rate.

CSISecMthPrc: Inactive Monthly Item

This table contains inactive monthly item information.

Update Cycle: Daily

Adjusted: Yes

Indexes		Index Fields	
pkey_CSISECMTHPRC (Clustered)		GVKEY, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CSFSM	float	Y	CSFSM is the monthly common stock float shares – Canada.
CSHTRM	float	Y	CSHTRM is the monthly trading volume.
CURCDM	varchar(4)	Y	CURCDM is the monthly ISO currency code.
NAVM	float	Y	NAVM is the monthly net asset value.
PRCCM	float	Y	PRCCM is the absolute close market price for each calendar month.
PRCHM	float	Y	PRCHM is the absolute high market price for each calendar month.
PRCLM	float	Y	PRCLM is the absolute low market price for each calendar month.

CSISecMthSpt: Inactive Monthly Stock Splits

This table contains information for inactive monthly stock splits.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSISECMTHSPT (Clustered)		GVKEY, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
RAWPM	float	Y	RAWPM is the monthly raw adjustment factor – pay date.
RAWXM	float	Y	RAWXM is the monthly raw adjustment factor – ex date.

CSISecMSptFn: Inactive Monthly Stock Split Footnotes

This table contains information for inactive monthly stock split footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSISECMSPTFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSISECMSPTFN_1	GVKEY, Item, DATADATE
CSISECMSPTFN_2	GVKEY, DATADATE
CSISECMSPTFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSISECMSPTFN_4	GVKEY, IID, DATADATE
CSISECMSPTFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSISecMSptFn.Item and Group_ = 145.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSISecMDivFN: Inactive Monthly Dividend Footnotes

This table contains information for inactive monthly dividend footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSISECMDIVFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSISECMDIVFN_1	GVKEY, Item, DATADATE
CSISECMDIVFN_2	GVKEY, DATADATE
CSISECMDIVFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSISECMDIVFN_4	GVKEY, IID, DATADATE
CSISECMDIVFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.

Field	Type	Nullable	Description
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSISecMDivFN.Item and Group_ = 88
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

15 Compustat XF Daily Historical Research

CSIBkCoAFntInd: Inactive Annual Fundamental Footnotes Historical

This table contains information for historical inactive annual fundamental footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOAFNTIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOAFNTIND_1	GVKEY, Item, DATADATE
CSIBKCOAFNTIND_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item DATADATE
CSIBKCOAFNTIND_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoAFntInd.Item and Group_ = 246.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkCoAAudit: Inactive Auditor Group Historical

This table contains historical inactive auditor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOAAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CSIBKCOAAUDIT_1	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.

Field	Type	Nullable	Description
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
AU	varchar(9)	Y	AU lists the auditing firms that audited a company's financial statements. AU is translated by CSRAuditors where CSRAuditors.AUCD = CSBkCoAAudit.AU.
AUOP	varchar(9)	Y	AUOP is the auditor opinion. AUOP is translated by CSROPINIONS where CSROPINIONS.AUOPCD = CSBkCoAAudit.AUOP.
AUOPIC	char(1)	Y	AUOP is the auditor opinion of internal control. AUOPIC is translated by CSRAuopIC where CSRAuopIC.AUOPICCD = CSBkCoAAudit.AUOPIC.
CEOSO	char(1)	Y	CEOSO is the Chief Executive Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.
CFOSO	char(1)	Y	CFOSO is the Chief Financial Officer SOX Certification. This indicates whether a company has filed certification documents as required under section 302 of the Sarbanes-Oxley Act of 2002.

CSBkCoADesInd: Inactive Company Annual Descriptor - Industry Format Historical

This table contains industry format historical information for inactive company annual descriptor data.

Update Cycle: Daily **Adjusted:** No

Indexes	Index Fields
pkey_CSIBKCOADESIND (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL
CSIBKCOADESIND_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSIBKCOADESIND_2	GVKEY, FYEAR, INDFMT, DATAFMT, CONSOL
CSIBKCOADESIND_3	DATADATE, GVKEY, INDFMT, DATAFMT, CONSOL

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ACCTSTD	varchar(9)	Y	ACCTSTD identifies the accounting standard a company uses when preparing its financial statements. If a company does not reference a specific standard, a domestic standard is assumed. ACCTSTD is translated by CSRAccStd where CSRAccStd.ACCTSTD = CSBkCoADesInd.ACCTSTD.
ACQMETH	varchar(3)	Y	ACQMETH is the code that identifies the method a company uses to account for acquisitions. ACQMETH is translated by CSRAcqMeth where CSRAcqMeth.ACQMETHCD = CSBkCoADesInd.ACQMETH.
ADRR	float	Y	ADRR is the ADR (American Depositary Receipt) Ratio. This indicates the number of a foreign company's common or ordinary shares that are equivalent to

Field	Type	Nullable	Description
			one ADR or one ADS (American Depositary Share). This ratio is usually a whole number, and is available only for foreign companies that trade ADR or ADS in the U.S. ADRR is on an annual basis.
AJEX	float	Y	AJEX is the adjustment factor you use to adjust per-share data (such as price, earnings per share, and dividends per share) and share data (such as shares outstanding and shares traded) for all stock splits and stock dividends occurring subsequent to the end of a given period. The ex-dividend date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock split or stock dividend occurs. AJEX is on an annual basis.
AJP	float	Y	AJP is the adjustment factor you use to adjust dividends per share for all stock dividends occurring subsequent to the end of a given period. The payable date is used to determine the adjustment of per-share data. The cumulative adjustment factor changes whenever a stock dividend occurs. AJP is on an annual basis.
APDEDATE	datetime	Y	APDEDATE is the actual date the company closes their accounting period, which may be different from the last day of the month in the period. APDEDATE is in the form YYYY-MM-DD.
BSPR	varchar(9)	Y	BSPR is the balance sheet presentation method. BSPR is translated by CSRBalPres where CSRBalPres.BSPRCD = CSIBkCoADesInd.BSPR.
COMPST	varchar(9)	Y	COMPST is the comparability status which describes conditions under which data in one period may not be comparable to data in another period. COMPST is translated by CSRCompStat where CSRCompStat.COMPSTCD = CSIBkCoADesInd.COMPST.
CURCD	varchar(4)	Y	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURNCD	varchar(4)	Y	CURNCD is the native currency code and identifies the currency in which the company reports its financial data. When CURNCD is not the same as CURCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR.
CURRTR	float	Y	CURRTR is the currency translation rate. This is the rate of exchange used to translate international currency into U.S. dollars. The rate used is the rate in effect as of the date of the company's balance sheet. If an international company reports in U.S. dollars, the translation rate is 1.000.
CURUSCN	float	Y	CURUSCN is the rate of exchange used to translate Canadian currency amounts into U.S. dollar amounts. This is available only when a company reports in both U.S. and Canadian accounting standards.
FDATE	datetime	Y	FDATE is the date the data was finalized for that year or quarter.
FYEAR	smallint	Y	FYEAR represents the fiscal year of the current fiscal year-end month.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
ISMOD	smallint	Y	ISMOD is the income statement model number.
OGM	varchar(9)	Y	OGM is the method of reporting revenue used by the Oil & Gas company.
PDATE	datetime	Y	PDATE is the date the data for the company is updated on a preliminary basis for that year or quarter.
PDDUR	smallint	Y	PDDUR is a unique integer code that identifies the source of the data. PDDUR is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as PDDUR.
SCF	smallint	Y	SCF contains the numeric code that identifies the format of a company's flow of funds statement, statement of changes, or statement of cash flow.
SRC	smallint	N	SRC contains code that indicates the most recent source from which S&P obtained data for each fiscal period.
STALT	varchar(3)	Y	STALT is a unique integer code that identifies the source of the data. STALT is defined in TDW and is not received from the vendor. The vendor provides a two-character numeric code and is represented in the feed files as STALT.
UDPL	varchar(9)	Y	UDPL designates the method used by the utility company to account for Liberalized Depreciation.
UPD	smallint	Y	UPD contains the code that identifies the updated status of the data for the period. UPD consists of a one-character numeric code.

CSIBkCoAFndDC1: Inactive Annual Fundamental Data Codes

This table contains information for inactive annual fundamental data codes.

NOTE

Data group will provide industrial and financial service formats historical.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOAFNDDC1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOAFNDDC1_1	GVKEY, Item, DATADATE
CSIBKCOAFNDDC1_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIBKCOAFNDDC1_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoAFndDC1.Item and Group_ = 231.
VALUE_	smallint	Y	Value_ is the raw value provided by Compustat.

CSIBkCoAFndDC2: Inactive Annual Fundamental Data Codes

This table contains information for inactive annual fundamental data codes.

NOTE

Data group will provide industrial and financial service formats historical.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOAFNDDC2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOAFNDDC2_1	GVKEY, Item, DATADATE
CSIBKCOAFNDDC2_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIBKCOAFNDDC2_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.

Field	Type	Nullable	Description
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoAFndDC2.Item and Group_ = 232.
VALUE_	smallint	Y	Value_ is the raw value provided by Compustat.

CSIBkCoAFnd1: Inactive Annual Fundamental Data

This table contains information for inactive annual fundamental data.

NOTE

Data group will provide industrial and financial service formats historical.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOAFND1 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOAFND1_1	GVKEY, Item, DATADATE
CSIBKCOAFND1_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIBKCOAFND1_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSIBKCOAFND1_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoAFnd1.Item and Group_ = 233.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSIBkCoAFnd2: Inactive Annual Fundamental Data

This table contains information for inactive annual fundamental data.

NOTE

Data group will provide industrial and financial service formats historical.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOAFND2 (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOAFND2_1	GVKEY, Item, DATADATE
CSIBKCOAFND2_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIBKCOAFND2_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSIBKCOAFND2_4	GVKEY, DATAFMT, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoAFnd2.Item and Group_ = 234.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSIBkCoAInvVal: Inactive Inventory Evaluation Group Historical

This table contains historical inactive inventory evaluation group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOAINVVAL (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, RANK
CSIBKCOAINVVAL_1	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE
CSIBKCOAINVVAL_2	GVKEY, INDFMT, DATAFMT, CONSOL, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
INVVAL	int	Y	INVVAL contains the code that identifies the method used to value inventory.

CSIBkCoAMkt: Inactive Annual Market Data Group Historical

This table contains historical inactive annual market data group information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOAMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD
CSIBKCOAMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.

Field	Type	Nullable	Description
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
CLSM	smallint	Y	CLSM is the month of the company's last close price.
CSHTR	float	Y	CSHTR is the number of shares traded for companies listed on national stock exchanges and over-the-counter companies in the NASDAQ system on a fiscal, rather than calendar, basis.
DVPSP	float	Y	DVPSP is the cash dividends per share for which the payable dates occurred during the reporting period, unadjusted for all stock splits and stock dividends that occurred during the period.
DVPSX	float	Y	DVPSX is the cash dividends per share for which the ex-dividend dates occurred during the reporting period, adjusted for all stock splits and stock dividends that occurred during the period.
PRCC	float	Y	PRCC is the absolute close transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCH	float	Y	PRCH is the absolute high transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
PRCL	float	Y	PRCL is the absolute low transactions during the year for companies on national stock exchanges and bid prices for over-the-counter issues.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSIBkCoFortune: Inactive Fortune 500 Group Historical

This table contains historical inactive Fortune 500 group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOFORTUNE (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
FORI	smallint	Y	FORI contains the code that identifies the industry group of a Fortune 1000 company.
FORRK	smallint	Y	FORRK is the fortune rank.

CSIBkCoIAudit: Inactive Interim Auditor Group Historical

This table contains historical inactive interim auditor group information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOIAUDIT (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, RANK
CSIBKCOIAUDIT_1	GVKEY, INDFMT, CONSOL, DATAFMT, RANK, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
RANK	int	N	When a company has more than one auditor, RANK ranks the auditors from 1 to 6, with 1 as the primary auditor. When a company has more than one inventory valuation method, 1 indicates the method used most often.
CEOSOQ	char(1)	Y	CEOSOQ is the same as CEOSO , but is on a quarterly basis.
CFOSOQ	char(1)	Y	CFOSOQ is the same as CFOSO , but is on a quarterly basis.

CSIBkCoIDesInd: Inactive Company Interim Descriptor Historical

This table contains historical inactive company interim descriptor information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOIDESIND (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSIBKCOIDESIND_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSIBKCOIDESIND_2	GVKEY, FQTR, FYEARQ, INDFMT, CONSOL, DATAFMT
CSIBKCOIDESIND_3	DATADATE, GVKEY, INDFMT, CONSOL, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ACCTSTDQ	varchar(9)	Y	ACCTSTDQ is the same as ACCTSTD , but is on a quarterly basis.
ADRRQ	float	Y	ADRRQ is the same as ADRR , but is on a quarterly basis.
AJEXQ	float	Y	AJEXQ is the same as AJEX , but is on a quarterly basis.
AJPQ	float	Y	AJPQ is the same as AJP , but is on a quarterly basis.
APDEDATEQ	datetime	Y	APDEDATEQ is the same as APDEDATE, but is on a quarterly basis.
BSPRQ	varchar(9)	Y	BSPRQ is the same as BSPR , but is on a quarterly basis.
COMPSTQ	varchar(9)	Y	COMPSTQ is the same as COMPST , but is on a quarterly basis.
CURCDQ	varchar(4)	Y	CURCDQ is the same as CURCD , but is on a quarterly basis.
CURNCDQ	varchar(4)	Y	CURNCDQ is the same as CURNCD , but is on a quarterly basis.
CURRTRQ	float	Y	CURRTRQ is the same as CURRTR , but is on a quarterly basis.

Field	Type	Nullable	Description
CURUSCNQ	float	Y	CURUSCNQ is the same as CURUSCN , but is on a quarterly basis.
DATAQTR	varchar(7)	Y	DATAQTR is the calendar year and quarter.
DATAFQTR	varchar(7)	Y	DATAFQTR is the fiscal year and quarter.
FDATEQ	datetime	Y	FDATEQ is the same as FDATE , but is on a quarterly basis.
FQTR	smallint	Y	FQTR is the fiscal quarter of the company.
FYEARQ	smallint	Y	FYEARQ is the same as FYEAR , but is on a quarterly basis.
OGMQ	varchar(9)	Y	OGMQ is the same as OGM , but is on a quarterly basis.
PDATEQ	datetime	Y	PDATEQ is the same as PDATE , but is on a quarterly basis.
PDQ	smallint	Y	PDQ is the number of months in a quarterly, interim reporting period.
PDSA	smallint	Y	PDSA is the number of months in a semiannual, interim reporting period.
PDYTD	smallint	Y	PDYTD is the number of months in a year-to-date, interim reporting period.
RDQ	datetime	Y	RDQ is the date on which quarterly earnings per share are first publicly reported.
RP	varchar(3)	Y	RP is the interim reporting periodicity of a company for a specific year.
SCFQ	int	Y	SCFQ is the same as SCF , but is on a quarterly basis.
SRCQ	int	Y	SRCQ is the same as SRC , but is on a quarterly basis.
STALTQ	varchar(3)	Y	STALTQ is the same as STALT , but is on a quarterly basis.
UPDQ	smallint	Y	UPDQ is the same as UPD , but is on a quarterly basis.

CSIBkColFntYTD: Inactive Company Interim Fundamentals – Year-to-Date Footnotes Historical

This table contains year-to-date footnotes historical information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOIFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOIFNTYTD_1	GVKEY, Item, DATADATE
CSIBKCOIFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSIBKCOIFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkColFntYTD.Item and Group_ = 240.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkColFntQ: Inactive Company Interim Fundamentals – Quarterly Footnotes Historical

This table contains quarterly footnotes historical information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOIFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOIFNTQ_1	GVKEY, Item, DATADATE
CSIBKCOIFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE
CSIBKCOIFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	SMALLINT	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkColFntQ.Item and Group_ = 241.
VALUE_	VARCHAR(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkColFntSA: Inactive Company Interim Fundamentals – Semiannual Footnotes Historical

This table contains semiannual footnotes historical information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOIFNTSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOIFNTSA_1	GVKEY, Item, DATADATE
CSIBKCOIFNTSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item DATADATE,
CSIBKCOIFNTSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkColFntSA.Item and Group_ = 242.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkColMkt: Inactive Interim Market Group Historical

This table contains historical inactive interim market group information.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOIMKT (Clustered)	GVKEY, DATADATE, CFFLAG, CURCD, YEM
CSIBKCOIMKT_1	GVKEY, CFFLAG, CURCD, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CFFLAG	char(1)	N	CFFLAG indicates whether the year-end price represents the company's fiscal year-end or the calendar year-end. The calendar year-end will always be on December 31 (12/31/YYYY).
CURCD	tinyint	N	CURCD identifies the currency of the company's financial data within the database. When CURCD is not the same as CURNCD, Compustat has translated the data from CURNCD to CURCD using the translation rate reported in CURRTR. Since CURCD is part of the primary key in this table, the value is stored as an integer for faster data retrieval. To return the string value (e.g. USD, CAD), join CURCD to CsKeyCode .Code.
YEM	smallint	N	YEM works with CFFLAG to represent the month of the company's year-end price.
CLSMQ	smallint	Y	CLSMQ is the same as CLSM , but is on a quarterly basis.
CSHTRQ	float	Y	CSHTRQ is the same as CSHTR , but is on a quarterly basis.
DVPSPQ	float	Y	DVPSPQ is the same as DVPSP , but is on a quarterly basis.
DVPSXQ	float	Y	DVPSXQ is the same as DVPSX , but is on a quarterly basis.
PRCCQ	float	Y	PRCCQ is the same as PRCC , but is on a quarterly basis.
PRCHQ	float	Y	PRCHQ is the same as PRCH , but is on a quarterly basis.
PRCLQ	float	Y	PRCLQ is the same as PRCL , but is on a quarterly basis.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSIBkColIndstryPres: Inactive Company Industry Presentation Historical

This table contains historical inactive company industry presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOINDSTRYPRES (Clustered)	GVKEY, DATADATE, CONSOL, IPCD
CSIBKCOINDSTRYPRES_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
IPCD	char(1)	N	IPCD identifies the industry presentation of financial services companies trading outside of the United States and Canada.

CSIBkCoIndustry: Industry Classification Presentation Historical

This table contains historical industry classification presentation information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOINDUSTRY (Clustered)	GVKEY, DATADATE, CONSOL
CSIBKCOINDUSTRY_1	GVKEY, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	Y	FYR designates the month-end for a company's accounting year.
NAICSH	int	Y	NAICSH contains the historical NAICS code assigned to a company.
SICH	int	Y	SICH contains the SIC code that identifies the company's SIC Code in prior years.
YEAR_	smallint	Y	YEAR_ is the year of the data.

CSIBkCoMth: Inactive Company Monthly Historical

This table contains historical inactive company monthly information.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOMTH (Clustered)	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
BETA	float	Y	BETA is a measurement of the sensitivity of a company's stock price to the overall fluctuation in the Standard & Poor's 500 (S&P 500) Index Price for U.S. Companies, or the Toronto Stock Exchange 300 (TSE 300) Index Price for Canadian Companies.
SPCSRM	varchar(4)	Y	SPCSRM is an appraisal of the past performance of a stock's earnings and dividends and the stock's relative standing as of a company's current fiscal year-end.

CSIBkColFndQ: Inactive Company Interim Fundamentals – Quarterly Historical

This table contains quarterly historical information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOIFNDQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOIFNDQ_1	GVKEY, Item, DATADATE
CSIBKCOIFNDQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIBKCOIFNDQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSIBKCOIFNDQ_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkColFndQ.Item and Group_ = 247.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSIBkColFndYTD: Inactive Company Interim Fundamentals – Year to Date Historical

This table contains year-to-date historical information for inactive company interim fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOIFNDYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item

Indexes	Index Fields
CSIBKCOIFNDYTD_1	GVKEY, Item, DATADATE
CSIBKCOIFNDYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIBKCOIFNDYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSIBKCOIFNDYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkColFndYTD.Item and Group_ = 248
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSIBkColFndSA: Inactive Company Quarterly Fundamentals Historical

This table contains information for historical inactive company quarterly fundamentals.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOIFNDSA (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOIFNDSA_1	GVKEY, Item, DATADATE
CSIBKCOIFNDSA_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIBKCOIFNDSA_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSIBKCOIFNDSA_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.

Field	Type	Nullable	Description
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
Item	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkColFndSA.Item and Group_ = 249.
Value_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DValue	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FyrFlag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

CSIBkSecM: Inactive Monthly Descriptor Historical

This table contains historical inactive monthly descriptor information.

NOTE

As of 21 July 2020, SPGIM, SPIIM and SPMIM fields are no longer populated. These fields are set to NULL.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKSECM (Clustered)	GVKEY, IID, DATADATE
CSIBKSECM_1	GVKEY, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
AJEXM	float	Y	AJEXM is the monthly adjustment factor - cumulative by ex-date.
AJPM	float	Y	AJPM is the monthly adjustment factor - cumulative by payable date.
ISALRT	varchar(9)	Y	ISALRT is the issue status alert. It contains the two-character code that indicates when issue trading has been suspended.
PRIMISS	char(1)	Y	PRIMISS is a monthly market data descriptor that identifies the issue with the highest market presence.
SPGIM	varchar(9)	Y	SPGIM is the S&P Global Industry Classification Index code – historical.
SPIIM	varchar(9)	Y	SPIIM is the S&P Industry Index code –historical.
SPMIM	varchar(9)	Y	SPMIM is the S&P Major Index code – historical.

CSIBkSecMDv: Inactive Monthly Dividends Historical

This table contains information for historical inactive monthly dividends.

Update Cycle: Daily

Adjusted: Yes

Indexes		Index Fields	
pkey_CSIBKSECMDV (Clustered)		GVKEY, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CHEQVM	float	Y	CHEQVM is the monthly cash equivalent distributions per share - ex-date.
CURCDDVM	varchar(4)	Y	CURCDDVM is the monthly ISO currency code – dividend.
DVPSPM	float	Y	DVPSPM is the monthly dividends per share –pay date.
DVPSXM	float	Y	DVPSXM is the index monthly cash dividend paid per share by ex date. DVPSXM is adjusted for all stock splits and stock dividends that occurred during the period. This value does not include payments in preferred stock in lieu of cash, spin-offs, and stock of other corporations.
DVRATE	float	Y	DVRATE is the monthly indicated annual dividend rate.

CSIBkSecMPrc: Inactive Monthly Prices Historical

This table contains information for historical inactive monthly prices.

Update Cycle: Daily

Adjusted: Yes

Indexes		Index Fields	
pkey_CSIBKSECMPRC (Clustered)		GVKEY, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
CSFSM	float	Y	CSFSM is the monthly common stock float shares – Canada.
CSHTRM	float	Y	CSHTRM is the monthly trading volume.
CURCDM	varchar(4)	Y	CURCDM is the monthly ISO currency code.
NAVM	float	Y	NAVM is the monthly net asset value.
PRCCM	float	Y	PRCCM is the absolute close market price for each calendar month.
PRCHM	float	Y	PRCHM is the absolute high market price for each calendar month.
PRCLM	float	Y	PRCLM is the absolute low market price for each calendar month.

CSIBkSecMSS: Inactive Monthly Stock Split Factors Historical

This table contains information for historical inactive monthly stock split factors.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSIBKSECMSS (Clustered)		GVKEY, IID, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
RAWPM	float	Y	RAWPM is the monthly raw adjustment factor – pay date.
RAWXM	float	Y	RAWXM is the monthly raw adjustment factor – ex date.

CSIBkSecMSSFn: Inactive Monthly Stock Split Footnotes

This table contains information for inactive monthly stock split footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKSECMSSFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSIBKSECMSSFN_1	GVKEY, Item, DATADATE
CSIBKSECMSSFN_2	GVKEY, DATADATE
CSIBKSECMSSFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSIBKSECMSSFN_4	GVKEY, IID, DATADATE
CSIBKSECMSSFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkSecMSSFN.Item and Group_ = 164.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkSecMDvFn: Inactive Monthly Dividend Footnotes

This table contains information for inactive monthly dividend footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKSECMDVFN (Clustered)	GVKEY, IID, DATADATE, DATAITEM, Item
CSIBKSECMDVFN_1	GVKEY, Item, DATADATE
CSIBKSECMDVFN_2	GVKEY, DATADATE
CSIBKSECMDVFN_3	GVKEY, IID, DATAITEM, Item, DATADATE
CSIBKSECMDVFN_4	GVKEY, IID, DATADATE
CSIBKSECMDVFN_5	GVKEY, IID, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is the Global Company Key.
IID	varchar(4)	N	IID is the issue identifier. It uniquely identifies each issue of a company.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
DATAITEM	varchar(17)	N	DATAITEM is the data item to which a footnote is related. This field contains the data item mnemonic.

Field	Type	Nullable	Description
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkSecMDvFn.Item and Group_ = 163.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

16 Compustat XF Daily Pension Research

CSIACoPnFndQ: Inactive Company Annual Pension and Post-Retirement Footnotes

This table contains information for inactive company annual pension and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSIACOPNFNDQ (Clustered)		GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT	
CSIACOPNFNDQ_1		GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERQ	float	Y	PBECERQ is the amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECERQ_DC	smallint	Y	PBECERQ_DC is the data code of the amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECQ	float	Y	PBECQ is the quarterly amount of contributions the company made to its pension plans during the current period.
PBECQ_DC	smallint	Y	PBECQ_DC is the data code of the quarterly amount of contributions the company made to its pension plans during the current period.
PPCQ	float	Y	PPCQ is the periodic pension cost on a quarterly basis.
PPCQ_DC	smallint	Y	PPCQ_DC is the data code of the periodic pension cost on a quarterly basis.
PPICQ	float	Y	PPICQ is the accrual of interest for the year on the projected pension benefit obligation on a quarterly basis.
PPICQ_DC	smallint	Y	PPICQ_DC is the data code of the accrual of interest for the year on the projected pension benefit obligation on a quarterly basis.
PPOPCCQ	float	Y	PPOPCCQ is all quarterly additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
hPPORCCQ_DC	smallint	Y	PPORCCQ_DC is the data code of all quarterly additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPRPAQ	float	Y	PPRPAQ is the quarterly expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.

Field	Type	Nullable	Description
PPRPAQ_DC	smallint	Y	PPRPAQ_DC is the data code of the quarterly expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPSCQ	float	Y	PPSCQ is the quarterly present value of expected future pension payments attributed to employee services performed during the current year.
PPSCQ_DC	smallint	Y	PPSCQ_DC is the data code of the present value of expected future pension payments attributed to employee services performed during the current year.

CSIACoPnFndYTD: Inactive Company Year-to-Date Pension and Post-Retirement Data

This table contains information for inactive company year-to-date pension and post-retirement data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIAcOPNFNDYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSIAcOPNFNDYTD_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERY	float	Y	PBECERY is the year-to-date amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECERY_DC	smallint	Y	PBECERY_DC is the data code of the year-to-date amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECY	float	Y	PBECY is the year-to-date amount of contributions the company made to its pension plans during the current period.
PBECY_DC	smallint	Y	PBECY_DC is the data code of the year-to-date amount of contributions the company made to its pension plans during the current period.
PPCY	float	Y	PPCY is the year-to-date periodic pension cost.
PPCY_DC	smallint	Y	PPCY_DC is the data code of the year-to-date periodic pension cost.
PPICY	float	Y	PPICY is the year-to-date accrual of interest for the year on the projected pension benefit obligation.
PPICY_DC	smallint	Y	PPICY_DC is the data code of the year-to-date accrual of interest for the year on the projected pension benefit obligation.
PPOPCCY	float	Y	PPOPCCY is all year-to-date additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPORCCY_DC	smallint	Y	PPORCCY_DC is the data code of all year-to-date additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.

Field	Type	Nullable	Description
PPRPAY	float	Y	PPRPAY is the year-to-date expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPRPAY_DC	smallint	Y	PPRPAY_DC is the data code of the year-to-date expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPSCY	float	Y	PPSCY is the year-to-date present value of expected future pension payments attributed to employee services performed during the current year.
PPSCY_DC	smallint	Y	PPSCY_DC is the data code of the year-to-date present value of expected future pension payments attributed to employee services performed during the current year.

CSIACoPnFntA: Inactive Company Annual and Post-Retirement Footnotes

This table contains information for inactive company annual and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIAcOPNFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIAcOPNFNTA_1	GVKEY, Item, DATADATE
CSIAcOPNFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIAcOPNFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIAcOPnFntA.Item and Group_ = 269.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIACoPnFntQ: Inactive Company Quarterly and Post-Retirement Footnotes

This table contains information for inactive company quarterly and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIAcOPNFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSIAcOPNFNTQ_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.

Field	Type	Nullable	Description
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERQ_FN	varchar(9)	Y	PBECERQ_FN is the additional contributions expected remainder of the year footnote.
PBECQ_FN	varchar(9)	Y	PBECQ_FN is the pension employer contribution footnote.
PPCQ_FN	varchar(9)	Y	PPCQ_FN is the periodic pension cost footnote.
PPICQ_FN	varchar(9)	Y	PPICQ_FN is the pension plans interest cost footnote.
PPOPCCQ_FN	varchar(9)	Y	PPOPCCQ_FN is the pension plans other periodic cost components footnote.
PPRPAQ_FN	varchar(9)	Y	PPRPAQ_FN is the expected change in market value of pension plan assets footnote.
PPSCQ_FN	varchar(9)	Y	PPSCQ_FN is the pension plans service cost footnote.

CSIACoPnFntYTD: Inactive Company Year-to-Date Pension and Post-Retirement Footnotes

This table contains information for inactive company year-to-date pension and post-retirement footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIAcOPNFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSIAcOPNFNTYTD_1	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
PBECERY_FN	varchar(9)	Y	PBECERY_FN is the year-to-date footnote amount of contributions the company expects to make to its pension plans during the rest of the year (as of the end of the current period).
PBECY_FN	varchar(9)	Y	PBECY_FN is the year-to-date footnote amount of contributions the company made to its pension plans during the current period.
PPCY_FN	varchar(9)	Y	PPCY_FN is the year-to-date periodic pension cost footnote.
PPICY_FN	varchar(9)	Y	PPICY_FN is the year-to-date footnote accrual of interest for the year on the projected pension benefit obligation.

Field	Type	Nullable	Description
PPOPCCY_FN	varchar(9)	Y	PPOPCCY_FN is all year-to-date footnote additional reported parts of Net Periodic Pension Cost other than Service Cost, Interest Cost, and Actual Return on Plan Assets.
PPRPAY_FN	varchar(9)	Y	PPRPAY_FN is the year-to-date footnote expected change in market value of pension plan assets, excluding contributions to the plan or payments by the plan.
PPSCY_FN	varchar(9)	Y	PPSCY_FN is the year-to-date footnote present value of expected future pension payments attributed to employee services performed during the current year.

CSIACoPnFndA: Inactive Company Annual and Post-Retirement Data

This table contains information for inactive company annual and post-retirement data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIAcOPNFNDa (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIAcOPNFNDa_1	GVKEY, Item, DATADATE
CSIAcOPNFNDa_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIACoPnFndA.Item and Group_ = 268.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

17 Compustat XF Daily Pension Historical Research

CSIBkCoPnFntA: Inactive Annual Pension Footnotes Historical

This table contains information for historical inactive annual pension footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKOPNFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKOPNFNTA_1	GVKEY, Item, DATADATE
CSIBKOPNFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIBKOPNFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number.Number = CSIBkCoPnFntA.Item and Group_ = 271.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkCoPnFndA: Inactive Company Annual and Post-Retirement Data Historical

This table contains information for historical inactive company annual and post-retirement data.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKOPNFNDA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKOPNFNDA_1	GVKEY, Item, DATADATE
CSIBKOPNFNDA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoPnFndA.Item and Group_ = 270.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

18 Compustat XF Daily Industry Research

CSIAColndFntA: Inactive Annual Industry Statistics Footnotes

This table contains information for inactive annual industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIAColndFntA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIAColndFntA_1	GVKEY, Item, DATADATE
CSIAColndFntA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIAColndFntA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIAColndFntA.Item and Group_ = 271.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIAColndStQC: Inactive Quarterly Industry Statistics

This table contains information for inactive quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIAColndStQC (Clustered)	KeyCode, Item
CSIAColndStQC_1	KeyCode

Field	Type	Nullable	Description
KEYCODE	int	N	
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIAColndStQC.Item and Group_ = 251.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSIACoIndStQP: Inactive Company Quarterly Industry Statistics

This table contains information for inactive company quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIACOINDSTQP (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, KEYCODE
CSIACOINDSTQP_1	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSIACOINDSTQP_2	KEYCODE
CSIACOINDSTQP_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE, KEYCODE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
KEYCODE	int	N	
UEDODF	datetime	Y	UEDODF is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODF_DC	tinyint	Y	UEDODF_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODS	datetime	Y	UEDODS is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODS_DC	tinyint	Y	UEDODS_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODT	datetime	Y	UEDODT is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UEDODT_DC	tinyint	Y	UEDODT_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UGDODF	datetime	Y	UGDODF is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODF_DC	tinyint	Y	UGDODF_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODS	datetime	Y	UGDODS is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODS_DC	tinyint	Y	UGDODS_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODT	datetime	Y	UGDODT is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).
UGDODT_DC	tinyint	Y+	UGDODT_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).

CSIAColndStA: Inactive Annual Industry Statistics Historical

This table contains information for historical inactive annual industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIACOINDSTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIACOINDSTA_1	GVKEY, Item, DATADATE
CSIACOINDSTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIAColndStA.Item and Group_ = 252.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSIAColndFntQ: Inactive Quarterly Industry Statistics Footnotes

This table contains information for inactive quarterly industry statistics footnotes.

Update Cycle: Daily **Adjusted:** No

Indexes	Index Fields
pkey_CSIACOINDFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIACOINDFNTQ_1	GVKEY, Item, DATADATE
CSIACOINDFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIACOINDFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIAColndFntQ.Item and Group_ = 253.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIACoIndFntYTD: Inactive Year-to-Date Industry Statistics Footnotes

This table contains information for inactive year-to-date industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIACOINDFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIACOINDFNTYTD_1	GVKEY, Item, DATADATE
CSIACOINDFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIACOINDFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIACoIndFntYTD.Item and Group_ = 254.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIACoIndStYTD: Inactive Year-to-Date Industry Statistics

This table contains information for inactive year-to-date industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIACOINDSTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIACOINDSTYTD_1	GVKEY, Item, DATADATE
CSIACOINDSTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIACOINDSTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSIACOINDSTYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE, DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	tinyint	N	FYR designates the month-end for a company's accounting year.

Field	Type	Nullable	Description
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIAColndStYTD.Item and Group_ = 256.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
Fyrflag	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

19 Compustat XF Daily Industry Historical Research

CSIBkCoINDFNTA: Inactive Annual Industry Statistics Footnotes Historical

This table contains information for historical inactive annual industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOINDFNTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOINDFNTA_1	GVKEY, Item, DATADATE
CSIBKCOINDFNTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE
CSIBKCOINDFNTA_3	GVKEY, INDFMT, DATAFMT, CONSOL, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoINDFNTA.Item and Group_ = 262.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkCoINDSTQC: Inactive Quarterly Industry Statistics Historical

This table contains information for historical inactive quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOINDSTQC (Clustered)	KeyCode, Item
CSIBKCOINDSTQC_1	KeyCode

Field	Type	Nullable	Description
KEYCODE	int	N	
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoINDSTQC.Item and Group_ = 256.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSIBkCoINDSTQP: Inactive Company Quarterly Industry Statistics Historical

This table contains information for historical inactive company quarterly industry statistics.

Update Cycle: Daily

Adjusted: Yes

Indexes	Index Fields
pkey_CSIBKCOINDSTQP (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, KEYCODE
CSIBKCOINDSTQP_1	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT
CSIBKCOINDSTQP_2	KEYCODE
CSIBKCOINDSTQP_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE, KEYCODE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
KEYCODE	int	N	
UEDODF	datetime	Y	UEDODF is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODF_DC	tinyint	Y	UEDODF_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (first state).
UEDODS	datetime	Y	UEDODS is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODS_DC	tinyint	Y	UEDODS_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (second state).
UEDODT	datetime	Y	UEDODT is the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UEDODT_DC	tinyint	Y	UEDODT_DC is the data code of the date on which the most recent electric rate order issued by the state regulatory commission is authorized (third state).
UGDODF	datetime	Y	UGDODF is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODF_DC	tinyint	Y	UGDODF_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (first state).
UGDODS	datetime	Y	UGDODS is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODS_DC	tinyint	Y	UGDODS_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (second state).
UGDODT	datetime	Y	UGDODT is the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).
UGDODT_DC	tinyint	Y	UGDODT_DC is the data code of the date on which the most recent gas rate order issued by the state regulatory commission is authorized (third state).

CSIBkCoINDFNTQ: Inactive Quarterly Industry Statistics Footnotes Historical

This table contains information for historical inactive quarterly industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOINDFNTQ (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOINDFNTQ_1	GVKEY, Item, DATADATE
CSIBKCOINDFNTQ_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIBKCOINDFNTQ_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoINDFNTQ.Item and Group_ = 260.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkCoINDFNTYTD: Inactive Year-to-Date Industry Statistics Footnotes Historical

This table contains information for historical inactive year-to-date industry statistics footnotes.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOINDFNTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOINDFNTYTD_1	GVKEY, Item, DATADATE
CSIBKCOINDFNTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIBKCOINDFNTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.

Field	Type	Nullable	Description
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoINDFNTYTD.Item and Group_ = 261.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.

CSIBkCoINDSTA: Inactive Annual Industry Statistics Historical

This table contains information for historical inactive annual industry statistics.

Update Cycle:

Adjusted:

Indexes	Index Fields
pkey_CSIBKCOINDSTA (Clustered)	GVKEY, DATADATE, INDFMT, DATAFMT, CONSOL, Item
CSIBKCOINDSTA_1	GVKEY, Item, DATADATE
CSIBKCOINDSTA_2	GVKEY, INDFMT, DATAFMT, CONSOL, Item, DATADATE

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoINDSTA.Item and Group_ = 259.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
DataCode	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .

CSIBkCoINDSTYTD: Inactive Year-to-Date Industry Statistics Historical

This table contains information for historical inactive year-to-date industry statistics.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_CSIBKCOINDSTYTD (Clustered)	GVKEY, DATADATE, INDFMT, CONSOL, FYR, DATAFMT, Item
CSIBKCOINDSTYTD_1	GVKEY, Item, DATADATE
CSIBKCOINDSTYTD_2	GVKEY, INDFMT, CONSOL, DATAFMT, Item, DATADATE
CSIBKCOINDSTYTD_3	GVKEY, INDFMT, CONSOL, DATAFMT, DATADATE
CSIBKCOINDSTYTD_4	GVKEY, INDFMT, CONSOL, Item, DATADATE DATAFMT

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.

Field	Type	Nullable	Description
INDFMT	tinyint	N	INDFMT is the industry format. This describes whether a company reports in a financial services or industrial format. INDFMT is translated in CSKeyCode where FIELDNAME = INDFMT.
CONSOL	tinyint	N	CONSOL is the level of consolidation of the company's financial statements in a company record. CONSOL is translated by CSKeyCode where FIELDNAME = CONSOL.
FYR	smallint	N	FYR designates the month-end for a company's accounting year.
DATAFMT	tinyint	N	DATAFMT describes how data is collected and presented. DATAFMT is translated by CSKeyCode where FIELDNAME = DATAFMT.
ITEM	smallint	N	Item is the Compustat item; it cross-references CSNAItem where CSNAItem.Number = CSIBkCoINDSTYTD.Item and Group_ = 263.
VALUE_	varchar(9)	Y	Value_ is the raw value provided by Compustat.
DATACODE	tinyint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
DVALUE	float	Y	DValue is the derived quarterly value for semi-annual or annual figures.
FYRFLAG	tinyint	Y	FyrFlag identifies values affected by FYR changes or DataCode adjustments; the possible values are below: – 0 = No FYR or Datacode adjustment – 1 = Fyr adjusted, the DValue is derived from raw data of a different record – 2 = Datacode adjusted, the original value is 2x DValue – 3 = Fyr and Datacode adjusted, the original value is 2x DValue and is from another record – 4 = DataCode adjusted, the original value is 4x DValue – 5 = Fyr and Datacode adjusted, the original value is 4x DValue and is from another record

20 Compustat XF Daily Issuer Credit Ratings Research

CSIADSPRate: Inactive S&P Ratings – Monthly

This table contains information for monthly inactive S&P ratings.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSIADSPRATE (Clustered)		GVKEY, DATADATE	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
DATADATE	datetime	N	DATADATE is the end date of the quarter for which the data was reported.
SPLTICRM	varchar(11)	Y	SPLTICRM is the S&P domestic long-term issuer credit rating.
SPSDRM	varchar(11)	Y	SPSDRM is the monthly S&P subordinated debt rating.
SPSTICRM	varchar(11)	Y	SPSTICRM is the S&P domestic short-term issuer credit rating.

21 Compustat XF Daily Current Issuer Credit Ratings Research

CSIADSPRateC: S&P Ratings – Current

This table contains information for current S&P ratings.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_CSIADSPRATEC (Clustered)		GVKEY	

Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
SPLTICRC	varchar(11)	Y	SPLTICRC is the current S&P domestic long-term issuer credit rating.
SPSTICRC	varchar(11)	Y	SPSTICRC is the current S&P domestic short-term issuer credit rating.

22 Compustat Xpressfeed Point-in-Time

CSPITAdj: Compustat PIT Adjustment

This table contains Compustat PIT adjustment information.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitadj (Clustered)		GvKey, Pointdate, Datadate	
Field	Type	Nullable	Description
GVKEY	int	N	GVKEY is a unique company key and is the primary link for all CS* tables.
POINTDATE	smalldatetime	N	Pointdate is not significant in this table.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
ADJFACTOR	float	Y	AdjFactor is the cumulative adjustment for data date. To adjust PIT data, reference CSPITItem for adjustment method. Calculate adjusted value using AdjFactor where Datadate = Cspit* FND.Datadate.

CSPITAdjC: Compustat PIT Adjustment—Canadian

This table contains Compustat PIT Canadian adjustment information.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitadjc (Clustered)		GvKey, Pointdate, Datadate	
Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
POINTDATE	smalldatetime	N	Pointdate is not significant in this table.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
ADJFACTOR	float	Y	AdjFactor is the cumulative adjustment for data date. To adjust PIT data, reference CSPITItem for adjustment method. Calculate adjusted value using AdjFactor where Datadate = Cspit* FND.Datadate.

CSPITCmp: Compustat PIT Companies

This table contains information for Compustat PIT companies.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitcmp (Clustered)		GvKey	
Cspitcmp_CoNm		CoNm, GvKey	
Cspitcmp_Cusip		Cusip, GvKey	
Cspitcmp_Tic		Tic, GvKey	

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
CONM	varchar(49)	Y	CoNm is the company name.
SIC	int	Y	Sic is the SIC code.
TIC	varchar(8)	Y	Tic the trading symbol.
EXCHG	smallint	Y	Exchg is the exchange.
CUSIP	varchar(9)	Y	Cusip is a unique identifier for each company on Compustat.
FIC	int	Y	Fic is the FIC.
STKO	smallint	Y	Stko is the company STKO.
START_	smalldatetime	Y	Start_ is the production date of the database when a company first appeared in Compustat.
COSTAT	varchar(1)	Y	Costat is the company status.

CSPITCmpC: Compustat PIT Companies—Canadian

This table contains information for Compustat PIT Canadian companies.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitcmpc (Clustered)	GvKey
Cspitcmpc_CoNm	CoNm, GvKey
Cspitcmpc_Cusip	Cusip, GvKey
Cspitcmpc_Tic	Tic, GvKey

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
CONM	varchar(49)	Y	CoNm is the company name.
SIC	int	Y	Sic is the SIC code.
TIC	varchar(8)	Y	Tic the trading symbol.
EXCHG	smallint	Y	Exchg is the exchange.
CUSIP	varchar(9)	Y	Cusip is a unique identifier for each company on Compustat.
FIC	int	Y	Fic is the FIC.
STKO	smallint	Y	Stko is the company STKO.
START_	smalldatetime	Y	Start_ is the production date of the database when a company first appeared in Compustat.
COSTAT	varchar(1)	Y	Costat is the company status.

CSPITDFnd: Compustat PIT As First Reported and Fully Restated Data

This table contains information for Compustat PIT as first reported and fully restated data.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitdfnd (Clustered)	Item, GvKey, Pointdate, Datadate, Valuetype

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.

Field	Type	Nullable	Description
POINTDATE	smalldatetime	N	Pointdate is not significant in this table.
ITEM	int	N	Item cross references CSPITItem where item = CSPITItem.number.
DATACODE	smallint	Y	Datacode is described in the Datacode section on page 165.
VALUETYPE	smallint	N	Valuetype can be one of the following values: – 0 = Final restated – 1 = AFR
VALUE_	float	Y	Value_ is unadjusted. Reference CSPITAdj for adjustment factor where DataDate = CSPITAdj.Datadate.

NOTE

The full history of restatements between AFR and fully restated, inclusive, is the combination of [CSPITDFnd](#) and [CSPITDHstFnd](#).

Datacode

Datacode is the data code for the item. Possible values include:

- 0 = OK; normal. Data in corresponding field is normal.
- 1 = NA; not applicable. Data in corresponding field is normal.
- 2 = SF; semi-annual figure. Data in corresponding field is a semi-annual (6 month) value.
- 3 = AF; annual figure. Data in corresponding field is an annual (12 month) value.
- 4 = CF; combined figure. Data in corresponding field is a combined figure (included in the value of another data item).
- 6 = NM; not meaningful. Data in corresponding field is not meaningful.
- 7 = NR; not reported. Data in corresponding fields should not be used as no data was reported for that DATADATE at that POINTDATE.
- 8 = IF; insignificant figure. Data in corresponding field insignificant figure.
- 9 = IR; irrelevant figure. Data in corresponding field is irrelevant figure.

CSPITDFndC: Compustat PIT As First Reported and Fully Restated Data—Canadian

This table contains information for Compustat PIT Canadian as first reported and fully restated data.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitdfndc (Clustered)	Item, GvKey, Pointdate, Datadate, Valuetype

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
POINTDATE	smalldatetime	N	Pointdate is not significant in this table.
ITEM	int	N	Item cross references CSPITItem where item = CSPITItem.number.
DATACODE	smallint	Y	Datacode is described in the Datacode section on page 165.
VALUETYPE	smallint	N	Valuetype can be one of the following values: – 0 = Final restated – 1 = AFR
VALUE_	float	Y	Value_ is unadjusted. Reference CSPITAdj for adjustment factor where DataDate = CSPITAdj.Datadate.

CSPITDHstFnd: Compustat PIT Historically Restated Data

This table contains information for Compustat PIT historically restated data.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitdhstfnd (Clustered)		Item, GvKey, Pointdate, Datadate, Valuetype	
Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
POINTDATE	smalldatetime	N	Pointdate is the date for restated value given that point in time; Pointdate granularity is monthly.
ITEM	int	N	Item cross references CSPITItem where item = CSPITItem.number.
DATACODE	smallint	Y	Datadate is described in the Datacode section on page 165.
VALUETYPE	smallint	N	Valuetype signifies historically restated data and has a value of two.
VALUE_	float	Y	Value_ is unadjusted. Refer to CSPITAdj for adjustment factor where DataDate = CSPITAdj.Datadate.

NOTE

Historical restatements will be recorded in this table if interim restatements exist between AFR and final. The full history of restatements between AFR and fully restated, inclusive, is the combination of [CSPITDFnd](#) and [CSPITDHstFnd](#).

CSPITDHstFndC: Compustat PIT Historically Restated Data—Canadian

This table contains information for Compustat PIT Canadian historically restated data.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitdhstfndc (Clustered)		Item, GvKey, Pointdate, Datadate, Valuetype	
Field	Type	Nullable	Description
GVKEY	int	N	GvKey is a unique company key and is the primary link for all CS* tables.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
POINTDATE	smalldatetime	N	Pointdate is the date for restated value given that point in time; Pointdate granularity is monthly.
ITEM	int	N	Item cross references CSPITItem where item = CSPITItem.number.
DATACODE	smallint	Y	Datadate is described in the Datacode section on page 165.
VALUETYPE	smallint	N	Valuetype signifies historically restated data and has a value of two.
VALUE_	float	Y	Value_ is unadjusted. Refer to CSPITAdj for adjustment factor where DataDate = CSPITAdj.Datadate.

CSPITFn: Compustat PIT Footnotes

This table contains information for Compustat PIT footnotes.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitfn (Clustered)		Category, GvKey, Item, Datadate, Pointdate, Valuetype	
Field	Type	Nullable	Description
CATEGORY	smallint	N	Category is the type of data item and can be one of the following: – 1 = Balance – 2 = Cash Flow – 3 = Miscellaneous – 4 = Income
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
ITEM	int	N	Item cross references CSPITItem where item = CSPITItem.number.
DATADATE	smalldatetime	N	Datadate is the fiscal quarter for which value_ is reporting.
POINTDATE	smalldatetime	N	Pointdate is the point in time restated date. Pointdate is insignificant for AFR and final restated valuetypes.
DATACODE	smallint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
VALUETYPE	smallint	N	Valuetype can be one of the following: – 0 = Final restated – 1 = AFR – 2 = Historically restated
VALUE_	varchar(3)	Y	Value_ is unadjusted. Refer to CSPITAdj for adjustment factor where DataDate = CSPITAdj.Datadate.

NOTE

To return footnote value for PIT reported data value reference [CSPITDFnd](#) or [CSPITDHstFnd](#) tables where DataDate = Cspit*fnd.datadate and PointDate = Cspit*fnd.PointDate and valuetype = Cspit*fnd.valuetype.

CSPITFnC: Compustat PIT Footnotes—Canadian

This table contains information for Compustat PIT Canadian footnotes.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitfnc (Clustered)		Category, GvKey, Item, Datadate, Pointdate, Valuetype	
Field	Type	Nullable	Description
CATEGORY	smallint	N	Category is the type of data item and can be one of the following: – 1 = Balance – 2 = Cash Flow – 3 = Miscellaneous – 4 = Income
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
ITEM	int	N	Item cross references CSPITItem where item = CSPITItem.number.
DATADATE	smalldatetime	N	Datadate is the fiscal quarter for which value_ is reporting.

Field	Type	Nullable	Description
POINTDATE	smalldatetime	N	Pointdate is the point in time restated date. Pointdate is insignificant for AFR and final restated valuetypes.
DATACODE	smallint	Y	DataCode flags non-normal values; descriptions are found in CSRDataCode .
VALUETYPE	smallint	N	Valuetype can be one of the following: – 0 = Final restated – 1 = AFR – 2 = Historically restated
VALUE_	varchar(3)	Y	Value_ is unadjusted. Refer to CSPITAdj for adjustment factor where DataDate = CSPITAdj.DataDate.

CSPITFndInfo: Compustat PIT Fully Restated Dates Information

This table contains Compustat PIT fully restated dates information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitfndinfo (Clustered)	Category, GvKey, Datadate, Pointdate
Cspitfndinfo_Category	Category, GvKey, Year_, Qtr, Pointdate

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
DATADATE	smalldatetime	N	Datadate is the fiscal quarter end date.
QTRSBACK	smallint	Y	Qtrsback indicates, at each Pointdate, how many quarters back a reporting quarter is from the most recently finalized quarter.
QTR	smallint	Y	Qtr is the calendar quarter of the data date. For example, Q1, Q2, Q3, and Q4.
YEAR_	smallint	Y	Year_ is the fiscal year of the data date.
POINTDATE	smalldatetime	N	Pointdate is the point in time restated date. Pointdate is insignificant for AFR and final restated valuetypes.
CATEGORY	smallint	N	Category is the type of data item and can be one of the following: – 1 = Balance – 2 = Cash Flow – 3 = Miscellaneous – 4 = Income

CSPITFndInfoC: Compustat PIT Fully Restated Dates Information—Canadian

This table contains Compustat PIT Canadian fully restated dates information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitfndinfoc (Clustered)	Category, GvKey, Datadate, Pointdate
Cspitfndinfoc_Category	Category, GvKey, Year_, Qtr, Pointdate

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
DATADATE	smalldatetime	N	Datadate is the fiscal quarter end date.

Field	Type	Nullable	Description
QTRSBACK	smallint	Y	Qtrsback indicates, at each Pointdate, how many quarters back a reporting quarter is from the most recently finalized quarter.
QTR	smallint	Y	Qtr is the calendar quarter of the data date. For example, Q1, Q2, Q3, and Q4.
YEAR_	smallint	Y	Year_ is the fiscal year of the data date.
POINTDATE	smalldatetime	N	Pointdate is the point in time restated date. Pointdate is insignificant for AFR and final restated valuetypes.
CATEGORY	smallint	N	Category is the type of data item and can be one of the following: – 1 = Balance – 2 = Cash Flow – 3 = Miscellaneous – 4 = Income

CSPITHFndInfo: Compustat PIT Historical Dates Information

This table contains Compustat PIT historical dates information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspithfndinfo (Clustered)	Category, GvKey, Datadate, Pointdate
Cspithfndinfo_Category	Category, GvKey, Year_, Qtr, Pointdate

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
DATADATE	smalldatetime	N	Datadate is the fiscal quarter end date.
QTRSBACK	smallint	Y	Qtrsback indicates, at each Pointdate, how many quarters back a reporting quarter is from the most recently finalized quarter.
QTR	smallint	Y	Qtr is the calendar quarter mark. For example, Q1, Q2, Q3, Q4.
YEAR_	smallint	Y	Year_ is the fiscal year of the data date.
POINTDATE	smalldatetime	N	Pointdate is the monthly point in time date. Each point date can have up to 20 quarters look back.
CATEGORY	smallint	N	Category is the type of data item and can be one of the following: – 1 = Balance – 2 = Cash Flow – 3 = Miscellaneous – 4 = Income

CSPITHFndInfoC: Compustat PIT Historical Dates Information—Canadian

This table contains Compustat PIT Canadian historical dates information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspithfndinfoc (Clustered)	Category, GvKey, Datadate, Pointdate
Cspithfndinfoc_Category	Category, GvKey, Year_, Qtr, Pointdate

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
DATADATE	smalldatetime	N	Datadate is the fiscal quarter end date.

Field	Type	Nullable	Description
QTRSBACK	smallint	Y	Qtrsback indicates, at each Pointdate, how many quarters back a reporting quarter is from the most recently finalized quarter.
QTR	smallint	Y	Qtr is the calendar quarter mark. For example, Q1, Q2, Q3, Q4.
YEAR_	smallint	Y	Year_ is the fiscal year of the data date.
POINTDATE	smalldatetime	N	Pointdate is the monthly point in time date. Each point date can have up to 20 quarters look back.
CATEGORY	smallint	N	Category is the type of data item and can be one of the following: – 1 = Balance – 2 = Cash Flow – 3 = Miscellaneous – 4 = Income

CSPITId: Compustat PIT Historical Identification Information

This table contains Compustat PIT historical identification information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitid (Clustered)	GvKey, Changedate

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
CHANGEDATE	smalldatetime	N	ChangeDate is the date identification data changed.
NAME	varchar(49)	Y	Name is the index corporation action name.
TICKER	varchar(11)	Y	Ticker is the ticker symbol.
EXCH	smallint	Y	Exch can be cross-referenced with CSCode where Exch = CSCode.code and CSCode.number = 115.
CUSIP	varchar(9)	Y	Cusip is a unique identifier for each company on Compustat.

CSPITIdC: Compustat PIT Historical Identification Information—Canadian

This table contains Compustat PIT Canadian historical identification information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitidc (Clustered)	GvKey, Changedate

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary key across all Cspit* tables.
CHANGEDATE	smalldatetime	N	ChangeDate is the date identification data changed.
NAME	varchar(49)	Y	Name is the index corporation action name.
TICKER	varchar(11)	Y	Ticker is the ticker symbol.
EXCH	smallint	Y	Exch can be cross-referenced with CSCode where Exch = CSCode.code and CSCode.number = 115.
CUSIP	varchar(9)	Y	Cusip is a unique identifier for each company on Compustat.

CSPITItem: Compustat PIT Item Information

This table contains Compustat PIT item information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspititem (Clustered)	Mnemonic
Cspititem_Desc_	Desc_, Mnemonic
Cspititem_Number	Number
Cspititem_Synonym	Synonym, Mnemonic

Field	Type	Nullable	Description
MNEMONIC	varchar(14)	N	Mnemonic directly relates to Compustat documentation.
DATATYPE	smallint	Y	Datatype can be one of the following: – 0 = float – 4 = foot note
FORMAT	varchar(6)	Y	
DESC_	varchar(49)	Y	Desc_ contains the coded item description.
SYNONYM	varchar(6)	Y	Synonym directly relates to Compustat documentation.
CATEGORY	varchar(11)	Y	Category is the category of the data item.
CATEGORY1	varchar(11)	Y	Category1 is the category of the data item.
NUMBER	smallint	Y	Number is the key across for linking all Compustat PIT items to Value_. Reference CSPIT data tables where number = Cspit* .item.
ADJUSTMETHOD	smallint	Y	AdjustMethod can contain one of the following: – 0 = No adjustment – 1 = Add adjustment factor – 2 = Increasing share count on split and decreasing on reverse split – 3 = Decreasing on split and increasing on reverse split – 4 = Increasing share count on split and decreasing on reverse split, restated – 5 = Decreasing on split and increasing on reverse split, restated – 6 = Increasing share count on split and decreasing on reverse split, pay date – 7 = Decreasing on split and increasing on reverse split, pay date
BASIS	smallint	Y	

NOTE

All data items in PIT are quarterly items.

CSPITMnt: Compustat PIT Monthly Tag Information

This table contains Compustat PIT monthly tag information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitmnt (Clustered)	GvKey, Pointdate, QtrDate
Cspitmnt_GvKey	GvKey, Pointdate, Qtr, Year_
Cspitmnt_Pointdate	GvKey, Pointdate, Qtrsback

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is the primary key across all Cspit* tables.
POINTDATE	smalldatetime	N	Pointdate is the monthly point in time date. Each point date can have up to 20 quarters look back.
QTR	smallint	Y	Qtr is the calendar quarter of the data date. For example, Q1, Q2, Q3, and Q4.
YEAR_	smallint	Y	Year_ is the calendar year.
QTRDATE	smalldatetime	N	QtrDate is the date of the quarter.
QTRSBACK	smallint	Y	Qtrsback indicates, at each Pointdate, how many quarters back a reporting quarter is from the most recently finalized quarter.

CSPITMntC: Compustat PIT Monthly Tag Information—Canadian

This table contains Compustat PIT Canadian monthly tag information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitmntc (Clustered)	GvKey, Pointdate, QtrDate
Cspitmntc_GvKey	GvKey, Pointdate, Qtr, Year_
Cspitmntc_Pointdate	GvKey, Pointdate, Qtrsback

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is the primary key across all Cspit* tables.
POINTDATE	smalldatetime	N	Pointdate is the monthly point in time date. Each point date can have up to 20 quarters look back.
QTR	smallint	Y	Qtr is the calendar quarter of the data date. For example, Q1, Q2, Q3, and Q4.
YEAR_	smallint	Y	Year_ is the calendar year.
QTRDATE	smalldatetime	N	QtrDate is the date of the quarter.
QTRSBACK	smallint	Y	Qtrsback indicates, at each Pointdate, how many quarters back a reporting quarter is from the most recently finalized quarter.

CSPITPQtr: Compustat PIT Quarterly Tag Information

This table contains Compustat PIT quarterly tag information.

Update Cycle: Monthly

Adjusted: No

Indexes	Index Fields
pkey_Cspitpqtr (Clustered)	Gvkey, Datadate
Cspitpqtr_GvKey	Gvkey, QtrYear, FQtr

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is the primary key across all Cspit* tables.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
UPDQ	smallint	Y	Updq is the update code, and cross-references CSCode where Updq = CSCode.code and CSCode.number = 58.
SRCQ	smallint	Y	Srcq is the source document, and cross-references CSCode where Srcq = CSCode.code and CSCode.number = 61.
SRCQR	smallint	Y	Srcqr is the source document unrestated. See Srcq for the cross-reference.
FYEAR	smallint	Y	FYear is the fiscal year end month.
FQTR	smallint	Y	FQtr is the fiscal quarter.
QTRYEAR	smalldatetime	Y	QtrYear is the year of the quarter.
QTREND	smalldatetime	Y	QtrEnd is the date of the end of quarter.

Field	Type	Nullable	Description
PRELIMQPRD	smalldatetime	Y	Prelimqprd is the first time data that has been entered into PIT database with an UPDQ code = 2, for a given fiscal quarter.
FINALQPRD	smalldatetime	Y	Finalqprd is the first time data has been entered into PIT database with an UPDQ code = 3.
COMPSTQ	varchar(2)	Y	Compstq is described in the Compstq section on page 173.
COMPSTQR	varchar(2)	Y	Compstqr is the code (unrestated) regarding events or circumstances that make data incomparable from quarter to quarter. See Compstq on page 173 for descriptions.
RDQ	smalldatetime	Y	Rdq is the date of preliminary announcement. If preliminary announcement was not issued, it is the day following 10Q/10K filing.
SCFQ	smallint	Y	Scfq is the Cash Flow Format, it cross-references CSCode where Scfq = CSCode.code and CSCode.number = 9.
STALTQ	varchar(2)	Y	Staltq is the status alert, and breaks down as follows: – TL = Company in bankruptcy or liquidation. – TO = Company has undergone a leveraged buyout.
STALTQR	varchar(2)	Y	Staltqr is the status alert unrestated. See Staltq for descriptions.

Compstq

Compstq is the code regarding events or circumstances that make data incomparable from quarter to quarter. It breaks down as follows:

Code	Description
AA	Data reflects a merger or acquisition
AB	Data reflects a major merger resulting in the formation of a new company.
AC	Data reflects an accounting change
AF	Combination AA and AN
AG	Combination AC and AN
AH	Combination AN and AZ
AN	Data reflects the adoption of new accounting principles and presentation methods pursuant to revised national regulations and guidelines
AR	Combination AA and AZ
AS	Combination AA and AC
AT	Combination AC and AZ
AZ	Data excludes discontinued operations (North America); data reflects disposals (outside North America)
CA	Includes six months of a merger or acquisition
CB	Includes nine months of a merger or acquisition
CC	Includes 12 months of a merger or acquisition
CE	Excludes six months of discontinued operations
CF	Excludes nine months of discontinued operations
CG	Excludes 12 months of discontinued operations
DB	Company has undergone a fiscal year change. Some or all data may not be available
DZ	Company has been in operation for less than one year. Some or all data may not be available
IP	Company has undergone an initial public offering

CSPITPQtrC: Compustat PIT Quarterly Tag Information—Canadian

This table contains Compustat PIT Canadian quarterly tag information.

Update Cycle: Monthly

Adjusted: No

Indexes		Index Fields	
pkey_Cspitpqtrc (Clustered)		Gvkey, Datadate	
Cspitpqtrc_GvKey		Gvkey, QtrYear, FQtr	

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is the primary key across all Cspit* tables.
DATADATE	smalldatetime	N	Datadate is the end date of the quarter for which the data was reported.
UPDQ	smallint	Y	Updq is the update code, and cross-references CSCode where Updq = CSCode.code and CSCode.number = 58.
SRCQ	smallint	Y	Srcq is the source document, and cross-references CSCode where Srcq = CSCode.code and CSCode.number = 61.
SRCQR	smallint	Y	Srcqr is the source document unrestated. See Srcq for the cross-reference.
FYEAR	smallint	Y	FYear is the fiscal year end month.
FQTR	smallint	Y	FQtr is the fiscal quarter.
QTRYEAR	smalldatetime	Y	QtrYear is the year of the quarter.
QTREND	smalldatetime	Y	QtrEnd is the date of the end of quarter.
PRELIMQPRD	smalldatetime	Y	Prelimqprd is the first time data that has been entered into PIT database with an UPDQ code = 2, for a given fiscal quarter.
FINALQPRD	smalldatetime	Y	Finalqprd is the first time data has been entered into PIT database with an UPDQ code = 3.
COMPSTQ	varchar(2)	Y	Compstq is described in the Compstq section on page 173.
COMPSTQR	varchar(2)	Y	Compstqr is the code (unrestated) regarding events or circumstances that make data incomparable from quarter to quarter. See Compstq on page 173 for descriptions.
RDQ	smalldatetime	Y	Rdq is the date of preliminary announcement. If preliminary announcement was not issued, it is the day following 10Q/10K filing.
SCFQ	smallint	Y	Scfq is the Cash Flow Format, it cross-references CSCode where Scfq = CSCode.code and CSCode.number = 9.
STALTQ	varchar(2)	Y	Staltq is the status alert, and breaks down as follows: – TL = Company in bankruptcy or liquidation. – TO = Company has undergone a leveraged buyout.
STALTQR	varchar(2)	Y	Staltqr is the status alert unrestated. See Staltq for descriptions.

23 Compustat Xpressfeed Backtest

CSBData: Compustat Quarterly As First Reported Data

This table contains information for Compustat quarterly as first reported data.

Update Cycle: Monthly (vendor releases first week of the month)

Adjusted: Yes

Indexes		Index Fields	
pkey_csbdata (Clustered)		Code, Item, Date_	
Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross references with CSBItem_csbitem: Compustat_AFR where Item = CSBItem.Number.
DATE_	smalldatetime	N	Date_ cross references with CSBPrD where Code = CSBPrD.Code and Date_ = CSBPrD.EndDate. Use CSBPrD to determine the fiscal year of the period end date.
FLAG	smallint	Y	Flag contains the following values: – 0 = No Value_/ValueR available – 1 = Quarterly number – 2 = Data supplied by Compustat contained an Annual Figure Code (@AF). Since the AFR database is stored adjusted, the original number was divided by 4 to conform to the Quarterly structure of the CSBData table. – 3 = Data supplied by Compustat contained a Semi-annual Figure Code (@SF). Since the AFR database is stored adjusted, the original number was divided by 2 to conform to the Quarterly structure of the CSBData table. – 11-13 = Data supplied by Compustat contained a Combined Figure Code (@CF). The value is combined into some other Compustat item not specifically mentioned.
FLAGR	smallint	Y	See Flag for a description of FlagR.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.
VALUER	float	Y	ValueR represents the originally reported value (subject to flags listed below).

CSBFtn: Compustat AFR Footnotes

This table contains information for Compustat AFR footnotes.

Update Cycle: Monthly (vendor releases 1st week of the month)

Adjusted: N/A

Indexes		Index Fields	
pkey_csbftn (Clustered)		Item, Code	
Field	Type	Nullable	Description
ITEM	smallint	N	Item cross references with CSBItem_csbitem: Compustat_AFR where Item = CSBItem.Number.

Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
DESC_	varchar(159)	Y	Desc_ contains the coded item description.

CSBItem: Compustat AFR Items

This table contains information for Compustat AFR items.

Update Cycle: Updated only when new items are released from the vendor

Adjusted: N/A

Indexes	Index Fields
pkey_csbitem (Clustered)	Mnemonic
csbitem_Name	Name
csbitem_Number	Number
csbitem_Synonym	Synonym

Field	Type	Nullable	Description
MNEMONIC	varchar(32)	N	Mnemonic corresponds to the standard naming convention of Compustat data items.
SYNONYM	varchar(5)	Y	Synonym corresponds to the standard naming convention of Compustat data items.
NAME	varchar(32)	Y	Name is the index corporation action name.
NUMBER	smallint	Y	Number is used to cross-reference all the supporting CSB* tables where Item occurs.
DATATYPE	smallint	Y	DataType can contain one of the following values: – 0 = Double – 1 = int – 3 = String – 5 = Date
ADJUST	smallint	Y	Adjust can contain one of the following values: – 0 = No adjustment – 1 = Add adjustment factor – 2 = Increasing share count on split & decreasing on reverse split – 3 = Decreasing on split & increasing on reverse split

CSBPrD: Compustat AFR Period Dates

This table contains information for Compustat AFR period dates.

Update Cycle: Monthly (vendor releases 1st week of the month)

Adjusted: Yes

Indexes	Index Fields
pkey_csbprd (Clustered)	Code, EndDate
csbprd_cyr	Code, CYr, CQtr
csbprd_fyr	Code, FYr, FQtr

Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ENDDATE	smalldatetime	N	EndDate is the end of period date.
CYR	smallint	Y	CYr is an integer in YYYY format that represents the calendar year.
CQTR	smallint	Y	CQtr is an integer ranging from 1 through 4 representing the calendar quarter.
FYR	smallint	Y	FYr is an integer in YYYY format and represents the fiscal year.

Field	Type	Nullable	Description
FQTR	smallint	Y	FQtr is an integer ranging from 1 through 4 representing the fiscal quarter.
FYE	smallint	Y	Fye is an integer from 1 through 12 representing the month end of the fiscal year.
PREDATE	smalldatetime	Y	PreDate is the preliminary report date.
FINDATE	smalldatetime	Y	FinDate is the final report date.

24 Compustat Xpressfeed Preliminary Data

CSPDesc: Compustat Preliminary Data Coded Item Descriptions

This table contains information for Compustat preliminary data coded item descriptions.

Update Cycle: N/A

Adjusted: N/A

Indexes		Index Fields	
pkey_cspdesc (Clustered)		Item, Value_	
Field	Type	Nullable	Description
ITEM	smallint	N	Item cross references CSPIItem where Item = CSPIItem.Desc_.
VALUE_	varchar(10)	N	Value_ cross references CSP*DATA on value_ = CSP*DATA.Value_and CSPIItem.Desc_ = CSP*DATA.item.
DESC_	varchar(160)	Y	Desc_ contains the coded item description.

CSPIItem: Compustat Preliminary Data Item Descriptions

This table contains information for Compustat preliminary data item descriptions.

Update Cycle: N/A

Adjusted: N/A

Indexes		Index Fields	
pkey_cspitem (Clustered)		Mnemonic	
cspitem_Name		Name	
cspitem_Number		Number	
cspitem_Synonym		Synonym	
Field	Type	Nullable	Description
MNEMONIC	varchar(32)	N	Mnemonic corresponds to the standard naming convention of Compustat data items.
SYNONYM	varchar(10)	Y	Synonym corresponds to the standard naming convention of Compustat data items.
NAME	varchar(40)	Y	Name is the index corporation action name.
NUMBER	smallint	Y	Number is used to cross reference all the supporting CSB* tables where Item occurs.
DATATYPE	smallint	Y	DataType can contain one of the following values: – 1 = Integer – 2 = Double – 3 = Date – 4 = String
DESC_	smallint	Y	Desc_ contains the coded item description.
FREQ	smallint	Y	Freq is the item frequency and breaks down as follows: – 0 = NA – 1 = Annual Item

Field	Type	Nullable	Description
			– 2 = Quarterly Item
BASIS	smallint	Y	
ADJUST	smallint	Y	Adjust can contain one of the following values: – 0 = No adjustment – 1 = Add adjustment factor – 2 = Increasing share count on split and decreasing on reverse split – 3 = Decreasing on split and increasing on reverse split – 4 = Increasing share count on split and decreasing on reverse split, restated – 5 = Decreasing on split and increasing on reverse split, restated – 6 = Increasing share count on split and decreasing on reverse split, pay date – 7 = Decreasing on split and increasing on reverse split, pay date

CSPNData: Compustat Preliminary Numeric Data

This table contains information for Compustat preliminary numeric data.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_cspndata (Clustered)	GvKey, Item, Prelim, Date_

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary link across all CSP* tables.
ITEM	smallint	N	Item cross references CSPIItem where Item = CSPIItem.number.
PRELIM	tinyint	N	Prelim is a flag that specifies if the value is preliminary, where 1 = Preliminary.
DATE_	smalldatetime	N	Date_ cross references with CSBPrD where Code = CSBPrD.Code and Date_ = CSBPrD.EndDate. Use CSBPrD to determine the fiscal year of the period end date.
FLAG	tinyint	Y	Flag is the data availability flag. Refer to the Datacode section on page 165 for the values that Flag can contain.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSPPrD: Compustat Preliminary Periods Data

This table contains information for Compustat preliminary periods data.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_cspprd (Clustered)	GvKey, Freq, EndDate
cspprd_cyr	GvKey, Freq, CYr, CQtr
cspprd_fyr	GvKey, Freq, FYr, FQtr

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary link across all CSP* tables.
FREQ	smallint	N	Freq represents the periodicity and can be either 1 for Annual or 2 for Quarterly.
ENDDATE	smalldatetime	N	EndDate is the end of period date.
CYR	smallint	Y	CYr is an integer in YYYY format that represents the calendar year.
CQTR	smallint	Y	CQtr is an integer ranging from 1 through 4 representing the calendar quarter.

Field	Type	Nullable	Description
FYR	smallint	Y	FYr is an integer in YYYY format that represents the fiscal year.
FQTR	smallint	Y	FQtr is an integer ranging from 1 through 4 representing the fiscal quarter.
FYE	smallint	Y	Fye is an integer from 1 through 12 representing the month end of the fiscal year.
PREDATE	smalldatetime	Y	PreDate is the preliminary report date.
FINDATE	smalldatetime	Y	FinDate is the final report date.

CSPSData: Compustat Preliminary String Data

This table contains information for Compustat preliminary string data.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_cspdata (Clustered)	GvKey, Item, Prelim, Date_

Field	Type	Nullable	Description
GVKEY	int	N	GvKey is the primary link across all CSP* tables.
ITEM	smallint	N	Item cross references CSPIItem where Item = CSPIItem.number.
PRELIM	tinyint	N	Prelim is a flag that specifies if the value is preliminary, where 1 = Preliminary.
DATE_	smalldatetime	N	Date_ cross references with CSBPrD where Code = CSBPrD.Code and Date_ = CSBPrD.EndDate. Use CSBPrD to determine the fiscal year of the period end date.
FLAG	tinyint	Y	Flag is the data availability flag. Refer to the Datacode section on page 165 for the values that Flag can contain.
VALUE_	varchar(20)	Y	Value_ is the raw value provided by Compustat.

25 Compustat FTP Basic Data

NOTE

This data was discontinued by S&P in 2007; it has been replaced by Xpressfeed. If you subscribe to Compustat Daily, consult [CSDlyFnd](#) first for the most current data. It is possible that CSDlyFnd contains the last data point of the historical database or the most recently released quarterly/annual/monthly data. Consult Compustat documentation for a list of available data items.

CSDacPDE: Compustat U.S. Industrial Annual (with data codes)

This table contains Compustat U.S. industrial annual information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes		Index Fields	
pkey_csdacpde (Clustered)		Code, Item, Date_	
Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross-references with CSItem where Item = CSItem.Number and CSItem.Group_ = 3.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

CSCdnPDE: Compustat Canadian Price Dividends and Earnings

This table contains information for Compustat Canadian price dividends and earnings.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes		Index Fields	
pkey_cscdnpde (Clustered)		Item, Code, Date_	
Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross-references with CSItem where Item = CSItem.Number and CSItem.Group_ = 4.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

For items on a fiscal basis, cross-reference Date_ with [CSFYE](#) where Code = CSFYE.Code and Date_ = CSFYE.Date_ and CSFYE.Type_ = 2. Refer to Chapter 8 of the Compustat Technical Reference Guide for a listing of available data items.

CSDescr: Compustat Business Descriptions

This table contains information for Compustat business descriptions.

Update Cycle: N/A

Adjusted: N/A

Indexes	Index Fields
pkey_csdscr (Clustered)	Code, Number

Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
NUMBER	smallint	N	Number is the sequential number of the Desc_ fields.
DESC_	varchar(80)	Y	Desc_ is the item description.

CSIndPDE: Compustat U.S. Industrial Price Dividends and Earnings

This table contains information for Compustat U.S. industrial price dividends and earnings.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_csindpde (Clustered)	Item, Code, Date_

Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross-references with CSItem where Item = CSItem.Number and CSItem.Group_ = 4.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

NOTE

For items on a fiscal basis, cross-reference Date_ with [CSFYE](#) where Code = CSFYE.Code and Date_ = CSFYE.Date_ and CSFYE.Type_ = 2. Refer to Chapter 8 of the Compustat Technical Reference Guide for a listing of available data items.

CSSgCmp: Compustat Segment Company

This table contains Compustat segments company information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgcmp (Clustered)	Gvkey
cssgcmp_Cusip	Cusip
cssgcmp_Tic	Tic

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
DNUM	int	Y	Dnum is the Standard Industry Classification code (Primary).
CIC	varchar(6)	Y	Cic is the CUSIP issuer code.
CIN	varchar(2)	Y	Cin is the CUSIP issue number.
CCD	varchar(1)	Y	Ccd is the CUSIP check digit.
CUSIP	varchar(8)	Y	Cusip is a unique identifier for each company on Compustat.

Field	Type	Nullable	Description
CONM	varchar(50)	Y	Conm is the company name.
TIC	varchar(8)	Y	Tic is the trading symbol.
INCORP	varchar(3)	Y	Incorp is the Incorporation ISO country code.
NAICS	int	Y	Naics is a six-digit coding system for classifying establishments on a production/process-oriented basis.
GIC	int	Y	Gic is the GIC (Guaranteed Investment Certificate).

NOTE

Data definitions and data values can be found in Chapter 5 of the Compustat User Guide.

CSSgCst: Compustat Segment Customer

This table contains Compustat segment customer information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgcst (Clustered)	Gvkey, Recnum
cssgcst_Date_	Gvkey, Date_, Cid

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
RECNUM	smallint	N	Recnum is the record number.
DATE_	smalldatetime	Y	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
CID	smallint	Y	Cid is the customer identifier.
CTYPE	varchar(8)	Y	Ctype is the customer type.
CNAME	varchar(50)	Y	Cname is the customer name.
CSALE	float	Y	Csale is the customer revenues.
CGEOCD	varchar(8)	Y	Cgeocd is the geographic area code.
CGEOAR	varchar(8)	Y	Cgeoar is the geographic area type.
CSTYPE	smallint	Y	Cstyp is the segment type and acts as a segment link. – 0 = No value – 1 = Business segment – 2 = Geographic segment – 3 = Operating segment – 4 = State segment
CSID	smallint	Y	Csid is the segment identifier, and acts as a segment link.

CSSgCur: Compustat Segment Currency Rate

This table contains Compustat segment currency rate information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgcur (Clustered)	Gvkey, Date_

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
YEAR_	smallint	Y	Year_ is the data year.
FYR	smallint	Y	Fyr is the data fiscal year end month.
SRCCUR	varchar(3)	Y	Srccur is the source currency code.
CYR	smallint	Y	Cyr is the data calendar year.
XRATE	float	Y	Xrate is the period end exchange rate.
XRATE12	float	Y	Xrate12 is the 12-month moving exchange rate.
CURCD	varchar(3)	Y	Curcd is the ISO Currency Code.

CSSgDtl: Compustat Segment Detail

This table contains Compustat segment detail information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgdtl (Clustered)	Gvkey, Recnum
cssgdtl_Date_	Gvkey, Date_, Stype, Sid

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
RECNUM	smallint	N	Recnum is the record number.
DATE_	smalldatetime	Y	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
STYPE	smallint	Y	Stype is the segment type. – 1 = Business segment – 2 = Geographic segment – 3 = Operating segment – 4 = State segment
SID	smallint	Y	Sid is the segment identifier.
SNAME	varchar(253)	Y	Sname is the segment name.
SOPTP1	varchar(8)	Y	Soptp1 is the operating segment type 1.
SOPTP2	varchar(8)	Y	Soptp2 is the operating segment type 2.
SGEOTP	varchar(8)	Y	Sgeotp is the geographic segment type.

CSSgGeo: Compustat Segment Geographic Area Codes

This table contains information for Compustat segment geographic area codes.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssggeo (Clustered)	Gvkey, Recnum
cssggeo_Date_	Gvkey, Date_, Stype, Sid, Sgeocd

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
RECNUM	smallint	N	Recnum is the record number.
DATE_	smalldatetime	Y	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
STYPE	smallint	Y	Stype is the segment type.
SID	smallint	Y	Sid is the segment identifier.
SGEOCD	varchar(8)	Y	Sgeocd is the geographic area code.
SGEOTP	varchar(8)	Y	Sgeotp is the geographic segment type.

CSSgltm: Compustat Segment Item Value

This table contains Compustat segment item value information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgltm (Clustered)	Gvkey, Recnum
cssgltm_Date_	Gvkey, Date_, Stype, Sid, Datadate

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
RECNUM	smallint	N	Recnum is the record number.
DATE_	smalldatetime	Y	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
STYPE	smallint	Y	Stype is the segment type.
SID	smallint	Y	Sid is the segment identifier.
YEAR_	smallint	Y	Year_ is the fiscal year of the data date.
FYR	smallint	Y	Fyr is the data fiscal year end month.
DATADATE	smalldatetime	Y	Datadate is the end date of the quarter for which the data was reported.
CYR	smallint	Y	Cyr is the data calendar year.
SALE	float	Y	Sale is the net sales.
OIBD	float	Y	Oibd is the operating income before depreciation.
DP	float	Y	Dp is the depreciation and amortization.
OIAD	float	Y	Oiad is the operating income after depreciation.
CAPX	float	Y	Capx is the capital expenditures.
AT_	float	Y	At_ is the total assets.
EQEARN	float	Y	Eqearn is the equity in earnings.
INVEQ	float	Y	Inveq is the investments at equity.
EMP	float	Y	Emp is the employees.
RD	float	Y	Rd is the research and developments.
OBKLG	float	Y	Obklg is the order backlog.
EXPORT	float	Y	Export is the export sales.
INTSEG	float	Y	Intseg is the intersegment eliminations.
PI	float	Y	Pi is the pretax income.
IB	float	Y	Ib is the income before extraordinary items.

Field	Type	Nullable	Description
NI	float	Y	Ni is the net income (loss).
OPS	float	Y	Ops is the operating profit.
SALEF	smallint	Y	Salef is the sales footnote.
OPINCF	smallint	Y	Opincf is the operating profit footnote.
CAPXF	smallint	Y	Capxf is the capital expenditures footnote.
EQEARNF	smallint	Y	Egearnf is the equity in earnings footnote.
EMPF	smallint	Y	Empf is the employees footnote.
RDF	smallint	Y	Rdf is the research and development footnote.

CSSgNAI: Compustat Segment NAICS

This table contains Compustat segment NAICS information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgnai (Clustered)	Gvkey, Recnum
cssgnai_Date_	Gvkey, Date_, Stype, Sid, Rank

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
RECNUM	smallint	N	Recnum is the record number.
DATE_	smalldatetime	Y	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
STYPE	smallint	Y	Stype is the segment type.
SID	smallint	Y	Sid is the segment identifier.
RANK	smallint	Y	Rank is the ranking.
SNAICS	int	Y	Snaics is the segment NAICS code.
SSIC	smallint	Y	Ssic is the segment SIC code.

CSSgPrd: Compustat Segment Products

This table contains information for Compustat segment products.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgprd (Clustered)	Gvkey, Recnum
cssgprd_Date_	Gvkey, Date_, Pdid

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
RECNUM	smallint	N	Recnum is the record number.
DATE_	smalldatetime	Y	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
PDID	smallint	Y	Pdid the product identifier.

Field	Type	Nullable	Description
PNAME	varchar(50)	Y	Pname is the product name.
PNAICS	int	Y	Pnaics is the product NAICS.
PSALE	float	Y	Psale is the external revenues.
PSTYPE	smallint	Y	Pstype is the segment type and serves as a segment link.
PSID	smallint	Y	Psid is the segment identifier and serves as a segment link.

CSSgSrc: Compustat Segment Source

This table contains Compustat segment source information.

Update Cycle: Weekly (vendor releases files Friday; updates go out the following Monday evening)

Adjusted: Yes

Indexes	Index Fields
pkey_cssgsrc (Clustered)	Gvkey, Date_

Field	Type	Nullable	Description
GVKEY	int	N	Gvkey is a unique company key and is the primary link for all CS* tables.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
SRCYR	smallint	Y	Srcyr is the source year.
SRCFYR	smallint	Y	Srcfyr is the source fiscal year end month.
SRCCYR	smallint	Y	Srccyr is the calendar year.
SSRCE	smallint	Y	Ssrce is the source document code.
SUCODE	smallint	Y	Sucode is the source update code.
HNAICS	int	Y	Hnaics is the primary historical NAICS.
CURCD	varchar(3)	Y	Curcd is the ISO currency code.
SRCCUR	varchar(3)	Y	Srccur is the source ISO currency code.

26 Compustat FTP Research (Legacy)

CSResPDE: Compustat Research Price Dividends and Earnings

This table contains information for Compustat research price dividends and earnings.

Update Cycle: Monthly (vendor releases files third Friday of the month; updates go out the following Monday evening)

Adjusted: Yes

Indexes		Index Fields	
pkey_csrespde (Clustered)		Item, Code, Date_	
Field	Type	Nullable	Description
CODE	int	N	Code is the primary link across all CS* tables.
ITEM	smallint	N	Item cross-references with CSItem where Item = CSItem.Number and CSItem.Group_ = 3.
DATE_	smalldatetime	N	Date_ represents the period end date or calendar date. Refer to CSItem.Basis to determine if the item is on a calendar basis or fiscal basis.
VALUE_	float	Y	Value_ is the raw value provided by Compustat.

NOTE

For items on a fiscal basis, cross-reference Date_ with [CSFYE](#) where Code = CSFYE.Code and Date_ = CSFYE.Date_ and CSFYE.Type_ = 2. Refer to Chapter 8 from the Compustat Technical Reference Guide for a listing of available data items.

Copyright © 2024 London Stock Exchange Group plc and its group of companies (LSEG) and/or its affiliates. All rights reserved. The LSEG content received through this service is the intellectual property of LSEG or its third party suppliers. Republication or redistribution of content provided by LSEG is expressly prohibited without the prior written consent of LSEG, except where permitted by the terms of the relevant LSEG service agreement. Neither LSEG nor its third party suppliers shall be liable for any errors, omissions or delays in content, or for any actions taken in reliance thereon. LSEG and its logo are trademarks of LSEG.

For more information visit us at www.lseg.com



LSEG DATA &
ANALYTICS