

LSEG Quantitative Analytics

Database Schema for LSEG Indices

Version 1.0.3



Contents

1 Introduction.....	3
In This Document.....	3
Intended Readership.....	3
Table Name Conventions	3
Pervasive and Oracle.....	3
Zero Values and Nulls.....	4
Service and Support	4
Feedback	5
Your Personal Information	5
2. LSEG Indices Data Tables	6
IdxTRChg: Index Change History	6
IdxTRCode: Numeric Codes	7
IdxTRConst: Index Compositions and Constituents	7
IdxTRDesc: Character Code Descriptions	7
IdxTRFxFRate: Index Forex Rate	8
IdxTRInfo: Index Static Values.....	8
IdxTRItem: Data Item Descriptions	9
IdxTRSecChg: Security Static Value Change History	9
IdxTRSecCls: Security Classification	10
IdxTRSecInfo: Security Static Value Information	10
IdxTRSecMktID: Security Identifier Information	11
IdxTRSecShares: Security Shares Information.....	11
IdxTRSecSharesOpen: Security SharesOpen Information	12
IdxTRSecVal: Security Value Information	12
IdxTRVal: Index Value and Market Cap Data	12

1 Introduction

In This Document

This document provides schema information about the **LSEG Indices** data tables in Quantitative Analytics.

NOTE

For information about the other Quantitative Analytics tables, refer to the other Database Schema documents posted on the [Quantitative Analytics](#) product page on [MyAccount](#).

The documentation for each table includes these main elements:

- **Vendor Database or License Name** – This element provides the vendor database or license name. Vendor databases generally correspond to vendor licensing options.
- **Table Name: Table Title** – This element provides the table name and title, followed by a description of the table contents.
- **Update Cycle** – This element indicates the frequency of updates from the data vendor. (For specific information about when this update is posted for your use, refer to your update logs. The update log schema description is available in the Database Schema for Quantitative Analytics Core Tables document.)
- **Adjusted** – This element indicates whether the data is stored adjusted, unadjusted, or if adjustment is not applicable (N/A).
- **Indexes, Index Fields** – This element lists the table's index(es) (for example, pkey_CSGCAD) and the index fields. The primary index contains a "pkey_" or "PK_" prefix. Clustered indexes are noted.
- **Field, Type, Nullable, Definition** – This element describes the table's fields, including field names, data types, and whether each field is nullable. The data types in Snowflake have equivalents available. For example, an *int* in SQL Server is a *number* in Snowflake.

Intended Readership

This document is intended for Quantitative Analytics clients licensed to use **LSEG Indices** data through LSEG. Note that the tables described in this document may be covered by several licenses; your access to the data in these tables is dependent on the licenses you have. Readers should have basic knowledge of Microsoft SQL Server 2016.

Table Name Conventions

In Quantitative Analytics, database tables are grouped by name. Generally, the first few letters of the table name refer to the data vendor or licensing group. For example, all tables that begin with **IdxTR*** are **LSEG Indices** data tables.

Pervasive and Oracle

This document is specific to Microsoft SQL Server 2016. If you are accessing the data directly through the Pervasive database, you may encounter slight differences in index names and data types. Please note that references to Pervasive and Actian are synonymous.

If you are accessing the data through Oracle, note that field names that correspond to Oracle reserved words are appended with an underscore. For example, field names "Number", "Synonym", and "UID" become "Number_", "Synonym_", and "UID_" in Oracle.

Zero Values and Nulls

Null values are usually recorded as "NULL". Occasionally, a table may contain a value of "-99999" or "-9999"; in these cases, there is no recorded data for that period. (It is null.) If the table contains a "0" value, the data was reported as having a "0" value.

Service and Support

[MyAccount](#) is the LSEG portal that provides a single access point for timesaving support services, along with billing, user management, and information.

Statement of Service

The [Quantitative Analytics Service Description](#) is available on the [Quantitative Analytics](#) product page at MyAccount.

Subscribe to Support Channels

You are encouraged to [subscribe](#) to the following support channels to keep informed of changes to products and data, and to be notified of any service issues or change. Please see the *Alerts and Notifications* section in the *Quantitative Analytics Service Description* available on the [Quantitative Analytics](#) product page at MyAccount for detailed instructions.

- **Change Notifications**
 - **Product Change Notifications (PCNs)** detail new, enhanced, or changed functionality, which may require your action, in products that you use.
 - **Data Notifications (DNs)** alert you to upcoming changes to real-time and historical data across all asset classes that are relevant to you.
 - **RIC Change Events** inform you of planned changes to RICs. RIC is the market level identifier key unique to LSEG used to identify securities.
- **Service Alerts**

Alert you about planned maintenance and unplanned service issues affecting your products and services, and be notified via SMS or email.

Documentation

You can access product documentation on the [Quantitative Analytics](#) product page at MyAccount.

Get Support

For support using Quantitative Analytics, please use one of the following methods:

Online

Access [Get Support](#) either via the blue [Get Support](#) button at the top right of each page or by selecting *Get Support* located under *Help and Support* on the left navigation pane at MyAccount.

From the *Get Support* page, choose *Get Product and Content Support* and then select the appropriate category from the next page. Complete the request making sure to include the following:

- Under Product, select Quantitative Analytics from the dropdown list.
- In the **How can we help you?** text box, include the following information:
 - Content set name (i.e. Worldscope)
 - Date applicable to a content inquiry
 - Table names and relevant fields
 - Security code (i.e. QA-ID, PermID, Sedol, InfoCode, etc.)
 - Script used to generate the output
 - Any other supporting detail

Telephone

Region	Telephone	Options
AMERS	+01 866 427 8390	Option 1 – Product Support Option 2 – Technical Support
EMEA	+44 203 341 1036	
APAC	+65 6403 7436	

Feedback

We invite your comments, corrections, and suggestions about this document: access the [Feedback](#) option under [Get Support](#) at MyAccount. Your feedback helps us continue to improve our user assistance.

Your Personal Information

LSEG is committed to the responsible handling and protection of personal information. We invite you to review our [Privacy Statement](#), which describes how we collect, use, disclose, transfer, and store personal information when needed to provide our services and for our operational and business purposes.

2. LSEG Indices Data Tables

IdxTRChg: Index Change History

This table contains the history related to changes in static values for a particular index.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRChg (Clustered)		IdxCode, StartDate	

Field	Type	Nullable	Description
IdxCode	int	N	IdxCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the index RIC.
StartDate	datetime	N	StartDate is the date an index changes.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of an index change.
RIC	varchar(64)	Y	RIC is the LSEG identifier for an index.
BrdgSym	varchar(15)	Y	BrdgSym is the bridge identifier.
IdxName	varchar(255)	Y	IdxName is the short name for an index.
CtryRegCode	int	Y	CtryRegCode is the country or region name for an index. IdxTRChg.CtryRegCode cross-references with IdxTRCode .Code where Type_ = 2. The two-letter country code descriptions cross-reference with IdxTRDesc .Code where Type_ = 1.
RetTypeCode	char(1)	Y	RetTypeCode can be the following: – P = Price only – T = Total return IdxTRChg.RetTypeCode cross-references with IdxTRDesc .Code where Type_ = 2.
TRBCSectCode	int	Y	TRBCSectCode is the The Reference Business Classification (TRBC) sector group code.
TRBCSectName	varchar(255)	Y	TRBCSectName is the The Reference Business Classification (TRBC) sector name.
CapCode	char(2)	Y	CapCode is the capitalization group code for the index: – L = Large Cap – M = Mid Cap – S = Small Cap IdxTRChg.CapCode cross-references with IdxTRDesc .Code where Type_ = 4.
LicFlag	int	Y	LicFlag is the license flag that helps identify the entitlement requirements for permissioning LSEG Indices data. IdxTRChg.LicFlag cross-references with IdxTRCode .Code where Type_ = 3.

IdxTRCode: Numeric Codes

This table contains descriptions of numeric codes.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRCode (Clustered)		Type_, Code	
Field	Type	Nullable	Description
Type_	int	N	Type_ is a numeric code for a type of data.
Code	int	N	Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_.
Desc_	varchar(150)	Y	Desc_ is a plain-language description of the element defined by Type_ and Code.

IdxTRConst: Index Compositions and Constituents

This table contains information about index compositions and constituents.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRConst (Clustered)		IdxCode, SecCode, StartDate	
Field	Type	Nullable	Description
IdxCode	int	N	IdxCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the index RIC.
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
StartDate	datetime	N	StartDate is the market date on which the security became part of a particular index.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of a security change.
LicFlag	int	Y	LicFlag is the license flag that helps identify the entitlement requirements for permissioning LSEG Indices data. IdxTRConst.LicFlag cross-references with IdxTRCode.Code where Type_ = 3.

IdxTRDesc: Character Code Descriptions

This table contains descriptions of character codes.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRDesc (Clustered)		Type_, Code	
Field	Type	Nullable	Description
Type_	int	N	Type_ is a numeric code for a type of data.
Code	varchar(20)	N	Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_.
Desc_	varchar(150)	Y	Desc_ is a plain-language description of the element defined by Type_ and Code.

IdxTRFxRate: Index Forex Rate

This table contains information about the foreign exchange rate (security currency rate in index currency).

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRFxRate (Clustered)		CrossRate, CtryRegCode, Date_	
Field	Type	Nullable	Description
CrossRate	int	N	CrossRate is the foreign exchange cross rate based on the Cur and IX_Cur fields from the ICW file. IdxTRFxRate.CrossRate cross-references with IdxTRCode .Code where Type_ = 1.
CtryRegCode	int	N	CtryRegCode is the country or region name for an index only. IdxTRFxRate.CtryRegCode cross-references with IdxTRCode .Code where Type_ = 2. The two-letter country code descriptions cross-reference with IdxTRDesc .Code where Type_ = 1.
Date_	datetime	N	Date_ is the market date for which the data in the file is valid.
FxRate	float	Y	FxRate is the security currency rate in index currency.

IdxTRInfo: Index Static Values

This table contains information about static values for a particular index.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRInfo (Clustered)		IdxCode	
IdxTRInfo_1		CtryRegCode, RetTypeCode	
IdxTRInfo_2		RetTypeCode	
IdxTRInfo_3		RIC	
Field	Type	Nullable	Description
IdxCode	int	N	IdxCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the index RIC.
RIC	varchar(64)	Y	RIC is the LSEG identifier for an index.
BrdgSym	varchar(15)	Y	BrdgSym is the bridge identifier.
IdxName	varchar(255)	Y	IdxName is the short name for an index.
CtryRegCode	int	Y	CtryRegCode is the country or region name for an index. IdxTRInfo.CtryRegCode cross-references with IdxTRCode .Code where Type_ = 2. The two-letter country code descriptions cross-reference with IdxTRDesc .Code where Type_ = 1.
RetTypeCode	char(1)	Y	RetTypeCode can be the following: – P = Price only – T = Total return IdxTRInfo.RetTypeCode cross-references with IdxTRDesc .Code where Type_ = 2.
TRBCSectCode	int	Y	TRBCSectCode is the The Reference Business Classification (TRBC) sector group code.
TRBCSectName	varchar(255)	Y	TRBCSectName is the The Reference Business Classification (TRBC) sector name.
CapCode	char(2)	Y	CapCode is the capitalization group code for the index.

Field	Type	Nullable	Description
			IdxTRInfo.CapCode cross-references with IdxTRDesc .Code where Type_ = 4.
LicFlag	int	Y	LicFlag is the license flag that helps identify the entitlement requirements for permissioning LSEG Indices data. IdxTRInfo.LicFlag cross-references with IdxTRCode .Code where Type_ = 3.

IdxTRItem: Data Item Descriptions

This table contains descriptive information about data items. These data items are coded to an integer that is referenced in the data tables.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRItem (Clustered)		Item	
Field	Type	Nullable	Description
Item	int	N	Item is the integer equivalent for each LSEG Indices mnemonic. This field is cross-referenced from other tables.
Mnemonic	varchar(10)	Y	Mnemonic is the single-word, alphanumeric coded name.
Desc_	varchar(150)	Y	Desc_ is the short description for the mnemonic.
DataType	char(1)	Y	DataType is the data type for the item. For example, percentage, money, text, boolean, numeral, date/time (not the SQL datatype).
TableName	varchar(20)	Y	TableName contains the data table item.

IdxTRSecChg: Security Static Value Change History

This table contains the history related to changes in static values (for example, identifiers) for a security that is part of the LSEG Index group.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRSecChg (Clustered)		SecCode, StartDate	
Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
StartDate	datetime	N	StartDate is the date a security changes.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of a security change.
Ticker	varchar(20)	Y	Ticker is the ticker.
SecName	varchar(80)	Y	SecName is the short name of the security being held.
ExchCode	varchar(15)	Y	ExchCode is the exchange code. IdxTRSecChg.ExchCode cross-references with IdxTRDesc .Code where Type_ = 6.
CtryCode	int	Y	CtryCode is the country of headquarters. IdxTRSecChg.CtryCode cross-references with IdxTRCode .Code where Type_ = 2. The two-letter country code descriptions cross-reference with IdxTRDesc .Code where Type_ = 1.
CapCode	char(2)	Y	CapCode is the capitalization code for the stock of the security.

Field	Type	Nullable	Description
			IdxTRSecChg.CapCode cross-references with IdxTRDesc .Code where Type_ = 4.

IdxTRSecCls: Security Classification

This table contains TRBC classification information for a security that is part of the LSEG Index group.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_IdxTRSecCls (Clustered)	SecCode, StartDate

Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
StartDate	datetime	N	StartDate is the date a security changes.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of a security change.
TRBCSectCode	int	Y	TRBCSectCode is the TRBC sector code for the stock as of last rebalance.
TRBCSectCodeLev1	int	Y	TRBCSectCodeLev1 is the code of Economic Sector (when an index is created as of last rebalance).
TRBCSectCodeLev2	int	Y	TRBCSectCodeLev2 is the code of Business Sector (when an index is created as of last rebalance).
TRBCSectCodeLev3	int	Y	TRBCSectCodeLev3 is the code of Industry Groups (when an index is created as of last rebalance).
TRBCSectCodeLev4	int	Y	TRBCSectCodeLev4 is the code of Industry (when an index is created as of last rebalance).

IdxTRSecInfo: Security Static Value Information

This table describes the static values (for example, identifiers) for a security that is part of the LSEG Index group.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_IdxTRSecInfo (Clustered)	SecCode
IdxTRSecInfo_1	Ticker
IdxTRSecInfo_2	SecName
IdxTRSecInfo_3	CtryCode

Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
Ticker	varchar(20)	Y	Ticker is the ticker.
SecName	varchar(80)	Y	SecName is the short name of the security being held.
ExchCode	varchar(15)	Y	ExchCode is the exchange code. IdxTRSecInfo.ExchCode cross-references with IdxTRDesc .Code where Type_ = 6.
CtryCode	int	Y	CtryCode is the country of headquarters.

Field	Type	Nullable	Description
			IdxTRSecInfo.CtryCode cross-references with IdxTRCode .Code where Type_ = 2. The two-letter country code descriptions cross-reference with IdxTRDesc .Code where Type_ = 1.
CapCode	char(2)	Y	CapCode is the capitalization code for the stock of the security. IdxTRSecInfo.CapCode cross-references with IdxTRDesc .Code where Type_ = 4.

IdxTRSecMktID: Security Identifier Information

This table describes the values of various identifiers for a security that is part of the LSEG Index group.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_IdxTRSecMktID (Clustered)	SecCode, Item, StartDate

Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
Item	int	N	Item is the code representing the respective identifier (RIC, ISIN, and SEDOL). Refer to the item field in the IdxTRItem table for a complete list of codes.
StartDate	datetime	N	StartDate is the date a security changes.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of a security change.
Value_	varchar(64)	Y	Value_ is the value for the respective item.
LicFlag	int	Y	LicFlag is the license flag that helps identify the entitlement requirements for permissioning LSEG Indices data. IdxTRSecMktID.LicFlag cross-references with IdxTRCode .Code where Type_ = 3.

IdxTRSecShares: Security Shares Information

This table contains shares information for securities.

Update Cycle: Daily

Adjusted: No

Indexes	Index Fields
pkey_IdxTRSecShares (Clustered)	SecCode, StartDate

Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
StartDate	datetime	N	StartDate is the date a security changes. The default StartDate is the first date the security is received from the ICW (constituent data) file.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of a security change.
SharesClose	float	Y	SharesClose is the shares held in the index at market close.
FFFactor	float	Y	FFFactor is the free float factor.

IdxTRSecSharesOpen: Security SharesOpen Information

This table contains shares information for securities, as of the start of the following day.

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_IdxTRSecSharesOpen (Clustered)		SecCode, StartDate	
Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
StartDate	datetime	N	StartDate is the date a security changes. The default StartDate is the first date the security is received from the ICW (constituent data) file.
EndDate	datetime	Y	EndDate is one day prior to the StartDate of a security change.
SharesOpen	float	Y	SharesOpen is the shares held in the index, as of the start of the following day.

IdxTRSecVal: Security Value Information

This table contains information about the value of a security (for example, price).

Update Cycle: Daily

Adjusted: No

Indexes		Index Fields	
pkey_IdxTRSecVal (Clustered)		SecCode, Date_	
Field	Type	Nullable	Description
SecCode	int	N	SecCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the combination of Security RIC, ISIN, SEDOL, and Ticker.
Date_	datetime	N	Date_ is the market date on which the data in the file is valid.
Close_	float	Y	Close_ is the closing price of the security, as of the recent market close.
ISOCurCode	char(3)	Y	ISOCurCode is the currency of the last price. IdxTRSecVal.ISOCurCode cross-references with IdxTRDesc.Code where Type_ = 3.

IdxTRVal: Index Value and Market Cap Data

This table contains the index value and the market cap data for an index.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_IdxTRVal (Clustered)		IdxCode, Date_	
Field	Type	Nullable	Description
IdxCode	int	N	IdxCode is a unique integer code that identifies an index. This code is defined in the Quantitative Data Warehouse (QDW) and is not received from the vendor. This code is generated based on the index RIC.
Date_	datetime	N	Date_ is the market date on which the data in the file is valid.
ISOCurCode	char(3)	Y	ISOCurCode is the country currency.

Field	Type	Nullable	Description
			IdxTRVal.ISOCurCode cross-references with IdxTRDesc . Code where Type_ = 3.
IdxVal	float	Y	IdxVal is the closing index value, as of the recent market close.
MktCap	float	Y	MktCap is the total market cap for the index, as of the recent market close.
Divisor	float	Y	Divisor is the index divisor, as of the recent market close.
NumConst	int	Y	NumConst is the total number of securities held in the index at market close.
LicFlag	int	Y	LicFlag is the license flag that helps identify the entitlement requirements for permissioning LSEG Indices data. IdxTRVal.LicFlag cross-references with IdxTRCode . Code where Type_ = 3.

Copyright © 2024 London Stock Exchange Group plc and its group of companies (LSEG) and/or its affiliates. All rights reserved. The LSEG content received through this service is the intellectual property of LSEG or its third party suppliers. Republication or redistribution of content provided by LSEG is expressly prohibited without the prior written consent of LSEG, except where permitted by the terms of the relevant LSEG service agreement. Neither LSEG nor its third party suppliers shall be liable for any errors, omissions or delays in content, or for any actions taken in reliance thereon. LSEG and its logo are trademarks of LSEG.

For more information visit us at www.lseg.com



LSEG DATA &
ANALYTICS