

LSEG Quantitative Analytics

Database Schema for MSCI

Version 1.0.5



Contents

1 Introduction.....	3
In This Document.....	3
Intended Readership.....	3
Table Name Conventions	3
Pervasive and Oracle.....	3
Zero Values and Nulls.....	3
Legacy Empty Tables	4
Service and Support	4
Feedback	5
Your Personal Information	5
2. MSCI Version 2 Schema	6
Design Notes	6
MSCI V2 Index Level Tables.....	7
MSCI V2 Security Level Tables	18
MSCI V2 Miscellaneous Tables	37
Item/Code Tables.....	37
Fx Rate Tables.....	37
Miscellaneous Tables	37

1 Introduction

In This Document

This document provides schema information about the **MSCI** data tables in Quantitative Analytics.

NOTE

For information about the other Quantitative Analytics tables, refer to the other Database Schema documents posted on the [Quantitative Analytics](#) product page on [MyAccount](#).

The documentation for each table includes these main elements:

- **Vendor Database or License Name** – This element provides the vendor database or license name. Vendor databases generally correspond to vendor licensing options.
- **Table Name: Table Title** – This element provides the table name and title, followed by a description of the table contents.
- **Update Cycle** – This element indicates the frequency of updates from the data vendor. (For specific information about when this update is posted for your use, refer to your update logs. The update log schema description is available in the Database Schema for Quantitative Analytics Core Tables document.)
- **Adjusted** – This element indicates whether the data is stored adjusted, unadjusted, or if adjustment is not applicable (N/A).
- **Indexes, Index Fields** – This element lists the table's index(es) (for example, pkey_CSGCAD) and the index fields. The primary index contains a "pkey_" or "PK_" prefix. Clustered indexes are noted.
- **Field, Type, Nullable, Definition** – This element describes the table's fields, including field names, data types, and whether each field is nullable. The data types in Snowflake have equivalents available. For example, an *int* in SQL Server is a *number* in Snowflake.

Intended Readership

This document is intended for Quantitative Analytics clients licensed to use **MSCI** data through LSEG. Note that the tables described in this document may be covered by several licenses; your access to the data in these tables is dependent on the licenses you have. Readers should have basic knowledge of Microsoft SQL Server 2016.

Table Name Conventions

In Quantitative Analytics, database tables are grouped by name. Generally, the first few letters of the table name refer to the data vendor or licensing group. For example, all tables that begin with **MS2*** are **MSCI Version 2** data tables. All tables beginning with **MS*** are **MSCI legacy** data tables.

Pervasive and Oracle

This document is specific to Microsoft SQL Server 2016. If you are accessing the data directly through the Pervasive database, you may encounter slight differences in index names and data types. Please note that references to Pervasive and Actian are synonymous.

If you are accessing the data through Oracle, note that field names that correspond to Oracle reserved words are appended with an underscore. For example, field names "Number", "Synonym", and "UID" become "Number_", "Synonym_", and "UID_" in Oracle.

Zero Values and Nulls

Null values are usually recorded as "NULL". Occasionally, a table may contain a value of "-99999" or "-9999"; in these cases, there is no recorded data for that period. (It is null.) If the table contains a "0" value, the data was reported as having a "0" value.

Legacy Empty Tables

MSCI data tables beginning with the letters **MSH*** are empty, or are not maintained, and should not be used. These tables are:

- Mshchg
- Mshcons
- Mshfxdly
- Mshfxmth
- Mshidx
- Mshidxdly
- Mshidxmth
- Mshsec
- Mshsecdly

Service and Support

[MyAccount](#) is the LSEG portal that provides a single access point for timesaving support services, along with billing, user management, and information.

Statement of Service

The [Quantitative Analytics Service Description](#) is available on the [Quantitative Analytics](#) product page at MyAccount.

Subscribe to Support Channels

You are encouraged to [subscribe](#) to the following support channels to keep informed of changes to products and data, and to be notified of any service issues or change. Please see the *Alerts and Notifications* section in the *Quantitative Analytics Service Description*, available on the [Quantitative Analytics](#) product page at MyAccount for detailed instructions.

- **Change Notifications**
 - **Product Change Notifications (PCNs)** detail new, enhanced, or changed functionality, which may require your action, in products that you use.
 - **Data Notifications (DNs)** alert you to upcoming changes to real-time and historical data across all asset classes that are relevant to you.
 - **RIC Change Events** inform you of planned changes to RICs. RIC is the market level identifier key unique to LSEG used to identify securities.
- **Service Alerts**

Alert you about planned maintenance and unplanned service issues affecting your products and services, and be notified via SMS or email.

Documentation

You can access product documentation on the [Quantitative Analytics](#) product page at MyAccount.

Get Support

For support using Quantitative Analytics, please use one of the following methods:

Online

Access [Get Support](#) either via the blue **Get Support** button at the top right of each page or by selecting *Get Support* located under *Help and Support* on the left navigation pane at MyAccount.

From the *Get Support* page, choose *Get Product and Content Support* and then select the appropriate category from the next page. Complete the request making sure to include the following:

- Under Product, select Quantitative Analytics from the dropdown list.
- In the **How can we help you?** text box, include the following information:
 - Content set name (i.e. Worldscope)

- Date applicable to a content inquiry
- Table names and relevant fields
- Security code (i.e. QA-ID, PermID, Sedol, InfoCode, etc.)
- Script used to generate the output
- Any other supporting detail

Telephone

Region	Telephone	Options
AMERS	+01 866 427 8390	Option 1 – Product Support Option 2 – Technical Support
EMEA	+44 203 341 1036	
APAC	+65 6403 7436	

Feedback

We invite your comments, corrections, and suggestions about this document: access the [Feedback](#) option under [Get Support](#) at MyAccount. Your feedback helps us continue to improve our user assistance.

Your Personal Information

LSEG is committed to the responsible handling and protection of personal information. We invite you to review our [Privacy Statement](#), which describes how we collect, use, disclose, transfer, and store personal information when needed to provide our services and for our operational and business purposes.

2. MSCI Version 2 Schema

Design Notes

Empty Tables

The MSCI version 2 schema was designed to be flexible, enabling new data items to be included easily if/when they are provided by MSCI.

In this design, the data is organized in tables by index or security and then by data type. For example, daily index data is contained in MSDIDXDLy in the legacy implementation. In the version 2 implementation, this data is contained in multiple tables by data type: MS2IdxDDLy (date data), MS2IdxFDly (float data), MS2IdxIDly (integer data), and MS2IdxSDly (string varchar data).

To maintain the symmetry of this design and enable the addition of future items with limited impact to clients, several tables were created that are not currently populated. We may populate these tables if/when additional data items are provided by MSCI. But, in the current design (as of January 2012), these tables are intentionally empty:

- MS2IdxDDLy
- MS2SecDDLy
- MS2IdxIDly
- MS2SecDivMth
- MS2IdxSDly
- MS2SecIDly
- MS2SecD
- MS2SecSDly
- MS2SecDACE

Table Name Format

The names of the MSCI version 2 data tables reflect the type of data items they contain. The table name format is **MS2[Idx|Sec][Datatype][Frq][ACE]** where:

- **[Idx|Sec]** indicates whether the data is index-level or security-level.
- **[Datatype]** indicates the type of data: I = integer data, S = varchar data, D = date data, F = float data, and SMax = very large varchar data.
- **[Frq]** indicates whether the data is daily or monthly. "Mth" indicates monthly data. Both "Dly" and no [Frq] suffix indicate daily data. The difference is that items in the "*Dly" tables are updated daily (usually pricing related). Items in a table with no [Frq] value change infrequently; we get updates for these every day, but generally the value is the same every day.
- The tables with a "Dly" or "Mth" suffix have a single Date_ field. The tables without either suffix have a StartDate/EndDate pair. Tables with the "Mth" suffix are included for clients with a monthly or daily license. Tables with no suffix or with the "Dly" suffix are only given to clients with a daily license.
- **[ACE]** indicates whether the data is ACE data. If a table name ends with "ACE", it contains ACE data. If not, the table does not contain ACE data.

MSCI V2 Index Level Tables

Diagrams

Index Info Tables

MS2IdxInfo

MSCICode	INTEGER
Name_	VARCHAR(40)
ISOtryCode	CHAR(2)
RegCode	CHAR(4)
RIC	VARCHAR(20)
RTTicker	VARCHAR(20)
IdxFam	TINYINT
EndDate	INTEGER
ModDate	INTEGER
LicFlag	INTEGER

MS2IdxInfoChg

MSCICode	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Name_	VARCHAR(40)
ISOtryCode	CHAR(2)
RegCode	CHAR(4)
RIC	VARCHAR(20)
RTTicker	VARCHAR(20)
IdxFam	TINYINT
LicFlag	INTEGER

Start/End Date Index Tables

MS2IdxD

MSCICode	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxF

MSCICode	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxI

MSCICode	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxS

MSCICode	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	VARCHAR(75)
NextValue	VARCHAR(75)
LicFlag	INTEGER

Daily Index Tables

MS2IdxConstDly

MSCICode	int
SecID	int
StartDate	int
EndDate	int
TotIncFactor	float
NextTotIncFactor	float
LicFlag	int

MS2IdxDDly

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxFDly

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxIDly

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxSDly

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	VARCHAR(75)
NextValue	VARCHAR(75)
LicFlag	INTEGER

Monthly Index Tables

MS2IdxConstMth

MSCICode	int
SecID	int
StartDate	int
EndDate	int
TotIncFactor	float
NextTotIncFactor	float
LicFlag	int

MS2IdxDMth

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxFMth

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	FLOAT
NextValue	FLOAT
LicFlag	INTEGER

MS2IdxIMth

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2IdxSMth

MSCICode	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	VARCHAR(75)
NextValue	VARCHAR(75)
LicFlag	INTEGER

MS2IdxConstDly: Daily MSCI Index Constituents

This table contains daily MSCI index constituents data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes			Index Fields
pkey_MS2IdxConstDly (Clustered)			MSCICode, SecID, StartDate

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
SecID	int	N	SecID is the security ID.
StartDate	datetime	N	If you are licensed for MSCI Deep History content: - StartDate is the date the security became part of the index. If you are not licensed for MSCI Deep History content: - If StartDate is more recent than 13 months ago from today (the beginning of the daily data rolling window), StartDate is the date the security became part of the index. In this scenario, the security joined the index within the current 13-month rolling window. - A StartDate that is older than 13 months ago from today indicates the security joined the index prior to the beginning of the 13-month rolling window. In this scenario, the value of StartDate does not represent the actual date the security joined the index. To receive the actual date the security joined the index, you must be licensed for MSCI Deep History content.
EndDate	datetime	Y	When applicable, EndDate is the date the security was removed from the index.
TotIncFactor	float	Y	TotIncFactor is the total inclusion factor. This is a derived field created by LSEG Quantitative Analytics.
NextTotIncFactor	float	Y	NextTotIncFactor is the next day total inclusion factor.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxConstMth: Monthly MSCI Index Constituents

This table contains monthly MSCI index constituents data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Update Cycle: Monthly

Adjusted: N/A

Indexes			Index Fields
pkey_MS2IdxConstMth (Clustered)			MSCICode, SecID, StartDate

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
SecID	int	N	SecID is the security ID.

Field	Type	Nullable	Description
StartDate	datetime	N	This date reflects the last calendar day of the month, and not the last business day. If you are licensed for MSCI Deep History content: – StartDate is the date the security became part of the index. If you are not licensed for MSCI Deep History content: – If StartDate is more recent than 7 years ago from today (the beginning of the monthly data rolling window), StartDate is the date the security became part of the index. In this scenario, the security joined the index within the current 7-year rolling window. – A StartDate that is older than 7 years ago from today indicates the security joined the index prior to the beginning of the 7-year rolling window. In this scenario, the value of StartDate does not represent the actual date the security joined the index. To receive the actual date the security joined the index, you must be licensed for MSCI Deep History content.
EndDate	datetime	Y	When applicable, EndDate is the date the security was removed from the index. This date reflects the last calendar day of the month, and not the last business day.
TotIncFactor	float	Y	TotIncFactor is the total inclusion factor.
NextTotIncFactor	float	Y	NextTotIncFactor is the next day total inclusion factor.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxD: MSCI Index Date Data

This table contains daily MSCI index date data that changes infrequently.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2IdxD (Clustered)	StartDate, MSCICode, Item

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxDDly: Daily MSCI Index Date Data**NOTE**

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI index date data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxDDly (Clustered)		Date_, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxDMth: Monthly MSCI Index Date Data

This table contains monthly MSCI index date data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Update Cycle: Monthly

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxDMth (Clustered)		Date_, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxF: MSCI Index Float Data

This table contains daily MSCI index float data that changes infrequently.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxF (Clustered)		StartDate, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxFDly: Daily MSCI Index Float Data

This table contains daily MSCI index float data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxFDly (Clustered)		Date_, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxFMth: Monthly MSCI Index Float Data

This table contains monthly MSCI index float data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Update Cycle: Monthly

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxFMth (Clustered)		Date_, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxI: MSCI Index Integer Data

This table contains daily MSCI index integer data that changes infrequently.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxI (Clustered)		StartDate, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxIDly: Daily MSCI Index Integer Data**NOTE**

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI index integer data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxIDly (Clustered)		Date_, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxIMth: Monthly MSCI Index Integer Data

This table contains monthly MSCI index integer data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Update Cycle: Monthly

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxIMth (Clustered)		Date_, MSCICode, Item	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxInfo: Current MSCI Index Information

This table contains MSCI index information.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxInfo (Clustered)		MSCICode	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables.
Name_	varchar(40)	Y	Name_ is the index name.
ISOtryCode	char(2)	Y	ISOtryCode is the ISO country code. It is a two-digit alphabetic code for country classification. MS2IdxInfo.ISOtryCode joins with MS2Desc .Code where Type_ = 1.
RegCode	char(4)	Y	RegCode is the region code for regional indexes. MS2IdxInfo.RegCode joins with MS2Desc .Code where Type_ = 3.
RIC	varchar(20)	Y	RIC is the LSEG Identification Code.
RTTicker	varchar(20)	Y	RTTicker is the real time ticker.
IdxFam	tinyint	Y	IdxFam is the index family. This field cross-references with MS2Code .Code where Type_ = 12.
EndDate	datetime	Y	EndDate is the date the period ends. This is the date on which an index becomes inactive.
ModDate	datetime	Y	ModDate is the date the index information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxInfoChg: Historical MSCI Index Information

This table contains a timeseries of current and historical MSCI index information.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2IdxInfoChg (Clustered)		MSCICode, StartDate	

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends. This is the date on which an index becomes inactive.
Name_	varchar(40)	Y	Name_ is the index name.
ISOtryCode	varchar(2)	Y	ISOtryCode is the ISO country code. It is a two-digit alphabetic code for country classification. MS2IdxInfoChg.ISOtryCode joins with MS2Desc .Code where Type_ = 1.
RegCode	varchar(4)	Y	RegCode is the region code for regional indexes. MS2IdxInfoChg.RegCode joins with MS2Desc .Code where Type_ = 3.

Field	Type	Nullable	Description
RIC	varchar(20)	Y	RIC is the LSEG Identification Code.
RTTicker	varchar(20)	Y	RTTicker is the real time ticker.
IdxFam	tinyint	Y	IdxFam is the index family. This field cross-references with MS2Code .Code where Type_ = 12.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxS: MSCI Index Varchar Data

This table contains daily MSCI index varchar data that changes infrequently.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2IdxS (Clustered)	StartDate, MSCICode, Item

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	varchar(75)	Y	Value_ is the alphanumeric information associated with given constraints.
NextValue	varchar(75)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxSDly: Daily MSCI Index Varchar Data

NOTE

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI index varchar data.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2IdxSDly (Clustered)	Date_, MSCICode, Item

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	varchar(75)	Y	Value_ is the alphanumeric information associated with given constraints.

Field	Type	Nullable	Description
NextValue	varchar(75)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2IdxSMth: Monthly MSCI Index Varchar Data

This table contains monthly MSCI index varchar data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Update Cycle: Monthly

Adjusted: N/A

Indexes	Index Fields
pkey_MS2IdxSMth (Clustered)	Date_, MSCICode, Item

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. It is the primary link across all MS2Idx* tables. MSCICode is defined in MS2IdxInfo .
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	varchar(75)	Y	Value_ is the alphanumeric information associated with given constraints.
NextValue	varchar(75)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MSCI V2 Security Level Tables

Diagrams

Security Info Tables

MS2SecInfo

SecID	INTEGER
TsCode	INTEGER
IssCode	INTEGER
SecCode	INTEGER
Name_	VARCHAR(40)
ISOtryCode	CHAR(2)
NextISOtryCode	CHAR(2)
MIC	CHAR(4)
NextMIC	CHAR(4)
BloomTkr	VARCHAR(25)
NextBloomTkr	VARCHAR(25)
ShareClassCode	TINYINT
ShareTypeCode	TINYINT
AltListingCode	TINYINT
BarralD	CHAR(8)
EndDate	INTEGER
ModDate	INTEGER
LicFlag	INTEGER

MS2SecInfoChg

SecID	INTEGER
StartDate	INTEGER
EndDate	INTEGER
TsCode	INTEGER
IssCode	INTEGER
SecCode	INTEGER
Name_	VARCHAR(40)
ISOtryCode	CHAR(2)
MIC	CHAR(4)
BloomTkr	VARCHAR(25)
ShareClassCode	TINYINT
ShareTypeCode	TINYINT
AltListingCode	TINYINT
BarralD	CHAR(8)
LicFlag	INTEGER

MS2SecCu

SecID	int
StartDate	int
EndDate	int
CUSIP	char(8)
LicFlag	int

MS2SecSed

SecID	int
StartDate	int
EndDate	int
SEDOL	char(6)
LicFlag	int

MS2SecISIN

SecID	int
StartDate	int
EndDate	int
ISIN	char(12)
LicFlag	int

Start/End Date Security Tables

MS2SecF

SecID	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	FLOAT
NextValue	FLOAT
LicFlag	INTEGER

MS2SecI

SecID	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2SecS

SecID	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	VARCHAR(75)
NextValue	VARCHAR(75)
LicFlag	INTEGER

MS2SecD

SecID	INTEGER
Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

Daily Security Tables

MS2SecAdvDiv

SecID	INTEGER
IdxFam	TINYINT
Date_	INTEGER
DivCode	INTEGER
DivDesc	TINYINT
XDDate	INTEGER
ReinvDate	INTEGER
Div	FLOAT
AdjGRSDiv	FLOAT
AdjNETDiv	FLOAT
ISOCurrCode	CHAR(3)
DivSubUnit	FLOAT
LicFlag	INTEGER

MS2SecDDly

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2SecFDly

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	FLOAT
NextValue	FLOAT
LicFlag	INTEGER

MS2SecDivDly

SecID	INTEGER
IdxFam	TINYINT
Date_	INTEGER
DivCode	INTEGER
DivDesc	TINYINT
XDDate	INTEGER
CorrectionFlag	TINYINT
ReinvDate	INTEGER
Div	FLOAT
AdjGRSDiv	FLOAT
AdjNETDiv	FLOAT
ISOCurrCode	CHAR(3)
DivSubUnit	FLOAT
DivAdjFactor	FLOAT
DTRNumShares	FLOAT
LicFlag	INTEGER

MS2SecIDly

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2SecSDly

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	VARCHAR(75)
NextValue	VARCHAR(75)
LicFlag	INTEGER

Ms2SecSMaxDly

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
LicFlag	INTEGER
Value_	VARCHAR(0)

Monthly Security Tables

MS2SecDMth

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2SecDivMth

SecID	INTEGER
IdxFam	TINYINT
Date_	INTEGER
DivCode	INTEGER
DivDesc	TINYINT
XDDate	INTEGER
CorrectionFlag	TINYINT
ReinvDate	INTEGER
Div	FLOAT
AdjGRSDiv	FLOAT
AdjNETDiv	FLOAT
ISOCurrCode	CHAR(3)
DivSubUnit	FLOAT
DivAdjFactor	FLOAT
DTRNumShares	FLOAT
LicFlag	INTEGER

MS2SecFMth

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	FLOAT
NextValue	FLOAT
LicFlag	INTEGER

MS2SecIMth

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	INTEGER
NextValue	INTEGER
LicFlag	INTEGER

MS2SecSMth

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
Value_	VARCHAR(75)
NextValue	VARCHAR(75)
LicFlag	INTEGER

Ms2SecSMaxMth

SecID	INTEGER
Item	INTEGER
Date_	INTEGER
LicFlag	INTEGER
Value_	VARCHAR(0)

Advanced Corporate Event (ACE) Security Tables

MS2SecDACE

SecID	INTEGER
Item	INTEGER
EventId	INTEGER
Seq	TINYINT
Date_	INTEGER
StatusCode	TINYINT
EventCode	TINYINT
Value_	INTEGER
NextValue	INTEGER
AddDate	INTEGER
ModDate	INTEGER
LicFlag	INTEGER

MS2SecFACE

SecID	INTEGER
Item	INTEGER
EventId	INTEGER
Seq	TINYINT
Date_	INTEGER
StatusCode	TINYINT
EventCode	TINYINT
Value_	FLOAT
NextValue	FLOAT
AddDate	INTEGER
ModDate	INTEGER
LicFlag	INTEGER

MS2SecIACE

SecID	INTEGER
Item	INTEGER
EventId	INTEGER
Seq	TINYINT
Date_	INTEGER
StatusCode	TINYINT
EventCode	TINYINT
Value_	INTEGER
NextValue	INTEGER
AddDate	INTEGER
ModDate	INTEGER
LicFlag	INTEGER

MS2SecSACE

SecID	INTEGER
Item	INTEGER
EventId	INTEGER
Seq	TINYINT
Date_	INTEGER
StatusCode	TINYINT
EventCode	TINYINT
Value_	VARCHAR(250)
NextValue	VARCHAR(250)
AddDate	INTEGER
ModDate	INTEGER
LicFlag	INTEGER

MS2SecSMaxACE

SecID	int
Item	int
EventId	int
Seq	smallint
Date_	int
StatusCode	tinyint
EventCode	tinyint
AddDate	int
ModDate	int
LicFlag	int
Value_	varchar(0)

MS2SecAdvDiv: MSCI Advance Dividends

This table contains MSCI advance dividends data.

NOTE

This table is populated going forward from 2011.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecAdvDiv (Clustered)	SecID, IdxFam, Date_, DivCode

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
IdxFam	tinyint	N	IdxFam is the index family. This field cross-references with MS2Code .Code where Type_ = 12.
Date_	datetime	N	Date_ is the date on which the data was calculated.
DivCode	int	N	DivCode is the MSCI dividend code, a unique identifier allocated by MSCI to a dividend event.
DivDesc	tinyint	Y	DivDesc is the MSCI dividend description: – 0 = Annual

Field	Type	Nullable	Description
			– 1 = Final – 2 = Interim – 3 = Quarterly – 4 = Extra – 5 = Monthly – 6 = Regular – 7 = Commemorative This field cross-references with MS2Code.Code where Type_ = 5.
XDDate	datetime	Y	XDDate is the dividend ex-date.
ReinvDate	datetime	Y	ReinvDate is the date as of which the dividend is reinvested in the index.
Div	float	Y	Div is the declared dividend amount.
AdjGRSDiv	float	Y	AdjGRSDiv is the gross dividend amount of withholding taxes to be reinvested in MSCI Daily Gross Total Return Indices.
AdjNETDiv	float	Y	AdjNETDiv is the net dividend amount of withholding taxes to be reinvested in MSCI Daily Net Total Return Indices for MSCI international indices.
ISOCurrCode	char(3)	Y	ISOCurrCode is the dividend ISO currency symbol. This field cross-references with MS2Desc .Code where Type_ = 2.
DivSubUnit	float	Y	DivSubUnit is the dividend sub-unit. It indicates whether the dividend amount is expressed for one share (1.000) or in lot (0.001); some securities in Brazil are provided in lot of 1000.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecCu: MSCI Security CUSIP Information

This table contains MSCI security CUSIP information.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecCu (Clustered)	SecID, StartDate

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
CUSIP	char(8)	Y	CUSIP is the CUSIP identifier.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecD: MSCI Security Date Data

NOTE

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI security date data that changes infrequently.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecD (Clustered)		StartDate, SecID, Item	
Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecDACE: MSCI Security Advanced Corporate Event Date Data

This table contains daily MSCI security advanced corporate event date data that changes infrequently.

NOTE

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecDACE (Clustered)		SecID, Item, EventId, Seq	
Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
EventId	int	N	EventId is the event ID.
Seq	tinyint	N	Seq is the sequence number.
Date_	datetime	Y	Date_ is the date on which the data was calculated.
StatusCode	tinyint	Y	StatusCode is the status code. MS2SecDACE.StatusCode joins with MS2Code.Code where Type_ = 6.
EventCode	tinyint	Y	EventCode is the event code. MS2SecDACE.EventCode joins with MS2Code.Code where Type_ = 7.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
AddDate	datetime	Y	AddDate is the add date.
ModDate	datetime	Y	ModDate is the date the security information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecDDly: Daily MSCI Security Date Data

NOTE

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI security date data.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecDDly (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecDMth: Monthly MSCI Security Date Data

This table contains monthly MSCI security date data.

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Update Cycle: Monthly

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecDMth (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	datetime	Y	Value_ is the date information associated with given constraints.
NextValue	datetime	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecDivDly: Daily MSCI Security Dividends Data

This table contains daily MSCI security dividends data.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecDivDly (Clustered)		SecID, IdxFam, Date_, DivCode	

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
IdxFam	tinyint	N	IdxFam is the index family. This field cross-references with MS2Code .Code where Type_ = 12.
Date_	datetime	N	Date_ is the date on which the data was calculated.
DivCode	int	N	DivCode is the MSCI dividend code, a unique identifier allocated by MSCI to a dividend event.
DivDesc	tinyint	Y	DivDesc is the MSCI dividend description: – 0 = Annual – 1 = Final – 2 = Interim – 3 = Quarterly – 4 = Extra – 5 = Monthly – 6 = Regular – 7 = Commemorative This field cross-references with MS2Code .Code where Type_ = 5.
XDDate	datetime	Y	XDDate is the dividend ex-date.
CorrectionFlag	tinyint	Y	CorrectionFlag indicates that the dividend amount is a correction of an already reinvested dividend. The difference between the correct and incorrect amount will show in the gross dividend amount, net dividend amount international, and net dividend amount domestic.
ReinvDate	datetime	Y	ReinvDate is the date as of which the dividend is reinvested in the index.
Div	float	Y	Div is the declared dividend amount.
AdjGRSDiv	float	Y	AdjGRSDiv is the gross dividend amount of withholding taxes to be reinvested in MSCI Daily Gross Total Return Indices.
AdjNETDiv	float	Y	AdjNETDiv is the net dividend amount of withholding taxes to be reinvested in MSCI Daily Net Total Return Indices for MSCI international indices.
ISOCurrCode	char(3)	Y	ISOCurrCode is the dividend ISO currency symbol. This field cross-references with MS2Desc .Code where Type_ = 2.
DivSubUnit	float	Y	DivSubUnit is the dividend sub-unit. It indicates whether the dividend amount is expressed for one share (1.000) or in lot (0.001); some securities in Brazil are provided in lot of 1000.
DivAdjFactor	float	Y	DivAdjFactor is the dividend adjustment factor. It reflects the impact of corporate events on the declared dividend amount.
DTRNumShares	float	Y	DTRNumShares is the number of shares used in the calculation of the MSCI DTR Indices, as of the dividend ex date, minus one.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecDivMth: Monthly MSCI Security Dividends**NOTE**

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains monthly MSCI security dividends data.

Update Cycle: Monthly

Adjusted: N/A

Indexes			Index Fields
pkey_MS2SecDivMth (Clustered)			SecID, IdxFam, Date_, DivCode

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
IdxFam	tinyint	N	IdxFam is the index family. This field cross-references with MS2Code .Code where Type_ = 12.
Date_	datetime	N	Date_ is the date on which the data was calculated.
DivCode	int	N	DivCode is the MSCI dividend code, a unique identifier allocated by MSCI to a dividend event.
DivDesc	tinyint	Y	DivDesc is the MSCI dividend description: – 0 = Annual – 1 = Final – 2 = Interim – 3 = Quarterly – 4 = Extra – 5 = Monthly – 6 = Regular – 7 = Commemorative This field cross-references with MS2Code .Code where Type_ = 5.
XDDate	datetime	Y	XDDate is the dividend ex-date.
CorrectionFlag	tinyint	Y	CorrectionFlag indicates that the dividend amount is a correction of an already reinvested dividend. The difference between the correct and incorrect amount will show in the gross dividend amount, net dividend amount international, and net dividend amount domestic.
ReinvDate	datetime	Y	ReinvDate is the date as of which the dividend is reinvested in the index.
Div	float	Y	Div is the declared dividend amount.
AdjGRSDiv	float	Y	AdjGRSDiv is the gross dividend amount of withholding taxes to be reinvested in MSCI Daily Gross Total Return Indices.
AdjNETDiv	float	Y	AdjNETDiv is the net dividend amount of withholding taxes to be reinvested in MSCI Daily Net Total Return Indices for MSCI international indices.
ISOCurrCode	char(3)	Y	ISOCurrCode is the dividend ISO currency symbol. This field cross-references with MS2Desc .Code where Type_ = 2.
DivSubUnit	float	Y	DivSubUnit is the dividend sub-unit. It indicates whether the dividend amount is expressed for one share (1.000) or in lot (0.001); some securities in Brazil are provided in lot of 1000.
DivAdjFactor	float	Y	DivAdjFactor is the dividend adjustment factor. It reflects the impact of corporate events on the declared dividend amount.
DTRNumShares	float	Y	DTRNumShares is the number of shares used in the calculation of the MSCI DTR Indices, as of the dividend ex date, minus one.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecF: MSCI Security Float Data

This table contains daily MSCI security float data that changes infrequently.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecF (Clustered)		StartDate, SecID, Item	
Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecFACE: MSCI Security Advanced Corporate Event Float Data

This table contains daily MSCI security advanced corporate event float data that changes infrequently.

NOTE

This table is populated going forward from 2011.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecFACE (Clustered)		SecID, Item, EventId, Seq	
Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
EventId	int	N	EventId is the event ID.
Seq	tinyint	N	Seq is the sequence number.
Date_	datetime	Y	Date_ is the date on which the data was calculated.
StatusCode	tinyint	Y	StatusCode is the status code. MS2SecFACE.StatusCode joins with MS2Code.Code where Type_ = 6.
EventCode	tinyint	Y	EventCode is the event code. MS2SecFACE.EventCode joins with MS2Code.Code where Type_ = 7.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.

Field	Type	Nullable	Description
AddDate	datetime	Y	AddDate is the add date.
ModDate	datetime	Y	ModDate is the date the security information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecFDly: Daily MSCI Security Float Data

This table contains daily MSCI security float data.

Update Cycle: Daily **Adjusted:** N/A

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Indexes	Index Fields
pkey_MS2SecFDly (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecFMth: Monthly MSCI Security Float Data

This table contains monthly MSCI security float data.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecFMth (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	float	Y	Value_ is the numeric information associated with given constraints.
NextValue	float	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecI: MSCI Security Integer Data

This table contains daily MSCI security integer data that changes infrequently.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecI (Clustered)		StartDate, SecID, Item	
Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecIACE: MSCI Security Advanced Corporate Event Integer Data

This table contains daily MSCI security advanced corporate event integer data that changes infrequently.

NOTE

This table is populated going forward from 2011.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecIACE (Clustered)		SecID, Item, EventId, Seq	
Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
EventId	int	N	EventId is the event ID.
Seq	tinyint	N	Seq is the sequence number.
Date_	datetime	Y	Date_ is the date on which the data was calculated.
StatusCode	tinyint	Y	StatusCode is the status code. MS2SecIACE.StatusCode joins with MS2Code .Code where Type_ = 6.
EventCode	tinyint	Y	EventCode is the event code. MS2SecIACE.EventCode joins with MS2Code .Code where Type_ = 7.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.

Field	Type	Nullable	Description
AddDate	datetime	Y	AddDate is the add date.
ModDate	datetime	Y	ModDate is the date the security information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecIDly: Daily MSCI Security Integer Data

NOTE

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI security integer data.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecIDly (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecIMth: Monthly MSCI Security Integer Data

This table contains monthly MSCI security integer data.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecIMth (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	int	Y	Value_ is the numeric information associated with given constraints.
NextValue	int	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecInfo: MSCI Security Information

This table contains MSCI security information.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecInfo (Clustered)		SecID	

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
TsCode	int	Y	TsCode is the MSCI time series code and unique security identifier.
IssCode	int	Y	IssCode is the MSCI issuer code. Not all issuers have an IssCode.
SecCode	int	Y	SecCode is the MSCI security code.
Name_	varchar(40)	Y	Name_ is the name of the security.
ISOtryCode	char(2)	Y	ISOtryCode is the ISO country code. It is a two-digit alphabetic code for country classification. MS2SecInfo.ISOtryCode joins with MS2Desc .Code where Type_ = 1.
NextISOtryCode	char(2)	Y	NextISOtryCode is the next day ISO country code.
MIC	char(4)	Y	MIC is the market identifier code. It specifies a universal method of identifying exchanges and trading platforms and regulated or non-regulated markets as sources of prices and related information in order to facilitate automated processing.
NextMIC	char(4)	Y	NextMIC is the next day market identifier code.
BloomTkr	varchar(25)	Y	BloomTkr is the Bloomberg ticker.
NextBloomTkr	varchar(25)	Y	NextBloomTkr is the next day Bloomberg ticker.
ShareClassCode	tinyint	Y	ShareClassCode is the share class code. It provides information on the main category of the security (for example, COMMON, PREFERRED, and UNIT). MS2SecInfo.ShareClassCode joins with MS2Code .Code where Type_ = 8.
ShareTypeCode	tinyint	Y	ShareTypeCode is the share type code. It provides information on the sub-category of the security (for example, A, B, and H). MS2SecInfo.ShareTypeCode joins with MS2Code .Code where Type_ = 9.
AltListingCode	tinyint	Y	AltListingCode is the alternate listing code. It provides information on the listing of the security (for example, ADR and GDR). MS2SecInfo.AltListingCode joins with MS2Code .Code where Type_ = 10.
BarraID	char(8)	Y	BarraID is the Barra security identifier.
EndDate	datetime	Y	EndDate is the date the period ends.
ModDate	datetime	Y	ModDate is the date the security information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecInfoChg: MSCI Security Information Change History

This table contains MSCI security information change history.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2SecInfoChg (Clustered)		SecID, StartDate	

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
TsCode	int	Y	TsCode is the MSCI time series code and unique security identifier.
IssCode	int	Y	IssCode is the MSCI issuer code. Not all issuers have an IssCode.
SecCode	int	Y	SecCode is the MSCI security code.
Name_	varchar(40)	Y	Name_ is the name of the security.
ISOtryCode	char(2)	Y	ISOtryCode is the ISO country code. It is a two-digit alphabetic code for country classification. MS2SecInfoChg.ISOtryCode joins with MS2Desc .Code where Type_ = 1.
MIC	char(4)	Y	MIC is the market identifier code. It specifies a universal method of identifying exchanges and trading platforms and regulated or non-regulated markets as sources of prices and related information in order to facilitate automated processing.
BloomTkr	varchar(25)	Y	BloomTkr is the Bloomberg ticker.
ShareClassCode	tinyint	Y	ShareClassCode is the share class code. It provides information on the main category of the security (for example, COMMON, PREFERRED, and UNIT). MS2SecInfoChg.ShareClassCode joins with MS2Code .Code where Type_ = 8.
ShareTypeCode	tinyint	Y	ShareTypeCode is the share type code. It provides information on the sub-category of the security (for example, A, B, and H). MS2SecInfoChg.ShareTypeCode joins with MS2Code .Code where Type_ = 9.
AltListingCode	tinyint	Y	AltListingCode is the alternate listing code. It provides information on the listing of the security (for example, ADR and GDR). MS2SecInfoChg.AltListingCode joins with MS2Code .Code where Type_ = 10.
BarraID	char(8)	Y	BarraID is the Barra security identifier.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecISIN: MSCI Security ISIN Information

This table contains MSCI security ISIN information.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecISIN (Clustered)	SecID, StartDate

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
ISIN	char(12)	Y	ISIN is the ISIN of the security.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecPrcDly: MSCI Daily Security Pricing Information

This table contains daily MSCI security pricing information.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecPrcDly (Clustered)	SecID, Date_
Ms2SecPrcDly_1	Licflag, Date_

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Shares	float	Y	Shares is the number of shares.
NextShares	float	Y	NextShares is the number of next day shares.
Price	float	Y	Price is the price.
PrcAdjFactor	float	Y	PrcAdjFactor is the price adjustment factor.
IsoCurCode	char(3)	Y	IsoCurCode is the dividend ISO currency symbol. This field cross-references MS2Desc .Code where Type_ = 2.
QuoteValue	float	Y	QuoteValue is the value of the quote (used for lot-priced securities).
NextQuoteValue	float	Y	NextQuoteValue is the next day value of the quote.
Licflag	int	Y	Licflag is a bit value that represents the license for this table.

MS2SecPrcMth: MSCI Monthly Security Pricing Information

This table contains monthly MSCI security pricing information.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecPrcMth (Clustered)	SecID, Date_
Ms2SecPrcMth_1	Licflag, Date_

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Shares	float	Y	Shares is the number of shares.
NextShares	float	Y	NextShares is the number of next day shares.

Field	Type	Nullable	Description
Price	float	Y	Price is the price.
PrcAdjFactor	float	Y	PrcAdjFactor is the price adjustment factor.
IsoCurCode	char(3)	Y	IsoCurCode is the dividend ISO currency symbol. This field cross-references with MS2Desc .Code where Type_ = 2.
QuoteValue	float	Y	QuoteValue is the value of the quote (used for lot-priced securities).
NextQuoteValue	float	Y	NextQuoteValue is the next day value of the quote.
Licflag	int	Y	Licflag is a bit value that represents the license for this table.

MS2SecS: MSCI Security Varchar Data

This table contains daily MSCI security varchar data that changes infrequently.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecS (Clustered)	StartDate, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Value_	varchar(75)	Y	Value_ is the alphanumeric information associated with given constraints.
NextValue	varchar(75)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecSACE: MSCI Security Advanced Corporate Event Varchar Data

This table contains daily MSCI security advanced corporate event integer data that changes infrequently.

NOTE

This table is populated going forward from 2011.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecSACE (Clustered)	SecID, Item, EventId, Seq

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.

Field	Type	Nullable	Description
EventId	int	N	EventId is the event ID.
Seq	tinyint	N	Seq is the sequence number.
Date_	datetime	Y	Date_ is the date on which the data was calculated.
StatusCode	tinyint	Y	StatusCode is the status code. MS2SecSACE.StatusCode joins with MS2Code .Code where Type_ = 6.
EventCode	tinyint	Y	EventCode is the event code. MS2SecSACE.EventCode joins with MS2Code .Code where Type_ = 7.
Value_	varchar(250)	Y	Value_ is the alphanumeric information associated with given constraints.
NextValue	varchar(250)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
AddDate	datetime	Y	AddDate is the add date.
ModDate	datetime	Y	ModDate is the date the security information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecSDly: Daily MSCI Security Varchar Data

NOTE

This table is reserved for future use. See [Empty Tables](#) on page 6 for details.

This table contains daily MSCI security varchar data.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecSDly (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	varchar(75)	Y	Value_ is the alphanumeric information associated with given constraints.
NextValue	varchar(75)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecSMth: Monthly MSCI Security Varchar Data

This table contains monthly MSCI security varchar data.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecSMth (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Value_	varchar(75)	Y	Value_ is the alphanumeric information associated with given constraints.
NextValue	varchar(75)	Y	NextValue is the next day value. NULL = Next Day Value not provided. If the value is not changing from one day to next, the same value is populated in both the Value_ and NextValue fields.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2SecSMaxACE: MSCI Security Advanced Corporate Event Large Varchar Data

This table contains daily MSCI advanced corporate event information for large varchar data items that changes infrequently.

NOTE

This table is populated going forward from 2011.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecSMaxACE (Clustered)	SecID, Item, EventId, Seq

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
EventId	int	N	EventId is the event ID.
Seq	tinyint	N	Seq is the sequence number.
Date_	datetime	Y	Date_ is the date on which the data was calculated.
StatusCode	tinyint	Y	StatusCode is the status code. MS2SecSMaxACE.StatusCode joins with MS2Code .Code where Type_ = 6.
EventCode	tinyint	Y	EventCode is the event code. MS2SecSMaxACE.EventCode joins with MS2Code .Code where Type_ = 7.
AddDate	datetime	Y	AddDate is the add date.
ModDate	datetime	Y	ModDate is the date the security information was last modified.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.
Value_	varchar(max)	Y	Value_ is the alphanumeric information associated with given constraints.

MS2SecSMaxDly: Daily MSCI Security Advanced Corporate Event Large Varchar Data

This table contains daily MSCI advanced corporate event information for large varchar data items.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecSMaxDly (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.
Value_	varchar(max)	Y	Value_ is the alphanumeric information associated with given constraints.

MS2SecSMaxMth: Monthly MSCI Security Advanced Corporate Event Large Varchar Data

This table contains monthly MSCI advanced corporate event information for large varchar data items.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2SecSMaxMth (Clustered)	Date_, SecID, Item

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
Date_	datetime	N	Date_ is the date on which the data was calculated.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.
Value_	varchar(max)	Y	Value_ is the alphanumeric information associated with given constraints.

MS2SecSed: MSCI Security SEDOL Information

This table contains MSCI security SEDOL information.

Update Cycle: Daily **Adjusted:** N/A

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Indexes	Index Fields
pkey_MS2SecSed (Clustered)	SecID, StartDate

Field	Type	Nullable	Description
SecID	int	N	SecID is the security ID.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
SEDOL	char(6)	Y	SEDOL is the SEDOL identifier.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MSCI V2 Miscellaneous Tables

Diagrams

Item/Code Tables

MS2Code

Type_	int
Code	int
Desc_	varchar(75)

MS2Desc

Type_	int
Code	varchar(10)
Desc_	varchar(75)

MS2Item

Item	INTEGER
Mnemonic	VARCHAR(50)
Desc_	VARCHAR(75)
AdjCode	TINYINT
FrqFlg	TINYINT
DlyFlg	TINYINT
MthFlg	TINYINT
ParentItem	INTEGER
CorrMnem	VARCHAR(15)
DataTypeCode	TINYINT
DecimalNum	TINYINT
ACEFlg	TINYINT
SecFlg	TINYINT
IdxFlg	TINYINT
DSFlg	TINYINT
BasicFlg	TINYINT
EnhFlg	TINYINT
LegacyMnem	VARCHAR(30)

MS2ItemChg

Item	INTEGER
StartDate	INTEGER
EndDate	INTEGER
Mnemonic	VARCHAR(50)
Desc_	VARCHAR(75)
CorrMnem	VARCHAR(15)
LegacyMnem	VARCHAR(30)

MS2ItemMap

DataTypeCode	TINYINT
SecFlg	TINYINT
IdxFlg	TINYINT
FrqFlg	TINYINT
DlyFlg	TINYINT
MthFlg	TINYINT
ACEFlg	TINYINT
TableName	VARCHAR(50)

Fx Rate Tables

MS2FxRateDly

ISOCurCode	char(3)
Date_	int
Rate	float
LicFlag	int

MS2FxRateMth

ISOCurCode	CHAR(3)
Date_	INTEGER
Rate	FLOAT
Rate1MthFwd	FLOAT
CoveringCost	FLOAT
LicFlag	INTEGER

Miscellaneous Tables

MS2CtyWgtDly

MSCICode	int
ISOCtryCode	char(2)
Date_	int
Weight	float
LicFlag	int

MS2CtyWgtMth

MSCICode	int
ISOCtryCode	char(2)
Date_	int
Weight	float
LicFlag	int

MS2Code: MSCI Numeric Codes

This table contains information about MSCI numeric codes.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2Code (Clustered)	Type_, Code

Field	Type	Nullable	Description
Type_	int	N	Type_ is a numeric code for a type of data.
Code	int	N	Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_.
Desc_	varchar(75)	Y	Desc_ is a plain-language description of the element defined by Type_ and Code.

MS2CtyWgtDly: Daily MSCI Country Weights

This table contains daily MSCI country weights data.

NOTE

This table is populated going forward from 2011.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2CtyWgtDly (Clustered)	MSCICode, ISOCTryCode, Date_

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. MSCICode is defined in MS2IdxInfo.
ISOCTryCode	char(2)	N	ISOCTryCode is the ISO country code. It is a two-digit alphabetic code for country classification. MS2CtyWgtDly.ISOCTryCode joins with MS2Desc.Code where Type_ = 1.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Weight	float	Y	Weight is the initial weight of the country in the index
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2CtyWgtMth: Monthly MSCI Country Weights

This table contains monthly MSCI country weights data.

NOTE

This table is populated going forward starting in 2011.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2CtyWgtMth (Clustered)	MSCICode, ISOCTryCode, Date_

Field	Type	Nullable	Description
MSCICode	int	N	MSCICode is the MSCI index identifier. MSCICode is defined in MS2IdxInfo .
ISOCTryCode	char(2)	N	ISOCTryCode is the ISO country code. It is a two-digit alphabetic code for country classification. MS2CtyWgtMth.ISOCTryCode joins with MS2Desc .Code where Type_ = 1.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Weight	float	Y	Weight is the initial weight of the country in the index
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2Desc: MSCI Text Codes

This table contains information about MSCI text codes.

Update Cycle: Daily**NOTE**

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2Desc (Clustered)	Type_, Code

Field	Type	Nullable	Description
Type_	int	N	Type_ is a numeric code for a type of data.
Code	varchar(10)	N	Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_.
Desc_	varchar(75)	Y	Desc_ is a plain-language description of the element defined by Type_ and Code.

MS2FxRateDly: Daily MSCI Exchange Rates

This table contains daily MSCI exchange rates data.

Update Cycle: Daily**NOTE**

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2FxRateDly (Clustered)	ISOCurCode, Date_

Field	Type	Nullable	Description
ISOCurCode	char(3)	N	ISOCurCode is the dividend ISO currency symbol. MS2FxRateDly.ISOCurCode joins with MS2Desc .Code where Type_ = 2.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Rate	float	Y	Rate is the 4:00 P.M. London time snapshot from WM/LSEG.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2FxRateMth: Monthly MSCI Exchange Rates

This table contains monthly MSCI exchange rates data.

Update Cycle: Monthly

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 7-year rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2FxRateMth (Clustered)		ISOCurCode, Date_	

Field	Type	Nullable	Description
ISOCurCode	char(3)	N	ISOCurCode is the dividend ISO currency symbol. MS2FxRateMth.ISOCurCode joins with MS2Desc .Code where Type_ = 2.
Date_	datetime	N	Date_ is the date on which the data was calculated.
Rate	float	Y	Rate is the 4:00 P.M. London time snapshot from WM/LSEG.
Rate1MthFwd	float	Y	Rate1MthFwd is the 4:00 P.M. London time snapshot from WM/LSEG as of calculation date.
CoveringCost	float	Y	CoveringCost is the cost of hedging an index against foreign currencies.
LicFlag	int	Y	LicFlag is a bit value that represents the license for this table.

MS2Item: MSCI Data Item Descriptions

This table contains the MSCI data items.

To determine which table(s) an item is stored in, refer to MS2ItemMap. The relationship between MS2Item and MS2ItemMap is described in [Relationship Between MS2Item and MS2ItemMap](#).

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2Item (Clustered)		Item	

Field	Type	Nullable	Description
Item	int	N	Item is an integer code that represents a data item. Item indicates what datapoint the record represents.
Mnemonic	varchar(50)	Y	Mnemonic is the item mnemonic.
Desc_	varchar(75)	Y	Desc_ is a plain-language description of the mnemonic.
AdjCode	tinyint	Y	AdjCode is the adjustment code (Multiplied, Divided, or Unaffected). MS2Item.AjdCode joins with MS2Code .Code where Type_ = 2.
FrqFlg	tinyint	Y	FrqFlg is a frequency flag and can be – 0 = daily – 1 = periodic This field only applies to items with DlyFlg = 1. FrqFlg is used with the MS2ItemMap table to indicate the data table. If an item has DlyFlg = 1 and FrqFlg = 0, it is a daily license item that changes daily. If an item has DlyFlg = 1 and FrqFlg = 1, it is a daily license item that only changes periodically.
DlyFlg	tinyint	Y	DlyFlg is the daily data flag. If DlyFlg = 1, the item is available to clients with a daily license.

Field	Type	Nullable	Description
MthFlg	tinyint	Y	MthFlg is the monthly data flag. If MthFlg = 1, the item is available to clients with a daily or monthly license.
ParentItem	int	Y	ParentItem is the parent item populated for next day items.
CorrMnem	varchar(15)	Y	CorrMnem is the correction mnemonic.
DataTypeCode	tinyint	Y	DataTypeCode is the data type code. MS2Item.DataTypeCode joins with MS2Code .Code where Type_ = 3.
DecimalNum	tinyint	Y	DecimalNum is the number of decimals for float data.
BoxFlg	tinyint	Y	BoxFlg is the boxes/fundamentals data flag.
ACEFlg	tinyint	Y	ACEFlg is the ACE (Advance Corporate Event) flag.
SecFlg	tinyint	Y	SecFlg is the security-level data flag.
IdxFlg	tinyint	Y	IdxFlg is the index-level data flag.
DSFlg	tinyint	Y	DSFlg is the Data Set flag and is for LSEG Quantitative Analytics internal use only.
BasicFlg	tinyint	Y	BasicFlg is the basic flag.
EnhFlg	tinyint	Y	EnhFlg is the enhanced license flag.
LegacyMnem	varchar(30)	Y	LegacyMnem is the legacy MSCI mnemonic.

MS2ItemChg: Historical MSCI Data Item Descriptions

This table contains a history of MSCI data item mnemonics and their descriptions.

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes	Index Fields
pkey_MS2ItemChg (Clustered)	Item, StartDate

Field	Type	Nullable	Description
Item	int	N	Item is an integer code that represents a data item. Item cross-references with MS2Item and indicates what datapoint the record represents.
StartDate	datetime	N	StartDate is the date the period begins.
EndDate	datetime	Y	EndDate is the date the period ends.
Mnemonic	varchar(50)	Y	Mnemonic is the item mnemonic.
Desc_	varchar(75)	Y	Desc_ is a plain-language description of the element.
CorrMnem	varchar(15)	Y	CorrMnem is the correction mnemonic.
LegacyMnem	varchar(30)	Y	LegacyMnem is the legacy MSCI mnemonic.

MS2ItemMap: MSCI Item and Table Mapping Information

This table contains MSCI item and table mapping information. It specifies the data table(s) associated with a particular data item. The relationship between MS2Item and MS2ItemMap is described in [Relationship Between MS2Item and MS2ItemMap](#).

Update Cycle: Daily

NOTE

Unless you are licensed for MSCI Deep History, the data in this table is purged on a 13-month rolling basis.

Adjusted: N/A

Indexes		Index Fields	
pkey_MS2ItemMap (Clustered)		DataTypeCode, SecFlg, IdxFlg, FrqFlg, DlyFlg, MthFlg, ACEFlg	

Field	Type	Nullable	Description
DataTypeCode	tinyint	N	DataTypeCode is the data type code. MS2ItemMap.DataTypeCode joins with MS2Code .Code where Type_ = 3.
SecFlg	tinyint	N	SecFlg is the security-level data flag.
IdxFlg	tinyint	N	IdxFlg is the index-level data flag.
FrqFlg	tinyint	N	FrqFlg is a frequency flag and can be – 0 = daily – 1 = periodic This field only applies to items with DlyFlg = 1. FrqFlg is used with the MS2ItemMap table to indicate the data table. If an item has DlyFlg = 1 and FrqFlg = 0, it is a daily license item that changes daily. If an item has DlyFlg = 1 and FrqFlg = 1, it is a daily license item that only changes periodically.
DlyFlg	tinyint	N	DlyFlg is the daily data flag.
MthFlg	tinyint	N	MthFlg is the monthly data flag.
ACEFlg	tinyint	N	ACEFlg is the ACE (Advance Corporate Event) flag.
TableName	varchar(50)	Y	TableName is the name of the table where the data item is stored.

Relationship Between MS2Item and MS2ItemMap

Use MS2ItemMap to determine the table in which a particular data item from MS2Item is stored. Each MSCI version 2 data item is stored in one or more tables. The location of a specific data item depends on whether it is index- or security-level, the data type, how often it is updated (daily or monthly), and whether it is Advanced Corporate Event (ACE) data.

The names of the MSCI version 2 data tables reflect the the type of data items they contain. The table name format is **MS2[Idx][Sec][Datatype][Frq][ACE]**. For details about this table name format, see [Table Name Format](#) on page 6. The following query returns the full mapping of the MSCI version 2 data items and corresponding data tables.

```
select i.Item, i.Mnemonic, i.Desc_, i.AdjCode, i.ParentItem,
       i.DataTypeCode, i.DecimalNum, i.BoxFlg, i.DSFlg,
       i.BasicFlg, i.EnhFlg, i.LegacyMnem,
       m.SecFlg, m.IdxFlg, m.FrqFlg, m.DlyFlg, m.MthFlg, m.ACEFlg, m.TableName
from MS2Item i
join MS2ItemMap m
on m.DataTypeCode = i.DataTypeCode
and ((m.SecFlg = i.SecFlg) or (m.IdxFlg = i.IdxFlg)) -- AN ITEM MAY BE SECURITY LEVEL,
INDEX LEVEL OR BOTH
and ((m.MthFlg = i.MthFlg)
or (m.DlyFlg = i.DlyFlg and m.FrqFlg = i.FrqFlg)) -- AN ITEM MAY BE MONTHLY OR
DAILY. IF DAILY, THE TABLE DETERMINED BY FREQUENCY FLAGS
--and m.ACEFlg = 1 -- FOR ADVANCE CORPORATE ACTION (ACE) ITEMS
--and m.SecFlg = 1 -- INCLUDE FOR SECURITY LEVEL ITEMS
--and m.IdxFlg = 1 -- INCLUDE FOR INDEX LEVEL ITEMS
--and m.MthFlg = 1 -- INCLUDE FOR MONTHLY ITEMS
--and m.DlyFlg = 1 -- INCLUDE FOR DAILY ITEMS
```

Copyright © 2024 London Stock Exchange Group plc and its group of companies (LSEG) and/or its affiliates. All rights reserved. The LSEG content received through this service is the intellectual property of LSEG or its third party suppliers. Republication or redistribution of content provided by LSEG is expressly prohibited without the prior written consent of LSEG, except where permitted by the terms of the relevant LSEG service agreement. Neither LSEG nor its third party suppliers shall be liable for any errors, omissions or delays in content, or for any actions taken in reliance thereon. LSEG and its logo are trademarks of LSEG.

For more information visit us at www.lseg.com



LSEG DATA &
ANALYTICS