

# LSEG Quantitative Analytics

Database Schema for Reference Data Convergence (RDC) Data

Version 1.4.6 (July 2023)



**LSEG** DATA &  
ANALYTICS

# Contents

|    |                                                                   |    |
|----|-------------------------------------------------------------------|----|
| 1. | Introduction .....                                                | 4  |
|    | In This Document.....                                             | 4  |
|    | Intended Readership.....                                          | 4  |
|    | Table Name Conventions.....                                       | 4  |
|    | Pervasive and Oracle.....                                         | 4  |
|    | Zero Values and Nulls.....                                        | 5  |
|    | Service and Support.....                                          | 5  |
|    | Statement of Service .....                                        | 5  |
|    | Subscribe to Support Channels .....                               | 5  |
|    | Documentation .....                                               | 5  |
|    | Get Support .....                                                 | 5  |
|    | Feedback .....                                                    | 6  |
|    | Your Personal Information .....                                   | 6  |
| 2. | Reference Data Convergence (RDC) Tables .....                     | 7  |
|    | Mapping Logic.....                                                | 7  |
|    | RDCCode: Numeric Codes .....                                      | 7  |
|    | RDCDesc: Character Code Descriptions .....                        | 7  |
|    | RDCOrgAddr: Address and Contact Information.....                  | 8  |
|    | RDCOrgInfo: Organization Information .....                        | 9  |
|    | RDCOrgMLInfo: Multi-Language Organization Information.....        | 10 |
|    | OrgTypeCode.....                                                  | 11 |
|    | RDCTRBCAudit: TRBC Audit Trail.....                               | 12 |
|    | RDCTRBCData: TRBC Primary Codes.....                              | 12 |
|    | RDCTRBCInfo: TRBC Item Information .....                          | 13 |
|    | RDCTRBCMLItem: TRBC Multi-Language Item Information .....         | 13 |
|    | RDCTRBCInfoChg: TRBC Item Change Information .....                | 14 |
|    | RDCTRBCMap: TRBC Mapping Information .....                        | 14 |
|    | RDCInstrInfo: Instrument Level Information .....                  | 15 |
|    | RDCInstrMLInfo: Multi-Language Instrument Level Information ..... | 17 |
|    | RDCSecMapX: RDC Security Map .....                                | 17 |
|    | RDCRICData: RDC RIC Information.....                              | 18 |
|    | RDCQuoteInfo: RDC Quote Information .....                         | 18 |
|    | RDCQuoteMLInfo: RDC Multi-Language Quote Information.....         | 19 |
|    | RDCCSecMapX: Global RDC Security Map .....                        | 20 |
|    | RDCCusipData: RDC Cusip Data .....                                | 20 |
|    | RDCDTData: RDC Date Time Data .....                               | 21 |
|    | RDCEntityMap: RDC Entity Map.....                                 | 21 |
|    | RDCFData: RDC Float Data .....                                    | 21 |

|                                                            |    |
|------------------------------------------------------------|----|
| RDCHistFData: RDC Historical Float Data .....              | 22 |
| RDCHistLNDData: RDC Historical Data .....                  | 22 |
| RDCHistLSData: RDC Historical Data .....                   | 23 |
| RDCHistMLData: RDC Multi-lingual Data .....                | 23 |
| RDCHistMSData: RDC Historical Data .....                   | 24 |
| RDCHistNData: RDC Historical Numeric Data .....            | 24 |
| RDCHistSSData: RDC Historical Data .....                   | 25 |
| RDCISINData: RDC ISIN Data .....                           | 25 |
| RDCItem: RDC Item .....                                    | 26 |
| RDCLNData: RDC Long Numeric Data .....                     | 27 |
| RDCLSDData: RDC Long Description Data .....                | 27 |
| RDCMSData: RDC Medium Description Data .....               | 28 |
| RDCNData: RDC Numeric Data .....                           | 28 |
| RDCOIQMap: RDC Organization Instrument Quote Mapping ..... | 28 |
| RDCSedolData: RDC SEDOL Data .....                         | 29 |
| RDCSSData: RDC Small Description Data .....                | 29 |
| RDCXLSDData: RDC Extra Large Description Data .....        | 30 |

# 1. Introduction

## In This Document

This document provides schema information about the **Reference Data Convergence (RDC)** data tables in LSEG Quantitative Analytics.

---

**Note:** For information about the other LSEG Quantitative Analytics tables, refer to the other Database Schema documents posted on the [LSEG Quantitative Analytics](#) product page on [MyAccount](#).

---

The documentation for each table includes these main elements:

- **hVendor Database or License Name** – This element provides the vendor database or license name. Vendor databases generally correspond to vendor licensing options.
- **Table Name: Table Title** – This element provides the table name and title, followed by a description of the table contents.
- **Update Cycle** – This element indicates the frequency of updates from the data vendor. (For specific information about when this update is posted for your use, refer to your update logs. The update log schema description is available in the Database Schema for LSEG Quantitative Analytics Core Tables document.)
- **Adjusted** – This element indicates whether the data is stored adjusted, unadjusted, or if adjustment is not applicable (N/A).
- **Indexes, Index Fields** – This element lists the table's index(es) (for example, pkey\_CSGCAD) and the index fields. The primary index contains a "pkey\_" or "PK\_" prefix. Clustered indexes are noted.
- **Field, Type, Nullable, Definition** – This element describes the table's fields, including field names, data types, and whether each field is nullable. The data types in Snowflake have equivalents available. For example, an *int* in SQL Server is a *number* in Snowflake.

## Intended Readership

This document is intended for LSEG Quantitative Analytics clients licensed to use TRBC data through LSEG. Note that the tables described in this document may be covered by several licenses; your access to the data in these tables is dependent on the licenses you have.

Readers should have basic knowledge of Microsoft SQL Server 2016.

## Table Name Conventions

In LSEG Quantitative Analytics, database tables are grouped by name. Generally, the first few letters of the table name refer to the data vendor or licensing group. For example, all tables beginning with **RDC\*** are **Reference Data Convergence (RDC)** data tables.

## Pervasive and Oracle

This document is specific to Microsoft SQL Server 2016.

If you are accessing the data directly through the Pervasive database, you may encounter slight differences in index names and data types.

If you are accessing the data through Oracle, note that field names that correspond to Oracle reserved words are appended with an underscore. For example, field names "Number", "Synonym", and "UID" become "Number\_", "Synonym\_", and "UID\_" in Oracle.

## Zero Values and Nulls

Null values are usually recorded as "NULL". A table may contain a value of "-99999" or "-9999"; in these cases, there is no recorded data for that period. (It is null.)

If the table contains a "0" value, the data was reported as having a "0" value.

## Service and Support

[MyAccount](#) is the LSEG portal that provides a single access point for timesaving support services, along with billing, user management, and information.

### Statement of Service

The *LSEG Quantitative Analytics Service Description* is available on the [LSEG Quantitative Analytics](#) product page at MyLSEG.

### Subscribe to Support Channels

You are encouraged to [subscribe](#) to the following support channels to keep informed of changes to products and data, and to be notified of any service issues or change. See the *Alerts and Notifications* section in the *LSEG Quantitative Analytics Service Description* available on the [LSEG Quantitative Analytics](#) product page at MyAccount for detailed instructions.

- Change Notifications
- [Product Change Notifications \(PCNs\)](#) detail new, enhanced, or changed functionality, which may require your action, in products that you use.
- [Content Notifications \(DNs\)](#) alert you to upcoming changes to real-time and historical data across all asset classes that are relevant to you.
- [RIC Change Events](#) inform you of planned changes to LSEG Identification Codes.

### Service Alerts

Alert you about planned maintenance and unplanned service issues affecting your products and services, and be notified via SMS or email.

## Documentation

You can access product documentation on the [LSEG Quantitative Analytics](#) product page at MyAccount.

## Get Support

For support using LSEG Quantitative Analytics, please use one of the following methods:

### Online

Access [Get Support](#) either via the blue [Get Support](#) button at the top right of each page or by selecting *Get Support* located under *Help and Support* on the left navigation pane at [MyAccount](#).

From the *Get Support* page, choose *Get Product and Content Support* and then select the appropriate category from the next page. Complete the request making sure to include the following:

- Under Product, select LSEG Quantitative Analytics from the dropdown list.
- In the "How can we help you?" text box, include the following information:
  - Content set name (i.e. Worldscope)
  - Date applicable to a content inquiry
  - Table names and relevant fields
  - Security code (i.e. QA-ID, PermID, Sedol, InfoCode, etc.)
  - Script used to generate the output
  - Any other supporting detail

## Telephone

QA Support: 1.866.427.8390

- Option 1 – Product Support
- Option 2 – Technical Support.

## Feedback

We invite your comments, corrections, and suggestions about this document: access the [Feedback](#) option under [Get Support](#) at [MyAccount](#). Your feedback helps us continue to improve our user assistance.

## Your Personal Information

LSEG is committed to the responsible handling and protection of personal information. We invite you to review our [Privacy and Cookie Statement | LSEG](#), which describes how we collect, use, disclose, transfer, and store personal information when needed to provide our services and for our operational and business purposes.

## 2. Reference Data Convergence (RDC) Tables

### Mapping Logic

To map from LSEG Quantitative Analytics SecCode to TRBC OrgID, use the following mapping logic:

- Map from SecCode to OrgID using mapping tables:
  - **Domestic securities:** SecMstrX.Seccode -> RDCSecMapX.Seccode where ventype=57 -> RDCSecMapX.vencode -> RDCOrgInfo.OrgID
  - **Global securities:** GSecMstrX.Seccode -> RDCGSecMapX.Seccode where ventype=57 -> RDCGSecMapX.vencode -> RDCOrgInfo.OrgID

### RDCCode: Numeric Codes

This table contains descriptions of Reference Data Convergence (RDC) numeric codes.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                  |  | Index Fields |  |
|--------------------------|--|--------------|--|
| pkey_RDCCode (Clustered) |  | Type_, Code  |  |

  

| Field | Type         | Nullable | Description                                                                                                                                                   |
|-------|--------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type_ | int          | N        | Type_ is a numeric code for a type of data.                                                                                                                   |
| Code  | int          | N        | Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_. |
| Desc_ | varchar(255) | Y        | Desc_ is a plain-language description of the element defined by Type_ and Code.                                                                               |

### RDCDesc: Character Code Descriptions

This table contains descriptions of Reference Data Convergence (RDC) character codes.

**Update Cycle:** One hour **Adjusted:** N/A

| Indexes                  |  | Index Fields |  |
|--------------------------|--|--------------|--|
| pkey_RDCDesc (Clustered) |  | Type_, Code  |  |

  

| Field | Type         | Nullable | Description                                                                                                                                                   |
|-------|--------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type_ | int          | N        | Type_ is a numeric code for a type of data.                                                                                                                   |
| Code  | varchar(50)  | N        | Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_. |
| Desc_ | varchar(255) | Y        | Desc_ is a plain-language description of the element defined by Type_ and Code.                                                                               |

## RDCOrgAddr: Address and Contact Information

This table contains the address and contact information of an organization.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |  | Index Fields |  |
|-----------------------------|--|--------------|--|
| pkey_RDCOrgAddr (Clustered) |  | OrgId        |  |

  

| Field        | Type         | Nullable | Description                                                                                                                                                                                                                                                 |
|--------------|--------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OrgId        | int          | N        | OrgId is the permanent identifier of the organization.                                                                                                                                                                                                      |
| AddrTypeCode | char(2)      | Y        | AddrTypeCode is the address type of the organization.<br>AddrTypeCode can be:<br>TR = Trading<br>MK = Marketing<br>RG = Registered<br>HQ = Headquarters<br>RDCOrgAddr.AddrTypeCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 80948. |
| EmailId      | varchar(255) | Y        | EmailId is the e-mail address of the organization.                                                                                                                                                                                                          |
| FaxNo        | varchar(75)  | Y        | FaxNo is the fax number.                                                                                                                                                                                                                                    |
| IndiEmailId  | varchar(255) | Y        | IndiEmailId is the e-mail address of the individual.                                                                                                                                                                                                        |
| IndiFaxNo    | varchar(75)  | Y        | IndiFaxNo is the fax number of the individual.                                                                                                                                                                                                              |
| IndiName     | varchar(110) | Y        | IndiName is the contact name of the individual.                                                                                                                                                                                                             |
| IndiTelNo    | varchar(75)  | Y        | IndiTelNo is the telephone number of the individual.                                                                                                                                                                                                        |
| PostalCode   | varchar(10)  | Y        | PostalCode is the first line of an address, excluding county, zip code, and country.                                                                                                                                                                        |
| StateCntry   | varchar(90)  | Y        | StateCntry is the state or country in the address.                                                                                                                                                                                                          |
| StrAddr      | varchar(255) | Y        | StrAddr is the first line of an address, excluding county, zip code, and country.                                                                                                                                                                           |
| CityTown     | varchar(90)  | Y        | CityTown is the city or town of an address.                                                                                                                                                                                                                 |
| TelNo        | varchar(75)  | Y        | TelNo is the telephone number.                                                                                                                                                                                                                              |
| TollFreeNo   | varchar(75)  | Y        | TollFreeNo is the toll free number of the organization.                                                                                                                                                                                                     |
| WebAddr      | varchar(255) | Y        | WebAddr is the organization's Web site.                                                                                                                                                                                                                     |



## RDCOrgInfo: Organization Information

This table contains information for organizations of interest in the capital markets.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |  | Index Fields |  |
|-----------------------------|--|--------------|--|
| pkey_RDCOrgInfo (Clustered) |  | OrgId        |  |

  

| Field           | Type         | Nullable | Description                                                                                                                                                                                                                                                                     |
|-----------------|--------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OrgId           | int          | N        | OrgId is the permanent identifier of the organization.                                                                                                                                                                                                                          |
| ComName         | varchar(110) | Y        | ComName is the name of the organization in mixed case, manually limited to 80 characters to meet OptionX requirements. The organization's legal name is used to populate this field when the legal name does not exceed 80 characters.                                          |
| LegalName       | varchar(255) | Y        | LegalName is the fully registered legal name of the company, or the official name of the institution.                                                                                                                                                                           |
| ShortName       | varchar(40)  | Y        | ShortName is the short name of the organization in mixed case (unless it is a recognized acronym entered in uppercase, such as IBM for International Business Machines Corp), manually limited to a maximum of 16 characters.                                                   |
| OrgStatus       | char(2)      | Y        | OrgStatus is the role-to-issue status of the organization. It can have the following values:<br>AC = Active<br>DC = Inactive<br>Values are to be populated automatically, according to the type of organization. Values are never populated or maintained manually.             |
| ContriCode      | varchar(20)  | Y        | ContriCode is the code used to identify organizations contributing data (usually quotes) to the real-time Integrated Data Network. (IDN).<br>RDCOrgInfo.ContriCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 27035.                                     |
| ContriTypeCode  | char(3)      | Y        | ContriTypeCode is the classifier of the contributing organization. ContriTypeCode can be bank or broker.<br>RDCOrgInfo.ContriTypeCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 110661.                                                                 |
| CISiteLocCode   | varchar(20)  | Y        | CISiteLocCode uniquely identifies the contributor. The code is comprised of the country code, followed by a generated sequence number of the contributor in that country.<br>RDCOrgInfo.CISiteLocCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 114785. |
| CntryHQISOCCode | char(3)      | Y        | CntryHQISOCCode is the geographical headquarters of the organization.<br>RDCOrgInfo.CntryHQISOCCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 27165.                                                                                                    |

| Field          | Type        | Nullable | Description                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------|-------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CntryOfIncCode | char(3)     | Y        | CntryOfIncCode is the country in which the party received its charter, allowing it to operate as a corporation. If the country of incorporation is not disclosed, or if the company is not a corporation, then this would be populated the same as the current country or where the company was formed.<br>RDCOrgInfo.CntryOfIncCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 30986. |
| ISOCurrCode    | char(3)     | Y        | ISOCurrCode is the currency of record of the fund entity.<br>RDCOrgInfo.ISOCurrCode cross-references with <a href="#">RDCDesc</a> .Code where Type_ = 80867.                                                                                                                                                                                                                                                  |
| OrgTypeCode    | varchar(5)  | Y        | OrgTypeCode is described in the <a href="#">OrgTypeCode</a> section on page 10.                                                                                                                                                                                                                                                                                                                               |
| DFlag          | int         | Y        | DFlag stores a bitmasked combination for the IsContributor, IsExch, and IsFundSupCmp data items.                                                                                                                                                                                                                                                                                                              |
| NDAOrgID       | bigint      | Y        | NDAOrgID is the unique permanent organization identifier provided by LSEG. This is different from OrgID, which is used within RDC only.                                                                                                                                                                                                                                                                       |
| TMTPermID      | varchar(10) | Y        | TMTPermID Entity Id for the Thomson Mapping Tool (TMT) Quotation Entity.                                                                                                                                                                                                                                                                                                                                      |
| GemPermID      | bigint      | Y        | GEMPermID Entity Id for the Global Entity Master (GEM) Quotation Entity.                                                                                                                                                                                                                                                                                                                                      |

## RDCOrgMLInfo: Multi-Language Organization Information

This table contains multi-language information for organizations of interest in the capital markets.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                       | Index Fields    |
|-------------------------------|-----------------|
| pkey_RDCOrgMLInfo (Clustered) | OrgId, LangCode |

| Field     | Type          | Nullable | Description                                                                                                                                                                                                                            |
|-----------|---------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OrgId     | int           | N        | OrgId is the permanent identifier of the organization.                                                                                                                                                                                 |
| LangCode  | tinyint       | N        | The code associated with the particular language.                                                                                                                                                                                      |
| ComName   | nvarchar(110) | Y        | ComName is the name of the organization in mixed case, manually limited to 80 characters to meet OptionX requirements. The organization's legal name is used to populate this field when the legal name does not exceed 80 characters. |
| LegalName | nvarchar(255) | Y        | LegalName is the fully registered legal name of the company,<br>or the official name of the institution.                                                                                                                               |
| ShortName | nvarchar(40)  | Y        | ShortName is the short name of the organization in mixed case (unless it is a recognized acronym entered in uppercase, such as IBM for International Business Machines Corp), manually limited to a maximum of 16 characters.          |
| IndiName  | nvarchar(110) | Y        | IndiName is the contact name of the individual.                                                                                                                                                                                        |

## OrgTypeCode

OrgTypeCode is the organization type. It can be:

| Code | Description                |
|------|----------------------------|
| CO   | Corporation                |
| FD   | Fund                       |
| GA   | Government Agency          |
| GP   | State & Provincial         |
| GT   | Government                 |
| SP   | Supranational              |
| CF   | Closed End Fund (not used) |
| OF   | Open End Fund (not used)   |
| NC   | Not Categorized            |
| PC   | Private Corporation        |
| CTLB | Central Bank               |
| MUNI | Municipal                  |
| TREA | Treasury                   |
| PS   | Pseudo Organization        |

## RDCTRBCAudit: TRBC Audit Trail

This data table contains audit trail for any change in TRBC assignments.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                       |          | Index Fields                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------|----------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkey_RDCTRBCAudit (Clustered) |          | OrgId, AuditCode, StartDate, StartTime |                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Field                         | Type     | Nullable                               | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| OrgId                         | int      | N                                      | OrgId is the permanent identifier of the organization entity.                                                                                                                                                                                                                                                                                                                                                                                                 |
| AuditCode                     | int      | N                                      | AuditCode represents the change type for TRBC assignments: <ul style="list-style-type: none"> <li>– GRO: Internal growth (business)</li> <li>– MAA: M&amp;A (business)</li> <li>– DIV: Divestiture (business)</li> <li>– DIS: Discontinuation (business)</li> <li>– SCH: Change in schema</li> <li>– ERR: Error Correction</li> <li>– REV: Review</li> </ul> RDCTRBCAudit.AuditCode cross-references with <a href="#">RDCCCode.Code</a> where Type_ = 115371. |
| StartDate                     | datetime | N                                      | StartDate is the date on which the validity of the attribute value begins.                                                                                                                                                                                                                                                                                                                                                                                    |
| StartTime                     | int      | N                                      | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT.                                                                                                                                                                                                                                                                                                                                                           |
| EndDate                       | datetime | Y                                      | EndDate is the date on which the validity of the attribute value ends.                                                                                                                                                                                                                                                                                                                                                                                        |
| EndTime                       | int      | Y                                      | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT.                                                                                                                                                                                                                                                                                                                                                           |

## RDCTRBCData: TRBC Primary Codes

This table contains the current and historic TRBC primary codes for an organization.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                      |          | Index Fields                        |                                                                                                                                      |
|------------------------------|----------|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| pkey_RDCTRBCData (Clustered) |          | OrgId, TRBCId, StartDate, StartTime |                                                                                                                                      |
| Field                        | Type     | Nullable                            | Description                                                                                                                          |
| OrgId                        | int      | N                                   | OrgId is the permanent identifier of the organization entity.                                                                        |
| TRBCId                       | smallint | N                                   | TRBCId is the current primary Reuters Business Sector Schema (RBSS) assignment. This field cross-references with RDCTRBCInfo.TRBCId. |

| Field     | Type     | Nullable | Description                                                                                         |
|-----------|----------|----------|-----------------------------------------------------------------------------------------------------|
| StartDate | datetime | N        | StartDate is the date on which the validity of the attribute value begins.                          |
| StartTime | int      | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime | Y        | EndDate is the date on which the validity of the attribute value ends.                              |
| EndTime   | int      | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| IsPrimary | tinyint  | Y        | IsPrimary indicates if TRBCId is the primary classification.                                        |

## RDCTRBCInfo: TRBC Item Information

This table contains TRBC item information.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                      | Index Fields |
|------------------------------|--------------|
| pkey_RDCTRBCInfo (Clustered) | TRBCId       |

| Field          | Type         | Nullable | Description                                                                                          |
|----------------|--------------|----------|------------------------------------------------------------------------------------------------------|
| TRBCId         | smallint     | N        | TRBCId identifies each business entity property. This field crossreferences with RDCTRBCData.TRBCId. |
| TRBCGrpId      | tinyint      | Y        | TRBCGrpId is the business entity to which each item belongs.                                         |
| HierarchicalId | int          | Y        | HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC).                     |
| Mnemonic       | varchar(5)   | Y        | Mnemonic is the char code assigned by RDC.                                                           |
| ShortTitle     | varchar(255) | Y        | ShortTitle is the short property name for each item.                                                 |
| Title          | varchar(255) | Y        | Title is the property name for each item.                                                            |
| ShortDesc      | varchar(350) | Y        | ShortDesc is the short description for each item.                                                    |
| LongDesc       | varchar(960) | Y        | LongDesc is the long description for each item.                                                      |

## RDCTRBCMLItem: TRBC Multi-Language Item Information

This table contains TRBC multi-language item information.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                        | Index Fields     |
|--------------------------------|------------------|
| pkey_RDCTRBCMLItem (Clustered) | TRBCId, LangCode |

| Field  | Type     | Nullable | Description                                                                                                               |
|--------|----------|----------|---------------------------------------------------------------------------------------------------------------------------|
| TRBCId | smallint | N        | TRBCId identifies each business entity property. This field cross references with <a href="#">RDCTRBCData</a> .IndTRBCId. |

| Field     | Type          | Nullable | Description                                       |
|-----------|---------------|----------|---------------------------------------------------|
| LangCode  | tinyint       | N        | The code associated with the particular language. |
| Title     | nvarchar(255) | Y        | Title is the property name for each item.         |
| ShortDesc | nvarchar(350) | Y        | ShortDesc is the short description for each item. |

## RDCTRBCInfoChg: TRBC Item Change Information

This table contains TRBC item information and captures and maintains the historical associations between 'TRBCId' and 'HierarchicalId.'

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields |
|---------------------------------|--------------|
| pkey_RDCTRBCInfoChg (Clustered) | TRBCId       |

| Field          | Type         | Nullable | Description                                                                                          |
|----------------|--------------|----------|------------------------------------------------------------------------------------------------------|
| TRBCId         | smallint     | N        | TRBCId identifies each business entity property. This field crossreferences with RDCTRBCData.TRBCId. |
| TRBCGrpId      | tinyint      | Y        | TRBCGrpId is the business entity to which each item belongs.                                         |
| HierarchicalId | int          | Y        | HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC).                     |
| Mnemonic       | varchar(5)   | Y        | Mnemonic is the char code assigned by RDC.                                                           |
| ShortTitle     | varchar(255) | Y        | ShortTitle is the short property name for each item.                                                 |
| Title          | varchar(255) | Y        | Title is the property name for each item.                                                            |
| ShortDesc      | varchar(350) | Y        | ShortDesc is the short description for each item.                                                    |
| LongDesc       | varchar(960) | Y        | LongDesc is the long description for each item.                                                      |
| StartDate      | datetime     | Y        | The date from which the attribute values are valid.                                                  |
| EndDate        | datetime     | Y        | The date till which the attribute values are valid.                                                  |

## RDCTRBCMap: TRBC Mapping Information

TRBC uses a 5-level hierarchical system with 10 economic sectors, 28 business sectors, 54 industry groups, 136 industries, and 837 activity codes. This table captures the association between all levels.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     | Index Fields |
|-----------------------------|--------------|
| pkey_RDCTRBCMap (Clustered) | AccTRBCId    |

| Field     | Type     | Nullable | Description                                                             |
|-----------|----------|----------|-------------------------------------------------------------------------|
| ActTRBCId | smallint | N        | ActTRBCId is the relevant activity code derived from RDCTRBC* tables.   |
| IndTRBCId | smallint | N        | IndTRBCId is the relevant industry sector derived from RDCTRBC* tables. |

| Field        | Type     | Nullable | Description                                                               |
|--------------|----------|----------|---------------------------------------------------------------------------|
| IndGrpTRBCId | smallint | N        | IndGrpTRBCId is the relevant industry group derived from RDCTRBC* tables. |
| BusTRBCId    | smallint | N        | BusTRBCId is the relevant business sector derived from RDCTRBC* tables.   |
| EcoTRBCId    | smallint | N        | EcoTRBCId is the relevant economic sector derived from RDCTRBC* tables.   |

## RDCInstrInfo: Instrument Level Information

This data table contains financial instruments and indicators with reference and descriptive information provided at the issue and contract level.

**Update Cycle:** Daily

**Adjusted:** N/A

| Indexes                       | Index Fields |
|-------------------------------|--------------|
| pkey_RDCInstrInfo (Clustered) | InstrID      |

| Field           | Type         | Nullable | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|--------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| InstrID         | int          | N        | InstrID is the Permanent Identifier of the instrument.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| InstrStatusCode | char(2)      | Y        | <p>For non-debt issues, if an issue asset/instrument has at least one quote that is active (AssetState = 'AC'), then AssetState is Active 'AC'. If all quote assets are deactivated (AssetState = 'DC'), then AssetState is Deactivated 'DC'. AssetState is derived for all asset types except debt issues that are maintained by the DBS forward feed.</p> <p>AssetState is 'NA' (Not Applicable) when no quote asset is found against the issue/instrument. In particular, new issues get 'NA' status as soon as they are created and until a quote is assigned to them. NA also applies to instruments not properly classified. States other than AC, DC, and NA are only set for fixed income issues.</p> <p>The full set of states is:</p> <ul style="list-style-type: none"> <li>– "CA" = "Called"</li> <li>– "DE" = "Defaulted"</li> <li>– "EX" = "Exchanged"</li> <li>– "ME" = "Merged"</li> <li>– "MA" = "Matured"</li> <li>– "RE" = "Redenominated"</li> <li>– "AC" = "Active"</li> <li>– "DC" = "De-activated"</li> <li>– "NA" = "Not applicable"</li> </ul> |
| ComName         | varchar(110) | Y        | In most instances, ComName is not populated, except for equity indices and warrants sourced from DBS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| InstrCatCode    | char(4)      | Y        | InstrCatCode cross-references <a href="#">RDCDesc</a> where InstrCatCode= RDCDesc.Code and RDCDesc.Type_ = 59.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

| Field            | Type        | Nullable | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------|-------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| InstrType        | varchar(40) | Y        | InstrType is the single-level, broad asset classification scheme, used principally as an internal scheme for time series classification. This field is always mapped to the more granular AssetCategory scheme.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| IssueISOCurrCode | char(3)     | Y        | <p>IssueISOCurrCode is derived according to logic from the following fields:</p> <ul style="list-style-type: none"> <li>– Valuation Quote's Base Currency for Equity Issues</li> <li>– Principal Currency for Fixed Income (Debt) Issues</li> <li>– Quote Asset's Quotation Currency for Warrant Issues</li> </ul> <p>The issue currency data is system-driven. It is a derived attribute that is not able to be updated by applications. It will be updated by changes to the source fields (the currency held in either Valuation Quote Currency or Principal Currency fields). All changes made to these fields will trigger a matching change to be made to IssueISOCurrCode.</p> <p>RDCInstrInfo.IssueISOCurrCode cross-references with <a href="#">RDCDesc</a>.Code where Type_ = 80867.</p> |
| IsCDSCnv         | tinyint     | Y        | IsCDSCnv is the most liquid contract for doc clause and currency.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| MifidStatusCode  | varchar(8)  | Y        | <p>MifidStatusCode indicates whether the security is subject to MIFID regulation:</p> <ul style="list-style-type: none"> <li>– MIFID-U: Mifid unconfirmed security</li> <li>– MIFID-E: Mifid eligible security</li> <li>– MIFID-L: Mifid top liquidity security</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| MostReleMrkt     | char(3)     | Y        | MostReleMrkt references the country where the instrument was first admitted to trading on a regulated market.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| RCSAssetCla      | varchar(10) | Y        | RCSAssetCla cross-references <a href="#">RDCDesc</a> where RCSAssetCla= RDCDesc.Code and RDCDesc.Type_ = 60.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ShortName        | varchar(20) | Y        | ShortName is not mandatory for Issue Assets. This field may hold a value for some debt and commodities instruments (sourced from DBS and CMI respectively). No formal standard has been set.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| OrgID            | int         | Y        | OrgID is the permanent identifier of the organization.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| PrimTrdQuotePI   | int         | Y        | PrimTrdQuotePI is similar to the VQ, but the tradable RIC is used. This is very US-specific where market cap for the issue must be calculated on a consolidated quote that is not a RIC you can trade. Therefore, PrimTrdQuotePI exists to denote the main "primary" quote of a multi-listed share line in the US that can be traded.                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| TMTPerId         | varchar(10) | Y        | TMTPerId is the permanent Identifier of the Instrument in the TMT/TKO Database.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| GemPerId         | bigint      | Y        | GemPerId is the unique entity ID for the Instrument Entity. This field is currently sourced from GEM.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |



## RDCInstrMLInfo: Multi-Language Instrument Level Information

This data table contains financial instruments and indicators with multi-language reference and descriptive information provided at the issue and contract level.

**Update Cycle:** Daily

**Adjusted:** N/A

| Indexes                         |  | Index Fields      |  |
|---------------------------------|--|-------------------|--|
| pkey_RDCInstrMLInfo (Clustered) |  | InstrID, LangCode |  |

  

| Field     | Type          | Nullable | Description                                                                                                                                                                                                                            |
|-----------|---------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| InstrID   | int           | N        | InstrID is the Permanent Identifier of the instrument.                                                                                                                                                                                 |
| LangCode  | tinyint       | N        | The code associated with the particular language.                                                                                                                                                                                      |
| ComName   | nvarchar(110) | Y        | ComName is the name of the organization in mixed case, manually limited to 80 characters to meet OptionX requirements. The organization's legal name is used to populate this field when the legal name does not exceed 80 characters. |
| ShortName | nvarchar(20)  | Y        | ShortName is not mandatory for Issue Assets. This field may hold a value for some debt and commodities instruments (sourced from DBS and CMI respectively). No formal standard has been set.                                           |

## RDCSecMapX: RDC Security Map

This table provides mapping to vendor codes including ranking and time series.

**Update Cycle:** Daily

**Adjusted:** N/A

| Indexes                     |  | Index Fields           |  |
|-----------------------------|--|------------------------|--|
| pkey_RDCSecMapX (Clustered) |  | SecCode, VenType, Rank |  |

  

| Field     | Type     | Nullable | Description                                                                                                                                                                                           |
|-----------|----------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SecCode   | int      | N        | SecCode links across the master tables.                                                                                                                                                               |
| VenType   | smallint | N        | VenType is a unique type code for each vendor. VenType is defined in SecVenType.                                                                                                                      |
| VenCode   | int      | Y        | VenCode is the corresponding vendor's unique code.                                                                                                                                                    |
| Rank      | smallint | N        | Rank is the issue rank for issuers with multiple issues.<br><b>Note:</b> Ranking is determined upon initial load, and will not necessarily change in response to new issues or volume/status changes. |
| Exchange  | smallint | Y        | Exchange identifies whether the security is a United States security (1) or a Canadian security (2). A value of 0 indicates that this field is not applicable.                                        |
| StartDate | datetime | Y        | StartDate is the first date issuer information is valid.                                                                                                                                              |
| EndDate   | datetime | Y        | EndDate is the last date issuer information is valid.                                                                                                                                                 |

## RDCRICData: RDC RIC Information

This table contains information on LSEG Instrument Codes (RIC).

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |             | Index Fields                         |                                                                                                                                |
|-----------------------------|-------------|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| pkey_RDCRICData (Clustered) |             | QuoteID, SeqNo, StartDate, StartTime |                                                                                                                                |
| Field                       | Type        | Nullable                             | Description                                                                                                                    |
| QuoteID                     | int         | No                                   | Unique Entity Id for the Quote Entity.<br>This is a numeric, system generated, non-changing identifier for the specific quote. |
| SeqNo                       | smallint    | No                                   | The sequential number of the quote.                                                                                            |
| Start Date                  | datetime    | No                                   | Identifies the date of the start of validity for the instrument.                                                               |
| Start Time                  | int         | No                                   | Identifies the time of the start of validity for the instrument, noted in seconds after midnight (GMT).                        |
| End Date                    | datetime    | Yes                                  | Identifies the time of the end of validity for the instrument.                                                                 |
| End Time                    | int         | Yes                                  | Identifies the time of the end of validity for the instrument, noted in seconds after midnight (GMT).                          |
| RIC                         | varchar(21) | Yes                                  | LSEG Instrument Code, a unique identifier owned by LSEG.                                                                       |

## RDCQuoteInfo: RDC Quote Information

This table contains information on LSEG Instrument Codes (RIC).

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                        |              | Index Fields |                                                                                                                                                                |
|--------------------------------|--------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkey_RDCQuoteInfo (clustered)  |              | QuoteID      |                                                                                                                                                                |
| RDCQuoteInfo_1 (non-clustered) |              | InstrID      |                                                                                                                                                                |
| Field                          | Type         | Nullable     | Description                                                                                                                                                    |
| QuoteID                        | int          | No           | Unique Entity Id for the Quote Entity.<br>This is a numeric, system generated, non-changing identifier for the specific quote, within the NDA Oracle database. |
| QuoteStatusCode                | char(2)      | Yes          | The code indicating the status of the instrument.                                                                                                              |
| QuoteType                      | varchar(40)  | Yes          | Classifier (executable or indicative) of the quote.                                                                                                            |
| QuoteCatCode                   | char(4)      | Yes          | QuoteCatCode cross-references <a href="#">RDCDesc</a> where QuoteCatCode= RDCDesc.Code and RDCDesc.Type_ = 59.                                                 |
| ComName                        | varchar(110) | Yes          | The common name used for the quote, often same as the display name.                                                                                            |

| Field            | Type         | Nullable | Description                                                                                                                                                                   |
|------------------|--------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IsSuspended      | char(1)      | Yes      | Indicates whether a capitalisation quote is suspended.                                                                                                                        |
| QuoteISOCurrCode | char(3)      | Yes      | The currency in which the quote asset is quoted.                                                                                                                              |
| QuoteGrpByPsExch | varchar(3)   | Yes      | Exchange code for the given quote asset - includes both real world and pseudo exchange codes.                                                                                 |
| QuoteCla         | char(3)      | Yes      | The Classification the instrument belongs to.                                                                                                                                 |
| RateTypeCode     | varchar(6)   | Yes      | Quote, calculated or composite.                                                                                                                                               |
| RSCAssetCla      | varchar(10)  | Yes      | RSCAssetCla cross-references <a href="#">RDCDesc</a> where RSCAssetCla= RDCDesc.Code and RDCDesc.Type_ = 60.                                                                  |
| ShortName        | varchar(20)  | Yes      | Shortened name of the quote.                                                                                                                                                  |
| TagCla           | varchar(255) | Yes      | Timeseries Asset Group (TAG) that the quote is in.                                                                                                                            |
| InstrID          | int          | Yes      | Permanent Identifier of the instrument.                                                                                                                                       |
| Mic              | varchar(4)   | Yes      | Market Identification Code.                                                                                                                                                   |
| Opol             | varchar(4)   | Yes      | Official Place of Listing. This is the same as the MIC code and is assigned to the instrument decreed by the LSE to be the Official Place of Listing in a particular country. |
| Ticker           | varchar(25)  | Yes      | Tickers or Symbols related to the Quote.                                                                                                                                      |
| TMTPermID        | varchar(10)  | Yes      | Entity Id for the Thomson Mapping Tool (TMT) Quotation Entity.                                                                                                                |
| GEMPermID        | bigint       | Yes      | Entity Id for the Global Entity Master (GEM) Quotation Entity.                                                                                                                |

## RDCQuoteMLInfo: RDC Multi-Language Quote Information

This table contains multi-language information on LSEG Instrument Codes (RIC).

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields    |
|---------------------------------|-----------------|
| pkey_RDCQuoteMLInfo (clustered) | OrgId, LangCode |

| Field     | Type          | Nullable | Description                                                                                                                                                                                                                            |
|-----------|---------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OrgId     | int           | N        | OrgId is the permanent identifier of the organization.                                                                                                                                                                                 |
| LangCode  | tinyint       | N        | The code associated with the particular language.                                                                                                                                                                                      |
| ComName   | nvarchar(220) | Y        | ComName is the name of the organization in mixed case, manually limited to 80 characters to meet OptionX requirements. The organization's legal name is used to populate this field when the legal name does not exceed 80 characters. |
| ShortName | nvarchar(40)  | Y        | Shortened name of the quote.                                                                                                                                                                                                           |
| Ticker    | nvarchar(50)  | Y        | Tickers or Symbols related to the Quote.                                                                                                                                                                                               |

## RDCGSecMapX: Global RDC Security Map

This table provides mapping to all available vendor codes including ranking and time series.

**Update Cycle:** Daily

**Adjusted:** N/A

| Indexes          |  | Index Fields           |  |
|------------------|--|------------------------|--|
| pkey_RDCGSecMapX |  | SecCode, VenType, Rank |  |

  

| Field     | Type     | Nullable | Description                                                                                                                                                                                           |
|-----------|----------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SecCode   | int      | N        | SecCode links across the master tables.                                                                                                                                                               |
| VenType   | smallint | N        | VenType is a unique type code for each vendor. VenType is defined in SecVenType.                                                                                                                      |
| VenCode   | int      | Y        | VenCode is the corresponding vendor's unique code. For RDC, VenType = 55.                                                                                                                             |
| Rank      | smallint | N        | Rank is the issue rank for issuers with multiple issues.<br><b>Note:</b> Ranking is determined upon initial load, and will not necessarily change in response to new issues or volume/status changes. |
| Exchange  | smallint | Y        | (Reserved for future development.)                                                                                                                                                                    |
| StartDate | datetime | Y        | StartDate is the first date issuer information is valid.                                                                                                                                              |
| EndDate   | datetime | Y        | EndDate is the last date issuer information is valid.                                                                                                                                                 |

## RDCCusipData: RDC Cusip Data

The RDCCusipData table will store all the current and historic Cusip values for an instrument.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                       |  | Index Fields                               |  |
|-------------------------------|--|--------------------------------------------|--|
| pkey_RDCCusipData (Clustered) |  | InstrID, Item, SeqNo, StartDate, StartTime |  |

  

| Field      | Type       | Nullable | Description                                                                                         |
|------------|------------|----------|-----------------------------------------------------------------------------------------------------|
| InstrID    | int        | N        | Primary Identifier of the entity.                                                                   |
| Item       | int        | N        | Integer unique identifier to uniquely identify each business entity property (attribute).           |
| SeqNo      | smallint   | N        | Sequence Number in case the entity has multiple entries.                                            |
| StartDate_ | datetime   | N        | The date from which validity of the attribute value begins.                                         |
| StartTime  | int        | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate    | datetime   | Y        | The date when validity of the attribute value ends.                                                 |
| EndTime    | int        | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_     | Varchar(9) | Y        | This will hold cusip/cincusip value with and without the checkdigit.                                |

## RDCDTData: RDC Date Time Data

The RDCDTData table stores the date and time details for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |          | Index Fields          |                                                                                |
|-----------------------------|----------|-----------------------|--------------------------------------------------------------------------------|
| pkey_ RDCDTData (Clustered) |          | EntityID, Item, SeqNo |                                                                                |
| Field                       | Type     | Nullable              | Description                                                                    |
| EntityID                    | int      | N                     | Primary Identifier of the entity.                                              |
| Item                        | int      | N                     | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo                       | smallint | N                     | Sequential number in cases where the entity has multiple entries.              |
| DateValue_                  | int      | Y                     | Date associated with each entity attribute.                                    |
| TimeValue_                  | int      | Y                     | Time associated with each entity attribute.                                    |

## RDCEntityMap: RDC Entity Map

The RDCEntityMap table maintains the relationship between the various entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                        |      | Index Fields                                           |                                                              |
|--------------------------------|------|--------------------------------------------------------|--------------------------------------------------------------|
| pkey_ RDCEntityMap (Clustered) |      | EntityID1, EntityTypeCode1, EntityID2, EntityTypeCode2 |                                                              |
| Field                          | Type | Nullable                                               | Description                                                  |
| EntityID1                      | INT  | N                                                      | Primary Identifier of the first entity in the relationship.  |
| EntityTypeCode1                | INT  | N                                                      | Codified value describing the first business entity.         |
| EntityID2                      | INT  | N                                                      | Primary Identifier of the second entity in the relationship. |
| EntityTypeCode2                | INT  | N                                                      | Codified value describing the second business entity.        |

## RDCFData: RDC Float Data

The RDCFData table stores all the current FLOAT values for the business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                    |      | Index Fields          |                                                                                |
|----------------------------|------|-----------------------|--------------------------------------------------------------------------------|
| pkey_ RDCFData (Clustered) |      | EntityID, Item, SeqNo |                                                                                |
| Field                      | Type | Nullable              | Description                                                                    |
| EntityID                   | int  | N                     | Primary Identifier of the entity.                                              |
| Item                       | int  | N                     | Identifier that uniquely identifies each business entity property (attribute). |

| Field  | Type     | Nullable | Description                                                       |
|--------|----------|----------|-------------------------------------------------------------------|
| SeqNo  | smallint | N        | Sequential number in cases where the entity has multiple entries. |
| Value_ | float    | Y        | Value of each item.                                               |

## RDCHistFData: RDC Historical Float Data

The RDCHistFData table stores all the historical FLOAT values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                        | Index Fields                                |
|--------------------------------|---------------------------------------------|
| pkey_ RDCHistFData (Clustered) | EntityID, Item, SeqNo, StartDate, StartTime |

| Field     | Type     | Nullable | Description                                                                                         |
|-----------|----------|----------|-----------------------------------------------------------------------------------------------------|
| EntityID  | int      | N        | Primary Identifier of the entity.                                                                   |
| Item      | int      | N        | Identifier that uniquely identifies each business entity property (attribute).                      |
| SeqNo     | smallint | N        | Sequential number in cases where the entity has multiple entries.                                   |
| StartDate | datetime | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int      | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime | Y        | The date till which the attribute value is valid.                                                   |
| EndTime   | int      | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_    | float    | Y        | Value of each item.                                                                                 |

## RDCHistLNData: RDC Historical Data

The RDCHistLNData table stores the historical BIG INT values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields                                |
|---------------------------------|---------------------------------------------|
| pkey_ RDCHistLNData (Clustered) | EntityID, Item, SeqNo, StartDate, StartTime |

| Field     | Type     | Nullable | Description                                                                                         |
|-----------|----------|----------|-----------------------------------------------------------------------------------------------------|
| EntityID  | int      | N        | Primary Identifier of the entity.                                                                   |
| Item      | int      | N        | Identifier that uniquely identifies each business entity property (attribute).                      |
| SeqNo     | smallint | N        | Sequential number in cases where the entity has multiple entries.                                   |
| StartDate | datetime | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int      | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |

| Field   | Type     | Nullable | Description                                                                                         |
|---------|----------|----------|-----------------------------------------------------------------------------------------------------|
| EndDate | datetime | Y        | The date till which the attribute value is valid.                                                   |
| EndTime | int      | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_  | bigint   | Y        | Value of each item.                                                                                 |

## RDCHistLSData: RDC Historical Data

The RDCHistLSData table stores the historical LARGE VARCHAR (>40 & <=255) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields                                |
|---------------------------------|---------------------------------------------|
| pkey_ RDCHistLSData (Clustered) | EntityID, Item, SeqNo, StartDate, StartTime |

| Field     | Type         | Nullable | Description                                                                                         |
|-----------|--------------|----------|-----------------------------------------------------------------------------------------------------|
| EntityID  | int          | N        | Primary Identifier of the entity.                                                                   |
| Item      | int          | N        | Identifier that uniquely identifies each business entity property (attribute).                      |
| SeqNo     | smallint     | N        | Sequential number in cases where the entity has multiple entries.                                   |
| StartDate | datetime     | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int          | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime     | Y        | The date till which the attribute value is valid.                                                   |
| EndTime   | int          | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_    | varchar(255) | Y        | Value of each item.                                                                                 |

## RDCHistMLData: RDC Multi-lingual Data

The RDCHistMLData table stores the historical Multi Language values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields                                          |
|---------------------------------|-------------------------------------------------------|
| pkey_ RDCHistMLData (Clustered) | EntityID, Item, SeqNo, LangCode, StartDate, StartTime |

| Field    | Type     | Nullable | Description                                                                    |
|----------|----------|----------|--------------------------------------------------------------------------------|
| EntityID | int      | N        | Primary Identifier of the entity.                                              |
| Item     | int      | N        | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo    | smallint | N        | Sequential number in cases where the entity has multiple entries.              |
| LangCode | tinyint  | N        | The code associated with the particular language.                              |

| Field     | Type           | Nullable | Description                                                                                         |
|-----------|----------------|----------|-----------------------------------------------------------------------------------------------------|
| StartDate | datetime       | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int            | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime       | Y        | The date till which the attribute value is valid.                                                   |
| EndTime   | int            | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_    | nvarchar(1000) | Y        | Value of each item.                                                                                 |

## RDCHistMSData: RDC Historical Data

The RDCHistMSData table stores all the historical MEDIUM VARCHAR (>12 & <=40) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields                                |
|---------------------------------|---------------------------------------------|
| pkey_ RDCHistMSData (Clustered) | EntityID, Item, SeqNo, StartDate, StartTime |

| Field     | Type        | Nullable | Description                                                                                         |
|-----------|-------------|----------|-----------------------------------------------------------------------------------------------------|
| EntityID  | int         | N        | Primary Identifier of the entity.                                                                   |
| Item      | int         | N        | Identifier that uniquely identifies each business entity property (attribute).                      |
| SeqNo     | smallint    | N        | Sequential number in cases where the entity has multiple entries.                                   |
| StartDate | datetime    | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int         | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime    | Y        | The date till which the attribute value is valid.                                                   |
| EndTime   | int         | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_    | varchar(40) | Y        | Value of each item.                                                                                 |

## RDCHistNData: RDC Historical Numeric Data

The RDCHistNData table stores the historical NUMERIC values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                        | Index Fields                                |
|--------------------------------|---------------------------------------------|
| pkey_ RDCHistNData (Clustered) | EntityID, Item, SeqNo, StartDate, StartTime |

| Field    | Type | Nullable | Description                                                                    |
|----------|------|----------|--------------------------------------------------------------------------------|
| EntityID | int  | N        | Primary Identifier of the entity.                                              |
| Item     | int  | N        | Identifier that uniquely identifies each business entity property (attribute). |



| Field     | Type     | Nullable | Description                                                                                         |
|-----------|----------|----------|-----------------------------------------------------------------------------------------------------|
| SeqNo     | smallint | N        | Sequential number in cases where the entity has multiple entries.                                   |
| StartDate | datetime | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int      | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime | Y        | The date till which the attribute value is valid.                                                   |
| EndTime   | int      | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_    | int      | Y        | Value of each item.                                                                                 |

## RDCHistSSData: RDC Historical Data

The RDCHistSSData table stores all the historical SMALL VARCHAR(<=12) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                         | Index Fields                                |
|---------------------------------|---------------------------------------------|
| pkey_ RDCHistSSData (Clustered) | EntityID, Item, SeqNo, StartDate, StartTime |

| Field     | Type        | Nullable | Description                                                                                         |
|-----------|-------------|----------|-----------------------------------------------------------------------------------------------------|
| EntityID  | int         | N        | Primary Identifier of the entity.                                                                   |
| Item      | int         | N        | Identifier that uniquely identifies each business entity property (attribute).                      |
| SeqNo     | smallint    | N        | Sequential number in cases where the entity has multiple entries.                                   |
| StartDate | datetime    | N        | The date from which the attribute value is valid.                                                   |
| StartTime | int         | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate   | datetime    | Y        | The date till which the attribute value is valid.                                                   |
| EndTime   | int         | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_    | varchar(12) | Y        | Value of each item.                                                                                 |

## RDCISINData: RDC ISIN Data

The RDCISINData table will store all the current and historic ISIN values for an instrument.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                       | Index Fields                               |
|-------------------------------|--------------------------------------------|
| pkey_ RDCIsinData (Clustered) | InstrID, Item, SeqNo, StartDate, StartTime |

| Field   | Type | Nullable | Description                       |
|---------|------|----------|-----------------------------------|
| InstrID | int  | N        | Primary Identifier of the Entity. |

| Field      | Type        | Nullable | Description                                                                                         |
|------------|-------------|----------|-----------------------------------------------------------------------------------------------------|
| Item       | int         | N        | Integer unique identifier to uniquely identify each business entity property (attribute).           |
| SeqNo      | smallint    | N        | Sequence Number in case the entity has multiple entries.                                            |
| StartDate_ | datetime    | N        | The date from which validity of the attribute value begins.                                         |
| StartTime  | int         | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| EndDate    | datetime    | Y        | The date when validity of the attribute value ends.                                                 |
| EndTime    | int         | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT. |
| Value_     | varchar(12) | Y        | Holds ISIN and AlternateISIN values.                                                                |

### RDCItem: RDC Item

The RDCItem is an item table which stores all the attributes of all the business entities for the purpose of storing data in time series data table.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                   | Index Fields |
|---------------------------|--------------|
| pkey_ RDCItem (Clustered) | Item         |

| Field          | Type         | Nullable | Description                                                                                                                                                                                                                      |
|----------------|--------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item           | int          | N        | Identifier that uniquely identifies each business entity property (attribute).                                                                                                                                                   |
| EntityTypeCode | int          | Y        | The type of the Entity to which the Item belongs.                                                                                                                                                                                |
| Name_          | varchar(20)  | Y        | Property name for each unique item.                                                                                                                                                                                              |
| Desc_          | varchar(200) | Y        | Short or long description for each item.                                                                                                                                                                                         |
| DataTypeCode   | tinyint      | Y        | Not the TSQL data type but rather items like, percentage, money, text, Boolean, numeric, date/time.                                                                                                                              |
| TableCode      | int          | Y        | Data table in which the item is contained. RDCItem.TableCode cross-references with RDCCode.Code where Type_ = 5.<br>Data table in which the item is contained. Descriptions for TableCode can be found in RDCCode where Type_=5. |
| IsHistory      | tinyint      | Y        | An indicator to determine whether the entity has history values.                                                                                                                                                                 |
| IsMultiOccur   | tinyint      | Y        | An indicator to determine whether multiple occurrences exist.                                                                                                                                                                    |
| IsMultiLang    | tinyint      | Y        | An indicator to determine whether the attribute has values provided in multiple languages.                                                                                                                                       |
| Time_Flag      | tinyint      | Y        | An indicator to determine whether a time value is present along with the date values.                                                                                                                                            |
| CodeNumb       | int          | Y        | The code number assigned in the code table.                                                                                                                                                                                      |

## RDCLNData: RDC Long Numeric Data

The RDCLNData table stores the current BIG INT values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |          | Index Fields          |                                                                                |
|-----------------------------|----------|-----------------------|--------------------------------------------------------------------------------|
| pkey_ RDCLNData (Clustered) |          | EntityID, Item, SeqNo |                                                                                |
| Field                       | Type     | Nullable              | Description                                                                    |
| EntityID                    | int      | N                     | Primary Identifier of the entity.                                              |
| Item                        | int      | N                     | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo                       | smallint | N                     | Sequential number in cases where the entity has multiple entries.              |
| Value_                      | bigint   | Y                     | Value of each item.                                                            |

## RDCLSDData: RDC Long Description Data

The RDCLSDData table stores the current LARGE VARCHAR (>40 & <=255) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                      |              | Index Fields          |                                                                                |
|------------------------------|--------------|-----------------------|--------------------------------------------------------------------------------|
| pkey_ RDCLSDData (Clustered) |              | EntityID, Item, SeqNo |                                                                                |
| Field                        | Type         | Nullable              | Description                                                                    |
| EntityID                     | int          | N                     | Primary Identifier of the entity.                                              |
| Item                         | int          | N                     | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo                        | smallint     | N                     | Sequential number in cases where the entity has multiple entries.              |
| Value_                       | varchar(255) | Y                     | Value of each item.                                                            |

## RDCMSData: RDC Medium Description Data

The RDCMSData table stores the current MEDIUM VARCHAR (>12 & <=40) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |  | Index Fields          |  |
|-----------------------------|--|-----------------------|--|
| pkey_ RDCMSData (Clustered) |  | EntityID, Item, SeqNo |  |

  

| Field    | Type        | Nullable | Description                                                                    |
|----------|-------------|----------|--------------------------------------------------------------------------------|
| EntityID | int         | N        | Primary Identifier of the entity.                                              |
| Item     | int         | N        | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo    | smallint    | N        | Sequential number in cases where the entity has multiple entries.              |
| Value_   | varchar(40) | Y        | Value of each item.                                                            |

## RDCNData: RDC Numeric Data

The RDCNData table stores the current NUMERIC values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                    |  | Index Fields          |  |
|----------------------------|--|-----------------------|--|
| pkey_ RDCNData (Clustered) |  | EntityID, Item, SeqNo |  |

  

| Field    | Type     | Nullable | Description                                                                    |
|----------|----------|----------|--------------------------------------------------------------------------------|
| EntityID | int      | N        | Primary Identifier of the entity.                                              |
| Item     | int      | N        | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo    | smallint | N        | Sequential number in cases where the entity has multiple entries.              |
| Value_   | int      | Y        | Value of each item.                                                            |

## RDCOIQMap: RDC Organization Instrument Quote Mapping

The RDCOIQMap table holds the primary keys for the Org, Instrument and Quote tables.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |  | Index Fields            |  |
|-----------------------------|--|-------------------------|--|
| pkey_ RDCOIQMap (Clustered) |  | OrgId, InstrID, QuoteID |  |

  

| Field    | Type | Nullable | Description                             |
|----------|------|----------|-----------------------------------------|
| OrgId    | int  | N        | Primary Identifier of the organization. |
| hInstrID | int  | N        | Primary Identifier of the instrument.   |
| QuoteID  | int  | N        | Primary Identifier of the quote.        |

## RDCSedolData: RDC SEDOL Data

The RDCSedolData table will store all the current and historic SEDOL values for a Quote.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                        |  | Index Fields                         |  |
|--------------------------------|--|--------------------------------------|--|
| pkey_ RDCSedolData (Clustered) |  | QuoteID, SeqNo, StartDate, StartTime |  |

  

| Field     | Type       | Nullable | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------|------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| QuoteID   | int        | N        | Primary Identifier of the entity.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| SeqNo     | smallint   | N        | Sequence Number in case the entity has multiple entries.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| StartDate | datetime   | N        | The date from which validity of the attribute value begins.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| StartTime | int        | N        | The time from which the attribute value is valid. Displayed in seconds-from-midnight format in GMT.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| EndDate   | datetime   | Y        | The date when validity of the attribute value ends.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| EndTime   | int        | Y        | The time till which the attribute value is valid. Displayed in seconds-from-midnight format in GMT.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Sedol6    | varchar(6) | Y        | Market level United Kingdom Code. The London Stock Exchange (LSE) allocates SEDOL (Stock Exchange Daily Official List) codes. The LSE introduced MIC and OPOL codes in 2004 and now attach SEDOL codes to regional quotations. Clients can now identify individual market-level quotes using a combination of SEDOL and MIC and identify the Official Place of Listing by using the OPOL. Note that FI SEDOLS are still stored at issue level (and not in this property). In order to catch the SEDOL for all quotes, consumers should use this and the SedolSecondaryQuote property. Truncated to 6 characters. |
| Sedol     | varchar(7) | Y        | This stores SEDOL without any truncation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

## RDCSSData: RDC Small Description Data

The RDCSSData table stores all the current SMALL VARCHAR (<=12) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                     |  | Index Fields          |  |
|-----------------------------|--|-----------------------|--|
| pkey_ RDCSSData (Clustered) |  | EntityID, Item, SeqNo |  |

  

| Field    | Type        | Nullable | Description                                                                    |
|----------|-------------|----------|--------------------------------------------------------------------------------|
| EntityID | int         | N        | Primary Identifier of the entity.                                              |
| Item     | int         | N        | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo    | smallint    | N        | Sequential number in cases where the entity has multiple entries.              |
| Value_   | varchar(12) | Y        | Value of each item.                                                            |

## RDCXLSData: RDC Extra Large Description Data

The RDCXLSData table stores the current EXTRA LARGE VARCHAR (>255) values for all business entities.

**Update Cycle:** One hour

**Adjusted:** N/A

| Indexes                      | Index Fields          |
|------------------------------|-----------------------|
| pkey_ RDCXLSData (Clustered) | EntityID, Item, SeqNo |

| Field    | Type          | Nullable | Description                                                                    |
|----------|---------------|----------|--------------------------------------------------------------------------------|
| EntityID | int           | N        | Primary Identifier of the entity.                                              |
| Item     | int           | N        | Identifier that uniquely identifies each business entity property (attribute). |
| SeqNo    | smallint      | N        | Sequential number in cases where the entity has multiple entries.              |
| Value_   | varchar(1000) | Y        | Value of each item.                                                            |

Copyright © 2023 London Stock Exchange Group plc and its group of companies (LSEG) and/or its affiliates. All rights reserved. The LSEG content received through this service is the intellectual property of LSEG or its third party suppliers. Republication or redistribution of content provided by LSEG is expressly prohibited without the prior written consent of LSEG, except where permitted by the terms of the relevant LSEG service agreement. Neither LSEG nor its third party suppliers shall be liable for any errors, omissions or delays in content, or for any actions taken in reliance thereon. LSEG and its logo are trademarks of LSEG.

For more information visit us at [www.lseg.com](https://www.lseg.com)



**LSEG** DATA &  
ANALYTICS