

LSEG Quantitative Analytics

Database Schema for The Reference Business
Classification (TRBC) Data

Version 1.1.4



Contents

1 Introduction.....	3
In This Document.....	3
Intended Readership.....	3
Table Name Conventions	3
Pervasive and Oracle.....	3
Zero Values and Nulls.....	4
Service and Support	4
Feedback	5
Your Personal Information	5
2. The Reference Business Classification (TRBC) Tables	6
Mapping Logic.....	6
RDCCode: Numeric Codes.....	6
RDCCDesc: Character Code Descriptions	6
RDCOrgAddr: Address and Contact Information	7
RDCOrgInfo: Organization Information	7
RDCTRBCAudit: TRBC Audit Trail	9
RDCTRBCData: TRBC Primary Codes	9
RDCTRBCInfo: TRBC Item Information.....	10
RDCTRBCInfoChg: TRBC Item Information Changes	10
RDCTRBCMap: TRBC Mapping Information	11
RDCInstrInfo: Instrument Level Information	11
RDCSecMapX: RDC Security Map	12
RDCGSecMapX: Global RDC Security Map.....	13
3. SQL Views	14
vw_TRBCMapping	14
vw_TRBCHistory.....	14
vw_TRBCOrgInfo.....	16
vw_TRBCInstrInfo	17

1 Introduction

In This Document

This document provides schema information about the **The Reference Business Classification (TRBC)** data tables in Quantitative Analytics.

NOTE

For information about the other Quantitative Analytics tables, refer to the other Database Schema documents posted on the [Quantitative Analytics](#) product page on [MyAccount](#).

The documentation for each table includes these main elements:

- **Vendor Database or License Name** – This element provides the vendor database or license name. Vendor databases generally correspond to vendor licensing options.
- **Table Name: Table Title** – This element provides the table name and title, followed by a description of the table contents.
- **Update Cycle** – This element indicates the frequency of updates from the data vendor. (For specific information about when this update is posted for your use, refer to your update logs. The update log schema description is available in the Database Schema for Quantitative Analytics Core Tables document.)
- **Adjusted** – This element indicates whether the data is stored adjusted, unadjusted, or if adjustment is not applicable (N/A).
- **Indexes, Index Fields** – This element lists the table's index(es) (for example, pkey_CSGCAD) and the index fields. The primary index contains a "pkey_" or "PK_" prefix. Clustered indexes are noted.
- **Field, Type, Nullable, Definition** – This element describes the table's fields, including field names, data types, and whether each field is nullable. The data types in Snowflake have equivalents available. For example, an *int* in SQL Server is a *number* in Snowflake.

Intended Readership

This document is intended for Quantitative Analytics clients licensed to use **The Reference Business Classification (TRBC)** data through LSEG. Note that the tables described in this document may be covered by several licenses; your access to the data in these tables is dependent on the licenses you have. Readers should have basic knowledge of Microsoft SQL Server 2016.

Table Name Conventions

In Quantitative Analytics, database tables are grouped by name. Generally, the first few letters of the table name refer to the data vendor or licensing group. For example, all tables that begin with **RDCTRBC*** are **The Reference Business Classification (TRBC)** data tables.

Pervasive and Oracle

This document is specific to Microsoft SQL Server 2016. If you are accessing the data directly through the Pervasive database, you may encounter slight differences in index names and data types. Please note that references to Pervasive and Actian are synonymous.

If you are accessing the data through Oracle, note that field names that correspond to Oracle reserved words are appended with an underscore. For example, field names "Number", "Synonym", and "UID" become "Number_", "Synonym_", and "UID_" in Oracle.

Zero Values and Nulls

Null values are usually recorded as “NULL”. Occasionally, a table may contain a value of “-99999” or “-9999”; in these cases, there is no recorded data for that period. (It is null.) If the table contains a “0” value, the data was reported as having a “0” value.

Service and Support

[MyAccount](#) is the LSEG portal that provides a single access point for timesaving support services, along with billing, user management, and information.

Statement of Service

The [Quantitative Analytics Service Description](#) is available on the [Quantitative Analytics](#) product page at MyAccount.

Subscribe to Support Channels

You are encouraged to [subscribe](#) to the following support channels to keep informed of changes to products and data, and to be notified of any service issues or change. Please see the *Alerts and Notifications* section in the *Quantitative Analytics Service Description*, available on the [Quantitative Analytics](#) product page at MyAccount for detailed instructions.

– Change Notifications

- **Product Change Notifications (PCNs)** detail new, enhanced, or changed functionality, which may require your action, in products that you use.
- **Data Notifications (DNs)** alert you to upcoming changes to real-time and historical data across all asset classes that are relevant to you.
- **RIC Change Events** inform you of planned changes to RICs. RIC is the market level identifier key unique to LSEG used to identify securities.

– Service Alerts

Alert you about planned maintenance and unplanned service issues affecting your products and services, and be notified via SMS or email.

Documentation

You can access product documentation on the [Quantitative Analytics](#) product page at MyAccount.

Get Support

For support using Quantitative Analytics, please use one of the following methods:

Online

Access [Get Support](#) either via the blue [Get Support](#) button at the top right of each page or by selecting *Get Support* located under *Help and Support* on the left navigation pane at MyAccount.

From the *Get Support* page, choose *Get Product and Content Support* and then select the appropriate category from the next page. Complete the request making sure to include the following:

- Under Product, select Quantitative Analytics from the dropdown list.
- In the **How can we help you?** text box, include the following information:
 - Content set name (i.e. Worldscope)
 - Date applicable to a content inquiry
 - Table names and relevant fields
 - Security code (i.e. QA-ID, PermID, Sedol, InfoCode, etc.)
 - Script used to generate the output
 - Any other supporting detail

Telephone

Region	Telephone	Options
AMERS	+01 866 427 8390	Option 1 – Product Support Option 2 – Technical Support
EMEA	+44 203 341 1036	
APAC	+65 6403 7436	

Feedback

We invite your comments, corrections, and suggestions about this document: access the [Feedback](#) option under [Get Support](#) at MyAccount. Your feedback helps us continue to improve our user assistance.

Your Personal Information

LSEG is committed to the responsible handling and protection of personal information. We invite you to review our [Privacy Statement](#), which describes how we collect, use, disclose, transfer, and store personal information when needed to provide our services and for our operational and business purposes.

2. The Reference Business Classification (TRBC) Tables

Mapping Logic

To map from Quantitative Analytics SecCode to TRBC OrgID, use the following mapping logic:

- **Domestic securities:** SecMstrX.SecCode → RDCSecMapX.SecCode where VenType = 49 → RDCSecMapX.VenCode → RDCInstrInfo.InstrID → RDCInstrInfo.OrgID → RDCTRBCData.OrgID
- **Global securities:** GSecMstrX.SecCode → RDCGSecMapX.SecCode where VenType = 49 → RDCGSecMapX.VenCode → RDCInstrInfo.InstrID → RDCInstrInfo.OrgID → RDCTRBCData.OrgID

RDCCode: Numeric Codes

This table contains descriptions of Reference Data Convergence (RDC) numeric codes.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes		Index Fields	
pkey_RDCCode (Clustered)		Type_, Code	
Field	Type	Nullable	Description
Type_	int	N	Type_ is a numeric code for a type of data.
Code	int	N	Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_.
Desc_	varchar(255)	Y	Desc_ is a plain-language description of the element defined by Type_ and Code.

RDCDesc: Character Code Descriptions

This table contains descriptions of Reference Data Convergence (RDC) character codes.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes		Index Fields	
pkey_RDCDesc (Clustered)		Type_, Code	
Field	Type	Nullable	Description
Type_	int	N	Type_ is a numeric code for a type of data.
Code	varchar(50)	N	Code is a coded value for an element of Type_. When Type_ = 0, Code is the numeric code for each Type_ other than 0 and Desc_ is a description of each Type_.
Desc_	varchar(255)	Y	Desc_ is a plain-language description of the element defined by Type_ and Code.

RDCOrgAddr: Address and Contact Information

This table contains the address and contact information of an organization.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes			Index Fields
pkey_RDCOrgAddr (Clustered)			OrgId
Field	Type	Nullable	Description
OrgId	int	N	OrgId is the permanent identifier of the organization.
AddrTypeCode	char(2)	Y	AddrTypeCode is the address type of the organization. AddrTypeCode can be: – TR = Trading – MK = Marketing – RG = Registered – HQ = Headquarters RDCOrgAddr.AddrTypeCode cross-references with RDCDesc.Code where Type_ = 80948.
EmailId	varchar(255)	Y	EmailId is the e-mail address of the organization.
FaxNo	varchar(75)	Y	FaxNo is the fax number.
IndiEmailId	varchar(255)	Y	IndiEmailId is the e-mail address of the individual.
IndiFaxNo	varchar(75)	Y	IndiFaxNo is the fax number of the individual.
IndiName	varchar(110)	Y	IndiName is the contact name of the individual.
IndiTelNo	varchar(75)	Y	IndiTelNo is the telephone number of the individual.
PostalCode	varchar(10)	Y	PostalCode is the first line of an address, excluding county, zip code, and country.
StateCntry	varchar(90)	Y	StateCntry is the state or country in the address.
StrAddr	varchar(255)	Y	StrAddr is the first line of an address, excluding county, zip code, and country.
CityTown	varchar(90)	Y	CityTown is the city or town of an address.
TelNo	varchar(75)	Y	TelNo is the telephone number.
TollFreeNo	varchar(75)	Y	TollFreeNo is the toll free number of the organization.
WebAddr	varchar(255)	Y	WebAddr is the organization's Web site.

RDCOrgInfo: Organization Information

This table contains information for organizations of interest in the capital markets.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes			Index Fields
pkey_RDCOrgInfo (Clustered)			OrgId
Field	Type	Nullable	Description
OrgId	int	N	OrgId is the permanent identifier of the organization.
ComName	varchar(110)	Y	ComName is the name of the organization in mixed case, manually limited to 80 characters to meet OptionX requirements. The organization's legal name is used to populate this field when the legal name does not exceed 80 characters.
LegalName	varchar(255)	Y	LegalName is the fully registered legal name of the company, or the official name of the institution.

Field	Type	Nullable	Description
ShortName	varchar(40)	Y	ShortName is the short name of the organization in mixed case (unless it is a recognized acronym entered in uppercase, such as IBM for International Business Machines Corp), manually limited to a maximum of 16 characters.
OrgStatus	char(2)	Y	OrgStatus is the role-to-issue status of the organization. It can have the following values: – AC = Active – DC = Inactive Values are to be populated automatically, according to the type of organization. Values are never populated or maintained manually.
ContriCode	varchar(20)	Y	ContriCode is the code used to identify organizations contributing data (usually quotes) to the real-time Integrated Data Network. (IDN). RDCOrgInfo.ContriCode cross-references with RDCDesc.Code where Type_ = 27035.
ContriTypeCode	char(3)	Y	ContriTypeCode is the classifier of the contributing organization. ContriTypeCode can be bank or broker. RDCOrgInfo.ContriTypeCode cross-references with RDCDesc.Code where Type_ = 110661.
CISiteLocCode	varchar(20)	Y	CISiteLocCode uniquely identifies the contributor. The code is comprised of the country code, followed by a generated sequence number of the contributor in that country. RDCOrgInfo.CISiteLocCode cross-references with RDCDesc.Code where Type_ = 114785.
CntryHQISOCCode	char(3)	Y	CntryHQISOCCode is the geographical headquarters of the organization. RDCOrgInfo.CntryHQISOCCode cross-references with RDCDesc.Code where Type_ = 27165.
CntryOfIncCode	char(3)	Y	CntryOfIncCode is the country in which the party received its charter, allowing it to operate as a corporation. If the country of incorporation is not disclosed, or if the company is not a corporation, then this would be populated the same as the current country or where the company was formed. RDCOrgInfo.CntryOfIncCode cross-references with RDCDesc.Code where Type_ = 30986.
ISOCurrCode	char(3)	Y	ISOCurrCode is the currency of record of the fund entity. RDCOrgInfo.ISOCurrCode cross-references with RDCDesc.Code where Type_ = 80867.
OrgTypeCode	varchar(5)	Y	OrgTypeCode is described in the OrgTypeCode section on page 8.
DFlag	int	Y	DFlag stores a bitmasked combination for the IsContributor, IsExch, and IsFundSupCmp data items.

OrgTypeCode

OrgTypeCode is the organization type. It can be:

Code	Description
CO	Corporation
FD	Fund
GA	Government Agency
GP	State & Provincial
GT	Government
SP	Supranational
CF	Closed End Fund (not used)
OF	Open End Fund (not used)
NC	Not Categorized
PC	Private Corporation

Code	Description
CTLB	Central Bank
MUNI	Municipal
TREA	Treasury
PS	Pseudo Organization

RDCTRBCAudit: TRBC Audit Trail

This data table contains audit trail for any change in TRBC assignments.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes	Index Fields
pkey_RDCTRBCAudit (Clustered)	OrgId, AuditCode, StartDate, StartTime

Field	Type	Nullable	Description
OrgId	int	N	OrgId is the permanent identifier of the organization entity.
AuditCode	int	N	AuditCode represents the change type for TRBC assignments: – GRO: Internal growth (business) – MAA: M&A (business) – DIV: Divestiture (business) – DIS: Discontinuation (business) – SCH: Change in schema – ERR: Error Correction – REV: Review RDCTRBCAudit.AuditCode cross-references with RDCCCode.Code where Type_ = 115371.
StartDate	datetime	N	StartDate is the date on which the validity of the attribute value begins.
StartTime	int	N	StartTime is the time when the validity of the attribute value begins.
EndDate	datetime	Y	EndDate is the date on which the validity of the attribute value ends.
EndTime	int	Y	EndTime is the time when the validity of the attribute value ends.

RDCTRBCData: TRBC Primary Codes

This table contains the current and historic TRBC primary codes for an organization.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes	Index Fields
pkey_RDCTRBCData (Clustered)	OrgId, TRBCId, StartDate, StartTime

Field	Type	Nullable	Description
OrgId	int	N	OrgId is the permanent identifier of the organization entity.
TRBCId	smallint	N	TRBCId identifies each business entity property.
StartDate	datetime	N	StartDate is the date on which the validity of the attribute value begins.
StartTime	int	N	StartTime is the time when the validity of the attribute value begins.
EndDate	datetime	Y	EndDate is the date on which the validity of the attribute value ends.
EndTime	int	Y	EndTime is the time when the validity of the attribute value ends.
IsPrimary	tinyint	Y	IsPrimary indicates if TRBCId is the primary classification.

RDCTRBCInfo: TRBC Item Information

This table contains TRBC item information.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes			Index Fields
pkey_RDCTRBCInfo (Clustered)			TRBCId
Field	Type	Nullable	Description
TRBCId	smallint	N	TRBCId identifies each business entity property. This field cross-references with RDCTRBCData .TRBCId.
TRBCGrpId	tinyint	Y	TRBCGrpId is the business entity to which each item belongs.
HierarchicalId	bigint	Y	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC).
Mnemonic	varchar(5)	Y	Mnemonic is the char code assigned by RDC.
ShortTitle	varchar(255)	Y	ShortTitle is the short property name for each item.
Title	varchar(255)	Y	Title is the property name for each item.
ShortDesc	varchar(350)	Y	ShortDesc is the short description for each item.
LongDesc	varchar(960)	Y	LongDesc is the long description for each item.

RDCTRBCInfoChg: TRBC Item Information Changes

This table contains information on changes to the TRBC Ids.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes			Index Fields
pkey_RDCTRBCInfo (Clustered)			TRBCId, StartDate
Field	Type	Nullable	Description
TRBCId	smallint	N	TRBCId identifies each business entity property. This field cross-references with RDCTRBCData .TRBCId.
StartDate	datetime	N	
EndDate	datetime	N	
TRBCGrpId	tinyint	Y	TRBCGrpId is the business entity to which each item belongs.
HierarchicalId	bigint	Y	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC).
Mnemonic	varchar(5)	Y	Mnemonic is the char code assigned by RDC.
ShortTitle	varchar(255)	Y	ShortTitle is the short property name for each item.
Title	varchar(255)	Y	Title is the property name for each item.
ShortDesc	varchar(350)	Y	ShortDesc is the short description for each item.
LongDesc	varchar(960)	Y	LongDesc is the long description for each item.

RDCTRBCMap: TRBC Mapping Information

TRBC uses a 5-level hierarchical system with 10 economic sectors, 28 business sectors, 54 industry groups, 136 industries, and 837 Activity codes. This table captures the association between all levels.

An Activity is a new, more granular industry level within TRBC. For the first time users will have an investment focused alternative to NAICS and SIC codes.

Update Cycle: Full refresh is available weekly. Incremental updates from RDC are available every 15 minutes.

Adjusted: N/A

Indexes		Index Fields	
pkey_RDCTRBCMap (Clustered)		ActTRBCId	

Field	Type	Nullable	Description
ActTRBCId	smallint	N	ActTRBCId is the relevant activity code derived from RDCTRBC* tables.
IndTRBCId	smallint	Y	IndTRBCId is the relevant industry sector derived from RDCTRBC* tables.
IndGrpTRBCId	smallint	Y	IndGrpTRBCId is the relevant industry group derived from RDCTRBC* tables.
BusTRBCId	smallint	Y	BusTRBCId is the relevant business sector derived from RDCTRBC* tables.
EcoTRBCId	smallint	Y	EcoTRBCId is the relevant economic sector derived from RDCTRBC* tables.

RDCInstrInfo: Instrument Level Information

This data table contains financial instruments and indicators with reference and descriptive information provided at the issue and contract level.

Update Cycle: Daily

Adjusted: N/A

Indexes		Index Fields	
pkey_RDCInstrInfo (Clustered)		InstrID	

Field	Type	Nullable	Description
InstrID	int	N	InstrID is the Permanent Identifier of the instrument.
InstrStatusCode	char(2)	Y	For non-debt issues, if an issue asset/instrument has at least one quote that is active (AssetState = 'AC'), then AssetState is Active 'AC'. If all quote assets are deactivated (AssetState = 'DC'), then AssetState is Deactivated 'DC'. AssetState is derived for all asset types except debt issues that are maintained by the DBS forward feed. AssetState is 'NA' (Not Applicable) when no quote asset is found against the issue/instrument. In particular, new issues get 'NA' status as soon as they are created and until a quote is assigned to them. NA also applies to instruments not properly classified. States other than AC, DC, and NA are only set for fixed income issues. The full set of states is: – "CA" = "Called" – "DE" = "Defaulted" – "EX" = "Exchanged" – "ME" = "Merged" – "MA" = "Matured" – "RE" = "Redenominated" – "AC" = "Active" – "DC" = "De-activated" – "NA" = "Not applicable"
ComName	varchar(110)	Y	In most instances, ComName is not populated, except for equity indices and warrants sourced from DBS.

Field	Type	Nullable	Description
InstrCatCode	char(4)	Y	InstrCatCode is the two-level hierarchical asset classification scheme. Wherever possible, an asset is given a category from the lower level in the hierarchy. This field is always mapped to AssetType.
InstrType	varchar(40)	Y	InstrType is the single-level, broad asset classification scheme, used principally as an internal scheme for time series classification. This field is always mapped to the more granular AssetCategory scheme.
IssueISOCurrCode	char(3)	Y	IssueISOCurrCode is derived according to logic from the following fields: – Valuation Quote's Base Currency for Equity Issues – Principal Currency for Fixed Income (Debt) Issues – Quote Asset's Quotation Currency for Warrant Issues The issue currency data is system-driven. It is a derived attribute that is not able to be updated by applications. It will be updated by changes to the source fields (the currency held in either Valuation Quote Currency or Principal Currency fields). All changes made to these fields will trigger a matching change to be made to IssueISOCurrCode. RDCInstrInfo.IssueISOCurrCode cross-references with RDCDesc.Code where Type_ = 80867.
IsCDSCnv	tinyint	Y	IsCDSCnv is the most liquid contract for doc clause and currency.
MifidStatusCode	varchar(8)	Y	MifidStatusCode indicates whether the security is subject to MIFID regulation: – MIFID-U: Mifid unconfirmed security – MIFID-E: Mifid eligible security – MIFID-L: Mifid top liquidity security
MostReleMrkt	char(3)	Y	MostReleMrkt references the country where the instrument was first admitted to trading on a regulated market.
RCSAssetCla	varchar(10)	Y	RCSAssetCla is the Reference Classification Scheme classification.
ShortName	varchar(20)	Y	ShortName is not mandatory for Issue Assets. This field may hold a value for some debt and commodities instruments (sourced from DBS and CMI respectively). No formal standard has been set.
OrgID	int	Y	OrgID is the permanent identifier of the organization.
PrimTrdQuotePI	int	Y	PrimTrdQuotePI is similar to the VQ, but the tradable RIC is used. This is very US-specific where market cap for the issue must be calculated on a consolidated quote that is not a RIC you can trade. Therefore, PrimTrdQuotePI exists to denote the main "primary" quote of a multi-listed share line in the US that can be traded.
TMTPermlId	varchar(10)	Y	TMTPermlId is the permanent Identifier of the Instrument in the TMT/TKO Database.
GemPermlId	bigint	Y	GemPermlId is the unique entity ID for the Instrument Entity. This field is currently sourced from GEM.

RDCSecMapX: RDC Security Map

This table provides mapping to vendor codes including ranking and time series.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_RDCSecMapX (Clustered)	SecCode, VenType, Rank

Field	Type	Nullable	Description
SecCode	int	N	SecCode links across the master tables.

Field	Type	Nullable	Description
VenType	smallint	N	VenType is a unique type code for each vendor. VenType is defined in SecVenType. For RDC, VenType = 49.
VenCode	int	Y	VenCode is the corresponding vendor's unique code.
Rank	smallint	N	Rank is the issue rank for issuers with multiple issues. Note: Ranking is determined upon initial load, and will not necessarily change in response to new issues or volume/status changes.
Exchange	smallint	Y	Exchange identifies whether the security is a United States security (1) or a Canadian security (2). A value of 0 indicates that this field is not applicable.
StartDate	datetime	Y	StartDate is the first date issuer information is valid.
EndDate	datetime	Y	EndDate is the last date issuer information is valid.

RDCGSecMapX: Global RDC Security Map

This table provides mapping to all available vendor codes including ranking and time series.

Update Cycle: Daily

Adjusted: N/A

Indexes	Index Fields
pkey_RDCGSecMapX	SecCode, VenType, Rank

Field	Type	Nullable	Description
SecCode	int	N	SecCode links across the master tables.
VenType	smallint	N	VenType is a unique type code for each vendor. VenType is defined in SecVenType.
VenCode	int	Y	VenCode is the corresponding vendor's unique code. For RDC, VenType = 49.
Rank	smallint	N	Rank is the issue rank for issuers with multiple issues. Note: Ranking is determined upon initial load, and will not necessarily change in response to new issues or volume/status changes.
Exchange	smallint	Y	(Reserved for future development.)
StartDate	datetime	Y	StartDate is the first date issuer information is valid.
EndDate	datetime	Y	EndDate is the last date issuer information is valid.

3. SQL Views

The SQL Views provide simplified calls that run complex SQL code and address key data nuances and mapping requests in the LSEG Quantitative Analytics database, making it much easier to access data through LSEG Quantitative Analytics.

Customers are able to see the underlying SQL code and modify/customize it as required, as well as being able to save the modified code as their proprietary code.

The LSEG Support Team is available to provide training on the library structure and how to use the SQL Views. Please contact [Support](#) if you would like the SQL views added to your server.

vw_TRBCMapping

This view provides the mapping for TRBC.

Index Fields			
SecCode, Typ			
Field	Type	Nullable	Description
IsrCode	int	YES	IsrCode is the issue's issuer code. Cross-reference with Prc.Prclsr where Prc.Prclss.isrcode = Prc.Prclsr.isrcode.
SecCode	int	NO	SecCode links across the master tables.
Typ	int	NO	6 for Global and 1 for North America.
orgID	int	YES	OrgID is the permanent identifier of the organization.
IssueVenCode	int	YES	VenCode is the corresponding vendor's unique code (Issue level).

Example Use Case:

```
--This query shows the TRBC mapping for QAID @honda9
select *
from vw_SecurityMasterX aa
join vw_TRBCMapping bb
  on bb.seccode = aa.seccode
  and bb.typ = aa.typ
where aa.id = '@HONDA9'
```

vw_TRBCHistory

This view provides the historical TRBC codes for OrgIDs.

Index Fields			
OrgID, TRBCID, StartDate			
Field	Type	Nullable	Description
OrgID	int	NO	OrgID is the permanent identifier of the organization.
TRBCID	smallint	NO	TRBCID identifies each business entity property.
HierarchicalID	bigint	YES	HierarchicalID is the numeric code assigned by Reference Data Convergence (RDC).
StartDate	datetime	YES	The start date of the record.
EndDate	datetime	YES	The end date of the record.

Field	Type	Nullable	Description
EcoSectCode	bigint	YES	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC) (Economic sector level).
EcoMnemonic	varchar	YES	Mnemonic is the char code assigned by RDC (Economic sector level).
EcoShortTitle	varchar	YES	ShortTitle is the short property name for each item (Economic sector level).
EconomicSector	varchar	YES	Title is the property name for each item (Economic sector level).
EcoShortDesc	varchar	YES	ShortDesc is the short description for each item (Economic sector level).
EcoLongDesc	varchar	YES	LongDesc is the long description for each item (Economic sector level).
BusSectCode	bigint	YES	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC) (Business sector level).
BusMnemonic	varchar	YES	Mnemonic is the char code assigned by RDC (Business sector level).
BusShortTitle	varchar	YES	ShortTitle is the short property name for each item (Business sector level).
BusinessSector	varchar	YES	Title is the property name for each item (Business sector level).
BusShortDesc	varchar	YES	ShortDesc is the short description for each item (Business sector level).
BusLongDesc	varchar	YES	LongDesc is the long description for each item (Business sector level).
IndGrpCode	bigint	YES	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC) (Industry group level).
IndGrpMnemonic	varchar	YES	Mnemonic is the char code assigned by RDC (Industry group level).
IndGrpShortTitle	varchar	YES	ShortTitle is the short property name for each item (Industry group level).
IndustryGroup	varchar	YES	Title is the property name for each item (Industry group level).
IndGrpShortDesc	varchar	YES	ShortDesc is the short description for each item (Industry group level).
IndGrpLongDesc	varchar	YES	LongDesc is the long description for each item (Industry group level).
IndCode	bigint	YES	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC) (Industry level).
IndMnemonic	varchar	YES	Mnemonic is the char code assigned by RDC (Industry level).
IndShortTitle	varchar	YES	ShortTitle is the short property name for each item (Industry level).
Industry	varchar	YES	Title is the property name for each item (Industry level).
IndShortDesc	varchar	YES	ShortDesc is the short description for each item (Industry level).
IndLongDesc	varchar	YES	LongDesc is the long description for each item (Industry level).
ActCode	bigint	YES	HierarchicalId is the numeric code assigned by Reference Data Convergence (RDC) (Activity level).
ActMnemonic	varchar	YES	Mnemonic is the char code assigned by RDC (Activity level).
ActShortTitle	varchar	YES	ShortTitle is the short property name for each item (Activity level).
Activity	varchar	YES	Title is the property name for each item (Activity level).
ActShortDesc	varchar	YES	ShortDesc is the short description for each item (Activity level).
ActLongDesc	varchar	YES	LongDesc is the long description for each item (Activity level).

Example Use Case:

```
--This query shows the TRBC history for QAID @HONDA9
```

```
select aa.*, cc.*
from vw_SecurityMasterX aa
```

```

join vw_TRBCMapping bb
  on bb.seccode = aa.seccode
  and bb.typ = aa.typ
join vw_TRBCHistory cc
  on cc.OrgId = bb.OrgID
where aa.id = '@HONDA9'
order by cc.StartDate

```

vw_TRBCOrgInfo

This view provides the basic information for each OrgID.

Index Fields			
OrgID			
Field	Type	Nullable	Description
OrgId	int	NO	OrgId is the permanent identifier of the organization.
CommonName	varchar	YES	CommonName is the name of the organization in mixed case, manually limited to 80 characters to meet OptionX requirements. The organization's legal name is used to populate this field when the legal name does not exceed 80 characters.
LegalName	varchar	YES	LegalName is the fully registered legal name of the company, or the official name of the institution.
ShortName	varchar	YES	ShortName is the short name of the organization in mixed case (unless it is a recognized acronym entered in uppercase, such as IBM for International Business Machines Corp), manually limited to a maximum of 16 characters.
orgStatus	varchar	YES	OrgStatus is the role-to-issue status of the organization. It can have the following values: • AC = Active • DC = Inactive. Values are to be populated automatically, according to the type of organization. Values are never populated or maintained manually.
CntryHQISOCCode	char	YES	CntryHQISOCCode is the geographical headquarters of the organization.
CntryHQ	varchar	YES	The description of CntryHQISOCCode.
CntryOfIncCode	char	YES	CntryOfIncCode is the country in which the party received its charter, allowing it to operate as a corporation. If the country of incorporation is not disclosed, or if the company is not a corporation, then this would be populated the same as the current country or where the company was formed.
CntryOfInc	varchar	YES	The description of CntryOfIncCode.
ISOCurrCode	char	YES	ISOCurrCode is the currency of record of the fund entity.
Currency	varchar	YES	The description of ISOCurrCode.
OrgTypeCode	varchar	YES	OrgTypeCode is the organization type.
OrgType	varchar	YES	The description of OrgTypeCode.

Example Use Case:

```

--This query shows the basic information for Microsoft
select aa.*, cc.*
from vw_SecurityMasterX aa
join vw_TRBCMapping bb
  on bb.seccode = aa.seccode
  and bb.typ = aa.typ

```



```

join vw_TRBCOrgInfo cc
  on cc.OrgId = bb.OrgID
where aa.id = 'MSFT'

```

vw_TRBCInstrInfo

This view provides the basic information for each InstrID.

Index Fields			
InstrID			
Field	Type	Nullable	Description
InstrID	int	NO	InstrID is the Permanent Identifier of the instrument.
InstrStatusCode	char	YES	For non-debt issues, if an issue asset/instrument has at least one quote that is active (AssetState = 'AC'), then AssetState is Active 'AC'. If all quote assets are deactivated (AssetState = 'DC'), then AssetState is Deactivated 'DC'. AssetState is derived for all asset types except debt issues that are maintained by the DBS forward feed. AssetState is 'NA' (Not Applicable) when no quote asset is found against the issue/instrument. In particular, new issues get 'NA' status as soon as they are created and until a quote is assigned to them. NA also applies to instruments not properly classified. States other than AC, DC, and NA are only set for fixed income issues.
InstrStatus	varchar	YES	The description of InstrStatusCode.
CommonName	varchar	YES	In most instances, ComName is not populated, except for equity indices and warrants sourced from DBS.
InstrType	varchar	YES	InstrType is the single-level, broad asset classification scheme, used principally as an internal scheme for time series classification. This field is always mapped to the more granular AssetCategory scheme.
IssueSOCurrCode	char	YES	IssueSOCurrCode is derived according to logic from the following fields: • Valuation Quote's Base Currency for Equity Issues • Principal Currency for Fixed Income (Debt) Issues • Quote Asset's Quotation Currency for Warrant Issues. The issue currency data is system-driven. It is a derived attribute that is not able to be updated by applications. It will be updated by changes to the source fields (the currency held in either Valuation Quote Currency or Principal Currency fields). All changes made to these fields will trigger a matching change to be made to IssueSOCurrCode. RDCInstrInfo.IssueSOCurrCode cross-references with RDCDesc.Code where Type_ = 80867.
IssueCurrency	varchar	YES	The description of IssueSOCurrCode.
RCSAssetCla	varchar	YES	RCSAssetCla is the Reference Classification Scheme classification.
OrgID	int	YES	OrgID is the permanent identifier of the organization.

Example Use Case:

```

--This query shows the basic information for all the instruments linked to
Microsoft.
select aa.*, cc.*
from vw_SecurityMasterX aa
join vw_TRBCMapping bb
  on bb.seccode = aa.seccode
  and bb.typ = aa.typ
join vw_TRBCInstrInfo cc
  on cc.OrgId = bb.OrgID
where aa.id = 'MSFT'

```

Copyright © 2024 London Stock Exchange Group plc and its group of companies (LSEG) and/or its affiliates. All rights reserved. The LSEG content received through this service is the intellectual property of LSEG or its third party suppliers. Republication or redistribution of content provided by LSEG is expressly prohibited without the prior written consent of LSEG, except where permitted by the terms of the relevant LSEG service agreement. Neither LSEG nor its third party suppliers shall be liable for any errors, omissions or delays in content, or for any actions taken in reliance thereon. LSEG and its logo are trademarks of LSEG.

For more information visit us at www.lseg.com



LSEG DATA &
ANALYTICS