

# biber

A backend bibliography processor for biblatex

Philip Kime, François Charette  
[Philip@kime.org.uk](mailto:Philip@kime.org.uk),  
[firmicus@ankabut.net](mailto:firmicus@ankabut.net)

Version biber 1.7 (biblatex 2.7)  
3rd July 2013

## Contents

<b>1</b>	<b>Important Changes</b>	<b>1</b>	3.4	Logfile . . . . .	29
<b>2</b>	<b>Introduction</b>	<b>2</b>	3.5	Collation and Localisation	30
2.1	About . . . . .	2	3.6	Encoding of files . . . . .	32
2.2	Requirements . . . . .	3	3.7	List and Name Separators	35
2.3	Compatibility Matrix . .	3	3.8	Editor Integration . . . .	36
2.4	License . . . . .	3	3.9	BIB <sub>T</sub> <sub>E</sub> X macros and the MONTH field . . . . .	36
2.5	History . . . . .	3	3.10	Biber datasource drivers	37
2.6	Performance . . . . .	7	3.11	Visualising the Output .	37
2.7	Acknowledgements . . . .	7	3.12	Tool Mode . . . . .	38
<b>3</b>	<b>Use</b>	<b>7</b>	<b>4</b>	<b>Binaries</b>	<b>45</b>
3.1	Options and config file . .	8	4.1	Binary Caches . . . . .	46
3.2	Unicode . . . . .	28	4.2	Binary Architectures . . .	46
3.3	Input/Output File Loca- tions . . . . .	29	4.3	Installing . . . . .	47
			4.4	Building . . . . .	48

## 1 Important Changes

Please see the **Changes** file which accompanies Biber for the details on changes in each version. This section is just for important things like incompatible changes which users should be aware of.

### 1.0

The `--validate_structure` option is now called `--validate_datamodel`

### 0.9.9

The output format option `--graph` has been moved to a new option `--output_format`. The option `--graph` should now be specified as `--output_format=dot` and the `--dot_include` option should be used to specify the elements to include in the DOT output. For example:

```
biber --graph=section,field <file>
```

is now:

```
biber --output_format=dot --dot_include=section,field <file>
```

### 0.9.8

**The `sourcemap` option syntax has changed.** The syntax was too confusing. It is now simplified and more powerful. It uses a sequential processing model to apply mappings to an entry. See section 3.1.1.

### 0.9.7

**The user config file has a completely new format.** The reason for this is that the older `Config::General` format could not be extended to deal with more sophisticated features like per-datasource restrictions. An XML format is much better and in fact easier to understand. The old format of the `map` option (now called `sourcemap`) was rather confusing because of limitations in the old config file format. Please see section 3.1.1 and convert your config files to the new format.

### 0.9.6

**Matching of citation keys and datasource entry keys is now *case-sensitive*.** This is to enforce consistency across the entire BibLaTeX and Biber processing chain. All of the usual referencing mechanisms in LaTeX are case-sensitive and so is the matching in BibLaTeX of citations to entries in the `.bbl` file generated by Biber. It is inconsistent and messy to enforce case-insensitivity in only Biber's matching of citations keys to datasource entry keys. If Biber detects what looks like a case mismatch between citation keys, it will warn you.

**Summary of warnings/errors is now a new format.** When Biber finishes writing the `.bbl`, it gives a summary count of errors/warnings. It used to do this in the same format as BibTeX, for compatibility. Now it uses a more consistent and easier to parse format which matches all other Biber messages. Please note if you need to support Biber in an external tool. I have updated the notes on AUCTEX support below to reflect this.

## 2 Introduction

### 2.1 About

Biber is conceptually a BIBTEX replacement for Biblatex. It is written in Perl with the aim of providing a customised and sophisticated data preparation backend for Biblatex. You do *not* need to install Perl to use Biber—binaries are provided for many operating systems via the main TEX distributions (TEXLive, MacTEX, MiKTEX) and also via download from SourceForge. Functionally, Biber offers a superset of BIBTEX's capabilities but is tightly coupled with Biblatex and cannot

be used as a stand-alone tool with standard `.bst` styles. Biber's role is to support Biblatex by performing the following tasks:

- Parsing data from datasources
- Processing cross-references, entry sets, related entries
- Generating data for name, name list and name/year disambiguation
- Structural validation according to Biblatex data model
- Sorting reference lists
- Outputting data to a `.bb1` for Biblatex to consume

## 2.2 Requirements

Biber is distributed primarily as a stand-alone binary and is included in T<sub>E</sub>XLive, MacT<sub>E</sub>X and MiK<sub>T</sub>E<sub>X</sub>. If you are using any of these distributions, you do not need any additional software installed to use Biber. You do *not* need a Perl installation at all to use the binary distribution of Biber<sup>1</sup>.

Biber's git repository is on github<sup>2</sup>. Biber's documentation, binary downloads and supporting files are on SourceForge<sup>3</sup> and this is the primary location for development releases, forums and bugfixes etc. Biber is included into T<sub>E</sub>XLive, the binaries coming from SourceForge.

## 2.3 Compatibility Matrix

Biber versions are closely coupled with Biblatex versions. You need to have the right combination of the two. Biber will warn you during processing if it encounters information which comes from a Biblatex version which is incompatible. Table 1 shows a compatibility matrix for the recent versions.

## 2.4 License

Biber is released under the free software Artistic License 2.0<sup>4</sup>

## 2.5 History

B<sub>I</sub>B<sub>T</sub>E<sub>X</sub> has been the default (only ...) integrated choice for bibliography processing in T<sub>E</sub>X for a long time. It has well known limitations which stem from its data format, data model and lack of Unicode support<sup>5</sup>. The `.bst` language for writing

---

<sup>1</sup>If you prefer, you can run Biber as a normal Perl program and doing this *does* require you to have a Perl interpreter installed. See section 4.

<sup>2</sup><https://github.com/plk/biber>

<sup>3</sup><http://sourceforge.net/projects/biblatex-biber/>

<sup>4</sup><http://www.opensource.org/licenses/artistic-license-2.0.php>

<sup>5</sup>In fact, there is now a Unicode version

Biber version	Biblatex version
1.6	2.6
1.5	2.5
1.4	2.4
1.3	2.3
1.2	2.1, 2.2
1.1	2.1
1.0	2.0
0.9.9	1.7x
0.9.8	1.7x
0.9.7	1.7x
0.9.6	1.7x
0.9.5	1.6x
0.9.4	1.5x
0.9.3	1.5x
0.9.2	1.4x
0.9.1	1.4x
0.9	1.4x

Table 1: Biber/Biblatex compatibility matrix

bibliography styles is painful to learn and use. It is not a general programming language and this makes it really very hard to do sophisticated automated processing of bibliographies.

Biblatex was a major advance for LaTeX users as it moved much of the bibliography processing into LaTeX macros. However, Biblatex still used BibTeX as a sorting engine for the bibliography and also to generate various labels for entries. BibTeX’s capabilities even for this reduced set of tasks was still quite restricted due to the lack of Unicode support and the more and more complex programming issues involved in label preparation and file encoding.

Biber was designed specifically for Biblatex in order to provide a powerful backend engine which could deal with any required tasks to do with .bbl preparation. Its main features are:

- Deals with the full range of UTF-8
- Sorts in a completely customisable manner using, when available, CLDR collation tailoring
- Allows for per-entrytype options
- Automatically encodes the .bbl into any supported encoding format<sup>6</sup>
- Processes all bibliography sections in one pass of the tool

---

<sup>6</sup>‘Supported’ here means encodings supported by the Perl `Encode` module

- Output to GraphViz instead of `.bb1` in order to help visualise complex bibliographies with many crossrefs etc. (see section 3.11)
- Handles UTF-8 citekeys and filenames (given a suitable fully UTF-8 compliant  $\text{\TeX}$  engine)
- Creates entry sets dynamically and allows easily defined static entry sets, all processed in one pass
- ‘Syntactic’ inheritance via new `@XDATA` entrytype and field. This can be thought of as a field-based generalisation of the  $\text{\BibTeX}$  `@STRING` functionality (which is also supported).
- ‘Semantic’ inheritance via a generalisation of the  $\text{\BibTeX}$  crossreference mechanism. This is highly customisable by the user—it is possible to choose which fields to inherit for which entrytypes and to inherit fields under different names etc. Nested crossreferences are also supported.
- Handles complex auto-expansion and contraction of names and namelists (See section 4.11.4 of the Bibl $\text{\TeX}$  manual for an excellent explanation with examples, this is quite an impressive feature ...)
- Extensible modular datasource architecture for ease of adding more datasource types
- Support for remote datasources
- User-definable mapping and suppression of fields and entrytypes in datasources. You can use this to, for example, ignore all `ABSTRACT` fields completely. See section 3.1.1
- Support for related entries, to enable generic treatment of things like ‘translated as’, ‘reprinted as’, ‘reprint of’ etc.
- Customisable labels
- Multiple bibliography lists in the same section with different sorting and filtering
- No more restriction to a static data model of specific fields and entrytypes
- Structural validation of the data against the data model with a customisable validation model

Figure 1 shows the main functional units of processing in Biber. The most difficult tasks which Biber performs are the processing of Bibl $\text{\TeX}$ ’s `uniquename` and `uniquelist` options<sup>7</sup>, the sorting of lists<sup>8</sup> and the initial data parse and remap into an internal data model. Biber is getting on for around 20,000 lines of mostly OO Perl and relies on certain splendid Perl modules such as `Unicode::Collate`, `Text::BibTeX` and `XML::LibXML`.

It may be useful to know something about the different routes a datasource entry can take as it passes through Biber.

---

<sup>7</sup>A rather tricky unbounded loop but with a guaranteed eventual stable exit state.

<sup>8</sup>This is a complex, arbitrary multi-field Schwartzian Transform which has to deal with potentially different case and order settings for every field.




Figure 1: Overview of Biber's main functional units

1. All cited entries which are subsequently found in a datasource are instantiated in the internal Biber data model.
2. Some uncited entries on which cited entries depend are instantiated in the internal Biber data model:
  - Entries with entrytype `@XDATA` which are referenced from cited entries.
  - Entries mentioned in the `CROSSREF` or `XREF` field of a cited entry (unless they are also cited themselves in which case they are already instantiated as per item 1 above).
  - Clones of entries mentioned as a ‘related’ entry of a cited entry.
  - Members of sets, either explicit `@SET` entrytype entries or dynamic sets.
3. Some uncited but instantiated entries are promoted to cited status so that they make it into the output:
  - Entries instantiated by being members of a set.
  - Entries instantiated by being mentioned as a `CROSSREF` are promoted to cited status if `CROSSREF`’ed or `XREF`’ed at least `mincrosref` times.
  - Clones of entries mentioned as a ‘related’ entry of a cited entry.
4. Some of these auto-cited entries have the ‘dataonly’ option set on them so that Biblatex will only use them for data and will not output them to the bibliography:
  - Clones of entries mentioned as a ‘related’ entry of a cited entry.

## 2.6 Performance

Biber can’t really be compared with BibTeX in any meaningful way performance-wise. Biber is written in Perl and does a *great* deal more than BibTeX which is written in C. One of Biber’s test cases is a 2150 entry, 15,000 line `.bib` file which references a 630 entry macros file with a resulting 160 or so page (A4) formatted bibliography. This takes Biber under 3 minutes to process on a reasonable computer. This is perfectly acceptable, especially for a batch program.

## 2.7 Acknowledgements

François Charette originally wrote a first modest version of Biber. Philip Kime joined in the development in 2009 and is largely responsible for making it what it is today.

## 3 Use

Firstly, please note that Biber will *not* attempt to sanitise the content of BibTeX datasources. That is, don’t expect it to auto-escape any TeX special characters like

‘&’ or ‘%’ which it finds in, for example, your `TITLE` fields. It used to do this in earlier versions in some cases but as of version 0.9, it doesn’t because it’s fraught with problems and leads to inconsistent expectations and behaviour between different datasource types. In your `BIBTEX` data sources, please make sure your entries are legal `TEX` code.

Running `biber --help` will display all options and a brief description of each. This is the most useful brief source of usage information. Biber returns an exit code of 0 on success or 1 if there was an error.

Most Biber options can be specified in long or short format. When mentioning options below, they are referred to as ‘**long form**|**short form**’ when an option has both a long and short form. As usual with such options, when the option requires an argument, the long form is followed by an equals sign ‘=’ and then the argument, the short form is followed by a space and then the argument. For example, the `--configfile|-g` option can be given in two ways:

```
biber --configfile=somefile.conf
biber -g somefile.conf
```

With the `backend=biber` option, Bibl<sub>at</sub>ex switches its backend interface and passes all options and information relevant to Biber’s operation in a control file with extension `.bcf`<sup>9</sup>. This is conceptually equivalent to the `.aux` file which LaTeX uses to pass information to `BIBTEX`. The `.bcf` file is XML and contains many options and settings which configure how Biber is to process the bibliography and generate the `.bbl` file.

The usual way to call Biber is simply with the `.bcf` file as the only argument. Bibl<sub>at</sub>ex always writes the control file with a `.bcf` extension. Specifying the ‘`.bcf`’ extension to Biber is optional. Assuming a control file called `test.bcf`, the following two commands are equivalent:

```
biber test.bcf
biber test
```

Figure 2 is a graphical overview of the data flow for data model information. See Figure 1 for a more complete overview of Biber’s processing steps.

### 3.1 Options and config file

Bibl<sub>at</sub>ex options which Biber needs to know about are passed via the `.bcf` file. See Table 2 for the Bibl<sub>at</sub>ex options which Biber uses and also for the scopes which are supported for each option. Biber also has its own options which are set using the

---

<sup>9</sup>Bibl<sub>at</sub>ex Control File





Figure 2: Model data flow in Biber

following resource chain, given in decreasing precedence order:

```

command line options →
  biber.conf file →
    .bcf file →
      Biber hard-coded defaults
  
```

Users do not need to care directly about the contents or format of the `.bcf` file as this is generated from the options which they specify via Biblatex. The config file is a place to set commonly used command-line options and also to set options which cannot be set on the command line.

The configuration file is by default called `biber.conf` but this can be changed using the `--configfile|-g` option. Unless `--configfile|-g` is used, the config file is looked for in the following places, in decreasing order of preference:

```

biber.conf in the current directory →
  $HOME/.biber.conf →
    $XDG_CONFIG_HOME/biber/biber.conf →
      $HOME/Library/biber/biber.conf (Mac OSX only)
      $APPDATA/biber.conf (Windows only) →
        the output of 'kpsewhich biber.conf' (if available on the system)
  
```

Biblatex option	Global	Per-type	Per-entry
alphaothers	✓	✓	
dataonly		✓	✓
inheritance	✓		
labelalpha	✓	✓	
labelalphatemplate	✓	✓	
labeldate	✓	✓	
labeldatespec	✓	✓	
labelnamespec	✓	✓	
labelnumber	✓	✓	
labeltitle	✓	✓	
labeltitleyear	✓	✓	
maxalphanames	✓	✓	✓
maxbibnames	✓	✓	✓
maxcitenames	✓	✓	✓
maxitems	✓	✓	✓
minalphanames	✓	✓	✓
minbibnames	✓	✓	✓
mincitenames	✓	✓	✓
minitems	✓	✓	✓
presort	✓	✓	✓
singletitle	✓	✓	
skipbib		✓	✓
skiplab		✓	✓
skiplos		✓	✓
sortalphaothers	✓	✓	
sortexclusion		✓	
sortfirstinits	✓		
sorting	✓		
uniquelist	✓	✓	✓
uniquename	✓	✓	✓
useauthor	✓	✓	✓
useeditor	✓	✓	✓
useprefix	✓	✓	✓
usetranslator	✓	✓	✓

Table 2: Biblatex options which Biber uses

The config file is XML. Here Below is an example config file which displays the Biber defaults:

```
<?xml version="1.0" encoding="UTF-8"?>
<config>
  <clrmacros>0</clrmacros>
  <collate>1</collate>
  <collate_options>
    <option name="level" value="4"/>
    <option name="variable" value="non-ignorable"/>
  </collate_options>
  <debug>0</debug>
  <decodecharsset>base</decodecharsset>
  <fastsort>0</fastsort>
  <graph>0</graph>
  <input_encoding>UTF-8</input_encoding>
  <listsep>and</listsep>
  <mincrossrefs>0</mincrossrefs>
  <namesep>and</namesep>
  <nodieonerror>0</nodieonerror>
  <noinit>
    <!-- strip lowercase prefices like 'al-' when generating initials -->
    <option value="\b\p{Ll}{2}\p{Pd}"/>
    <!-- strip diacritics when generating initials -->
    <option value="[\x{2bf}\x{2018}]/>
  </noinit>
  <nolog>0</nolog>
  <nostdmacros>0</nostdmacros>
  <nosort>
    <!-- strip prefices like 'El-' when sorting name fields -->
    <option name="type_name" value="\A\p{L}{2}\p{Pd}"/>
    <!-- strip some diacritics when sorting name fields -->
    <option name="type_name" value="[\x{2bf}\x{2018}]/>
  </nosort>
  <onlylog>0</onlylog>
  <others_string>others</others_string>
  <output_encoding>UTF-8</output_encoding>
  <output_format>bbl</output_format>
  <output_safechars>0</output_safechars>
  <output_safecharsset>base</output_safecharsset>
  <quiet>0</quiet>
  <sortcase>true</sortcase>
  <sortlocale>en_US.utf8</sortlocale>
  <sortupper>true</sortupper>
  <tool>false</tool>
  <tool_align>1</tool_align>
```

```

<tool_datatype>bibtex</tool_datatype>
<tool_fieldcase>upper</tool_fieldcase>
<tool_indent>2</tool_indent>
<trace>0</trace>
<validate_config>0</validate_config>
<validate_control>0</validate_control>
<validate_structure>0</validate_structure>
<wraplines>0</wraplines>
</config>

```

In practice, the most commonly used options will be set via Biblatex macros in your document and automatically passed to Biber via the `.bcf` file. Certain options apply only to Biber and can only be set in the config file, particularly the more complex options. Most options are simple tags. Exceptions are the `nosort`, `noinit` and `collate_options` options which are slightly more complex and can have sub-options as shown. A much more complex option is the `sourcemap` option which is not set by default and which is described in section 3.1.1.

### 3.1.1 The `sourcemap` option

The datasource drivers implement a mapping from datasource entrytypes and fields into the Biblatex data model. If you want to override or augment the driver mappings you can use the `sourcemap` option which makes it possible to, for example, have a datasource with non-standard entrytypes or fields and to have these automatically mapped into other entrytypes/fields without modifying your datasource. Essentially, this alters the source data stream which Biber uses to build the internal Biblatex data model and is an automatic way of editing the datasource as it is read by Biber.

Source mappings can be defined at different ‘levels’ which are applied in a defined order. See the Biblatex manual regarding these macros:

```

user-level maps defined with \DeclareSourcemap→
  user-level maps defined in the Biber config file (described below)→
    style-level maps defined with \DeclareStyleSourcemap→
      driver-level maps defined with \DeclareDriverSourcemap

```

The `sourcemap` option can only be set in the config file and not on the command line as it has a complex structure. This option allows you to perform various data-source mapping tasks which can be useful for pre-processing data which you do not generate yourself:

- Map datasource entrytypes to different entrytypes.
- Map datasource fields to different fields.

- Add new fields to an entry
- Remove fields from an entry
- Modify the contents of a field using standard Perl regular expression match and replace.
- Restrict any of the above operations to entries coming from particular data-sources which you defined in `\addressource{}` macros.
- Restrict any of the above operations to entries only of a certain entrytype.

There is in fact, more flexibility than the above suggests, examples will show this below. The format of the `sourcemap` option section in the config file is described below, followed by examples which will make things clearer. Items in **red** are not literal, they are descriptive meta-values which are explained in the accompanying text. Items in **blue** are optional within their parent section or element. The general structure is:

```
<sourcemap>
  <maps datatype="driver1" map_overwrite="1|0">
    <map1 map_overwrite="1|0"> ... </map1>
      ⋮
    <mapn map_overwrite="1|0"> ... </mapn>
  </maps>
  ⋮
  <maps datatype="drivern" map_overwrite="1|0">
    <map1 map_overwrite="1|0"> ... </map1>
      ⋮
    <mapn map_overwrite="1|0"> ... </mapn>
  </maps>
</sourcemap>
```

Here, **driver<sub>1</sub>...driver<sub>n</sub>** are the names of valid Biber data source drivers (see section 3.10). One thing to note here is the `map_overwrite` attribute. This boolean attribute determines whether, for this driver mapping section, you may overwrite existing fields when adding new fields or mapping them. This attribute can be overridden on a per-map basis, see below. A warning will be issued either way saying whether an existing field will or will not be overwritten. If omitted, it defaults to '0'.

The `map` elements are processed in sequence and contain a number of `map_steps` which are also processed in sequence. Each `map_step` allows you to do a particular thing or combination of things:

- Change the entrytype of an entry
- Change the name of a field
- Add extra fields the entry
- Change the contents of a field

These facilities are explained in more detail below, with examples. A `map` element looks like this:

```
<map map_overwrite="0|1">
  <per_datasource>datasource</per_datasource>
  <per_type>entrytype</per_type>
  <map_step map_type_source="source-entrytype"
    map_field_source="source-field"
    map_type_target="target-entrytype"
    map_field_target="target-field"
    map_match="match-regex"
    map_nomatch="match-regex"
    map_replace="replace-regex"
    map_field_set="set-field"
    map_field_value="set-value"
    map_append="1"
    map_null="1"
    map_entry_null="1"
    map_origfield="1"
    map_origfieldval="1"
    map_origentrytype="1"
    map_final="1"/>
</map>
```

- If there are any `datasources` named in `per_datasource` elements, this mapping only applies to entries coming from the named `datasources`. There can be multiple `per_datasource` elements each specifying one of the `datasource` names given in a Biblatex `\addbibresource` macro.
- If there are any `entrytypes` named in `per_type` elements, this mapping only applies to entries of the named `entrytypes`.
- The `map_overwrite` attribute can be used to override the value for this attribute set on the parent `maps` element. If omitted, it defaults to the parent `maps` attribute value.

Each `map_step` is looked at in turn and compared with the `datasource` entry being processed. A `map_step` works like this:

- If `map_entry_null` is set, processing of the `map` immediately terminates and the current entry is not created. It is as if it did not exist in the `datasource`. Obviously, you should select the entries which you want to apply this to using prior mapping steps.
- Change the `source-entrytype` to `target-entrytype`, if defined. If `map_final` is set then if the `entrytype` of the entry is not `source-entrytype`, processing of this `map` immediately terminates.

- Change the **source-field** to **target-field**, if defined. If **map\_final** is set, then if there is no **source-field** field in the entry, processing of this **map** immediately terminates.
- If **map\_match** is defined but **map\_replace** is not, only apply the step if the **source-field** matches **map\_match**. You can use parentheses as usual to capture parts of the match and can then use these later when setting a **map\_field\_value**.
- **map\_notmatch** is the same as **map\_match** but with the logic reversed.
- Perform a Perl regular expression match and replace on the value of **source-field** if **map\_match** and **map\_replace** are defined. You may use (and almost certainly will want to use) parentheses for back-references in **map\_replace**. Do not quote the regular expressions in any special (i.e. non-Perl) way—it's not necessary.
- If **map\_field\_set** is defined, then its value is **set-field** which will be set to a value specified by further attributes. If **map\_overwrite** is false for this step and the field to set already exists then the map step is ignored. If **map\_final** is also set on this step, then processing of the parent map stops at this point. If **map\_append** is set, then the value to set is appended to the current value of **set-field**. The value to set is specified by a mandatory one and only one of the following attributes:
  - **map\_field\_value** — The **set-field** is set to **set-value**
  - **map\_null** — The field is ignored, as if it did not exist in the datasource
  - **map\_origentrytype** — The **set-field** is set to the most recently mentioned **source-entrytype** name.
  - **map\_origfield** — The **set-field** is set to the most recently mentioned **source-field** name
  - **map\_origfieldval** — The **set-field** is set to the most recently mentioned **source-field** value

With BibTeX and RIS datasources, you can specify the pseudo-field 'entrykey' for **source-field** which is the citation key of the entry. Naturally, this 'field' cannot be changed (used as **set-field**, **target-field** or changed using **map\_replace**).

Note that for XML datasources (Endnote, Zotero RDF/XML etc.), the names of fields and entrytypes are matched in a case sensitive manner. For all other datasource types (BIBTEX, RIS etc.) entrytype and field name matching is case insensitive. Here are some examples:

```
<map>
  <per_datasource>example1.bib</per_datasource>
  <per_datasource>example2.bib</per_datasource>
  <map_step map_field_set="KEYWORDS" map_field_value="keyw1, keyw2"/>
  <map_step map_field_source="ENTRYKEY"/>
  <map_step map_field_set="NOTE" map_origfieldval="1"/>
</map>
```

This would add a KEYWORDS field with value 'keyw1, keyw2' and set the NOTE field to citation key for the entry to all entries which are found in either the examples1.bib or examples2.bib files. This assumes that the Biblatex source contains \addresource{example1.bib} and \addresource{example2.bib}.

```
<map map_overwrite="0">
  <map_step map_field_source="TITLE"/>
  <map_step map_field_set="NOTE" map_origfieldval="1"/>
</map>
```

Copy the TITLE field to the NOTE field unless the NOTE field already exists.

```
<map map_overwrite="0">
  <map_step map_field_source="AUTHOR" />
  <map_step map_field_set="SORTNAME" map_origfieldval="1" map_final="1"/>
  <map_step map_field_source="SORTNAME" map_match="\A(.+)\s+and.*" map_replace="$1"/>
</map>
```

For any entry with an AUTHOR field, try to set SORTNAME to the same as AUTHOR. If this fails because SORTNAME already exists, stop, otherwise truncate SORTNAME to just the first name in the name list.

```
<map map_overwrite="0">
  <map_step map_type_source="CHAT" map_type_target="CUSTOMA" map_final="1"/>
  <map_step map_field_set="TYPE" map_origentrytype="1"/>
</map>
```

Any @CHAT entrytypes would become @CUSTOMA entrytypes and would automatically have a TYPE field set to 'CHAT' unless the TYPE field already exists in the entry (because map\_overwrite is false). This mapping applies only to entries of type @CHAT since the first step has map\_final set and so if the map\_type\_source does not match the entry, processing of this map immediately terminates.

```
<map>
  <per_datasource>examples.bib</per_datasource>
  <per_type>ARTICLE</per_type>
  <per_type>BOOK</per_type>
  <map_step map_field_set="ABSTRACT" map_null="1"/>
  <map_step map_field_set="NOTE" map_field_value="Auto-created this field"/>
</map>
```

Any entries of entrytype ARTICLE or BOOK from the 'examples.bib' datasource would have their ABSTRACT fields removed and a NOTE field added with value 'Auto-created this field'.



```

<map>
  <map_step map_field_set="ABSTRACT" map_null="1"/>
  <map_step map_field_source="CONDUCTOR" map_field_target="NAMEA"/>
  <map_step map_field_source="GPS" map_field_target="USERA"/>
</map>

```

This removes ABSTRACT fields from any entry, changes CONDUCTOR fields to NAMEA fields and changes GPS fields to USERA fields

```

<map>
  <map_step map_field_source="PUBMEDID"
    map_field_target="EPRINT"
    map_final="1"/>
  <map_step map_field_set="EPRINTTYPE" map_origfield="1"/>
  <map_step map_field_set="USERD"
    map_field_value="Some string of things"/>
</map>

```

Applies only to entries with PUBMED fields and maps PUBMEDID fields to EPRINT fields, sets the EPRINTTYPE field to 'PUBMEDID' and also sets the USERD field to the string 'Some string of things'.

```

<map>
  <map_step map_field_source="SERIES"
    map_match="\A\d*(.+)"
    map_replace="\L$1"/>
</map>

```

Here, the contents of the SERIES field have leading numbers stripped and the remainder of the contents lowercased.

```

<map>
  <map_step map_field_source="TITLE"
    map_match="Collected\s+Works.+Freud"
    map_final="1"/>
  <map_step map_field_set="KEYWORDS" map_field_value="freud"/>
</map>

```

Here, if for an entry, the TITLE field matches a particular regular expression, we set a special keyword so we can, for example, make a references section just for certain items.

```

<map>
  <map_step map_field_source="LISTA" map_match="regexp" map_final="1"/>
  <map_step map_field_set="LISTA" map_null="1"/>
</map>

```

If an entry has a LISTA field which matches regular expression ‘regex’, then it is removed.

```
<map>
  <map_step map_field_source="AUTHOR"
    map_match="Smith, Bill" map_replace="Smith, William"/>
  <map_step map_field_source="AUTHOR"
    map_match="Jones, Baz" map_replace="Jones, Barry"/>
</map>
```

Here, we use multiple match/replace for the same field to regularise some inconstant name variants. Bear in mind that match/replace processing within a **map** element is sequential and the changes from a previous match/replace are already committed.

```
<map map_overwrite="1">
  <map_step map_field_source="AUTHOR" map_match="Doe," map_final="1"/>
  <map_step map_field_set="SHORTAUTHOR" map_origfieldval="1"/>
  <map_step map_field_set="SORTNAME" map_origfieldval="1"/>
  <map_step map_field_source="SHORTAUTHOR"
    map_match="Doe,\s*(?:\.|ohn)(?:[-]*)(?:P\.|Paul)*"
    map_replace="Doe, John Paul"/>
  <map_step map_field_source="SORTNAME"
    map_match="Doe,\s*(?:\.|ohn)(?:[-]*)(?:P\.|Paul)*"
    map_replace="Doe, John Paul"/>
</map>
```

Only applies to entries with an AUTHOR field matching ‘Doe,’. First the AUTHOR field is copied to both the SHORTAUTHOR and SORTNAME fields, overwriting them if they already exist. Then, these two new fields are modified to canonicalise a particular name, which presumably has some variants in the datasource.

```
<map>
  <map_step map_field_source="TITLE" map_match="A Title" map_final="1"/>
  <map_step map_entry_null="1"/>
</map>
```

Any entry with a TITLE field matching ‘A Title’ will be completely ignored.

### Other datasource types

For datasources other than BIBTEX, (e.g. ris, endnotexml and zoterordfxml), the source entrytypes and fields are usually very differently modelled and named. For example, here is how to drop dc:subject fields from various entrytypes in Zotero XML RDF format data sources:

```

<maps datatype="zoterordfxml" map_overwrite="1">
  <map>
    <per_type>journalArticle</per_type>
    <per_type>book</per_type>
    <per_type>bookSection</per_type>
    <map_step map_field_set="dc:subject" map_null="1"/>
  </map>
</maps>

```

Or here, mapping journal articles into `@Report` entries for Endnote XML format datasources within a particular datasource.

```

<maps datatype="endnotexml" map_overwrite="1">
  <map>
    <per_datasource>endnote.xml</per_datasource>
    <map_step map_type_source="Journal Article" map_type_target="Report"/>
  </map>
</maps>

```

Or here, dropping the N2 field from RIS datasources, which are commonly used for abstracts:

```

<maps datatype="ris" map_overwrite="1">
  <map>
    <map_step map_field_set="N2" map_null="1"/>
  </map>
</maps>

```

### 3.1.2 The inheritance option

The `inheritance` option defines the inheritance rules for data inheritance between entries using, for example, BibTeX's `CROSSREF` field. The default setup for this is defined by Biblatex and is passed in the `.bcf` file. Defining inheritance rules in the Biber configuration file is rarely something you would want to do with one notably exceptional case being when using Biber in tool mode where you might want to ‘materialise’ special inheritance rules (see section 3.12). Here we define the format of the config file inheritance section, should you need to understand or modify it. Items in **red** are not literal, they are descriptive meta-values which are explained in the accompanying text. Items in **blue** are optional within their parent section or element.

```

<inheritance>
  <defaults inherit_all="true|false" override_target="true|false">
    <type_pair source="source" target="target">

```

```

        inherit_all="true|false"
        override_target="true|false"/>
        :
    </defaults>
    <inherit>
        <type_pair source="source" target="target"/>
        :
        <field source="source"
            target="target"
            skip="true|false"
            override_target="true|false"/>
        :
    </inherit>
    :
</inheritance>

```

- The **defaults** section specifies the default inheritance rules which are not otherwise covered by a specific **inherit** rule. **inherit\_all** specifies that by default a **target** inherits all fields from a **source**. **override\_target** specifies that by default an existing **target** field will be overwritten by a **source** field if it already exists in the **target**. A **type\_pair** element specifies the defaults for a particular **source** and **target** entrytype combination. **source** or **target** can take the value '\*' which is a wildcard representing all possible entrytypes.
- An **inherit** element specifies how one or more **source** fields are inherited by one more **source/target** pairs which are specified in one or more **type\_pair** elements within the same **inherit** element. **override\_target** can be specified on a per-field basis as can the **skip** attribute which indicates that a particular field is not to be inherited by the **target**.

Here is an example:

```

<inheritance>
  <defaults inherit_all="true" override_target="false">
  </defaults>
  <inherit>
    <type_pair source="mvbook" target="inbook"/>
    <type_pair source="mvbook" target="bookinbook"/>
    <type_pair source="mvbook" target="suppbook"/>
    <type_pair source="book" target="inbook"/>
    <type_pair source="book" target="bookinbook"/>
    <type_pair source="book" target="suppbook"/>
    <field source="author" target="author"/>
    <field source="author" target="bookauthor"/>
  </inherit>
  <inherit>

```

```

    <type_pair source="*" target="inbook"/>
    <type_pair source="*" target="incollection"/>
    <field source="*" skip="true"/>
  </inherit>
</inheritance>

```

Here we can see that the default is to inherit all fields from the **source** and not to override existing **target** fields if they already exist. Then we see that for some combinations of **sources** and **targets**, the AUTHOR field is inherited from the **source** and also the AUTHOR field in the **source** is inherited as the BOOKAUTHOR field in the **target**.

The second **inherit** element says that INBOOK and INCOLLECTION entries never inherit the INTRODUCTION field from any **source**.

In general, it is probably best to copy the default Biblatex inheritance rules and modify them to your needs. See section 3.12.

### 3.1.3 The **noinit** option

The value of the **noinit** option can only be set in the config file and not on the command line. This is because the values are Perl regular expressions and would need special quoting to set on the command line. This can get a bit tricky on some OSes (like Windows) so it's safer to set them in the config file. **noinit** allows you to ignore parts of a name when generating initials. This is done using Perl regular expressions which specify what to ignore. You can specify multiple regular expressions and they will be removed from the name before it is passed to the initials generating system.

For example, this option can be used to ignore diacritic marks and prefixes in names which should not be considered when sorting. Given (the default):

```

<noinit>
  <!-- strip lowercase prefixes like 'al-' when generating initials -->
  <option value="\b\p{Ll}{2}\p{Pd}"/>
  <!-- strip diacritics when generating initials -->
  <option value="[\x{2bf}\x{2018}]/>
</noinit>

```

and the **BIBTEX** datasource entry:

```
AUTHOR = {{al-Hasan}, {Alī},
```

the initials for the last name will be 'H' and not 'a-H'. The initial for the first name will be 'A' as the diacritic is also ignored. This is tricky in general as you cannot often determine the difference between a name with a prefix and a hyphenated name with

only, say, two chars in the first part such as ‘Ho-Pun’. You can adjust this option for your individual cases. By default, only lowercased prefixes are looked for so as to avoid breaking things like ‘Ho-Pun’ where you want the initials to be ‘H.-P.’, for example. See the Perl regular expression manual page for details of the regular expression syntax<sup>10</sup>.

### 3.1.4 The sorting option

The `sorting` option defines the sorting rules for the bibliography lists. Biblatex allows multiple sorting specifications referenced by name as it can print bibliography information as many times as the user wishes with different filtering and sorting. This is normally handled by macros in Biblatex which write the XML sorting specification(s) to the `.bcf` file for Biber to read but there may be occasions (usually when using Biber in ‘tool’ mode (see section 3.12) when you need to specify the global sorting specification directly in a Biber config file. This section documents the XML format of the sorting specification. Items in red are not literal, they are descriptive meta-values which are explained in the accompanying text. Items in blue are optional within their parent section or element. See also the `nosort` option in section 3.1.5.

```
<sorting>
  <presort type=type>string</presort>
  <sortexclusion type=type>
    <exclusion>field</exclusion>
    :
  </sortexclusion>
  <sort order="n"
    final=1
    sort_direction="ascending|descending"
    sort_case="1|0"
    sort_upper="1|0">
    <sortitem order="m"
      substring_side="left|right"
      substring_width=int"
      pad_side="left|right"
      pad_width=int"
      pad_char=string">field|literal|citeorder</sortitem>
      :
    </sort>
    :
  </sorting>
```

---

<sup>10</sup><http://perldoc.perl.org/perlre.html>

Sorting in Biber is a sophisticated procedure of building up a sorting object for an entry based on a sorting scheme template, the general form of which is shown above. The sorting routine first traverses every entry in the bibliography list and generates a sorting object based on the sorting scheme. When this is done, it sorts the entries according to the sorting objects it has generated for each entry.

A sorting specification is comprised of a number of **sort** elements. Sorting is essentially a process of comparing whatever information the **n**th **sort** element collected for every entry (otherwise known as ‘multi-field’ sorting). Within a **sort** element, there can be any number of **sortitem** elements which describe what information to look for in the entry in order to construct this part of the sorting object; either a field, a literal string or the special ‘citeorder’ pseudo-field.

When generating the sorting information for an entry, within each **sort** element, the first **sortitem** to return a non-empty value for the bibliography entry is used and the rest of the **sortitems** in the **sort** are skipped. A **sortitem** essentially looks for a piece of information in the entry and adds this to the sorting object. If it is looking for a **field**, then the field must exist in the entry. If it does not, the **sortitem** is skipped. If the **field** does exist, it is added to the sorting object for the entry after being modified by the attributes of the **sortitem**.

Once a **sortitem** has returned the contents of a **field**, you can use the **substring\_side** (default ‘left’ if any other **substring** attributes are set) and **substring\_width** (default ‘4’ if any other **substring** attributes are set) attributes to truncate the contents of the **field** by reducing it to a substring taken from the left or right side of the string and of a number of (UTF-8) characters of your choice. You can also pad the **field** with repeated arbitrary characters on either side using the **pad\_side** (default ‘left’ if any other **pad** attributes are set), **pad\_width** (default ‘4’ if any other **pad** attributes are set) and **pad\_char** (default ‘0’—the digit zero if any other **pad** attributes are set) attributes.

A **sortitem** which is neither a known bibliography sorting field nor the special ‘citeorder’ string is treated as a literal string to add to the sorting object. Naturally, such a **sortitem** always ‘finds’ something to add to the sorting object and so it should never have any other **sortitems** after it within the **sort** section as they will never be considered. The ‘citeorder’ **sortitem** value has a special meaning. It requests a sort based on the lexical order of the actual citations. For entries cited in Biblatex within the same citation command like:

```
\cite{one,two}
```

there is a distinction between the lexical order and the semantic order. Here ‘one’ and ‘two’ have the same semantic order but a unique lexical order. The semantic order only matters if you specify further sorting to disambiguate entries with the same semantic order. For example, this is the definition of the Biblatex **none** sorting scheme:

```

<sorting>
  <presort>mm</presort>
  <sort order="1">
    <sortitem order="1">citeorder</sortitem>
  </sort>
</sorting>

```

This sorts the bibliography purely lexically by the order of the keys in the citation commands. In the example above, it sorts entry ‘one’ before ‘two’. However, suppose that you consider ‘one’ and ‘two’ to have the same order (semantic order) since they are cited at the same time and want to further sort these by year. Suppose ‘two’ has an earlier YEAR than ‘one’:

```

<sorting>
  <presort>mm</presort>
  <sort order="1">
    <sortitem order="1">citeorder</sortitem>
  </sort>
  <sort order="2">
    <sortitem order="1">year</sortitem>
  </sort>
</sorting>

```

This sorts ‘two’ before ‘one’, even though lexically, ‘one’ would sort before ‘two’. This is possible because the semantic order can be disambiguated by the further sorting on year. With the standard Biblatex **none** sorting scheme, the lexical order and semantic order are identical because there is nothing further to disambiguate them. This means that you can use ‘citeorder’ just like any other **sortitem** value, choosing how to further sort entries cited at the same time (in the same citation command).

Both **sort** and **sortitem** elements have a mandatory **order** attribute which should start at ‘1’ and increase for each further element. Order numbers for **sortitem** elements within a **sort** element always begin with ‘1’ and don’t increase between **sort** elements.

Once a **sortitem** element has added something to the sorting object (or all **sortitem** elements within a **sort** have been processed, regardless of whether anything was added to the sort object for the entry), some attributes are applied to the information added and the next **sort** element is processed. These attributes on the **sort** element further determine how any sorting specification added by the **sortitem** elements will be used in the sorting.

If the **sort** element has the **final** attribute set to ‘1’, then if any **sortitem** within the **sort** returned a non-empty string to add to the sorting object, the construction of the sorting object for the entry ceases at this point and no more **sort** elements are processed. This is used typically to make sure that master sorting keys such as



those specified with the `SORTKEY` field, if found, are the only thing used to construct the sorting object. The `sort` element may further specify that the information at order ‘`n`’ should be sorted in ascending order or descending order (default ‘ascending’), whether case should be considered when sorting (default depends on the Biber `sortcase` option which defaults to true) and whether uppercase characters should be sorted before lower (default depends on the Biber ‘`sortupper`’ option which defaults to true).

Finally, there are two special sorting section elements to consider. The `presort` element is mandatory and specifies a literal `string` to add to the very beginning of all sorting objects for all entries. This is useful when combined with the fact that you may specify an optional `type` attribute which specifies a particular entry type for the `presort string` specified. Using this mechanism, you can sort, for example, all `ARTICLE` entries before all `BOOK` entries and then all other types of entry:

```
<sorting>
  <presort type="article">aa</presort>
  <presort type="book">bb</presort>
  <presort>mm</presort>
  :
</sorting>
```

This makes it easy to divide a bibliography by type of entry.

The optional `sortexclusion` element allows you to exclude fields from consideration by `sortitem` on a per-type basis. For example, if you wanted to ignore the `YEAR` field of any `REPORT` entry types because they are not reliably populated with data representing a year, you could do:

```
<sorting>
  :
  <sortexclusion type="report">year</sortexclusion>
  :
</sorting>
```

It is much easier to see how intuitive this all is if you look at a standard sorting scheme definition. Below is the default Biblatex sorting scheme which appears in the `.bcf` when you run Biblatex with no `sorting` option. This is fully documented and described in the Biblatex manual along with the LaTeX macros which generate this XML in the `.bcf`:

```
<sorting>
  <presort>mm</presort>
  <sort order="1">
    <sortitem order="1">presort</sortitem>
  </sort>
  <sort order="2" final="1">
```

```

    <sortitem order="1">sortkey</sortitem>
  </sort>
  <sort order="3">
    <sortitem order="1">sortname</sortitem>
    <sortitem order="2">author</sortitem>
    <sortitem order="3">editor</sortitem>
    <sortitem order="4">translator</sortitem>
    <sortitem order="5">sorttitle</sortitem>
    <sortitem order="6">title</sortitem>
  </sort>
  <sort order="4">
    <sortitem order="1">sortyear</sortitem>
    <sortitem order="2">year</sortitem>
  </sort>
  <sort order="5">
    <sortitem order="1">sorttitle</sortitem>
    <sortitem order="2">title</sortitem>
  </sort>
  <sort order="6">
    <sortitem order="1" pad_side="left" pad_width="4" pad_char="0">volume</sortitem>
    <sortitem order="2">0000</sortitem>
  </sort>
</sorting>

```

### 3.1.5 The nosort option

The value of the **nosort** option can only be set in the config file and not on the command line. This is because the values are Perl regular expressions and would need special quoting to set on the command line. This can get a bit tricky on some Oses (like Windows) so it's safer to set them in the config file. In any case, it's unlikely you would want to set them for particular Biber runs; they would more likely be set as your personal default and thus they would naturally be set in the config file anyway. **nosort** allows you to ignore parts of a field for sorting. This is done using Perl regular expressions which specify what to ignore in a field. You can specify as many patterns as you like for a specific field. Also available are some field type aliases so you can, for example, specify patterns for all name fields or all title fields. These field types all begin with the string **'type\_'**, see Table 3.

For example, this option can be used to ignore some diacritic marks and prefixes in names which should not be considered when sorting. Given (the default):

```

<nosort>
  <!-- strip prefixes like 'al-' when sorting names -->
  <option name="type_name" value="\A\p{L}{2}\p{Pd}"/>
  <!-- strip diacritics when sorting names -->

```

Alias	Fields
type_name	author
	afterword
	annotator
	bookauthor
	commentator
	editor
	editora
	editorb
	editorc
	foreword
	holder
	introduction
	namea
	nameb
	namec
	shortauthor
	shorteditor
	translator
type_title	booktitle
	eventtitle
	issuetitle
	journaltitle
	maintitle
	origtitle
	title

Table 3: nosort option field type aliases

```
<option name="type_name" value="[\x{2bf}\x{2018}]" />
</nosort>
```

and the `BIBTEX` datasource entry:

```
AUTHOR = {{al-Hasan}, {Alī}},
```

the prefix ‘al-’ and the diacritic ‘*ˆ*’ will not be considered when sorting. See the Perl regular expression manual page for details of the regular expression syntax<sup>11</sup>.

You may specify any number of `option` elements. If a `nosort` option is found for a specific field, it will override any option for a type which also covers that field.

Here is another example. Suppose you wanted to ignore ‘The’ at the beginning of a `TITLE` field when sorting, you could add this to your `biber.conf`:

```
<nosort>
  <option name="title" value="\AThe\s+" />
</nosort>
```

If you wanted to do this for all title fields listed in Table 3, then you would do this:

```
<nosort>
  <option name="type_title" value="\AThe\s+" />
</nosort>
```

**Note:** `nosort` can be specified for most fields but not for things like dates and special fields as that wouldn’t make much sense.

### 3.1.6 The `collate_options` option

The `collate_options` option has format similar to `nosort`. See Section 3.5 for details about the option, here is an example of a config file setting:

```
<collate_options>
  <option name="level" value="3" />
  <option name="table" value="/home/user/data/otherkeys.txt" />
</collate_options>
```

## 3.2 Unicode

Biber uses NFD UTF-8 internally. All data is converted to NFD UTF-8 when read. If UTF-8 output is requested (to `.bbl` for example), the UTF-8 will always be NFC.

---

<sup>11</sup><http://perldoc.perl.org/perlre.html>

### 3.3 Input/Output File Locations

#### 3.3.1 Control file

The control file is normally passed as the only argument to Biber. It is searched for in the following locations, in decreasing order of priority:

Absolute filename →

    In the `--output_directory`, if specified→

        Relative to current directory→

            Using `kpsewhich`, if available

#### 3.3.2 Data sources

Local datasources of type ‘file’ are searched for in the following locations, in decreasing order of priority:

Absolute filename →

    In the `--output_directory`, if specified→

        Relative to current directory→

            In the same directory as the control file→

                Using `kpsewhich` for supported formats, if available

Remote file datasources (beginning with `http://` or `ftp://`) are retrieved to a temp file and processed as normal. Users do not specify explicitly the bibliography database files; they are passed in the `.bcf` control file, which is constructed from the Biblatex ‘`\addbibresource{}`’ macros.

### 3.4 Logfile

By default, the logfile for Biber will be named `\jobname.blg`, so, if you run

```
biber <options> test.bcf
```

then the logfile will be called ‘`test.blg`’. Like the `.bbl` output file, it will be created in the `--output_directory|-c`, if this option is defined. You can override the logfile name by using the `--logfile` option:

```
biber --logfile=lfname test.bcf
```

results in a logfile called ‘`lfname.blg`’.

**Warning:** be careful if you are expecting Biber to write to directories which you don't have appropriate permissions to. This is more commonly an issue on non-Windows OSes. For example, if you rely on `kpsewhich` to find your database files which are in system `TeX` directories, you may well not have write permission there so Biber will not be able to write the `.bbl`. Use the `--output_file|-O` option to specify the location to write the `.bbl` to in such cases.

### 3.5 Collation and Localisation

Biber takes care of collating the bibliography for Biblatex. It writes entries to the `.bbl` file sorted by a completely customisable set of rules which are passed in the `.bcf` file by Biblatex. Biber has two ways of performing collation:

`--collate|-C`

The default. This option makes Biber use the Perl `Unicode::Collate` module for collation which implements the full UCA (Unicode Collation Algorithm). It also has CLDR (Common Locale Data Repository) tailoring to deal with cases which are not covered by the UCA. It is a little slower than `--fastsort|-f` but the advantages are such that it's rarely worth using `--fastsort|-f`

`--fastsort|-f`

Biber will sort using the OS locale collation tables. The drawback for this method is that special collation tailoring for various languages are not implemented in the collation tables for many OSes. For example, few OSes correctly sort 'ä' before 'å' in the Swedish (`sv_SE`) locale. If you are using a common latin alphabet, then this is probably not a problem for you.

The locale used for collation is determined by the following resource chain which is given in decreasing precedence order:

```
--collate_options|-c (e.g. -c 'locale => "de_DE"') →  
  --sortlocale|-l →  
    LC_COLLATE environment variable →  
      LANG environment variable →  
        LC_ALL environment variable
```

With the default `--collate|-C` option, the locale will be used to look for a collation tailoring for that locale. It will generate an informational warning if it finds none.

This is not a problem as the vast majority of collation cases are covered by the standard UCA and many locales neither have nor need any special collation tailoring.

With the `--fastsort|-f` option, the locale will be used to locate an OS locale definition to use for the collation. This may or may not be correctly tailored, depending on the locale and the OS.

Collation is by default case sensitive. You can turn this off globally using the Biber option `--sortcase=false` or from Biblatex using its option `sortcase=false`. The option can also be defined per-field so you can sort some fields case sensitively and others case insensitively. See the Biblatex manual.

`--collate|-C` by default collates uppercase before lower. You can reverse this globally for all sorting using the Biber option `--sortupper=false` or from Biblatex by using its option `sortupper=false`. The option can also be defined per-field so you can sort some fields uppercase before lower and others lower before upper. See the Biblatex manual. Be aware though that some locales rightly enforce a particular setting for this (for example, Danish). You will be able to override it but Biber will warn you if you do. `sortupper` has no effect when using `--fastsort|-f`—you are at the mercy of what your OS locale does.

There are in fact many options to `Unicode::Collate` which can tailor the collation in various ways in addition to the locale tailoring which is automatically performed. Users should see the the documentation to the module for the various options, most of which the vast majority of users will never need<sup>12</sup>. Options are passed using the `--collate_options|-c` option as a single quoted string, each option separated by comma, each key and value separated by `'=>'`. See examples.

**Note:** Biber sets the Unicode collation tailoring ‘variable’ to ‘non-ignorable’. Effectively, this means that punctuation is not ignored when sorting. The default setting is to ignore such ‘variable weight’ elements. Sorting bibliographies is slightly more specialised than collating general text and punctuation often matters. In case you want the UCA default behaviour, see examples.

### 3.5.1 Examples

biber

Call Biber using all settings from the `.bcf` generated from the LaTeX run. Case sensitive UCA sorting is performed taking the locale for tailoring from the environment if no `sortlocale` is defined in the `.bcf`

biber `--sortlocale=de_DE`

Override any locale setting in the `.bcf` or the environment.

biber `--fastsort`

Use slightly quicker internal sorting routine. This uses the OS locale files which may or may not be accurate.

---

<sup>12</sup>For details on the various options, see <http://search.cpan.org/search?query=Unicode%3A%3ACollate&mode=all>

```
biber --sortcase=false
    Case insensitive sorting.
biber --sortupper=false --collate_options="backwards => 2"
    Collate lowercase before upper and collate French accents in reverse order at UCA
    level 2.
biber --collate_options="variable => 'shifted'"
    Use the UCA default setting for variable weight punctuation (which is to ignore it
    for sorting, effectively).
```

### 3.6 Encoding of files

Biber takes care of re-encoding the datasource data as necessary. In normal use, Biblatex passes its `input_encoding` option value to Biber via the `.bcf` file. It also passes the value of its `texencoding` option (which maps to Biber's `--output_encoding|-E` option) the default value of which depends on which TeX engine and encoding packages you are using (see Biblatex manual for details).

Biber performs the following tasks:

1. Decodes the datasource into UTF-8 if it is not UTF-8 already
2. Decodes LaTeX character macros into UTF-8 if `--output_encoding|-E` is UTF-8
3. Encodes the output so that the `.bbl` is in the encoding that `--output_encoding|-E` specifies
4. Warns if it is asked to output to the `.bbl` any UTF-8 decoded LaTeX character macros which are not in the `--output_encoding|-E` encoding. Replaces with a suitable LaTeX macro

Normally, you do not need to set the encoding options on the Biber command line as they are passed in the `.bcf` via the information in your Biblatex environment. However, you can override the `.bcf` settings with the command line. The resource chain for encoding settings is, in decreasing order of preference:

```
--input_encoding|-e and --output_encoding|-E →
    Biber config file →
        .bcf control file
```

#### 3.6.1 LaTeX macro decoding

As mentioned above, Biber sometimes converts LaTeX character macros into UTF-8. In fact there are two situations in which this occurs.

1. When `--output_encoding|-E` is UTF-8



## 2. Always for internal sorting purposes

This decoding is very useful but take note of the following two scenarios, which relate to each of the two situations in which LaTeX macro decoding occurs:

### Decoding when output is UTF-8

If you are using PDFLaTeX and `\usepackage[utf8]{inputenc}`, it is possible that the UTF-8 characters resulting from Biber's internal LaTeX character macro decoding break `inputenc`. This is because `inputenc` does not implement all of UTF-8, only a commonly used subset.

An example—if you had `\DJ` in your `.bib` datasource, Biber decodes this correctly to ‘Đ’ and this breaks `inputenc` because it doesn't understand that UTF-8 character. The real solution here is to switch to a TeX engine with full UTF-8 support like XeTeX or LuaTeX as these don't use or need `inputenc`. However, you can also try the `--output_safechars` option which will try to convert any UTF-8 chars into LaTeX macros on output. For information on the `--output_safechars` option, see section 3.6.2.

### Decoding for internal sorting

If your `output_encoding` is not UTF-8, and you are using some UTF-8 equivalent LaTeX character macros in your `.bib` datasource, then some `.bbl` fields (currently only `\sortinit{}`) might end up with invalid characters in them, according to the `.bbl` encoding. This is because some fields must be generated from the final sorting data which is only available after the LaTeX character macro decoding step.

For example, suppose you are using PDFLaTeX with `\usepackage[latin1]{inputenc}` and the following BibTeX datasource entry:

```
@BOOK{citekey1,
  AUTHOR = {{\v S}imple, Simon},
}
```

With normal LaTeX character macro decoding, the `{\v S}` is decoded into ‘Š’ and so with name-first sorting, `\sortinit{}` would be ‘Š’. This is an invalid character in `latin1` encoding and so the `.bbl` would be broken. In such cases when `\sortinit{}` is a char not valid in the `output_encoding`, Biber tries to replace the character with a suitable LaTeX macro. The solution is really to use UTF-8 `.bbl` encoding whenever possible. In extreme cases where even with UTF-8 encoding, the char is not recognised by LaTeX due to an incomplete UTF-8 implementation (as with `inputenc`), this might also mean switching TeX engines to one that supports full UTF-8 (like XeTeX or LuaTeX).

### 3.6.2 LaTeX macro encoding

The opposite of decoding; converting UTF-8 characters into LaTeX macros. You can force this with the `--output_safechars` option which will do a generally good job of making your `.bbl` plain ASCII. It can be useful in certain edge cases where your bibliography introduces characters which can't be handled by your main document. See section 3.6.1 above for an example such case.

A common use case for LaTeX macro encoding is when the bibliography datasource is not ASCII but the `.tex` file is and so this case is automated for you: if the Biblalex option `'texencoding'` (which corresponds to the Biber option `'--output_encoding|-E'`) is set to an ASCII encoding (`'ascii'` or `'x-ascii'`) and `'--input_encoding|-e'` is not ASCII, Biber will automatically set `--output_safechars`.

See also the `biber --help` output for the `--output_safecharsset` and `--decodecharsset` options which can customise the set of conversion rules to use. The builtin sets of characters and macros which Biber maps during encoding and decoding are documented<sup>13</sup>.

It is possible to provide a customised encode/decode mapping file using the `--recodedata` option. It must adhere to the format of the default data file for reencoding which is `recode_data.xml` located in the same Perl install directory as Biber's `Recode.pm` module. Of course it is easier to find this in the Biber source tree. It is most likely that if you want to use a custom mapping file, you would copy the default file and edit it, removing some things and perhaps defining some custom recoding sets for use with `--output_safecharsset` and `--decodecharsset`.

Be careful to classify the entries using the correct `'type'` attribute in the XML file as this determines how the macro is treated by the code that does the replacement. Just copy a similar type of macro from the default recoding data file if you are adding new entries, which is unlikely as the file is quite comprehensive. There is only one other thing to note. The `'preferred'` attribute tells Biber to use a specific LaTeX macro when mapping from UTF-8, just in case there are more than one mappings from UTF-8 for a particular character. It's unlikely you will need to use this.

### 3.6.3 Examples

`biber`

Set `input_encoding` and `output_encoding` from the config file or `.bcf`

`biber --output_encoding=latin2`

Encode the `.bbl` as `latin2`, overriding the `.bcf`

`biber --output_safechars`

Set `input_encoding` and `output_encoding` from the config file or `.bcf`. Force encoding of UTF-8 chars to LaTeX macros using default conversion set

---

<sup>13</sup><https://sourceforge.net/projects/biblatex-biber/files/biblatex-biber/1.7/documentation/utf8-macro-map.html>

```

biber --output_encoding=ascii
    Encode the .bbl as ascii, overriding the .bcf. Automatically sets --output_safechars
    to force UTF-8 to LaTeX macro conversion
biber --output_encoding=ascii --output_safecharsset=full
    Encode the .bbl as ascii, overriding the .bcf. Automatically sets --output_safechars
    to force UTF-8 to LaTeX macro conversion using the full set of conversions
biber --decodecharsset=full
    Set input_encoding and output_encoding from the config file or .bcf. Use the
    full LaTeX macro to UTF-8 conversion set because you have some more obscure
    character macros in your .bib datasource which you want to sort correctly
biber --recodedata=/tmp/recode.xml --decodecharsset=special
    Specify a user-defined reencoding data file which defines a new reencoding set ‘spe-
    cial’ and use this set for decoding LaTeX macros to UTF-8.
biber -u
    Shortcut alias for biber --input_encoding=UTF-8
biber -U
    Shortcut alias for biber --output_encoding=UTF-8

```

### 3.7 List and Name Separators

With traditional BibTeX, the name and list field separator ‘and’ is hard-coded. The `btparse` C library and therefore Biber allows the use of any fixed string, subject to the same rules as ‘and’ (not at the beginning or end of the name/list, whitespace must surround the string etc.). This is settable using the options `listsep` and `namesep`, both of which default to the usual ‘and’. You can also change the default final name in a list which implies ‘et al’. In BibTeX, this is by default the English ‘others’ which is the Biber default also. Don’t try to put any whitespace in these strings, this is ignored by `btparse` anyway. Perhaps you prefer your `.bib` in more obvious German—set `--namesep=und` and `--others_string=andere` and then you can do:

```

@BOOK{key,
  AUTHOR = {Hans Harman und Barbara Blaupunkt und andere},
}

```

Bear in mind that these are global settings and apply to all entries in the BibTeX data format read by Biber. Also bear in mind that this is very unportable as all BibTeX input/output programs rely on the hard-coded ‘and’ and ‘others’. Hopefully this will change as these two hard-coded English terms look really rather bad in the context of multilingual bibliographies.

## 3.8 Editor Integration

Here is some information on how to integrate Biber into some of the more common editors

### 3.8.1 Emacs

Emacs has the powerful AUCT<sub>E</sub>X mode for editing T<sub>E</sub>X and running compilations. Biber is supported as of version 11.87 which has the following features relevant to Bibl<sub>a</sub>tex/Biber:

- Adds font-lock support for most Bibl<sub>a</sub>tex macros
- Auto-detects whether you are using Biber with Bibl<sub>a</sub>tex
- Can detect whether dependencies like datasources have changed without them being open in Emacs
- Understands Bibl<sub>a</sub>tex and Biber messages so that AUCT<sub>E</sub>X will prompt you with the best default command to run next when using C-cC-c

### 3.8.2 T<sub>E</sub>Xworks

It's very easy to add Biber support to T<sub>E</sub>Xworks. In the Preferences, select the Typesetting tab and then add a new Processing Tool as in Figure 3.




Figure 3: Screenshot of T<sub>E</sub>Xworks processing tool setup for Biber

## 3.9 BibT<sub>E</sub>X macros and the MONTH field

BibT<sub>E</sub>X defines macros for month abbreviations like ‘jan’, ‘feb’ etc. Biber also does this, defining them as numbers since that is what Bibl<sub>a</sub>tex wants. In case you are

also defining these yourself (although if you are only using Biblatex, there isn't much point), you will get macro redefinition warnings from the `btparse` library. You can turn off Biber's macro definitions to avoid this by using the option `--nostdmacros`.

Biber will look at any `MONTH` field in a `BIBTEX` data source and if it's not a number as Biblatex expects (because it wasn't one of the macros as mentioned above or these macros were disabled by `--nostdmacros`), it will try to turn it into the right number in the `.bbl`. If you only use Biblatex with your `BIBTEX` datasource files, you should probably make any `MONTH` fields be the numbers which Biblatex expects.

### 3.10 Biber datasource drivers

Biber uses a modular datasource driver model to provide access to supported datasources. The drivers are responsible for mapping driver entrytypes and fields to the Biblatex data model according to a data model specification in the Biblatex file `blx-dm.def`. The data model can be changed using Biblatex macros in case you would like to, for example, use your own entrytype or field names or perhaps have Biber do some validation on your datasources (see the Biblatex manual).

Data model mapping is an imprecise art and the drivers are the necessarily the most messy parts of Biber. Most datasource models are not designed with type-setting in mind and are usually not fine-grained enough to provide the sorts of information that Biblatex needs. Biber does its best to obtain as much meaningful information from a datasource as possible. Currently supported datasources drivers are:

- `BIBTEX` — `BIBTEX` data files
- `endnotexml` — Endnote XML export format, version  $\geq$  Endnote X1
- `ris` — Research Information Systems format
- `zoterordfxml` — Zotero RDF XML format, version 2.0.9

### 3.11 Visualising the Output

The option `--output_format=dot` will cause Biber to write a GraphViz<sup>14</sup> `.dot` file instead of a `.bbl`. This file graphs the bibliographic data as it exists after all processing. You can transform this file using the `dot` program from GraphViz to generate a high quality graphical representation of the data in a format of your choice. A good output format choice with `dot` is SVG<sup>15</sup> which can be viewed in any modern web browser. This format has the advantage of tooltips and Biber uses these to give you more information on connections between entries: hover the cursor on an arrow in the output and it will tell you what it means. To output in SVG, use this command after installing GraphViz:

---

<sup>14</sup><http://www.graphviz.org>

<sup>15</sup>Scalable Vector Graphics

Sub-option	Description
crossref	Show crossreference relationships
field	Show fields within entries
related	Show related entries and clones
section	Show sections
xdata	Show XDATA relationships
xref	Show XREF relationships

Table 4: Valid sub-options for the `dot_include` option

```
dot -Tsvg <file>.dot -o <file>.svg
```

The `--dot_include` option takes a comma delimited string as argument. The elements of this string define the information to include in the `.dot` output graph. The valid sub-options are shown in Table 4. If the `--dot_include` option is not given then the default setting is implicitly used, which is:

```
--dot_include=crossref,section,xdata,xref
```


### 3.12 Tool Mode

Biber can run in ‘tool’ mode which is enabled with the `--tool` command-line only option. In this mode, Biber is called: `biber --tool <datasource>`. It does not read any `.bcf` and does not output any `.bbl`. Instead, it reads all entries from the file ‘datasource’, applies any changes specified in the command-line options and Biber config file and writes the resulting datasource out to a new file, defaulting to a BibTeX file called ‘<datasource>\_bibertool.bib’ if the options `output_file` and `output_format` are not specified.

Tool mode is useful if you need to programatically change your datasource using the semantics provided by Biber or if you would like to convert your data to a different format. For example, you could choose to reencode your datasource by turning all UTF-8 characters into LaTeX macros:

```
biber --tool --output_encoding=ascii file.bib
```

This would output a copy of `file.bib` called `file_bibertool.bib` with all UTF-8 chars changed to LaTeX macros (because when the output is ASCII and the input encoding is not (it is by default UTF-8), then the `--output_safechars` option is automatically enabled). If you utilise the Biber config file, you can set up a complex set of mappings to transform your datasource however you wish in a semantic



A  $\xrightarrow{\text{B inherits by CROSSREF from A}}$  B

A  $\dashrightarrow^{\text{B inherits by XREF from A}}$  B

A  $\xrightarrow{\text{B inherits by XDATA from A}}$  B

A  $\xrightarrow{\text{A is a related entry of B}}$  B

A  $\dashrightarrow^{\text{B is a clone of A}}$  B

Figure 4: Key to .dot output format

manner much more robust than just textual search/replace. You can also use the `--tool_resolve` option which will process any `XDATA` fields/entries, entry aliases and inheritance rules mentioned in the config file (see below).

Sometimes, you might wish to output fields which are BibTeX macros, that is, you might want this:

```
@Entrytype{key,
  Field = something,
}
```

instead of this:

```
@Entrytype{key,
  Field = {something},
}
```

That is, you might not want the output field in braces or quotes as this prevents BibTeX interpreting the field value as a macro. Use the `--tool_macro_fields` option to specify a comma-separated list of fields whose values you wish to output without any BibTeX quoting. You can have spaces between the items in the field list but then you must enclose the whole option value in quotes. For example, these two will do the same thing:

```
biber --tool --tool_macro_fields=month,publisher
biber --tool --tool_macro_fields='month, publisher'
```

Tool mode also allows some reformatting of the `.bib` file. The option `--tool_fieldcase` can be used to force the entrytype and fieldnames to upper, lower or title case. The option `--tool_indent` can be used to customise the indentation of fields. The option `tool_align` can be used to align all field values neatly. See the Biber `--help` output for documentation and defaults. For example, the command:

```
biber --tool --tool_fieldcase=title --tool_indent=4 \
      --tool_align=true file.bib
```

results in `.bib` entries which look like this:

```
@Entrytype{key,
  Author    = {...},
  Title     = {...},
  Publisher = {...},
  Year      = {...},
}
```

another example:



```
biber --tool --tool_fieldcase=upper --tool_indent=2 \
      --tool_align=false file.bib
```

results in entries like this:

```
@ENTRYTYPE{key,
  AUTHOR = {...},
  TITLE = {...},
  PUBLISHER = {...},
  YEAR = {...},
}
```

Here is an example using the Biber config file to specify all options. This example uses tool mode to reformat the .bib and also to do some transformations using the source map functionality. Suppose `test.bib` contains the following:

```
@book{book1,
  author = {Doe,J.P.},
  title = {Ökologische Enterprises},
  year = {2013}
}
```

Further suppose that the `biber-test.conf` contains the following:

```
<?xml version="1.0" encoding="UTF-8"?>
<config>
  <tool_fieldcase>title</tool_fieldcase>
  <output_encoding>ascii</output_encoding>
  <output_safechars>1</output_safechars>
  <sourcemap>
    <maps datatype="bibtex" map_overwrite="1">
      <map map_overwrite="1">
        <map_step map_field_source="AUTHOR" map_match="Doe," map_final="1"/>
        <map_step map_field_source="AUTHOR"
          map_match="Doe,\s*J(?:\.|ohn)(?:[-]*)(?:P\.|Paul)*"
          map_replace="Doe, John Paul"/>
      </map>
    </maps>
  </sourcemap>
</config>
```

Now you can run Biber like this:

```
biber --tool --configfile=biber-tool.conf test.bib
```

The result will be in `test_bibertool.bib` and will look like this:

```
@Book{book1,
  Author = {Doe, John Paul},
  Title  = {\{"{0}kologische Enterprises},
  Year   = {2013},
}
```

Tool mode is a versatile way of performing many different operations on a `.bib` file. By using the config file and tool mode, we have:

- Consistently indented and aligned the entry, normalising fields and entrytype to title case
- Normalised the `AUTHOR` field name using regular expressions
- Converted UTF-8 characters to LaTeX macros, and made the output pure ASCII

If you do not specify any configuration file to use in tool mode, Biber will by default look for a config file in the usual way (see section 3.1) with the only difference that if no config file is found, it will use the default `biber-tool.conf` which is located in the Biber install tree in the same location as the `Config.pm` file. This default config file contains the default Biblatex source mappings for BibTeX datasources and also the default inheritance rules for `CROSSREF` processing. This means that when you use the `--tool_resolve` option, inheritance processing is performed on the entries and the results of this are ‘materialised’ in the output. For example, consider a `test.bib` file:

```
@BOOK{xd1,
  AUTHOR = {Edward Ellington},
  DATE   = {2007},
  XDATA  = {macmillanalias}
}

@XDATA{macmillan,
  IDS    = {macmillanalias},
  XDATA  = {macmillan:pubALIAS, macmillan:loc}
}

@XDATA{macmillan:pub,
  IDS      = {macmillan:pubALIAS},
  PUBLISHER = {Macmillan}
}

@XDATA{macmillan:loc,
  LOCATION = {New York and London},
  NOTE     = {A Note}
}
```

```

@BOOK{b1,
  TITLE = {Booktitle},
  CROSSREF = {mvalias}
}

@MVBOOK{mv1,
  IDS = {mvalias},
  TITLE = {Maintitle},
  SUBTITLE = {Mainsubtitle},
  TITLEADDON = {Maintitleaddon}
}

```

Running Biber as:

```
biber --tool --tool_resolve test.bib
```

The result of this would be a file `test_bibertool.bib` with contents:

```

@BOOK{xd1,
  AUTHOR   = {Edward Ellington},
  DATE     = {2007},
  LOCATION = {New York and London},
  NOTE     = {A Note},
  PUBLISHER = {Macmillan},
}

@XDATA{macmillan,
  LOCATION = {New York and London},
  NOTE     = {A Note},
  PUBLISHER = {Macmillan},
}

@XDATA{macmillan:pub,
  PUBLISHER = {Macmillan},
}

@XDATA{macmillan:loc,
  LOCATION = {New York and London},
  NOTE     = {A Note},
}

@BOOK{b1,
  MAINSUBTITLE = {Mainsubtitle},
  MAINTITLE    = {Maintitle},
  MAINTITLEADDON = {Maintitleaddon},
  TITLE       = {Booktitle},
}

```

<i>Option</i>	<i>Output format</i>	
	bibtex	biblatexml
tool_align	✓	
tool_indent	✓	✓
tool_fieldcase	✓	
tool_macro_fields	✓	
tool_resolve	✓	✓

Table 5: Applicability of the tool mode options

```

}

@MVBOOK{mv1,
  SUBTITLE = {Mainsubtitle},
  TITLE    = {Maintitle},
  TITLEADDON = {Maintitleaddon},
}

```

Notice here that:

- XDATA references have been resolved completely for entry `xd1`
- CROSSREF inheritance has been resolved according to the default Biblatex inheritance rules for entry `b1`
- Entry key aliases have been resolved as required in order to perform these tasks

Tool mode can also be used to convert between datasource formats<sup>16</sup>. For example, if you wish to convert a BibTeX format data file to the experimental `biblatexml` XML format, you can do:

```
biber --tool --output_format=biblatexml file.bib
```

This will output a file `file_bibertool.bltxml` by default. The applicability of the various tool mode options depend on the output format as shown in table 5.

### 3.12.1 Customising Tool Mode Inheritance Resolution

The default `biber-tool.conf` contains, as mentioned above, the default Biblatex CROSSREF inheritance setup and BibTeX source mappings so that tool mode resolution works as expected. Of course it is possible to customise these. In Biblatex, this

<sup>16</sup>This is currently rather experimental

is accomplished by the `\DeclareDataInheritance` macros which write appropriate XML into the `.bcf` file. Since no `.bcf` file is used in tool mode, the desired configuration must be put into a Biber config file. The source mapping XML specification is given in section 3.1.1. The inheritance XML specification is given in section 3.1.2. It is recommended to copy the default `biber-tool.conf` file, modify this and then use it as your own `biber.conf` file or pass it explicitly using the `--configfile|-g` option. You can determine the location of the default tool mode config file by using the `--tool_config` option which will show you the location of the config file and exit.

### 3.12.2 Customising Tool Mode Sorting

A global sorting scheme can be defined in the config file in order to sort the entries in tool mode output. See section 3.1.4 for the format of the config file sorting specification. By default, if sorting is enabled in tool mode, the sorting scheme is the same as the Biblatex `none` scheme, that is, no sorting is performed.

## 4 Binaries

Biber is a Perl application which relies heavily on quite a few modules. It is packaged as a stand-alone binary using the excellent `PAR::Packer` module which can pack an entire Perl tree plus dependencies into one file which acts as a stand-alone binary and is indistinguishable from such to the end user. You can also simply download the Perl source and run it as a normal Perl program which requires you to have a working Perl 5.16+ installation and the ability to install the pre-requisite modules. You would typically only do this if you wanted to keep up with all the bleeding-edge git commits before they had been packaged as a binary. Almost all users will not want to do this and should use the binaries from their  $\text{\TeX}$  distribution or downloaded directly from SourceForge in case they need to use a more recent binary than is included in their  $\text{\TeX}$  distribution.

The binary distributions of Biber are made using the Perl `PAR::Packer` module. They can be used as a normal binary but have some behaviour which is worth noting:

- Don't be worried by the size of the binaries. `PAR::Packer` essentially constructs a self-extracting archive which unpacks the needed files first.
- On the first run of a new version (that is, with a specific hash), they actually unpack themselves to a temporary location which varies by operating system. This unpacking can take a little while and only happens on the first run of a new version. **Please don't kill the process if it seems to take some time to do anything on the first run of a new binary.** If you do, it will not unpack everything and it will almost certainly break Biber. You will then

have to delete your binary cache (see section 4.1 below) and re-run the Biber executable again for the first time to allow it to unpack properly.

## 4.1 Binary Caches

**PAR::Packer** works by unpacking the required files to a cache location. It only does this on the first run of a binary by computing a hash of the binary and comparing it with the cache directory name which contains the hash. So, if you run several versions of a binary, you will end up with several cached trees which are never used. This is particularly true if you are regularly testing new versions of the Biber binary. It is a good idea to delete the caches for older binaries as they are not needed and can take up a fair bit of space. The caches are located in a temporary location which varies from OS to OS. The cache name is:

```
par-<hex_encoded_username>/cache-<hash> (Linux/Unix/OSX)
par-<hex_encoded_username>\cache-<hash> (Windows)
```

The temp location is not always obvious but these are sensible places to look (where \* can vary depending on username):

- /var/folders/\*/\*/\*/ (OSX, local GUI login shell)
- /var/tmp/ (OSX (remote ssh login shell), Unix)
- /tmp/ (Linux)
- C:\Documents and Settings\<username>\Local Settings\Temp (Windows/Cygwin)
- C:\Windows\Temp (Windows)

To clean up, you can just remove the whole `par-<hex_encoded_username>` directory/folder and then run the current binary again. You can see the active cache by running biber with the `--cache` option which will print the current cache location and exit.

## 4.2 Binary Architectures

Binaries are available for many architectures, directly on SourceForge and also via `TEXLive`:

- linux\_x86\_32
- linux\_x86\_64
- MSWin32
- cygwin32
- darwin\_x86\_64

- darwin\_x86\_i386
- freebsd\_x86<sup>17</sup>
- freebsd\_amd64<sup>17</sup>
- solaris\_x86<sup>17</sup>

If you want to run development versions, they are usually only regularly updated for the core architectures which are not flagged as third-party built above. If you want to regularly run the latest development version, you should probably git clone the relevant branch and run Biber as a pure Perl program directly.

### 4.3 Installing

These instructions only apply to manually downloaded binaries. If Biber came with your T<sub>E</sub>X distribution just use it as normal.

Download the binary appropriate to you OS/arch<sup>18</sup>. Below I assume it's on your desktop.

You have to move the binary to somewhere in you command-line or T<sub>E</sub>X utility path so that it can be found. If you know how to do this, just ignore the rest of this section which contains some instructions for users who are not sure about this.

#### 4.3.1 OSX

If you are using the T<sub>E</sub>XLive MacT<sub>E</sub>X distribution:

```
sudo mv ~/Desktop/biber /usr/texbin/
sudo chmod +x /usr/texbin/biber
```

If you are using the MacPorts T<sub>E</sub>XLive distribution:

```
sudo mv ~/Desktop/biber /opt/local/bin/
sudo chmod +x /opt/local/bin/biber
```

The 'sudo' commands will prompt you for your password.

#### 4.3.2 Windows

The easiest way is to just move the executable into your C:\Windows directory since that is always in your path. A more elegant is to put it somewhere in your T<sub>E</sub>X distribution that is already in your path. For example if you are using MiK<sub>T</sub>E<sub>X</sub>:

C:\Program Files\MiKTeX 2.9\miktex\bin\

<sup>17</sup>Binary maintained by third party. See README in binary download directory for this platform for support/contact details. Usually, the binary maintainer is also the binary build provider for T<sub>E</sub>XLive.

<sup>18</sup><https://sourceforge.net/projects/biblatex-biber>

### 4.3.3 Unix/Linux

```
sudo mv ~/Desktop/biber /usr/local/bin/biber
sudo chmod +x /usr/local/bin/biber
```

Make sure `/usr/local/bin` is in your `PATH`. Search Google for ‘set `PATH` linux’ if unsure about this. There are many pages about this, for example: <http://www.cyberciti.biz/faq/unix-linux-adding-path/>

## 4.4 Building

Instructions for those who want/need to build an executable from the Perl version. For this, you will need to have Perl 5.16+ with the following modules:

- All Biber pre-requisites
- `PAR::Packer` and all dependencies

You should have the latest CPAN versions of all required modules as Biber is very specific in some cases about module versions and depends on recent fixes in many cases. You can see if you have the Biber Perl dependencies by the usual

```
perl ./Build.PL
```

invocation in the Biber Perl distribution tree directory. Normally, the build procedure for the binaries is as follows<sup>19</sup>:

- Get the Biber source tree from SF and put it on the architecture you are building for
- `cd` to the root of the source tree
- `perl Build.PL` (this will check your module dependencies)
- `Build test`
- `Build install` (may need to run this as `sudo` on Unix-like systems)
- `cd dist/<arch>`
- `build.sh` (`build.bat` on Windows)

This leaves a binary called ‘`biber-<arch>`’ (also with a ‘`.exe`’ extension on Windows/Cygwin) in your current directory. The tricky part is constructing the information for the build script. There are two things that need to be configured, both of which are required by the `PAR::Packer` module:

1. A list of modules/libraries to include in the binary which are not automatically detected by the `PAR::Packer` dependency scanner

---

<sup>19</sup>On Unix-like systems, you may need to specify a full path to the scripts e.g. `./Build`



2. A list of extra files to include in the binary which are not automatically detected by the `PAR::Packer` dependency scanner

To build Biber for a new architecture you need to define these two things as part of constructing new build scripts:

- Make a new sub-folder in the `dist` directory named after the architecture you are building for. This name is arbitrary but should be fairly obvious like `'solaris-sparc-64'`, for example.
- Copy the `biber.files` file from an existing build architecture into this directory.
- For all of the files with absolute pathnames in there (that is, ones we are not pulling from the Biber tree itself), locate these files in your Perl installation tree and put the correct path in the file.
- Copy the build script from a vaguely similar architecture (i.e. Windows/non-Windows ...) to your new architecture directory.
- Change the `--link` options to point to where the required libraries reside on your system.
- Change the `--output` option to name the resulting binary for your architecture.
- Run the build script

The `--link` options can be a little tricky sometimes. It is usually best to build without them once and then run `ldd` (or OS equivalent) on the binary to see which version/location of a library you should link to. You can also try just running the binary and it should complain about missing libraries and where it expected to find them. Put this path into the `--link` option. The `--module` options are the same for all architectures and do not need to be modified. On architectures which have or can have case-insensitive file systems, you should use the build script from either Windows or OSX as a reference as these include a step to copy the main Biber script to a new name before packing the binary. This is required as otherwise a spurious error is reported to the user on first run of the binary due to a name collision when it unpacks itself.

See the PAR wiki page<sup>20</sup> for FAQs and help on building with `PAR::Packer`. Take special note of the FAQs on including libraries with the packed binary<sup>21</sup>.

#### 4.4.1 Testing a binary build

You can test a binary that you have created by copying it to a machine which preferably doesn't have `perl` at all on it. Running the binary with no arguments

---

<sup>20</sup>[http://par.perl.org/wiki/Main\\_Page](http://par.perl.org/wiki/Main_Page)

<sup>21</sup><http://par.perl.org/wiki/FAQ>, section entitled 'My PAR executable needs some dynamic libraries'

will unpack it in the background and display the help. To really test it without having LaTeX available, get the two quick test files from SourceForge<sup>22</sup>, put them in a directory and run Biber in that directory like this:

```
biber --validate_control --convert_control test
```

This will run Biber normally on the test files plus it will also perform an XSLT transform on the .bcf and leave an HTML representation of it in the same directory thus testing the links to the XML and XSLT libraries as well as the BibTeX parsing libraries. The output should look something like this (may be differences of Biber version and locale of course but there should be no errors or warnings).

```
INFO - This is Biber 1.7
INFO - Logfile is 'test.blg'
INFO - BibLaTeX control file 'test.bcf' validates
INFO - Converted BibLaTeX control file 'test.bcf' to 'test.bcf.html'
INFO - Reading 'test.bcf'
INFO - Found 1 citekeys in bib section 0
INFO - Processing bib section 0
INFO - Looking for BibTeX format file 'test.bib' for section 0
INFO - Found BibTeX data file 'test.bib'
INFO - Decoding LaTeX character macros into UTF-8
INFO - Sorting list 'MAIN' keys
INFO - No sort tailoring available for locale 'en_GB.UTF-8'
INFO - Sorting list 'SHORTHANDS' keys
INFO - No sort tailoring available for locale 'en_GB.UTF-8'
INFO - Writing 'test.bbl' with encoding 'UTF-8'
INFO - Output to test.bbl
```

There should now be these new files in the directory:

```
test.bcf.html
test.blg
test.bbl
```

---

<sup>22</sup><https://sourceforge.net/projects/biblatex-biber/files/biblatex-biber/testfiles>