
Masarykova univerzita Přírodovědecká fakulta Ústav matematiky a statistiky

Bakalářská práce

Brno 2000 Jane Doe



Masarykova univerzita Přírodovědecká fakulta





Brno 2000

Principy matematické sazby v programu T_EX

Bakalářská práce

Jane Doe

Vedoucí práce: John Smith

Bibliografický záznam

Autor: Jane Doe

Přírodovědecká fakulta, Masarykova univerzita

Ústav matematiky a statistiky

Název práce: Principy matematické sazby v programu TeX

Studijní program: Matematika

Obor: Finanční a pojistná matematika

Vedoucí práce: John Smith

Akademický rok: 1999/2000

Počet stran: 19

Klíčová slova: klíčové slovo 1, klíčové slovo 2, ...

Bibliographic record

Author: Jane Doe

Faculty of Science, Masaryk University Department of Mathematics and Statistics

Title of Thesis: The Principles of the Typesetting of Mathe-

matics in TeX: the Program

Degree Programme: Mathematics

Field of study: Financial and Insurance Mathematics

Supervisor: John Smith

Academic Year: 1999/2000

Number of Pages: 19

Keywords: keyword1, keyword2, ...

Abstrakt

This is the abstract of my thesis, which can span multiple paragraphs.

Abstract

This is the English abstract of my thesis, which can span multiple paragraphs.

This is where a copy of the official signed thesis assignment is located in the printed version of the document.

Poděkování

This is the acknowledgement for my thesis, which can span multiple paragraphs.

Prohlášení

Prohlašuji, že jsem svoji bakalářskou práci vypracovala samostat	ně
s využitím informačních zdrojů, které jsou v práci citovány.	

Brno, 1. ledna 2000	
	Podpis autora

Contents

1	Introduction	1				
2	These are 2.1 the available	3 3 3				
3	Floats and references	5				
4	Mathematical equations	7				
5	We have several fonts at disposal	9				
6	Inserting the bibliography 11					
Bi	bliography	13				
7	Inserting the index	15				
In	dex	17				
A	An appendix	19				

List of Tables

3.1 A weather forecast 6

List of Figures

- 3.1
- 3.2

1 Introduction

Theses are rumoured to be the capstones of education, so I decided to write one of my own. If all goes well, I will soon have a diploma under my belt. Wish me luck!

Říká se, že závěrečné práce jsou vyvrcholením studia a tak jsem se rozhodl jednu také napsat. Pokud vše půjde podle plánu, odnesu si na konci semestru diplom. Držte mi palce!

Hovorí sa, že záverečné práce sú vyvrcholením štúdia a tak som sa rozhodol jednu tiež napísať. Ak všetko pôjde podľa plánu, odnesiem si na konci semestra diplom. Držte mi palce!

Man munkelt, dass die Dissertation die Krönung der Ausbildung ist. Deshalb habe ich mich beschlossen meine eigene zu schreiben. Wenn alles gut geht, bekomme ich bald ein Diplom. Wünsch mir Glück!

Говорят, что тезис – это кульминация обучения. Поэтому я и решил написать собственный тезис. Если всё сработает по плану, я скоро получу диплом. Желайте мне удачи!

2 These are

2.1 the available

2.1.1 sectioning

commands.

Paragraphs and

subparagraphs are available as well. Inside the text, you can also use unnumbered lists,

- such as
- this one
 - and they can be nested as well.
 - » You can even turn the bullets into something fancier,
 - § if you so desire.

Numbered lists are

- 1. very
 - (a) similar

and so are description lists:

Description list A list of terms with a description of each term

The spacing of these lists is geared towards paragraphs of text. For lists of words and phrases, the paralist package offers commands

- that
 - are
 - * better
 - · suited
- 1. to
 - (a) this
 - i. kind of

A. content.

The amsthm package provides the commands necessary for the typesetting of mathematical definitions, theorems, lemmas and proofs.

Theorem 2.1.1. This is a theorem that offers a profound insight into the mathematical sectioning commands.

Theorem 2.1.2 (Another theorem). *This is another theorem. Unlike the first one, this theorem has been endowed with a name.*

Lemma 2.1.3. Let us suppose that $x^2 + y^2 = z^2$. Then

$$\left\langle u \mid \sum_{i=1}^{n} F(e_i, v)e_i \right\rangle = F\left(\sum_{i=1}^{n} \langle e_i | u \rangle e_i, v\right).$$
 (2.1)

Proof.
$$\nabla^2 f(x,y) = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2}.$$

Corollary 2.1.4. *This is a corollary.*

Remark. This is a remark.

3 Floats and references

The logo of the Masaryk University is shown in Figure 3.1 and Figure 3.2 at pages 5 and 6. The weather forecast is shown in Table 3.1 at page 6. The following chapter is Chapter 4 and starts at page 7. Items 3, 3b, and 3(c)iv are starred in the following list:

- 1. some text
- 2. some other text
- 3. *
 - (a) some text
 - (b) *
 - (c) some other text
 - i. some text
 - ii. some other text
 - iii. yet another piece of text
 - iv. ⋆
 - (d) yet another piece of text
- 4. yet another piece of text

If your reference points to a place that has not yet been typeset, the \ref command will expand to ?? during the first run of pdflatex sci-pdflatex.tex and a second run is going to be needed for the references to resolve. With online services – such as Overleaf – this is performed automatically.



Figure 3.1: The logo of the Masaryk University at 40 mm



Figure 3.2: The logo of the Masaryk University at $\frac{2}{3}$ and $\frac{1}{3}$ of text width

Day	Min Temp	Max Temp	Summary
Monday	13°C	21°C	A clear day with low wind and no adverse current advisories.
Tuesday	11°C	17°C	A trough of low pressure will come from the northwest.
Wednesday	10°C	21°C	Rain will spread to all parts during the morning.

Table 3.1: A weather forecast

4 Mathematical equations

TEX comes pre-packed with the ability to typeset inline equations, such as $e^{ix} = \cos x + i \sin x$, and display equations, such as

$$\mathbf{A}^{-1} = \begin{bmatrix} a & b \\ c & d \end{bmatrix}^{-1} = \frac{1}{\det(\mathbf{A})} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix} = \frac{1}{ad - bc} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix}.$$

LATEX defines the automatically numbered equation environment:

$$\gamma Px = PAx = PAP^{-1}Px. \tag{4.1}$$

The package amsmath provides several additional environments that can be used to typeset complex equations:

1. An equation can be spread over multiple lines using the multline environment:

$$a + b + c + d + e + f + b + c + d + e + f + b + c + d + e + f + g + h + i + j + k + l + m + n + o + p + q$$
 (4.2)

2. Several aligned equations can be typeset using the align environment:

$$a + b = c + d \tag{4.3}$$

$$u = v + w + x \tag{4.4}$$

$$i + j + k + l = m \tag{4.5}$$

3. The alignat environment is similar to align, but it doesn't insert horizontal spaces between the individual columns:

$$a+b+c+d = 0 (4.6)$$

$$e + f + g = 5 \tag{4.7}$$

4. Much like chapter, sections, tables, figures, or list items, equations – such as (4.8) and (My equation) – can also be labeled and referenced:

$$b_{11}x_1 + b_{12}x_2 + b_{13}x_3 = y_1, (4.8)$$

$$b_{21}x_1 + b_{22}x_2 + b_{24}x_4 = y_2.$$
 (My equation)

4. Mathematical equations

5. The gather environment makes it possible to typeset several equations without any alignment:

$$\psi = \psi \psi, \tag{4.9}$$

$$\eta = \eta \eta \eta \eta \eta, \qquad (4.10)$$

$$\theta = \theta. \qquad (4.11)$$

$$\theta = \theta. \tag{4.11}$$

6. Several cases can be typeset using the cases environment:

$$|y| = \begin{cases} y & \text{if } z \ge 0, \\ -y & \text{otherwise.} \end{cases}$$
 (4.12)

For the complete list of environments and commands, consult the amsmath package manual¹.

 $See \ \ \texttt{http://mirrors.ctan.org/macros/latex/required/amslatex/math/}$ ${\tt amsldoc.pdf}.$ The ${\tt \url command}$ is provided by the package url.

5 We have several fonts at disposal

The serified roman font is used for the main body of the text. *Italics are typically used to denote emphasis or quotations*. The teletype font is typically used for source code listings. The **bold**, SMALL-CAPS and sans-serif variants of the base roman font can be used to denote specific types of information.

we can also change the font size, although it is usually not necessary.

A wide variety of mathematical fonts is also available, such as:

ABC, ABC, ABC, ABC, ABC, ABC

By loading the amsfonts packages, several additional fonts will become available:

ABC, ABC

Many other mathematical fonts are available¹.

^{1.} See http://tex.stackexchange.com/a/58124/70941.

6 Inserting the bibliography

After linking a bibliography database files to the document using the \thesissetup{bib={file1, file2, . . . }} command, you can start citing the entries. This is just dummy text [1] lightly sprinkled with citations [2, p. 123]. Several sources can be cited at once: [3, 4, 5]. "Fundamental Algorithms" was written by Knuth in 1973. We can also produce Knuth [1] or (Knuth [1], 1973). The full bibliographic citation is: KNUTH, Donald E. Fundamental Algorithms. In: Second. Reading, Massachusetts: Addison-Wesley, 1973, vol. 1, chap. 1.2, pp. 10–119. The Art of Computer Programming. This is a full INBOOK entry. We can easily insert a bibliographic citation into the footnote¹.

The \nocite command will not generate any output, but it will insert its arguments into the bibliography. The \nocite{*} command will insert all the records in the bibliography database file into the bibliography. Try uncommenting the command and watch the bibliography section come apart at the seams.

When typesetting the document for the first time, citing a work will expand to [work] and the \printbibliography command will produce no output. It is now necessary to generate the bibliography by running biber sci-pdflatex.bcf from the command line and then by typesetting the document again twice. During the first run, the bibliography section and the citations will be typeset, and in the second run, the bibliography section will appear in the table of contents.

The biber command needs to be executed from within the directory, where the LATEX source file is located. In Windows, the command line can be opened in a directory by holding down the Shift key and by clicking the right mouse button while hovering the cursor over a directory. Select the Open Command Window Here option in the context menu that opens shortly afterwards.

With online services – such as Overleaf – all commands are executed automatically. When you omit the \printbibliography command, its location will be decided by the template.

^{1.} Knuth, Donald E. Fundamental Algorithms. In: Second. Reading, Massachusetts: Addison-Wesley, 1973, vol. 1, chap. 1.2, pp. 10–119. The Art of Computer Programming. This is a full INBOOK entry.

Bibliography

- 1. KNUTH, Donald E. Fundamental Algorithms. In: Second. Reading, Massachusetts: Addison-Wesley, 1973, vol. 1, chap. 1.2, pp. 10–119. The Art of Computer Programming. This is a full INBOOK entry.
- LINCOLL, Daniel D. Semigroups of Recurrences. In: LIPCOLL, David J.; LAWRIE, D. H.; SAMEH, A. H. (eds.). High Speed Computer and Algorithm Organization. Third. New York: Academic Press, 1977, chap. 3, pp. 179–183. Fast Computers, no. 23. This is a full INCOL-LECTION entry.
- 3. OAHO, Alfred V.; ULLMAN, Jeffrey D.; YANNAKAKIS, Mihalis. On Notions of Information Transfer in VLSI Circuits. In: OZ, Wizard V.; YANNAKAKIS, Mihalis (eds.). *Proc. Fifteenth Annual ACM Symposium on the Theory of Computing*. Boston: Academic Press, 1983, pp. 133–139. All ACM Conferences, no. 17. This is a full INPROCEDINGS entry.
- 4. MANMAKER, Larry. *The Definitive Computer Manual*. Silver. Silicon Valley, 1986. This is a full MANUAL entry.
- 5. MASTERLY, Édouard. *Mastering Thesis Writing*. English Department, 1988. Master's project. Stanford University. This is a full MASTERS-THESIS entry.
- 6. KNVTH, Jill C. *The Programming of Computer Art* [Vernier Art Center]. Stanford, California, 1988. This is a full BOOKLET entry.

7 Inserting the index

After using the \makeindex macro and loading the makeidx package that provides additional indexing commands, index entries can be created by issuing the \index command. It is possible to create ranged index entries, which will encompass a span of text. To insert complex typographic material – such as α or TEX – into the index, you need to specify a text string, which will determine how the entry will be sorted. It is also possible to create hierarchal entries.

After typesetting the document, it is necessary to generate the index by running

```
texindy -I latex -C utf8 -L \langle locale \rangle sci-pdflatex.idx
```

from the command line, where $\langle locale \rangle$ corresponds to the main locale of your thesis – such as english, and then typesetting the document again.

The texindy command needs to be executed from within the directory, where the LATEX source file is located. In Windows, the command line can be opened in a directory by holding down the Shift key and by clicking the right mouse button while hovering the cursor over a directory. Select the Open Command Window Here option in the context menu that opens shortly afterwards.

With online services – such as Overleaf – the commands are executed automatically, although the locale may be erroneously detected, or the makeindex tool (which is only able to sort entries that contain digits and letters of the English alphabet) may be used instead of texindy. In either case, the index will be ill-sorted.

Index

```
A
α, 15

D
dummy text, 15

T
ΤΕΧ, 15

V
vehicles
speed cars, 15
trucks, 15
```

A An appendix

Here you can insert the appendices of your thesis.