

Using M↓ inside T_EX Documents

TUG@BachoT_EX 2017

https://github.com/witiko/markdown

Vít Novotný

Contents

- 1. Introduction
 - 1.1 The Case for Lightweight Markup
 - **1.2** Existing Solutions
- 2. The Markdown Package
 - 2.1 Building a Parser
 - 2.2 Using Markdown from Within ETFX
- 3. Conclusion
- 4. Bibliography

Section 1

Introduction

T_FX as a Markup Language

- 1. High Markup to Text Ratio
 - The T_FXbook (Knuth, 1986) is 22 % markup (plain T_FX).
 - Think Java (Downey et al., 2016) is 21% markup (上下X).

2. Zero Sandboxing Support

- The document you are typesetting may not compile.

```
\texttt{innocent_looking_underscores.tex}
```

The document you are typesetting may halt.

```
\def\whiletrue{\whiletrue} \whiletrue
```

- The document you are typesetting may access the system shell.

```
\immediate\write18{sudo rm -rf /}
```

3. Steep Learning Curve

Comparison of ETFX and Markdown

```
\section{This is a level one heading}
This is a text paragraph with \emph{emphasis}.
\begin{quotation}This paragraph will show as a quote.\end{quotation}
\begin{verbatim}
This is is a source code example.
\end{verbatim}
\begin{itemize}
  \item First item with \alert{strong emphasis}
  \item Second item with a link%
    \footnote{See \url{http://link.com} (Title)}
\end{itemize}
\begin{enumerate}
  \item First item with \verb`inline code`.
  \item Second item with an \includegraphics{image.png}
\end{enumerate}
```

Comparison of ETFX and Markdown

This is a level one heading

This is a text paragraph with <u>_emphasis_</u>.

> This paragraph will show as a quote.

This is is a source code example.

- * First item with **strong emphasis**
- * Second item with a [link](http://link.com/ "Title")
- 1. First item with `inline code`.
- 2. Second item with an ![image](image.png "Title")

The Language of Markdown

The overriding design goal for Markdown's formatting syntax is to make it as readable as possible. The idea is that a Markdown-formatted document should be publishable as-is, as plain text, without looking like it's been marked up with tags or formatting instructions. While Markdown's syntax has been influenced by several existing text-to-HTML filters, the single biggest source of inspiration for Markdown's syntax is the format of plain text email.

- Gruber (2004), emphasis mine

Markdown as a Markup language

- 1. Minimal Markup to Text Ratio
 - Recall: Knuth (1986) and Downey et al. (2016) are ~22 % markup.
 - Efficient R programming (Gillespie et al., 2016) is 5.5 % markup.
 - R for Data Science (Grolemund et al., 2016) is 3.8 % markup.
- 2. Either Sandboxing Support ...
 - A Markdown document converted to TFX will always compile.
 - The document may neither halt nor access the shell.
- 3. ... or Hybrid Markup Support
 - Structurally simple sections can use pure Markdown, complex sections may combine Markdown and the host markup.
- 4. Mild Learning Curve

Existing Solutions

The Swiss Army Knife of Pandoc

If you need to convert files from one markup format into another, Pandoc is your swiss-army knife.

- MacFarlane (2016b), emphasis mine
- A multi-target publishing software.
- Supports tens of markup languages (Markdown, 上X, HTML, XML Docbook) and output formats (ODF, OOXML, PDF).
- The use of Pandoc for the preparation of ETEX documents has been described in TUGBoat by Dominici (2014).

Existing Solutions

What is Wrong with Pandoc?

Difficult to Change Output Markup

```
# Heading {#link}
This is [a link](#link).

\limits \limits \limits \limits \left\ \left
```

- 2. Not a Part of T_EX Distributions
 - Markdown documents cannot be directly edited at collaborative
 TFX platforms such as Share ETFX or Overleaf.

Existing Solutions

What is Wrong with Pandoc?

3. Half-hybrid, Half-sandboxed

- The input is heuristically parsed and sanitized:

```
This {will} 2^n \begin{qet} s~nitized and \this{will}
not \begin{equation}2^n\end{equation} $2^n$.
```

```
This \{will\} 2\^{}n \textbackslash{}begin\{get\}
s\textasciitilde{}nitized and \this{will} not
\begin{equation}2^n\end{equation} \(2^n\).
```

Malicious input such as

```
\def\shell{18} \immediate\write\shell{sudo rm -rf /}
is left alone by Pandoc.
```

Section 2

The Markdown Package

Is T_EX Up to the Task?

There exist formal language parsers written solely in T_EX. These parsers recognize regular (ET_EX3 Project, 2016) and context-free LL(1) languages (Carlisle, 2000). Markdown is not context-free:

```
``There is a literal backtick (`) here.``
```

and a parser needs to be able to backtrack over the entire input:

```
[this is not a link](http://link.com/ "Title"
```

Implementing a recursive-descent parser with backtracking in T_EX is possible, but generally a bad idea:

- Difficult to Maintain, Highly Unidiomatic
- Lack of Efficient Data Structures

Can We Use Lua Instead of T_EX?

Lua is a powerful, efficient, lightweight, embeddable scripting language. It supports procedural programming, object-oriented programming, functional programming, data-driven programming, and data description.

- Lua Team (2016)

LuaT_EX is an extended version of pdfT_EX using Lua as an embedded scripting language.

— LuaT_EX Team (2016)

Can We Use Lua Instead of T_FX?

• With LuaT_FX, we can directly execute Lua code:

```
1 + 2 = \langle directlua \{ tex.sprint(1 + 2) \}
```

 With pdfT_EX and other modern T_EX engines, we can spawn a shell and execute the Lua code in a separate process:

```
1 + 2 = \newwrite\script
\immediate\openout\script=script.lua
\immediate\write\script{ print(1 + 2) }%
\immediate\closeout\script
\immediate\write18{texlua script.lua > output.tex}%
\input output.tex
```

The Lunamark Library


- Lunamark (MacFarlane, 2016a) is a Markdown parser in Lua.
- The language is specified using a Parsing Expression Grammar (PEG) via the LPeg C library (and a bit of cheating).
- The dependencies of Lunamark were all either compiled into LuaT_FX (LPeg, Slnunicode), or unneeded (Cosmo, Alt-getopt).
- The library has been released under the Expat (MIT) License.

The Lunamark Library

A modified version of Lunamark transforms an input Markdown document into a plain T_EX document that encodes its structure:

Heading

This is [a link](#link).



\markdownRendererHeadingOne{Heading}

This is \markdownRendererLink{a link}{#link}{#link}{}.

A plain T_EX macro package defines the \markdownRenderer... macros and typesets the plain T_EX document produced by Lunamark.

The Sandbox and Hybrid Modes

```
\documentclass{article}
\usepackage{markdown}
\begin{document}
\begin{markdown}
  Foo bar \TeX{} $2^n$.
\end{markdown}
\begin{markdown*}{hybrid}
  Foo bar \TeX{} $2^n$.
\end{markdown*}
\end{document}
Foo bar T_EX $2^n$. Foo bar T_EX 2<sup>n</sup>.
```

Mapping Markdown Tokens to T_FX Macros

```
\documentclass{article}
\usepackage{markdown}
\markdownSetup{renderers = {
  link = {#1\footnote{See \url{#3} (#4)}},
}}
\begin{document}
\begin{markdown}
  Foo [bar](http://link.com "Link").
\end{markdown}
\end{document}
Foo bar<sup>1</sup>.
```

¹See http://link.com (Link)

Syntax Extensions

- Some syntax extensions were already supported by Lunamark:
 - footnotes,
 - definition lists.
- New syntax extensions were added as a part of the project:
 - citations,
 - fenced code blocks.

Syntax Extensions - \markdownSetup{footnotes}

Here is a footnote reference, [^1] and another. [^long]

[^1]: Here is the footnote.

[^long]: Here's one with multiple blocks.

Subsequent paragraphs are indented to show that they belong to the footnote.

Subsequent paragraphs are indented to show that they belong to the footnote.

Here is a footnote reference,² and another.³

²Here is the footnote.

³Here's one with multiple paragraphs.

Syntax Extensions - \markdownSetup{definitionLists}

Term 1

: Definition

Term 2

: Definition with

multiple paragraphs

Term 1 Definition 1

Term 2 Definition with multiple paragraphs

Syntax Extensions - \markdownSetup{citations}

Here is a parenthetical citation [@knuth86] and a string of several [see @knuth86, pp. 33-35; also @gruber04, chap. 1].

Here is a text citation @knuth86 and a string of several @knuth86 [pp. 33-35; @gruber04, chap. 1].

Here is a parenthetical citation (Knuth, 1986) and a string of several (see Knuth, 1986, pp. 33-35; also Gruber, 2004, chap. 1). Here is a text citation Knuth (1986) and a string of several Knuth (1986, pp. 33-35) and Gruber (2004, chap. 1).

Syntax Extensions - \markdownSetup{fencedCode}

```
~~~ js
if (a > b)
  return c + 4;
else
  return d + 5;
if (a > b)
  return c + 4;
else
  return d + 5;
```

Section 3

Conclusion

Conclusion

The Missing Pieces of the Puzzle

- Apart from the LTEX interface, the package also exposes Lua, plain TEX and ConTEXt interfaces.
- The package includes 82 pages of user and technical documentation. (Novotný, 2016a)
- A section on writing ETEX documents in Markdown was added to the fithesis3 sample documents.
- The package was released under the MEX Project Public License (LPPL) 1.3 on the Comprehensive TEX Archive Network (CTAN), GitHub, and the faculty GitLab. (Novotný, 2016c) It is available in updated TEX Live 2016.

Conclusion

Reception by the Community

- The syntax extensions were backported to Lunamark and merged by MacFarlane, resulting in a new minor version release of the library (0.5.0). (Novotný, 2016b)
- The package was featured on the twitter profile of Overleaf a major online service for preparing ETEX documents – along with original example documents. (Overleaf, 2016)
- The package was reviewed in the bulletin of the German T_EX Users Group (DANTE e.V.). (Fenn, 2016, pp. 43)
- An article about the package has been accepted for publication in the bulletin of the Czechoslovak T_EX Users Group (CSTUG).

Section 4

Bibliography

Bibliography I

```
ETEX3 PROJECT, 2016. The l3regex package: regular expressions in TeX
[online] [visited on 2016-11-08]. Available from:
  http://mirrors.ctan.org/macros/latex/contrib/
l3experimental/l3regex.pdf.
```

CARLISLE, David, 2000. XMLT_EX: A non-validating (and not 100% conforming) namespace-aware XML parser implemented in T_EX. *TUGboat* [online]. Vol. 21, no. 3, pp. 193–199 [visited on 2016-11-08]. ISSN 0896-3207. Available from: https://www.tug.org/TUGboat/tb21-3/tb68carl.pdf.

Bibliography II

DOMINICI, Massimiliano, 2014. An overview of Pandoc. *TUGboat* [online]. Vol. 35, no. 1, pp. 44–50 [visited on 2016-08-15]. ISSN 0896-3207. Available from:

http://tug.org/TUGboat/tb35-1/tb109dominici.pdf.

DOWNEY, Allen B.; MAYFIELD, Chris, 2016. *Think Java: How to Think Like a Computer Scientist* [online]. Green Tea Press. Version 6.1.0 [visited on 2016-11-08]. Available from:

http://thinkjava.org/.

FENN, Jürgen, 2016. Neue Pakete auf CTAN. Die TeXnische Komödie. No. 3/2016. ISSN 1434-5897.

Bibliography III

FORD, Bryan, 2002. Packrat Parsing: Simple, powerful, lazy, linear time, functional pearl. In: *Packrat Parsing: Simple, powerful, lazy, linear time, functional pearl. ACM SIGPLAN Notices* [online]. Vol. 37, pp. 36–47 [visited on 2016-11-08]. No. 9. Available from DOI: 10.1145/581478.581483.

FORD, Bryan, 2004. Parsing expression grammars: A recognition-based syntactic foundation. In: Parsing expression grammars: A recognition-based syntactic foundation. ACM SIGPLAN Notices [online]. Vol. 39, pp. 111–122 [visited on 2016-08-16]. No. 1. Available from DOI: 10.1145/964001.964011.

Bibliography IV

```
GILLESPIE, Colin; LOVELACE, Robin, 2016. Efficient R programming [online]. O'Reilly Media [visited on 2016-11-08]. ISBN 978-1-4919-5078-4. Available from: https://github.com/hadley/r4ds/.
```

GROLEMUND, Garrett; WICKHAM, Hadley, 2016. *R for Data Science* [online]. O'Reilly Media [visited on 2016-11-08]. ISBN 978-1-4919-1039-9. Available from:

https://github.com/hadley/r4ds/.

GRUBER, John, 2004. *Markdown* [online] [visited on 2016-08-15]. Available from:

https://daringfireball.net/projects/markdown/.

Bibliography V

- KNUTH, Donald Ervin, 1986. *The T_EXbook* [online]. 3rd ed.
 Addison-Westley [visited on 2016-11-08]. ISBN 0-201-13447-0.
 Available from: https://mirrors.ctan.org/systems/knuth/dist/tex/texbook.tex.
- LUA TEAM, 2016. Lua: About [online] [visited on 2016-08-15]. Available from: https://www.lua.org/about.html.
- LUAT_EX TEAM, 2016. *LuaT_EX*: *Welcome* [online] [visited on 2016-08-15]. Available from: http://luatex.org/.
- MACFARLANE, John, 2016a. *Lunamark: Lua library for conversion between markup formats* [online] [visited on 2016-08-15]. Available from: https://github.com/jgm/lunamark.

Bibliography VI

MACFARLANE, John, 2016b. *Pandoc: a universal document converter* [online] [visited on 2016-08-15]. Available from: http://pandoc.org/.

NOVOTNÝ, Vít, 2016a. A Markdown Interpreter for TeX [online] [visited on 2016-08-17]. Available from: http://mirrors.ctan.org/macros/generic/markdown/markdown.pdf.

NOVOTNÝ, Vít, 2016b. Added support for Pandoc-style citations [online] [visited on 2016-08-15]. Available from: https://github.com/jgm/lunamark/pull/20.

Bibliography VII

```
NOVOTNÝ, Vít, 2016c. Markdown: A package for converting and
  rendering markdown documents inside T<sub>F</sub>X [online] [visited on
  2016-08-15] Available from: http://ctan.org/pkg/markdown,
  https://github.com/Witiko/markdown, and
  https://gitlab.fi.muni.cz/xnovot32/markdown.
```

```
OVERLEAF, 2016. Two great examples of how to use #markdown with
  @Overleaf - thanks @liantze! [online] [visited on 2016-08-15].
  Available from: https:
```

//twitter.com/overleaf/status/763395560682364928.