

Dynamic Memory Allocation


Memory statically, automatically, or dynamically

- Static-duration variables
 - Allocated in main memory
 - Along with the executable code of the program
 - Persist for the lifetime of the program
- Automatic-duration variables
 - Allocated on the stack
 - Come and go as functions are called and return
 - Stack size predefined by the compiler
 - Stack LIFO structure
 - Stack size OS and system architecture
- Both Static and Automatic require
 - Size of the allocation must be compile-time constant

Memory Allocation

[illegible]

Memory Allocation



Program Memory Allocation

```
#include <stdio.h>

int total; // only as an example
int Square(int);
int SquareOfSum(int, int);


int main() {
    int a = 4, b = 8;
    total = SquareOfSum(a, b);
    printf("Output = %d\n", total);
}

int Square(int x) { return x*x; }


int SquareOfSum(int x, int y) {
    int z = Square(x+y);
    return z; }
```

Program Memory Allocation


Stack




Global



Stack




Global




Program Memory Allocation


Stack




Global



Stack




Global




Program Memory Allocation


Stack




Global



Stack




Global




Program Memory Allocation


Stack



Stack



Global



Global



Dynamic Memory Allocation

- Fixed-size data objects is inadequate
- memory is more explicitly (but more flexibly) managed
- Refers to performing manual memory management
- Allows program to allocate/de-allocate memory at runtime
- Used when size of memory is not known at compile-time
- Four library functions provided defined in <stdlib.h>:
 - malloc() or "memory allocation"
 - calloc() or "contiguous allocation"
 - free() or "memory de-allocation"
 - realloc() or "re-allocation"

malloc(): Memory Allocation

- Used to allocate a single large block of memory
- Returns a pointer of type void*
- Pointer can be cast into a pointer of any form.
- Does not initialize memory at execution time
- Initial value of the allocated block is unknown

```
ptr = (cast-type*) malloc(byte-size);  
// Example:  
ptr = (int*) malloc(100 * sizeof(int));
```

calloc(): Contiguous Allocation

- Used to allocate a specified amount of memory
- Initialize it to zero
- Returns a void pointer to this memory location
- Pointer can be cast to the desired type
- Provide function specify number of elements and type
- Provided the number of elements and type
- Initializes all bits to zero

```
ptr = (cast-type*)calloc(n, element-size);  
// Example:  
ptr = (float*) calloc(25, sizeof(float));
```

Questions?