

NAME

pcsorg – get or set the PCS organization

SYNOPSIS

pcsorg [**-u** *user*] [**-s** *organization-name*] [**-R** *program-root*] [**-D**[=*n*>]] [**-V**]

DESCRIPTION**Introduction**

The *pcsorg* program is used by the Personal Communication Services (PCS) user to get or to set his personal organization name. By default the organization name of a user is set by the system administrator, but that organization name can be changed by the use of this program. By default (without any program options specified) the organization name of the user is printed to standard-output.

Options

The following options can be used to change the mode of operation.

- s** *organization* This option allows for setting of the organization name for the user. The organization name should be quoted if it contains either whitespace or other characters that would be interpreted by a SHELL.
- R** *program-root* This option allows for setting the program-root of the program. This is largely used for special debugging purposes.
- V** This option makes the program print the version of the program to standard-error and then causes the program to exit (no other functions are performed).

ENVIRONMENT VARIABLES

The following environment variables may change the default behavior of the program.

PCSORG_PROGRAMROOT

This environment variable is taken to contain the program root over any other such environment variable. The **-R** argument overrides this environment variable.

PCS

This environment variable is normally taken to contain the program root. The **-R** argument overrides this environment variable.

PROGRAMROOT

This environment variable is taken to contain the program root if not other suitable environment variable this this purpose are in the environment. The **-R** argument overrides this environment variable.

EXAMPLES

- ☞ simply get the current PCS organization name:

```
pcsorg
```

- ☞ get the PCS organization name for another user:

```
pcsorg -u johny
```

- ☞ set an organization name:

```
pcsorg -s "Acne Plumbing"
```

SEE ALSO

pcsname(1), pcsprojinfo(1), bb(1), vmail(1), msgs(1)

PATH TO

This program is currently located in `/usr/add-on/pcs/bin` or possibly where ever PCS programs are stored on your system. This is often at `${PCS}/bin` on some systems.

WARNINGS

Be careful to put at one space between all option key letters and the associated key letter parameter.

ACKNOWLEDGEMENTS

All previous PCS contributors and administrators.

AUTHOR

David A.D. Morano