

**NAME**

pcsprojinfo – get or set the PCS project-information

**SYNOPSIS**

**pcsprojinfo** [**-u** *user*] [**-s** *project-information*] [**-R** *program-root*] [**-D**[=<*n*>]] [**-V**]

**DESCRIPTION****Introduction**

The *pcsprojinfo* program is used by the Personal Communication Services (PCS) user to get or to set his personal project-information string. By default the project-information a user is set by the system administrator, but that can be changed by the use of this program. By default (without any program options specified) the project-information string of the user is printed to standard-output.

**Options**

The following options can be used to change the mode of operation.

- u** *username* Operate on an alternative user besides the default calling user. Proper privileges are required for setting the project information of another user.
- s** *project-information* This option allows for setting of the project-information string for the user. The project-information string should be quoted if it contains either whitespace or other characters that would be interpreted by a SHELL.
- R** *program-root* This option allows for setting the program-root of the program. This is largely used for special debugging purposes.
- V** This option makes the program print the version of the program to standard-error and then causes the program to exit (no other functions are performed).

**ENVIRONMENT VARIABLES**

The following environment variables may change the default behavior of the program.

**PCSPROJINFO\_PROGRAMROOT**

This environment variable is taken to contain the program root over any other such environment variable. The **-R** argument overrides this environment variable.

**PCS**

This environment variable is normally taken to contain the program root. The **-R** argument overrides this environment variable.

**PROGRAMROOT**

This environment variable is taken to contain the program root if not other suitable environment variable this this purpose are in the environment. The **-R** argument overrides this environment variable.


**EXAMPLES**

 simply get the current PCS project-information string:

```
pcsprojinfo
```

 get the PCS project-information string for another user:

```
pcsprojinfo -u johny
```

 set an organization name:

```
pcsprojinfo -s "Acne Plumbing"
```

**SEE ALSO**

pcsname(1), pcsorg(1), bb(1), vmail(1), msgs(1)

**PATH TO**

This program is currently located in `/usr/add-on/pcs/bin` or possibly where ever PCS programs are stored on your system. This is often at `${PCS}/bin` on some systems.

**WARNINGS**

Be careful to put at one space between all option key letters and the associated key letter parameter.

**ACKNOWLEDGEMENTS**

All previous PCS contributors and administrators.

**AUTHOR**

David A.D. Morano