Restful-booker API Testing: Practice Report and Test Log

Tester: David Remo
Date: 28 October 2026
Tool: Postman (manual testing)
System under test: restful-booker, a public practice API at https://restful-booker.herokuapp.com

1. Summary

I tested the restful-booker hotel booking API by hand in Postman. I ran the full lifecycle of a booking (authenticate, create, read, full update, partial update, delete), added negative tests along the way, and logged every result as expected vs actual.

Headline results

- Core create, read, update and delete flows work and return the data that was sent.
- Authorization is enforced: requests with a stale, missing or fake token were rejected with 403.
- Three behaviors do not follow standard API conventions and are worth reporting (section 5).
- Several results were affected by the shared server resetting its data, which I handled by re-creating my test data and repeating the check (section 6).

2. Scope and approach

Endpoints covered

Endpoint	Method	Purpose
/ping	GET	Health check
/booking	GET	List booking IDs, with optional filters
/booking/{id}	GET	Get one booking
/auth	POST	Create an auth token
/booking	POST	Create a booking
/booking/{id}	PUT	Replace a booking completely
/booking/{id}	PATCH	Change part of a booking
/booking/{id}	DELETE	Remove a booking

Approach: for each endpoint I checked the status code first, then the response body (field names, values and types), then ran negative tests with bad IDs, wrong credentials, missing tokens and incomplete data. I created my own test data immediately before using it, because the server is shared and resets periodically.

3. Test log

#	Request	Expected	Actual	Result
1	GET /ping	201 Created	201 Created (first call took 3.54 s while the server woke up)	Pass
2	GET /booking/9999999 (nonexistent ID)	404	404 Not Found	Pass
3	GET /booking/abc (text as ID)	404 or 400, not 500	404 Not Found	Pass
4	POST /auth, valid credentials	200 + token	Token returned	Pass
5	POST /auth, wrong password	401 or other error status	200 OK with body {"reason": "Bad credentials"}	**Fail (bug 1)**
6	POST /booking, valid data	200 + saved data	200, every field matched what I sent	Pass
7	GET /booking/3456, some minutes after creating it	200 + data	404 Not Found	Inconclusive (server reset)
8	Re-create booking, then GET it immediately	200 + same data	200, every field matched	Pass
9	PUT /booking/4338 with an old token	200	403 Forbidden	Expected (token had gone stale)
10	PUT on a booking that no longer exists, valid token	404	405 Method Not Allowed	**Quirk (bug 2)**
11	PUT with valid token on a fresh booking	200 + new data	200, all fields matched the new values	Pass
12	PUT with only firstname in the body	400	400 Bad Request	Pass
13	PATCH with only firstname	200, only firstname changed	200, firstname changed to Dave, all other fields unchanged	Pass
14	DELETE /booking/1518 with valid token	200 or 204	201 Created	**Quirk (bug 3)**

#	Request	Expected	Actual	Result
15	PATCH with no token (Cookie header switched off)	403	403 Forbidden	Pass
16	PATCH with a fake token (token=abc)	403	403 Forbidden	Pass
17	GET /booking/275 after it was deleted	404	404 Not Found	Pass
18	DELETE /booking/275 a second time, valid token	404 or another clean error	405 Method Not Allowed	Quirk (same as bug 2)

4. Key observations

PUT vs PATCH, proven with real data. The same body, {"firstname": "Dave"}, was rejected by PUT with a 400 (PUT needs every field) and accepted by PATCH, which changed only the first name and kept the other five fields intact.

Create is verified by reading back. A create response that echoes the data does not prove it was saved. Reading the booking back in a separate request did.

Status codes tell you where to look.

- 403: the server does not accept who you are (token problem)
- 404: the thing does not exist
- 405: the server will not do that action on that URL
- 400: the data sent was malformed or incomplete

5. Defects and quirks found

Bug 1: Failed login returns 200 OK

- **Steps:** send POST /auth with {"username": "admin", "password": "wrong"}
- **Expected:** an error status such as 401 Unauthorized
- **Actual:** 200 OK, with body {"reason": "Bad credentials"}
- **Impact:** clients that rely on the status code will treat a failed login as a success.

Bug 2: PUT or DELETE on a missing booking returns 405 instead of 404

- **Steps:** send PUT (or DELETE) to /booking/{id} for a booking that no longer exists, with a valid token
- **Expected:** 404 Not Found
- **Actual:** 405 Method Not Allowed
- **Impact:** misleading. The method is valid; the resource is missing. This makes failures harder to diagnose. I did not confirm the booking's absence with a separate GET at the time, so the likely cause is a server reset removing it. The same 405 came back when I deleted an already-deleted

booking (test 18), where a GET confirmed the booking was gone, so the behavior is reproducible.

Bug 3: DELETE returns 201 Created

- **Steps:** send DELETE to /booking/{id} with a valid token
- **Expected:** 200 OK or 204 No Content
- **Actual:** 201 Created, body "Created"
- **Impact:** 201 means something was created, which is the opposite of a delete. Clients checking for the conventional code would misread the result.

6. Test environment notes

Restful-booker is a shared public server that resets its data and tokens regularly. This caused three of my results:

- A booking read back a few minutes after creation returned 404. I re-created it and read it back immediately, and it worked, so this was a reset and not a defect.
- A saved token stopped working and returned 403. A fresh token fixed it.
- A booking vanished between steps, producing the 405 above.

The habit that follows from this: create test data right before using it, and get a fresh token before requests that need one. When a result surprises you, check your own setup before blaming the system.

7. What I learned

- How a request is built: method, URL, headers, body, and how a response is read: status code, body, time.
- The difference between query parameters (after the ?) and URL parameters (the ID in the path).
- Why a list endpoint returns only IDs and a separate endpoint returns the details.
- How token-based authorization works and how to test it with missing and fake tokens.
- How to write a bug report with steps, expected result, actual result and impact.
- How to tell an API defect apart from a test setup problem.

8. Next steps

- Re-read a booking after a rejected request to confirm its data was not changed.
- Add automated assertions in Postman's Scripts tab, for example checking that the status code equals 200 and that totalprice is a number.
- Save the requests as a collection and run it end to end with the Collection Runner.
- Try the same endpoints with XML bodies to see how the format changes.

9. Status code reference

The first digit tells you who to look at: 2xx means success, 4xx means the request was the problem, 5xx means the server was the problem.

Code	Name	Plain meaning	Where I saw it
200	OK	The request worked and data came back	Get booking, create, PUT, PATCH, and a failed login (bug 1)
201	Created	Normally: something new was made	/ping (healthy), and DELETE (bug 3)
400	Bad Request	The data sent was malformed or incomplete	PUT with only firstname
401	Unauthorized	Not logged in, or bad credentials	Not seen; what a failed login should return
403	Forbidden	The server understood but does not accept who you are	Stale, missing and fake tokens (tests 9, 15, 16)
404	Not Found	That thing does not exist	Nonexistent ID, text ID, deleted booking
405	Method Not Allowed	That action is not allowed on that URL	PUT or DELETE on a missing booking (bug 2)
500	Internal Server Error	The server broke	Not seen