

Nmap Scan Analysis Report

Report Date: Friday, October 2, 2026, 16:41:41 **Subject:** 28sepServiceScan.xml **Scan Type:** TCP SYN Scan **Network Range:** 192.168.50.0/24

1. Executive Summary

The scan of the 192.168.50.0/24 subnet identified several active hosts with varying security postures. The most significant finding is a high-risk, legacy Linux host (**192.168.50.22**) exhibiting multiple critical vulnerabilities, including an active unauthenticated root shell. Other hosts in the range appear to be either hardened, modern Linux systems, or network infrastructure (gateways) configured to drop probes.

2. Detailed Host Findings

Critical Risk: 192.168.50.22 (Metasploitable Target) This host presents a critical security risk due to a high density of outdated and insecure services. * **Identified Vulnerabilities:** * **Remote Access Backdoor:** Port **1524** (bindshell) is open, providing unauthenticated remote root access. * **Insecure Protocols:** Presence of **Telnet (23)** and **FTP (21 - vsftpd 2.3.4)**, the latter of which is historically associated with backdoor vulnerabilities. * **Unencrypted Management:** **VNC (5900)** and **RSH** services are active. * **Exploitable Services:** Outdated **Apache (2.2.8)**, **MySQL (5.0.51a)**, and **UnrealIRCd (6667)** are present, all of which have known public exploits. * **Impact:** High probability of full system compromise and lateral movement within the network.

Moderate Risk: 192.168.50.10

- **Services:** SSH (OpenSSH 9.6p1) and HTTP (Apache 2.4.58).
- **Status:** Running relatively modern software versions. No immediate critical vulnerabilities were identified during this scan, though the web service remains a potential attack vector for application-layer exploits.

Low Risk: 192.168.50.23

- **Services:** SSH (OpenSSH 8.4p1) and SMB (Samba 4).
- **Status:** Identified as a modern Debian 11 system. The reduced attack surface and updated service versions indicate a hardened configuration.

Infrastructure/Filtered Hosts

- **192.168.50.1:** Active, but all scanned ports are **Filtered**. This host likely functions as a firewall or gateway, effectively dropping incoming TCP probes.

- **192.168.50.20 & 192.168.50.21:** Active, but all scanned ports are **Closed**. These hosts are responding with TCP Resets (RST), indicating no services are currently listening on the scanned ports.

3. Summary Table of Active Hosts

IP Address	Risk Level	Key Services	Primary Observation
192.168.50.22	CRITICAL	FTP, SSH, Telnet, Bindshell, SMB	Active root shell and legacy vulnerabilities.
192.168.50.10	LOW	SSH, HTTP	Modern services; standard attack surface.
192.168.50.23	LOW	SSH, SMB	Hardened Debian system; minimal attack surface.
192.168.50.1	N/A	None (Filtered)	Likely a firewall/gateway.
192.168.50.20	N/A	None (Closed)	Active host with no open services.
192.168.50.21	N/A	None (Closed)	Active host with no open services.

4. Recommendations

1. **Immediate Action:** Isolate host **192.168.50.22** from the network to prevent unauthorized access via the identified bindshell and legacy services.
2. **Remediation:** Decommission or heavily harden the legacy services (Telnet, FTP, RSH) on any production systems.
3. **Continuous Monitoring:** Implement intrusion detection systems (IDS) to monitor for unauthorized connection attempts to the identified open ports.