

Nmap Scan Analysis Report

Date: 9 October 2026, 11:01am

Subject: 28sepServiceScan.xml

Type: TCP SYN

Network Range: 192.168.50.0/24

Executive Summary

256 addresses were scanned, with six showing as up and all others down. Four of the hosts had open ports, with 192.168.50.21 standing out with 23 ports open. This host appears to be a deliberately vulnerable Metasploitable lab VM, running outdated and unencrypted services. The other open hosts exposed only two or three services each.

Methodology

The scan was made on Monday 28/09/2026 at 21:37:18 NZDT on the file 28sepServiceScan.xml. The Nmap version was 7.99. The scan's duration was 184 seconds.

The command entered was `"/usr/lib/nmap/nmap --privileged -oX 28sepServiceScan.txt -sV 192.168.50.0/24"`. This scans the 1000 most common TCP ports on each host, and uses Service/Version detection (-sV). The scan was named as a TXT file, but was exported as an XML file.

Table of Active Hosts

IP	Open Ports (port service: product version)	Other ports
192.168.50.1	0	1000 filtered (no response)
192.168.50.10	22 ssh: OpenSSH 9.6p1 80 http: Apache httpd 2.4.58	998 closed
192.168.50.20	0	1000 filtered (no response)
192.168.50.21	21 ftp: vsftpd 2.3.4 22 ssh: OpenSSH 4.7p1 23 telnet: Linux telnetd 25 smtp: Postfix smtpd 53 domain: ISC BIND 9.4.2 80 http: Apache httpd 2.2.8 111 rpcbind: version 2 139 netbios-ssn: Samba smbd 3.X - 4.X 445 netbios-ssn: Samba smbd 3.X - 4.X 512 exec: netkit-rsh rexecd 513 login (not identified) 514 shell: Netkit rshd 1099 java-rmi: GNU Classpath grmiregistry 1524 bindshell: Metasploitable root shell 2049 nfs: versions 2-4 2121 ccproxy-ftp (not identified) 3306 mysql: MySQL 5.0.51a	977 closed

	5432 postgresql: PostgreSQL DB 8.3.0 - 8.3.7 5900 vnc: VNC 6000 X11 (not identified) 6667 irc: UnrealIRCd (not identified) 8009 ajp13: Apache Jserv 8180 http: Apache Tomcat/Coyote JSP engine 1.1	
192.168.50.22	445 microsoft-ds (not identified)	999 filtered (no response)
192.168.50.23	22 ssh: OpenSSH 8.4p1 139 netbios-ssn: Samba smbd 4 445 netbios-ssn: Samba smbd 4	997 closed

Observations

Hosts 192.168.50.1 and 192.168.50.20 returned no open ports.

Host 192.168.50.22 only had a single port running SMB. The host's TTL reply of 127 suggests a Windows machine.

Host 192.168.50.21 was running unencrypted legacy services (FTP, Telnet, Netkit-rsh).

For host 192.168.50.21:

Port 25 had the hostname metasploitable.localdomain.

Port 1524 was identified as a Metasploitable root shell.

Port 6667 had the hostname irc.Metasploitable.LAN.

Metasploit is a penetration testing tool used by security professionals. Metasploitable is a virtual machine that is left deliberately vulnerable for practice using Metasploit. This indicates that 192.168.50.21 is intended for training purposes.

Hosts 192.168.50.10 and 192.168.50.23 both had only a small number of open ports (2 and 3 respectively), and were running more recent versions of software.

Recommendations

As host 192.168.50.21 appears to be a deliberately vulnerable lab VM, I recommend it be kept isolated from the rest of the network, and its legacy services be decommissioned in favour of more modern services. If the host is kept running, the outdated software should be updated.