

EECS 332 Digital Image Analysis

Binary Image Analysis (I)

Ying Wu

Dept. Electrical Engineering & Computer Science
Northwestern University
Evanston, IL 60208

<http://www.ece.northwestern.edu/~yingwu>
yingwu@ece.northwestern.edu

Preface ...

- “Life is complex, but the answer is simple.”
- Sometimes, this is true.
- But sometimes, it is just the opposite.
 - For example, the operation of segmentation is natural and easy for human, but it is surprisingly difficult for computers.

Look at our task!


```

139 144 147 151 152 154 157 111 117 121 83 93 88 102 83 84 86 80 82 73 64 57 31 59 76
139 146 148 151 154 157 159 102 104 114 112 84 111 82 103 98 95 79 82 76 65 59 31 53 77
140 146 150 152 154 159 159 126 126 125 93 83 111 79 104 100 95 82 82 75 68 57 32 48 79
142 149 151 153 157 159 161 126 124 124 116 96 101 108 83 79 87 80 87 75 71 61 32 43 79
144 150 152 153 158 161 161 126 115 111 125 122 80 101 98 104 88 95 87 76 72 61 32 39 79
144 151 153 154 158 160 162 132 132 117 102 87 114 91 107 88 93 90 80 73 66 32 37 79
145 151 154 158 158 162 162 130 135 132 131 125 94 86 112 81 97 87 86 76 74 68 33 34 77
144 150 155 158 159 123 163 91 108 125 109 104 68 104 116 88 96 91 91 83 79 66 33 36 77
144 152 155 157 160 74 97 90 116 132 125 125 61 80 98 94 95 81 76 76 79 66 33 34 77
146 151 154 157 159 110 61 109 117 138 135 133 55 105 81 114 88 100 90 81 76 68 32 36 75
146 150 156 158 160 161 55 89 120 95 100 110 61 83 87 115 82 102 88 76 81 69 32 34 75
147 152 155 160 160 163 161 53 95 89 107 126 51 87 93 97 114 86 90 91 75 69 32 36 73
146 152 156 159 161 162 162 53 71 108 108 136 47 98 122 86 91 95 88 79 71 73 31 34 72
147 152 156 159 161 162 159 147 57 68 116 125 45 93 129 116 94 103 89 89 82 77 32 37 69
147 154 157 160 160 162 154 103 83 54 82 129 33 87 126 97 82 110 89 87 79 75 34 37 68
149 152 157 159 160 163 146 107 145 59 71 108 123 94 135 126 115 83 100 88 88 80 37 36 62
145 153 156 159 160 161 147 130 137 98 83 114 109 111 123 126 122 110 82 88 73 81 43 38 57
146 152 157 158 161 161 114 153 90 111 86 111 95 104 115 131 126 104 82 91 75 83 46 37 53
146 152 155 159 160 160 122 147 72 80 86 105 100 95 101 131 117 121 112 89 91 73 48 38 50
147 151 155 157 159 160 149 131 66 71 82 91 114 91 102 111 94 98 97 103 83 79 50 38 48
144 151 154 158 160 158 152 152 76 87 79 94 116 101 111 137 116 115 107 107 86 77 59 38 47
145 149 154 155 158 158 154 160 77 79 87 72 109 112 110 128 95 91 88 81 91 90 65 39 46
143 150 152 155 157 157 153 150 58 79 94 83 109 114 107 142 123 108 90 86 93 91 60 39 43
145 149 151 153 158 158 152 80 61 62 83 86 110 118 123 102 115 95 101 107 88 76 72 38 41
143 149 151 153 154 158 133 51 88 76 75 90 89 115 118 74 93 119 125 110 103 94 75 38 39
142 145 151 153 152 155 68 100 62 77 74 77 77 122 115 121 65 104 130 93 84 80 68 39 39
143 146 149 152 153 157 91 52 53 62 75 67 86 90 115 73 71 52 79 93 87 81 66 38 39
142 146 149 152 153 152 54 29 55 54 64 67 59 75 77 72 65 58 101 110 111 97 39 38 38
139 144 149 150 150 66 74 75 67 46 60 65 60 71 59 66 71 77 87 81 79 44 46 43 39
138 143 146 150 144 64 73 73 55 54 64 60 54 59 65 79 79 94 58 79 43 44 44 40
136 143 146 149 145 61 73 74 74 67 50 50 51 38 40 66 64 68 128 75 76 43 57 44 37
133 139 146 147 146 61 72 73 74 69 40 37 44 39 39 51 73 72 79 72 72 45 57 54 55
133 139 144 145 146 61 71 73 73 71 45 38 41 30 40 41 65 68 61 27 40 58 55 51 54
132 139 144 145 145 30 33 39 53 59 54 38 38 32 36 54 47 64 58 58 40 52 58 45 46
130 135 140 143 145 71 142 80 46 30 16 13 32 34 38 36 53 57 11 17 44 47 51 50 62
129 133 139 144 144 77 159 159 155 100 81 48 29 39 30 41 47 30 34 59 44 45 55 48 61
129 133 137 143 145 84 114 166 165 162 152 145 25 34 43 32 36 53 62 57 55 89 45 47 74
125 131 133 140 144 107 107 173 168 167 154 153 20 26 47 25 31 60 55 37 68 146 36 47 77
125 131 132 138 143 109 104 170 174 172 154 151 24 55 31 27 32 47 53 30 50 143 29 54 76
123 126 131 134 139 105 101 123 176 175 173 153 27 39 34 37 26 37 43 38 28 68 57 47 73
121 124 130 133 138 104 101 103 178 178 176 150 30 32 31 19 26 40 34 33 26 48 79 53 68
118 123 125 131 135 100 100 160 178 178 174 102 30 29 22 23 24 32 36 31 40 64 47 72
117 121 123 128 133 96 98 96 102 176 175 174 173 36 26 17 33 20 44 32 29 27 30 58 58
114 119 123 126 132 96 97 96 97 171 180 177 175 31 33 17 41 19 17 41 31 31 32 45 61
115 118 122 126 130 95 95 96 93 115 150 149 150 145 44 22 38 15 39 57 33 25 27 23 69

```

- Can you tell something from it?
- image analysis is to “find” something out of it!

The clue ...



- let's view a gray-scale image as a terrain
- analyzing an image is like exploring a terrain


An analogy

	Terrain of Chicago	Depth image of Chicago
	Height of a location	Pixel intensity
P1	Find down Chicago?	Image segmentation
P2	How large is the downtown?	Region area
P3	Find I-90?	Edge detection
P4	Driving along Lakeshore?	Edge following
P5	Is Michigan Ave straight?	Line fitting

Questions for today

- Let's "find" *downtown Chicago*
 - **Fit an ellipse to an elongated region**
 - ✓ where
 - ✓ how large
 - ✓ what is the orientation

Where?




- The task: $\forall I(u,v)$, make a decision 1/0
- Feature: the intensity \Leftrightarrow “the height of the location”
- A simple solution: \rightarrow thresholding

$$B(u,v) = \begin{cases} 1 & \text{(downtown)} & \text{if } I(u,v) > t \\ 0 & \text{(suburban)} & \text{otherwise} \end{cases}$$

A better idea

- Check the neighbor (or context)



- Then use the average of the neighbor

$$B(u,v) = \begin{cases} 1 & \text{if } \bar{I}[N(u,v)] > t \\ 0 & \text{otherwise} \end{cases}$$

Question

- How do you know the threshold?
 - Magic?
 - Ad hoc?
 - Heuristics?
 - Other ideas?
 - ✓ keep this question, we'll solve it in two weeks

How large?

- Size


$$A = \sum_{u=1}^n \sum_{v=1}^m B(u, v)$$

- Center

$$\left\{ \begin{array}{l} \bar{u} = \frac{\sum_{u=1}^n \sum_{v=1}^m u B(u, v)}{A} \\ \bar{v} = \frac{\sum_{u=1}^n \sum_{v=1}^m v B(u, v)}{A} \end{array} \right.$$

Orientation?

■ Task:



- To find a direction (or a line), such that the sum of squared distance of all object points to the line is minimized, i.e.,

$$D = \sum_{u=1}^n \sum_{v=1}^m d_{uv}^2 B(u, v)$$

Problem Formulation

■ To represent a line

- $\rho = u \cos\theta + v \sin\theta$ (WHY?)
- The normal of the line is $\mathbf{n} = [\cos\theta, \sin\theta]^T$
- A more compact model
 - ✓ $\rho = \mathbf{n}^T \mathbf{p}$
 - ✓ i.e, ρ is the projection of $\mathbf{p}=[u,v]^T$ on \mathbf{n}

■ Then, $\forall \mathbf{p}$, its distance to the line is

$$d = (\mathbf{n}^T \mathbf{p} - \rho) = (u \cos\theta + v \sin\theta - \rho)^2$$

■ So, the problem is formulated as:

$$(\rho^*, \theta^*) = \arg \min_{\rho, \theta} \sum_u \sum_v (u \cos\theta + v \sin\theta - \rho)^2 B(u, v)$$

Let's solve it

$$\partial D / \partial \rho = 2 \sum_u \sum_v (u \cos \theta + v \sin \theta - \rho) B(u, v) = 0$$

$$\Rightarrow \quad \bar{u} \cos \theta + \bar{v} \sin \theta - \rho = 0 \quad \text{Let's prove it}$$

i.e., the center is ON that line!

Cont.

$$\text{let } \begin{cases} \tilde{u} = u - \bar{u} \\ \tilde{v} = v - \bar{v} \end{cases}$$

$$d = (\tilde{u} \cos \theta + \tilde{v} \sin \theta)^2$$

$$D = \sum \sum \tilde{u}^2 B(u, v) \cos^2 \theta + 2 \sum \sum \tilde{u} \tilde{v} B(u, v) \cos \theta \sin \theta + \sum \sum \tilde{v}^2 B(u, v) \sin^2 \theta$$


$$= a \cos^2 \theta + b \sin \theta \cos \theta + c \sin^2 \theta$$

$$= \frac{1}{2} [(a + c) + (a - c) \cos 2\theta + b \sin 2\theta]$$

$$\Rightarrow \frac{\partial D}{\partial \theta} = -\frac{1}{2} (a - c) \sin 2\theta + \frac{1}{2} b \cos 2\theta = 0$$

$$\Rightarrow \tan 2\theta = \frac{b}{a - c}$$

A better solution: PCA



The least square error is

$$d = [e_v^T (p - t)]^2 = e_v^T (p - t)(p - t)^T e_v$$

$$D = \sum_k e_v^T (p_i - t)(p_i - t)^T e_v$$

$$= e_v^T \sum_k (p_i - t)(p_i - t)^T e_v = e_v^T \psi e_v$$

ψ is the covariance matrix

Formulation and solution

$$e_v^* = \arg \min_{e_v} e_v^T \psi e_v \quad \text{s.t.} \quad e_v^T e_v = 1$$

Let's solve this constrained optimization problem

Construct the Lagrangian $L = e_v^T \psi e_v - \lambda(e_v^T e_v - 1)$

$$\frac{\partial L}{\partial e_v} = 0 \Rightarrow \psi e_v - \lambda e_v = (\psi - \lambda I) e_v = 0$$


What is this?



e_v is an eigenvector of ψ !

So let $U = [e_1 \ e_2]$ Then, $\psi = U^T \Sigma U$

$$D = e_v^T U^T \begin{bmatrix} \lambda_u & \\ & \lambda_v \end{bmatrix} U e_v = \lambda_v$$



Principal Component Analysis

dataset $S = [s_1, s_2, \dots, s_N]$

[1] mean $t = \frac{1}{N} \sum_{k=1}^N s_k$ and $\tilde{s}_k = s_k - t$

[2] covariance matrix $M = \frac{1}{N} \sum_{k=1}^N \tilde{s}_k \tilde{s}_k^T$

[3] eigenvalue decomposition $M = U^T \Sigma U$

[4] sort eigenvalue $M = \begin{bmatrix} e_1^T \\ e_2^T \end{bmatrix} \begin{bmatrix} \lambda_1 & \\ & \lambda_2 \end{bmatrix} \begin{bmatrix} e_1 & e_2 \end{bmatrix}, \lambda_1 > \lambda_2$

principal axis : e_1

transformation : $\hat{s} = U(s - t)$

line : $e_1^T (x - t) = 0$

principal variance : $\sqrt{\lambda_1}$

EECS332 Digital Image Analysis

Binary Image Analysis (II)

Ying Wu

Dept. Electrical Engineering and Computer Science
Northwestern University
Evanston, IL 60208


<http://www.ece.northwestern.edu/~yingwu>
yingwu@ece.northwestern.edu

What we've learnt ...

- Calculate region area and centroid
- Calculate region orientation
- We can do these because the region has been segmented or isolated.
 - In other words, if there are a number of isolated regions, we have to identify them and label them.


CCL: the task

- How many isolated regions are there in an image, and where are they?




Definitions

- Neighbors



4-neighbor



8-neighbor

- Path: a sequence of pixel indices

$(u_0, v_0), (u_1, v_1), \dots, (u_n, v_n)$, s.t., (u_k, v_k) is neighbor of $(u_{k+1}, v_{k+1}), \forall k, 0 \leq k < n$

Definition

- Connectivity


- $p \in S$, p is connected to $q \in S$, if $\text{path}(p, q) \in S$

- Boundary

$$S' = \{p \mid p \in S, \forall N(p) \in \bar{S}\}$$

The Towers of Hanoi

- Given: N disks, three poles



- The puzzle: to move the disks one by one from $A \rightarrow B$

- Constraints: a disk can only be placed on top of a larger disk

Recursion

■ Statement:

- Begin w/ N disks on A, and 0 disks on B and C
- Solve Hanoi(N, A, B, C), or $A \xrightarrow[N]{C} B$

■ Solution

- Hanoi(N-1, A, C, B) $A \xrightarrow[N-1]{C} B$
- Hanoi(1, A, B, C) $A \xrightarrow{1^B} B$
- Hanoi(N-1, C, B, A) $C \xrightarrow[N-1]{A} B$

■ Pseudo code

```
Hanoi(count, source, dest, spare)
  if count ==1
    move from source to dest;
  else {
    Hanoi(count-1, source, spare, dest);
    Hanoi(1, source, dest, spare);
    Hanoi(count-1, spare, dest, source);
  }
}
```

A recursive solution to CCL

■ Find a “starting point”, $I(u,v)=1$ & $L(u,v)=0$

■ Recursion: Labeling(I, L, u, v, label)

```
if I(u,v)=0 | (I(u,v)=1 & L(u,v)≠0)
  Return;
else if L(u,v)=0 {
  L(u,v)=label;
  Labeling(I, L, u, v+1, label);
  Labeling(I, L, u+1, v, label);
  Labeling(I, L, u, v-1, label);
  Labeling(I, L, u-1, v, label);
}
```

■ Iteration (find component one by one)

Label ++

■ Discussion:

is this algorithm good?

A sequential solution to CCL

- Scan image: left \rightarrow right, top \rightarrow down

- cases

L_u : label of the upper pixel

L_l : label of the left pixel

	$L_u=0$	$L_u \neq 0$
$L_l=0$	$L(u,v)=L+1$	$L(u,v)=\max(L_u, L_l)$
$L_l \neq 0$	$L(u,v)=\max(L_u, L_l)$	$L_u=L_l$
		$L_u \neq L_l (E_table)$

A sequential solution to CCL

- First scanning

```


if I(u,v)=1{
     $L_u = L(u-1,v);$  // upper label
     $L_l = L(u,v-1);$  // left label
    if  $L_u = L_l \ \& \ L_u \neq 0 \ \& \ L_l \neq 0$  // the same label
         $L(u,v) = L_u;$ 
    else if  $L_u \neq L_l \ \& \ !(L_u \& L_l)$  //either is 0
         $L(u,v) = \max(L_u, L_l)$ 
    else if  $L_u \neq L_l \ \& \ L_u > 0 \ \& \ L_l > 0$  // both
         $L(u,v) = \min(L_u, L_l);$ 
         $E\_table(L_u, L_l);$ 
    else  $L(u,v) = L+1;$  // none
}

```

- Second scanning

– Renumbering the labels using the E_table

Example



		1	1						2	2		
		1	1						2	2		
									2	2		
	3	3	3	3			4	4	2	2	2	2
		3	3				4	4	2	2	2	2
		3	3						2	2		
		3	3						2	2		
		3	3						2	2	2	
		3	3						2	2	2	
		3	3						2	2		
	5	3	3	3					2			

1	2	3	4	5	6	7	8	9	10	11	12
---	---	---	---	---	---	---	---	---	----	----	----


 $2 \leftrightarrow 4$

1	2	3	2	5	6	7	8	9	10	11	12
---	---	---	---	---	---	---	---	---	----	----	----

 $3 \leftrightarrow 5$


1	2	3	2	3	6	7	8	9	10	11	12
---	---	---	---	---	---	---	---	---	----	----	----

Let's work this out



Size Filter

- Set a threshold to get rid of those components whose areas are less than the threshold



Region Boundary

- Boundary following algo:
 1. Starting pixel: $p_0 \in S$
 2. Current pixel $c = p_0$, and $b = \text{West}(c)$, $b \in \bar{S}$
 3. $8N(c) = \{n_1, n_2, \dots, n_8\}$ clockwise
 4. Find $k^* = \{k \mid \text{first } n_k \in S\}$
 5. Then, set

$$c \leftarrow n_{k^*}$$

$$b \leftarrow n_{k^*-1}$$
 6. Loop until $c = p_0$

Example

