

9.1 Origins and Uses of PHP

- *Origins*

- Rasmus Lerdorf - 1994
 - Developed to allow him to track visitors to his Web site
- PHP was originally an acronym for *Personal Home Page*, but later it became *PHP: Hypertext Preprocessor*
- PHP is used for form handling, file processing, and database access

9.2 Overview of PHP

- PHP is a server-side scripting language whose scripts are embedded in HTML documents
- PHP is an alternative to ASP.NET and JSP
- The PHP processor has two modes:
copy (HTML) and interpret (PHP)

9.2 Overview of PHP (continued)

- PHP syntax is similar to that of JavaScript
- PHP is dynamically typed
- PHP is purely interpreted

9.3 General Syntactic Characteristics

- PHP code can be specified in an HTML document internally or externally:

Internally: <?php
 ...
 ?>

Externally: `include ("myScript.inc")`

- the file can have both PHP and HTML
- If the file has PHP, the PHP must be in
 <?php .. ?>, even if the `include` is already in
 <?php .. ?>
- Every variable name begin with a \$

9.3 General Syntactic Characteristics (continued)

- **Comments** - three different kinds (Java and C)

```
// ...
```

```
# ...
```

```
/* ... */
```

- Compound statements are formed with braces
- Compound statements cannot be blocks

9.4 Primitives, Operations, and Expressions

- **Variables**
 - There are no type declarations
 - An unassigned (unbound) variable has the value, `NULL`
 - The `unset` function sets a variable to `NULL`
 - The `isset` function is used to determine whether a variable is `NULL`

9.4 Primitives, Operations, and Expressions (continued)

- `error_reporting(15);` - prevents PHP from using unbound variables
- PHP has many predefined variables, including the environment variables of the host operating system
 - You can get a list of the predefined variables by calling `phpinfo()` in a script
- *There are eight primitive types:*
 - Four scalar types: Boolean, integer, double, and string
 - Two compound types: array and object
 - Two special types: resource and `NULL`
- Integer & double are like those of other languages
- *Strings*
 - Characters are single bytes
 - String literals use single or double quotes

9.4 Primitives, Operations, and Expressions (continued)

- *Single-quoted string literals*

- Embedded variables are NOT interpolated
- Embedded escape sequences are NOT recognized

- *Double-quoted string literals*

- Embedded variables ARE interpolated
 - If there is a variable name in a double-quoted string but you don't want it interpolated, it must be backslashed
- Embedded escape sequences ARE recognized
- For both single- and double-quoted literal strings, embedded delimiters must be backslashed
- Boolean - values are `true` and `false` (case insensitive)
 - `0` and `""` and `"0"` are false; others are true

9.4 Primitives, Operations, and Expressions (continued)

- *Arithmetic Operators and Expressions*

- Usual operators

- If the result of integer division is not an integer, a double is returned

- Any integer operation that results in overflow produces a double

- The modulus operator (%) coerces its operands to integer, if necessary

- When a double is rounded to an integer, the rounding is always towards zero

- *Arithmetic functions*

- floor, ceil, round, abs, min, max, rand, etc.

- *String Operations and Functions*

- The only operator is period, for catenation

- Indexing - `$str{3}` is the fourth character

9.4 Primitives, Operations, and Expressions (continued)

- *String Operations and Functions* (continued)

`strlen`, `strcmp`, `strpos`, `substr`, as in C

`chop` – remove whitespace from the right end

`trim` – remove whitespace from both ends

`ltrim` – remove whitespace from the left end

`strtolower`, `strtoupper`

- *Scalar Type Conversions*

- Implicit (coercions)

- *String to numeric*

- If the string contains an `e` or an `E`, it is converted to double; otherwise to integer

- If the string does not begin with a sign or a digit, zero is used

9.4 Primitives, Operations, and Expressions (continued)

- *Scalar Type Conversions* (continued)

- Explicit conversions – casts

- e.g., `(int)$total` **or** `intval($total)` **or**
`settype($total, "integer")`

- The type of a variable can be determined with `gettype` **or** `is_type`

`gettype($total)` - it may return "unknown"

`is_integer($total)` – a predicate function

9.5 Output

- Output from a PHP script is HTML that is sent to the browser
- HTML is sent to the browser through standard output

9.5 Output (continued)

- There are two ways to produce output: `print` and `printf`
- `print` takes a string, but will coerce other values to strings

```
print "This is too <br /> much fun <br />";  
print 72;
```

- `printf` is exactly as in C

```
printf(literal_string, param1, param2, ...)
```

- PHP code is placed in the body of an HTML document

```
<html>  
<head><title> Trivial php example </title>  
</head>  
<body>  
<?php  
    print "Welcome to my Web site!";  
?>  
</body>  
</html>
```

→ **SHOW** `today.php` and display

9.6 Control Statements

- **Control Expressions**

- **Relational operators** - same as JavaScript, (including `===` and `!==`)
- **Boolean operators** - same as C (two sets, `&&` and `and`, etc.)

- **Selection statements**

- `if`, `if-else`, `elseif`
- `switch` - as in C
 - The `switch` expression type must be integer, double, or string

- `while` - just like C

- `do-while` - just like C

- `for` - just like C

- `foreach` - discussed later

9.6 Control Statements (continued)

- **break** - in any for, foreach, while, do-while, or switch
- **continue** - in any loop
- **Alternative compound delimiters** – more readability

```
if(...):  
    ...  
endif;
```

→ **SHOW** powers.php

- **HTML** can be intermingled with **PHP** script

```
<?php  
    $a = 7;  
    $b = 7;  
    if ($a == $b) {  
        $a = 3 * $a;  
    }  
?>  
<br /> At this point, $a and $b are  
    equal <br />  
So, we change $a to three times $a  
<?php  
    }  
?>
```

9.7 Arrays

- Not like the arrays of any other programming language
 - A PHP array is a generalization of the arrays of other languages
 - A PHP array is really a mapping of keys to values, where the keys can be numbers (to get a traditional array) or strings (to get a hash)
 - Array creation
 - Use the `array()` construct, which takes one or more key => value pairs as parameters and returns an array of them
 - The keys are non-negative integer literals or string literals
 - The values can be anything
- e.g., `$list = array(0 => "apples",
1 => "oranges", 2 => "grapes")`
- This is a “regular” array of strings

9.7 Arrays (continued)

- If a key is omitted and there have been integer keys, the default key will be the largest current key + 1
 - If a key is omitted and there have been no integer keys, 0 is the default key
 - If a key appears that has already appeared, the new value will overwrite the old one
- Arrays can have mixed kinds of elements
- e.g.,

```
$list = array("make" => "Cessna",  
              "model" => "C210",  
              "year" => 1960,  
              3 => "sold");
```

```
$list = array(1, 3, 5, 7, 9);
```

```
$list = array(5, 3 => 7, 5 => 10,  
              "month" => "May");
```

```
$colors = array('red', 'blue', 'green',  
                'yellow');
```

9.7 Arrays (continued)

- *Accessing array elements* – use brackets

```
$list[4] = 7;  
$list["day"] = "Tuesday";  
$list[] = 17;
```

- If an element with the specified key does not exist, it is created
- If the array does not exist, the array is created
- The keys or values can be extracted from an array

```
$highs = array("Mon" => 74, "Tue" => 70,  
               "Wed" => 67, "Thu" => 62,  
               "Fri" => 65);  
$days = array_keys($highs);  
$temps = array_values($highs);
```

- Testing whether an element exists

```
if (array_key_exists("Wed", $highs)) ...
```

- An array can be deleted with `unset`

```
unset($list);  
unset($list[4]); # Deletes index 4 element
```

9.7 Arrays (continued)

- `is_array($list)` returns true if `$list` is an array
- `in_array(17, $list)` returns true if 17 is an element of `$list`
- `sizeof(an_array)` returns the number of elements
- `explode(" ", $str)` creates an array with the values of the words from `$str`, split on a space
- `implode(" ", $list)` creates a string of the elements from `$list`, separated by a space

→ **SHOW Figure 9.3**

- *Sequential access to array elements*

- current and next

```
$colors = array("Blue", "red", "green",  
               "yellow");  
$color = current($colors);  
print("$color <br />");  
while ($color = next($colors))  
    print ("$color <br />");
```

9.7 Arrays (continued)

- This does not always work – for example, if the value in the array happens to be `FALSE`

- **Alternative:** `each`, instead of `next`

```
while ($element = each($colors)) {  
    print ("$element['value'] <br />");  
}
```

- The `prev` function moves current backwards

- `array_push($list, $element)` and
`array_pop($list)`

- Used to implement stacks in arrays

- `foreach (array_name as scalar_name) { ... }`

```
foreach ($colors as $color) {  
    print  
    "Is $color your favorite color?<br />";  
}
```

```
Is red your favorite color?  
Is blue your favorite color?  
Is green your favorite color?  
Is yellow your favorite color?
```


9.7 Arrays (continued)

- **foreach** can iterate through both keys and values:

```
foreach ($colors as $key => $color) { ... }
```

- **Inside the compound statement, both `$key` and `$color` are defined**

```
$ages = array("Bob" => 42, "Mary" => 43);  
foreach ($ages as $name => $age)  
    print("$name is $age years old <br />");
```

9.7 Arrays (continued)

- sort

- To sort the values of an array, leaving the keys in their present order - *intended for traditional arrays*

e.g., `sort($list);`

- The `sort` function does not return anything
- Works for both strings and numbers, even mixed strings and numbers

```
$list = ('h', 100, 'c', 20, 'a');  
sort($list);  
// Produces ('a', 'c', 'h', 20, 100)
```

- In PHP 4, the `sort` function can take a second parameter, which specifies a particular kind of sort

```
sort($list, SORT_NUMERIC);
```

- asort

- To sort the values of an array, but keeping the key/value relationships - *intended for hashes*

9.7 Arrays (continued)

- `rsort`

- To sort the values of an array into reverse order

- `ksort`

- To sort the elements of an array by the keys, maintaining the key/value relationships

e.g.,

```
$list("Fred" => 17, "Mary" => 21,  
      "Bob" => 49, "Jill" => 28);  
ksort($list);  
// $list is now ("Bob" => 49,  
// "Fred" => 17, "Jill" => 28, "Mary" => 21)
```

- `krsort`

- To sort the elements of an array by the keys into reverse order

→ **SHOW** `sorting.php`

9.8 User-Defined Functions

- *Syntactic form:*

```
function function_name (formal_parameters) {  
    ...  
}
```

- *General Characteristics*

- Functions need not be defined before they are called
- If you try to redefine a function, it is an error
- Functions can have a variable number of parameters
- Default parameter values are supported
- Function definitions can be nested
- Function names are NOT case sensitive
- The `return` function is used to return a value;
If there is no `return`, there is no returned value

9.8 User-Defined Functions (continued)

- *Parameters*

- If the caller sends too many actual parameters, the subprogram ignores the extra ones
- If the caller does not send enough parameters, the unmatched formal parameters are unbound
- The default parameter passing method is pass by value (one-way communication)
- To specify pass-by-reference, prepend an ampersand to the formal parameter

```
function set_max(&$max, $first, $second) {  
    if ($first >= $second)  
        $max = $first;  
    else  
        $max = $second;  
}
```

- If the function does not specify its parameter to be pass by reference, you can prepend an ampersand to the actual parameter and still get pass-by-reference semantics

9.8 User-Defined Functions (continued)

- *Return Values*

- Any type may be returned, including objects and arrays, using the `return`
- If a function returns a reference, the name of the function must have a prepended ampersand

```
function &newArray($x) { ... }
```

- *The Scope of Variables*

- An undeclared variable in a function has the scope of the function
- To access a nonlocal variable, it must be declared to be global, as in

```
global $sum;
```

- *The Lifetime of Variables*

- Normally, the lifetime of a variable in a function is from its first appearance to the end of the function's execution

```
static $sum = 0; # $sum is static
```

9.9 Pattern Matching

- PHP has two kinds: POSIX and Perl-compatible

`preg_match(regex, str)`

- Returns a Boolean value

`preg_split(regex, str)`

- Returns an array of the substrings

→ **SHOW** `word_table.php`

9.10 Form Handling

- Forms could be handled by the same document that creates the form, but that may be confusing
- PHP particulars:
 - It does not matter whether GET or POST method is used to transmit the form data
 - PHP builds an array of the form values (`$_GET` for the GET method and `$_POST` for the POST method – subscripts are the widget names)

→ **SHOW** `popcorn3.html & popcorn3.php`

9.11 Cookies

- Recall that the HTTP protocol is stateless; however, there are several reasons why it is useful for a server to relate a request to earlier requests
 - Targeted advertising
 - Shopping baskets
- A *cookie* is a name/value pair that is passed between a browser and a server in the HTTP header
- In PHP, cookies are created with `setcookie`

`setcookie(cookie_name, cookie_value, lifetime)`

e.g., `setcookie("voted", "true", time() + 86400);`

- Cookies are implicitly deleted when their lifetimes are over
- Cookies must be created before any other HTML is created by the script
- Cookies are obtained in a script the same way form values are gotten, using the `$_COOKIE` array

9.13 Session Tracking

- A *session* is the time span during which a browser interacts with a particular server
- For session tracking, PHP creates and maintains a session tracking id
- Create the id with a call to `session_start` with no parameters
- Subsequent calls to `session_start` retrieves any session variables that were previously registered in the session
- To create a session variable, use `session_register`
 - The only parameter is a string literal of the name of the session variable (without the dollar sign)
 - *Example:* count number of pages visited
 - Put the following code in all documents

```
session_start();  
if (!IsSet($page_number))  
    $page_number = 1;  
print("You have now visited $page_number");  
print(" pages <br />");  
$page_number++;  
$session_register("page_number");
```