

Assignment report for the course Automated Planning: Theory and Practice

Master's degree in Artificial Intelligence Systems; A.Y 2022/2023; Marco Roveri

Joy Battocchio

Davide Guidolin

I. INTRODUCTION

The following report aims to give a detailed explanation of the solutions of the 5 problems proposed in the assignment. The problems considered a scenario where one or more robots have to deliver emergency supplies to injured people located in space. These were the initial explicit assumptions:

- Each injured person is at a specific location, and does not move.
- Each box is initially at a specific location and can be filled with a specific content if empty. Box contents shall be modeled in a generic way, so that new contents can easily be introduced in the problem instance.
- Each person either has or does not have a box with a specific content.
- There can be more than one person at any given location.
- The robotic agents can move directly between arbitrary locations.
- We want to be able to expand this domain for multiple robotic agents in the future.

While the suggested actions were the following:

- Fill a box with a content. Robot box and content must be in the same place, box must be empty.
- Empty a box, satisfying the person at that specific location.
- Pick up a box located in the same place as the robot.
- Move to another location.
- Deliver a box.

Based on these assumptions here is the formulated solution used in all problems. We considered 5 main types:

- Robot
- Person
- Location
- Box
- Content

and 5 main actions:

- Fill
- Empty
- Load
- Move
- Unload

The main workflow the robot follow to satisfy a person is to **fill** a box with a content, **load** the box on itself and **move**

carrying the box toward the destination. Once it gets where the person is located it **unloads** the box and **empties** it giving the content to the person. After that the robot needs to restart in order to satisfy another person, so it can re-use the same box as before and carry it to the place where the supplies are stored, or look for another box. We assume the supplies are infinite where stored, but only one portion can fit in a box, so if 2 people need the same supply the robot must re-fill with it.

For doing so the following informations are needed:

- Where a robot is (**robot-at**).
- If a robot is carrying a box(**robot-loaded**).
- Which box a robot is carrying (**robot-has**).
- If a box is full (**box-full**).
- Where a box is (**box-at**).
- What is the content of a box (**box-contains**).
- Where a supply is stored (**content-at**); specified in the initial assumptions of the problem and fixed.
- Where a person is (**person-at**); specified in the initial assumptions of the problem and fixed.
- What supply a person has (**person-has**); which represent the goal.

For all problems we used **negative preconditions** since the predicates make more sense this way and it is supported by almost every planner. We also made a version without **negative precondition** that has very few differences, it is sufficient to use **box-empty** and **robot-unloaded** and remove the negated preconditions from the **move** action. Notice that this configuration ensure there are no constraints on the number of robots or boxes in order to satisfy any number of people.

II. PROBLEM 1

The first problem was solved simply by implementing what is described in the introduction above. We set the environment with 1 robot, 3 people, 5 locations (one of which is the depot where the supplies are stored), 2 boxes and 3 types of supply. Initially the 3 people are scattered over the locations, while robot, boxes and supplies are in the depot. The goal is to deliver medicine to person2, and to deliver food and medicine to person3; person1 does not need anything.

III. PROBLEM 2

The second problem required to think about the **move** action in a different perspective, ensuring that a robot can load the

boxes on a carrier instead of itself, and that the carrier can be transported by a robot to the destinations.

The solution we developed are two, the first one is simpler since it only has an additional type **carrier** and its **capacity** is represented through a function. The initial capacity of each carrier can be specified in the problem, and it is managed through the usage of fluents: **load** can be performed only if the capacity is greater than 0, and the effect is to decrement it, the opposite for **unload**.

Another solution has been implemented since the first one relies on the **fluents** requirement, which is not supported by many planner we used. We took inspiration by an example provided during the lab session, in which each a new type called **capacity-number** is used to described all the possible capacities. Then for each **load** and **unload** operation done on the carrier is important not to forget to specify the precondition **capacity-predecessor** through which we ensure the numbers we use to upload the capacity are consequent. The order of the capacity is specified in the problem as follows:

```
(capacity_predecessor capacity_0 capacity_1)
(capacity_predecessor capacity_1 capacity_2)
(capacity_predecessor capacity_2 capacity_3)
(capacity_predecessor capacity_3 capacity_4)
```

Plus the initial capacity of each carrier (4 as requested):

```
(capacity carrier1 capacity_4)
```

Finally the last modification with respect to the first problem is the **move** action, which no longer allow a robot to carry a box, but a carrier instead. Thanks to this any robot can carry any carrier, even if loaded by another robot.

To test it with a more complex environment we increased the number of people to 6, the boxes to 5, the locations to 8 and the supplies to 5, the robot and the carrier are just one each, as requested in the assignment. Of course there are no constraints neither in the number of robots nor of carriers.

IV. PROBLEM 3

Problem number 3 required a hierarchical implementation of the actions.

REFERENCES

- [1] M. Kharrazi, H. T. Sencar and N. Memon, "Blind source camera identification," 2004 International Conference on Image Processing, 2004.
- [2] J. Lukas, J. Fridrich, and M. Goljan, "Digital camera identification from sensor pattern noise".
- [3] L. Bondi, L. Baroffio, D. Guera, P. Bestagini, E. Delp, and S. Tubaro, "First Steps Toward Camera Model Identification with Convolutional Neural Networks".
- [4] S. Mandelli, D. Cozzolino, P. Bestagini, L. Verdoliva and S. Tubaro, "CNN-Based Fast Source Device Identification"